



1099-N



VIDEO

Product Description

Single gang electrical box for use with nonmetallic sheathed cable

Brand: fiberglassBOX™
Catalog #: 1099-N

Carton Quantity: 100
Carton Weight: 39 lb.

Height: 3-27/32 in.
Width: 2-1/4 in.
Depth: 3-9/16 in.
Volume: 22.5 cu. in.
Type of Installation: New Work
Wall Box
Number of Gangs: 1

UPC: 085339260004
UNSPSC: 39121308
Country of Origin: United States of America

FEATURES


Machine tapped device holes, offset gauge marks, leveling ribs, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures

APPLICATION

New work residential construction 2 HR fire resistive walls & ceilings

STANDARDS

ANSI / UL 514C: <http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/showpage.html?name=QCMZ.E30594&ccnshorttitle=Nonmetallic+Outlet+Boxes&objid=1074114794&cfgid=1No.E30594>



FIRE CLASSIFICATION

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)
Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 ½ inches
Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)

COLOR

Beige/tan

ADDITIONAL MATERIALS

Carbon steel fasteners

MATERIAL

Fiberglass reinforced polyester BMC

MOUNTING

Angled mid nails