



STUDIO FINISHES[®] GLITTER EFFECT 311

Features

- Studio Finishes[®] Latex Glitter Effect (311) is a topcoat that adds an iridescent sparkle to any previously painted interior surface
- Resists spattering during application
- Dries quickly
- Dries to a decorative finish that is extremely durable
- Is formulated to minimize lingering odors
- Soap and water clean-up
- Goes on easily and is washable

Recommended For

For interior use on previously painted surfaces, including ceilings, walls, trim and furniture. Use wherever a glitter finish is desired.

General Descriptions

Studio Finishes[®] Latex Glitter Effect (311) is a clear, low lustre topcoat that adds a whimsical, iridescent sparkle to any paintable surface or room in your home.

Limitations

- Do not apply when air and surface temperatures are below 50° F (10° C).

Product Information

Colors — Standard:	Technical Data [◇]	Clear
Clear	Vehicle Type	Vinyl Acrylic / Water
	Pigment Type	None
	Volume Solids	30%
— Tint Bases:	Coverage per Quart at Recommended Film Thickness	100 – 110 Sq. Ft.
Not available	Recommended Film Thickness — Wet	3.8 mils
	Recommended Film Thickness — Dry	1.1 mils
— Special Colors:	Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.	
Contact your Benjamin Moore representative.	Dry Time @ 77° F — To Touch	1 Hour
	(25° C) @ 50% RH — To Recoat	2 -3 Hour
Certification	Painted surfaces can be washed after two weeks. High humidity and cool temperatures will result in longer dry, recoat and service times.	
VOC compliant in all regulated areas	Dries By	Evaporation, Coalescence
	Viscosity	85 ± 1 KU
	Flash Point	None
	Gloss / Sheen	Low Lustre
	Surface Temperature — Min. at Application	50° F
	— Max	90° F
	Thin With	Clean Water
	Clean Up Thinner	Clean Water
	Weight Per Gallon	8.69 lbs
Technical Assistance:	Storage Temperature — Min.	40° F
Available through your local authorized independent Benjamin Moore retailer. For the location of the retailer nearest you, call 1-800-826-2623, see www.benjaminmoore.com , or consult your local Yellow Pages.	— Max	90° F
	Volatile Organic Compounds (VOC)	
	118 Grams/Liter	.98 lbs./Gallon

[◇] Reported values are for Clear. Contact Benjamin Moore for values of other bases or colors.

Surface Preparation

Surfaces must be clean, dry and free of wax, grease, dust, mildew, water-soluble materials and scaling paint. Hard, glossy areas should be dulled with sandpaper to ensure proper adhesion.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead

Primer/Finish Systems

Use the appropriate Fresh Start® primer. Follow label directions. For best results when significant color change is desired, tint the primer to the approximate base color. When dry, apply one or two finish coats of Benjamin Moore® Regal® Classic Eggshell (N319), Regal® Classic Pearl (N310), or Regal® Classic Semi-Gloss (N333) or other premium Benjamin Moore® products. Finish with one or two coats of Studio Finishes® Latex Glitter Effect (311).

Application

Stir thoroughly. Apply one or two coats. For best results, use a Benjamin Moore® custom-blended nylon/polyester brush, Benjamin Moore® roller, or a similar product. When brushing or rolling, apply generously using short overlapping strokes, always moving from unpainted into painted areas. Do not over apply. Let paint dry before touching up. Do not apply in temperatures below 50°F (10°C).

Thinning/Cleanup

Thinning is unnecessary, but if required to obtain desired application properties, a small amount of clean water may be added. Never add other paints or solvents. Wash painting tools in warm soapy water immediately after use. Spray equipment should be given a final rinse with mineral spirits to prevent rusting.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry, empty containers may be recycled in a can recycling program. **Local disposal requirements vary, consult your sanitation department or state-designated environmental agency on disposal options.**

Environmental, Health & Safety Information

Use only with adequate ventilation. Do not breathe spray mist or sanding dust. Avoid contact with eyes and prolonged or repeated contact with skin. Wear eye protection and gloves during application or sanding. A dust/particulate respirator approved by NIOSH should be worn when sanding or spraying. Close container after each use.

WARNING: This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm.

FIRST AID: If you experience difficulty in breathing, leave area to obtain fresh air. If continued difficulty is experienced, call physician immediately.

IN CASE OF: SPILL – Absorb with inert material and dispose of as specified under “**THINNING/CLEAN UP**”.

KEEP OUT OF REACH OF CHILDREN

Refer to Material Safety Data Sheet for additional health and safety information.