

Polyblend® Ceramic Tile Caulk

1 Product Name

Polyblend® Ceramic Tile Caulk

2 Manufacturer

Custom Building Products
 Technical Services
 10400 Pioneer Boulevard, Unit 3
 Santa Fe Springs, CA 90670
 Customer Support: 800-272-8786
 Technical Services: 800-282-8786
 Fax: 800- 200-7765
 Email: contactus@cbpmail.net
custombuildingproducts.com

3 Product Description

Our ceramic tile caulk is for caulking around sinks, tubs, showers and where tile meets tile or another surface. Also adheres bath fixtures and loose tile. Do not use to install grab bars. Maximum joint width and depth should not exceed 1/4" (6 mm). Do not use in areas with constant water exposure. For interior use only.

Key Features

- Use around tubs and sinks
- Use where horizontal and vertical surfaces meet
- Siliconized for ease of use

Suitable Tile Types

- Around tubs, showers and sinks
- Bonds bath fixtures and loose tiles

Composition of Product

Siliconized acrylic latex resins with fine fillers and colored pigments

Benefits of Product in the Installation

- For caulking around sinks, tubs and showers
- Adheres bath fixtures and loose tile.
- For joint up to 1/4" (6mm) wide and deep
- For interior use.
- Available in sanded and non-sanded versions to match grout texture.
- Mold and mildew resistant

Limitations to the Product

- Do not use to install grab bars.
- Maximum joint width and depth should not exceed 1/4" (6 mm).
- Do not use in areas with constant water exposure

Packaging

10.5 oz (310 ml) cartridge



4 Technical Data

Technical Chart

Tack-Free Time (ASTM C-679)	30 Minutes
Paintable	>Yes
Slump	< 0.15 mm
Shrinkage	< 30%
Stain Resistance	Excellent
Crack Resistance	Excellent
pH	7-9

Environmental Consideration

Custom® Building Products is committed to environmental responsibility in both products produced and in manufacturing practices. Use of this product can contribute towards LEED® v3 certification:

- Up to 2 points towards MR Credit 5, Regional Materials
- Up to 1 point towards IEQ Credit 4.1, Low-Emitting Materials – Adhesives & Sealants

5 Instructions

General Surface Prep

USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product.

Application of Product

Surfaces should be clean, dry and free of all contamination. Place cartridge in standard caulking gun. Cut tip off nozzle on a slant to desired opening size and completely fill joints with caulk. Smooth with wet finger. Clean off excess caulk with soap and water before it cures. Do not apply when temperature falls below 50°F (10°C).

Curing of Product

Minimum 24 hours before exposing to water. Cure time may be extended, depending on caulking thickness and ambient conditions.

Cleaning of equipment

Clean tools with water before material dries.



CUSTOM®

Polyblend® Ceramic Tile Caulk

Storage

Replace cap after each use. Store away from extreme heat or cold. Keep from freezing.

Health Precautions

Contains Petroleum Distillates. If ingested, do not induce vomiting, call a physician immediately. Use with adequate ventilation. Nonflammable. KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY. AVOID EYE CONTACT.

6 Availability & Cost

Sanded					
Location	Color #	Color	Item Code	Size	Package
USA	#9	Natural Gray	PC0910S-6	10.5 oz. (310 ml)	Cartridge
USA	#10	Antique White	PC1010S-6	10.5 oz. (310 ml)	Cartridge
USA	#11	Snow White	PC1110S-6	10.5 oz. (310 ml)	Cartridge
USA	#19	Pewter	PC1910S-6	10.5 oz. (310 ml)	Cartridge
USA	#22	Sahara Tan	PC2210S-6	10.5 oz. (310 ml)	Cartridge
USA	#52	Tobacco Brown	PC5210S-6	10.5 oz. (310 ml)	Cartridge
USA	#60	Charcoal	PC6010S-6	10.5 oz. (310 ml)	Cartridge
USA	#105	Earth	PC10510S-6	10.5 oz. (310 ml)	Cartridge
USA	#122	Linen	PC12210S-6	10.5 oz. (310 ml)	Cartridge
USA	#145	Light Smoke	PC14510S-6	10.5 oz. (310 ml)	Cartridge
USA	#165	Delorean Gray	PC16510S-6	10.5 oz. (310 ml)	Cartridge
USA	#180	Sandstone	PC18010S-6	10.5 oz. (310 ml)	Cartridge
USA	#380	Haystack	PC38010S-6	10.5 oz. (310 ml)	Cartridge
USA	#381	Bright White	PC38110S-6	10.5 oz. (310 ml)	Cartridge
USA	#382	Bone	PC38210S-6	10.5 oz. (310 ml)	Cartridge
Canada	#9	Natural Gray	CPC0910S-6	10.5 oz. (310 ml)	Cartridge
Canada	#10	Antique White	CPC1010S-6	10.5 oz. (310 ml)	Cartridge
Canada	#11	Snow White	CPC1110S-6	10.5 oz. (310 ml)	Cartridge
Canada	#19	Pewter	CPC1910S-6	10.5 oz. (310 ml)	Cartridge
Canada	#22	Sahara Tan	CPC2210S-6	10.5 oz. (310 ml)	Cartridge
Canada	#52	Tobacco Brown	CPC5210S-6	10.5 oz. (310 ml)	Cartridge
Canada	#60	Charcoal	CPC6010S-6	10.5 oz. (310 ml)	Cartridge
Canada	#105	Earth	CPC10510S-6	10.5 oz. (310 ml)	Cartridge
Canada	#122	Linen	CPC12210S-6	10.5 oz. (310 ml)	Cartridge
Canada	#145	Light Smoke	CPC14510S-6	10.5 oz. (310 ml)	Cartridge
Canada	#165	Delorean Gray	CPC16510S-6	10.5 oz. (310 ml)	Cartridge
Canada	#180	Sandstone	CPC18010S-6	10.5 oz. (310 ml)	Cartridge
Canada	#380	Haystack	CPC38010S-6	10.5 oz. (310 ml)	Cartridge
Canada	#381	Bright White	CPC38110S-6	10.5 oz. (310 ml)	Cartridge
Canada	#382	Bone	CPC38210S-6	10.5 oz. (310 ml)	Cartridge



CUSTOM®

Polyblend® Ceramic Tile Caulk

Non-Sanded					
Location	Color #	Color	Item Code	Size	Package
USA	#10	Antique White	PC1010N-6	10.5 oz. (310 ml)	Cartridge
USA	#11	Snow White	PC1110N-6	10.5 oz. (310 ml)	Cartridge
USA	#122	Linen	PC12210N-6	10.5 oz. (310 ml)	Cartridge
USA	#165	Delorean Gray	PC16510N-6	10.5 oz. (310 ml)	Cartridge
USA	#381	Bright White	PC38110N-6	10.5 oz. (310 ml)	Cartridge
Canada	#10	Antique White	CPC1010N-6	10.5 oz. (310 ml)	Cartridge
Canada	#11	Snow White	CPC1110N-6	10.5 oz. (310 ml)	Cartridge
Canada	#122	Linen	CPC12210N-6	10.5 oz. (310 ml)	Cartridge
Canada	#165	Delorean Gray	CPC16510N-6	10.5 oz. (310 ml)	Cartridge
Canada	#381	Bright White	CPC38110N-6	10.5 oz. (310 ml)	Cartridge

Additional colors may be available in select markets.

See our color card for truest color representation when selecting or specifying a grout color. Final installed shade may vary with the tile type, color and porosity as well as jobsite conditions and finishing techniques. For best results, perform a test on a small, inconspicuous area or create a sample board prior to installation.

7 Product Warranty

Obtain the applicable **LIMITED PRODUCT WARRANTY** at www.custombuildingproducts.com/product-warranty or send a written request to Custom Building Products, Inc., Five Concourse Parkway, Atlanta, GA 30328, USA. Manufactured under the authority of Custom Building Products, Inc. © 2017 Quikrete International, Inc.

8 Product Maintenance

Clean with a neutral cleaner such as Aquamix AquaKleen or Tilelab Grout & Tile Cleaner

9 Technical Services Information

For technical assistance, contact Custom technical services at 800-282-8786 or visit custombuildingproducts.com.

10 Filing System

Additional product information is available from the manufacturer upon request.

Related Products

Polyblend® Sanded Grout

Prism® Ultimate Performance Grout



Polyblend® Ceramic Tile Caulk

Coverage

Size	Coverage
10.1 oz. (300 mL)	24 lineal feet (7.3 M) of 1/4" x 1/4" (6 x 6 mm) joint