



Safety Data Sheet

24 Hour Emergency Phone Numbers

Medical/Poison Control:
In U.S.: Call 1-800-222-1222

Outside U.S.: Call your local poison control center

Transportation/National Response Center:

1-800-535-5053

1-352-323-3500

NOTE: The National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

IMPORTANT: Provide this information to employees, customers, and users of this product. Read this SDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this MSDS are further described in Section 16.

1. Identification

This Safety Data Sheet is available in American Spanish upon request.
Los Datos de Seguridad pueden obtenerse en Espanol si lo requiere.

| | | | |
|----------------------------|---|-------------------------|-------------|
| Product Name: | 3.0 Kitchen, Bath & Plumbing Sealant - White | Revision Date: | 6/19/2015 |
| Product UPC Number: | 00790, 05928, 05932 | Supersedes Date: | New SDS |
| Product Use/Class: | Caulking Compound | SDS No: | 00010026001 |
| Manufacturer: | DAP Products Inc. 2400 Boston Street Suite 200 Baltimore, MD 21224-4723 888-327-8477 (non - emergency matters) | | |
| Preparer: | Regulatory Department | | |

2. Hazards Identification

EMERGENCY OVERVIEW: Under normal use conditions, this product is not expected to cause adverse health effects. High concentration of vapors may cause irritation to eyes and respiratory system.

GHS Classification

Not a hazardous substance or mixture.

Symbol(s) of Product

None

Signal Word

Not a hazardous substance or mixture.

3. Composition/Information on Ingredients

| <u>Chemical Name</u> | <u>CAS-No.</u> | <u>Wt. %</u> | <u>GHS Symbols</u> | <u>GHS Statements</u> |
|------------------------------|----------------|--------------|--------------------|-----------------------|
| Calcium Carbonate | 471-34-1 | 25-50 | GHS03-GHS07 | H270-332 |
| Proprietary Phthalate Esters | Proprietary | 10-25 | GHS03-GHS07 | H270-332 |

| | | | | |
|------------------------------|-------------|---------|----------------|----------------|
| Limestone | 1317-65-3 | 10-25 | GHS03 | H270 |
| Titanium dioxide | 13463-67-7 | 2.5-10 | No Information | No Information |
| Trimethoxyvinylsilane | 2768-02-7 | 1.0-2.5 | GHS03-GHS07 | H270-332 |
| Proprietary Phthalate Esters | Proprietary | 1.0-2.5 | GHS03-GHS06 | H270-331 |

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

4. First-aid Measures

FIRST AID - INHALATION: Material is not likely to present an inhalation hazard at ambient conditions. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

FIRST AID - SKIN CONTACT: Wash skin with soap and water for 15 minutes. Get medical aid if symptoms persist.

FIRST AID - EYE CONTACT: In case of contact, immediately flush eyes with large quantities of water for at least 15 minutes until irritation subsides. Get medical attention immediately.

FIRST AID - INGESTION: If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately.

5. Fire-fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: 465 <undefined>

SPECIAL FIREFIGHTING PROCEDURES: Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam

6. Accidental Release Measures

ENVIRONMENTAL MEASURES: No Information

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Scrape up dried material and place into containers. Use personal protective equipment as necessary. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations.

7. Handling and Storage

HANDLING: KEEP OUT OF REACH OF CHILDREN! DO NOT TAKE INTERNALLY. Avoid breathing vapor and contact with eyes, skin and clothing. Use only with adequate ventilation. Ensure fresh air entry during application and drying. Wash thoroughly after handling.

STORAGE: Avoid excessive heat and freezing. Store away from caustics and oxidizers.

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

| <u>Chemical Name</u> | <u>ACGIH TLV-TWA</u> | <u>ACGIH-TLV STEL</u> | <u>OSHA PEL-TWA</u> | <u>OSHA PEL-CEILING</u> |
|------------------------------|----------------------|-----------------------|---|-------------------------|
| Calcium Carbonate | N.E. | N.E. | N.E. | N.E. |
| Proprietary Phthalate Esters | N.E. | N.E. | N.E. | N.E. |
| Limestone | N.E. | N.E. | 15 mg/m3 TWA total dust, 5 mg/m3 TWA respirable fraction | N.E. |
| Titanium dioxide | 10 mg/m3 TWA | N.E. | 15 mg/m3 TWA total dust | N.E. |
| Trimethoxyvinylsilane | N.E. | N.E. | N.E. | N.E. |
| Proprietary Phthalate Esters | N.E. | N.E. | N.E. | N.E. |

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation
Sk = Skin Sensitizer N.E. = Not Established

Personal Protection



RESPIRATORY PROTECTION: No personal respiratory protective equipment normally required.



SKIN PROTECTION: Wear nitrile or neoprene gloves. Natural rubber, butyl rubber and polyvinyl chloride gloves are not suitable protection against phthalates such as diisodecyl phthalate and diisononyl phthalate; neoprene is recommended.



EYE PROTECTION: Goggles or safety glasses with side shields.



OTHER PROTECTIVE EQUIPMENT: Not required under normal use.



HYGIENIC PRACTICES: Wash hands before breaks and at the end of workday. Remove and wash contaminated clothing before re-use.

9. Physical and Chemical Properties

| | | | |
|---------------------------------------|-----------------------------|---|-----------------|
| Appearance: | White to Off-White | Physical State: | Paste |
| Odor: | Slight | Odor Threshold: | Not Established |
| Density, g/cm³: | 1.47 - 1.47 | pH: | Not Applicable |
| Freeze Point, °C: | Not Established | Viscosity (mPa.s): | Not Established |
| Solubility in Water: | Not Established | Partition Coeff., n-octanol/water: | Not Established |
| Decomposition Temperature, °C: | Not Established | Explosive Limits, %: | N.I. - N.I. |
| Boiling Range, °C: | N.I. - N.I. | Auto-Ignition Temperature, °C | Not Established |
| Minimum Flash Point, °C: | 93.3 | Vapor Pressure, mmHg: | No Information |
| Evaporation Rate: | Slower Than n-Butyl Acetate | Flash Method: | Seta Closed Cup |
| Vapor Density: | Heavier Than Air | Flammability: | No Information |
| Combustibility: | Does not support combustion | | |

(See "Other information" Section for abbreviation legend)

(If product is an aerosol, the flash point stated above is that of the propellant.)

10. Stability and Reactivity

STABILITY: Stable under recommended storage conditions.

CONDITIONS TO AVOID: Excessive heat and freezing.

INCOMPATIBILITY: Incompatible with strong bases and oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Normal decomposition products, i.e., CO_x, NO_x.

11. Toxicological Information

EFFECT OF OVEREXPOSURE - INHALATION: Under normal use conditions, this product is not expected to cause adverse health effects. During application and cure, this product releases methanol. Methanol may affect the brain or nervous system causing dizziness, headache or nausea. Inhalation of vapors in high concentration may cause mild irritation of respiratory system (nose, mouth, mucous membranes).

EFFECT OF OVEREXPOSURE - SKIN CONTACT: Under normal use conditions, this product is not expected to cause adverse

health effects. Prolonged or repeated contact with skin may cause mild irritation.

EFFECT OF OVEREXPOSURE - EYE CONTACT: Under normal use conditions, this product is not expected to cause adverse health effects. Direct eye contact may cause irritation.

EFFECT OF OVEREXPOSURE - INGESTION: Under normal use conditions, this product is not expected to cause adverse health effects. Single dose oral toxicity is very low. Amounts ingested incidental to industrial handling are not likely to cause injury; however, ingestion of large amounts may cause injury. Ingestion may result in obstruction when material hardens.

CARCINOGENICITY: No Information

EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS: Repeated or prolonged exposure may cause irritation of eyes and skin. A mixture of diisodecyl phthalate and diisononyl phthalate has been tested in a two-generation toxicity study in laboratory animals. No effects on reproductive parameters were seen. However, a small but statistically significant increase in early offspring mortality was seen at high oral doses. The significance of this to humans is uncertain. Trimethoxyvinylsilane may cause heart muscle damage, anemia and lung, liver and kidney damage.

PRIMARY ROUTE(S) OF ENTRY: Inhalation, Skin Contact

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

| <u>CAS-No.</u> | <u>Chemical Name</u> | <u>Oral LD50</u> | <u>Dermal LD50</u> | <u>Vapor LC50</u> |
|----------------|------------------------------|------------------|---------------------|-------------------|
| 471-34-1 | Calcium Carbonate | 6450 mg/kg Rat | >2000 mg/kg Rat | >20 mg/L |
| 68515-49-1 | Proprietary Phthalate Esters | >60000 mg/kg Rat | 16000 mg/kg Rabbit | >12.54 mg/L Rat |
| 1317-65-3 | Limestone | 6450 mg/kg Rat | >2000 mg/kg | >20 mg/L |
| 13463-67-7 | Titanium dioxide | >10000 mg/kg Rat | >5000 mg/kg Rabbit | >20 mg/L |
| 2768-02-7 | Trimethoxyvinylsilane | 11000 mg/kg Rat | 3259.2 mg/kg Rabbit | >20 mg/L |
| 68515-48-0 | Proprietary Phthalate Esters | 2550 mg/kg Rat | >3160 mg/kg Rabbit | > 4.4 mg/L Rat |

N.I. = No Information

12. Ecological Information

ECOLOGICAL INFORMATION: Ecological injuries are not known or expected under normal use.

13. Disposal Information

DISPOSAL INFORMATION: This product does not meet the definition of a hazardous waste according to U.S. EPA Hazardous Waste Management Regulation, 40 CFR Section 261. Dispose as hazardous waste according to all local, state, federal and provincial regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste. Liquids cannot be disposed of in a landfill.

14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No Information

| | |
|---------------------------|----------------|
| DOT UN/NA Number: | N.A. |
| DOT Proper Shipping Name: | Not Regulated. |
| DOT Technical Name: | N.A. |
| DOT Hazard Class: | N.A. |
| Hazard SubClass: | N.A. |
| Packing Group: | N.A. |

GHS03



GHS06



GHS07



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

DAP believes the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS. Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.