



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® CAULK-BE-GONE® Latex Caulk Remover

PRODUCT DESCRIPTION

DAP® CAULK-BE-GONE® Latex Caulk Remover is specially formulated to soften most types of latex caulks and sealants for quick and easy removal. The fast-acting formula works in as little as two hours. CAULK-BE-GONE® is an easy-to-use green gel that stays where applied and has a fresh scent.



PACKAGING	COLOR	UPC
5.5 fl oz (162 mL)	Green Gel	7079818025

KEY FEATURES & BENEFITS

- Softens caulk for easy removal
- Removes most types of latex caulks and sealants
- Fast-acting, gel formula
- Fresh scent
- Easy water clean-up

FOR BEST RESULTS

- Product does not work on silicone, polyurethane or other non-latex based caulks/sealants.
- To avoid substrate damage, check for compatibility prior to use by testing a small, inconspicuous area.
- Do not use on refinished porcelain, soft plastics, vinyl, ABS plastic tubs/shower enclosures. Some fiberglass, other plastics or refinished surfaces may be affected.
- If possible, use painter's masking tape to mask the area adjacent to the old caulk being removed.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

- If caulk remover makes contact with wallpaper or painted/coated surfaces, wipe off immediately as it will soften them.
- Thicker caulk beads and painted caulk may take longer to soften or require multiple applications.
- Product cleans up with soap and water.

APPLICATION

Product Application

1. Remove cap and cut nozzle at 45° angle to desired bead size.
2. Apply the same size bead of CAULK-BE-GONE® Remover over bead of old caulk/sealant, being careful not to extend beyond the area of caulk/sealant being removed.
3. Allow CAULK-BE-GONE® Remover to set until old caulk becomes soft (at least 2 hours but no longer than 6 hours per application). Repeated applications may be needed for thicker beads of caulk.
4. Remove softened caulk with a plastic scraper or caulk removal tool.
5. Remove any remaining sealant film with a plastic scraper or soft plastic abrasive pad.
6. Thoroughly clean up area with soap and water. Use rubbing alcohol to remove any residue prior to applying new caulk/sealant. Area should be dry before applying new caulk/sealant.
7. Follow caulk/sealant manufacturer's instructions for applying sealant.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Typical Uncured Physical Properties	
Appearance/Consistency	Smooth green gel
Volatile	Water & solvent
Weight (% Solids)	2.5%
Odor	Fresh, clean scent
Application Temp Range	40-80°F
Clean Up	Water
Flash Point	>212°F
Freeze Thaw Stability (ASTM 1183)	Passes 5 cycles
Shelf Life	12 months unopened

CLEAN UP & STORAGE

Product cleans up from surfaces, hands and tools with soap and water. Reseal tube with cap and store in a cool, dry place for future use.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

SAFETY

See product label or Safety Data Sheet (SDS) for health and safety information. You can request a SDS sheet by visiting our website at dap.com or calling 888-DAP-TIPS.

WARRANTY

LIMITED WARRANTY: If product fails to perform when used as directed, within one year of date of purchase, call 888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP Products Inc. will not be responsible for incidental or consequential damages.

COMPANY IDENTIFICATION

Manufacturer: DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call 888-DAP-TIPS or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com