



Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-675-2100 or 800-543-3840

Revised: 7/26/2017

DAP® Vinyl Spackling

- Ready to use
- Interior Use

Packaging: 1/2 pint tub (236 mL), 1 pint tub (473 mL), 1 quart tub (946 mL), 1 gallon tub (3.78L)

Color: White

UPC Numbers: 70798 12130, 70798 12132, 70798 12133

Company Identification:

Manufacturer: DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call 888-DAP-TIPS or visit dap.com & click on “Ask the Expert”

Order Information: 800-327-3339

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com.

Product Description:

DAP® Vinyl Spackling is a ready mixed, easy-to-use patching material used to fill holes and cracks and treat surfaces prior to painting. The product has a smooth working consistency and sands easily. Recommended for interior use only.

Suggested Uses:

Ideal for filling holes, cracks and defects on:

- Drywall

Surface Preparation & Application:

- Surface must be clean, dry and free of foreign material.
- Stir before use. Apply with a clean putty knife.
- For a smoother finish, dip putty knife in water and lightly smooth spackling.
- For repairs deeper than 1/8”, apply two or more layers allowing spackling to dry between applications.
- May be sanded or painted in 3 to 6 hours depending on temperature, humidity and depth of fill. Wet sanding is recommended to avoid generation of dust.
- Clean tools immediately with water.

For Best Results:

- Do not use on floors or as caulk, sealant or joint filler over cracks and joints where expansion and contraction may occur.
- **DO NOT USE AS A SKIM COAT.**
- If a textured finish is desired, add clean sand to spackling compound prior to application.
- Do not use for tuck pointing applications on brick.
- For larger areas to be patched on bare concrete, use a latex fortified Portland cement-based dry mix.

Typical Physical & Chemical Characteristics:

Consistency:	Paste
Vehicle:	Latex
Volatile:	Water
Filler:	Inert Filler
Odor:	Very Mild Latex
Weight/Gallon:	15.5 ± .2 Pounds
Solids:	76% by weight
Application Temperature:	50°F Minimum
Service Temperature:	0°F to 150°F
Shelf Life:	1 Year
Freezing:	Freeze/Thaw Stable 5 Cycles at 0°F
Drying Time:	3 to 6 hours depending on temperature and relative humidity and depth of fill.
Painting:	Takes either oil or latex-base paint when dry.
SDS No.:	00010405001

Clean Up & Storage:

Wash tools immediately after use with water. Be sure container is closed and tightly sealed. Store in a cool, dry place.

Safety:

See product label and Safety Data Sheet (SDS) for safety information. You can request an SDS by visiting our website at www.dap.com or by calling 888-DAP-TIPS.

Satisfaction Guaranteed:

If product fails to perform as directed, within one year from the date of purchase, call 1-888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP will not be responsible for incidental or consequential damages.