

	<h1>Safety Data Sheet</h1>	<p>24 Hour Emergency Phone Numbers Medical/Poison Control: In U.S.: Call 1-800-222-1222</p> <p>Outside U.S.: Call your local poison control center</p> <p>Transportation/National Response Center:</p> <p style="text-align: center;">1-800-535-5053 1-352-323-3500</p> <p>NOTE: The National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.</p>
---	----------------------------	---

IMPORTANT: Provide this information to employees, customers, and users of this product. Read this SDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this MSDS are further described in Section 16.

1. Identification

This Safety Data Sheet is available in American Spanish upon request.
 Los Datos de Seguridad pueden obtenerse en Espanol si lo requiere.

Product Name:	Spackling Paste (Ready To Use)	Revision Date:	6/19/2015
Product UPC Number:	10200, 10202, 10204	Supercedes Date:	New SDS
Product Use/Class:	Spackling Compound	SDS No:	00071080001
Manufacturer:	DAP Products Inc. 2400 Boston Street Suite 200 Baltimore, MD 21224-4723 888-327-8477 (non - emergency matters)		
Preparer:	Regulatory Department		

2. Hazards Identification

EMERGENCY OVERVIEW: Product dust may be irritating to eyes, skin and respiratory system. Removal of this product after use or by dry sanding will generate dust and exposure to this dust may be irritating to the eyes, ears, nose and mouth. May cause irritation to the respiratory tract.

GHS Classification

Acute Tox. 4 Inhalation, Carc. 1A, Carc. 2, Eye Irrit. 2, Skin Irrit. 2

Symbol(s) of Product



Signal Word

Danger

GHS HAZARD STATEMENTS

Skin Irritation, category 2

H315

Causes skin irritation.

Eye Irritation, category 2	H319	Causes serious eye irritation.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
Carcinogenicity, category 1A	H350	May cause cancer. Classified as carcinogenic Category 1 on the basis of epidemiological and/or animal data. Mixtures are classified as carcinogenic when at least 1 ingredient has been classified as carcinogenic and is present at 0.1% or above. Routes of exposure are dependant on ingredient form.
Carcinogenicity, category 2	H351	Suspected of causing cancer. Classified as Category 2 based on limited evidence on human and/or animal studies. Mixtures with concentrations of suspected carcinogens ingredients at concentration present between 0.1% and 1.0% labelling the SDS will be optional depending on authorities. If Category 2 carcinogenic present at a concentration of 1% or above labelling the SDS will be expected. Routes of exposure are dependant on ingredient form.

3. Composition/Information on Ingredients

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
Limestone	1317-65-3	50-75	GHS03	H270
Attapulgate	12174-11-7	1.0-2.5	GHS03-GHS07	H270-332
Clay	1332-58-7	1.0-2.5	GHS03	H270
Quartz	14808-60-7	0.1-1.0	GHS03-GHS07	H270-302

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

4. First-aid Measures

FIRST AID - INHALATION: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

FIRST AID - SKIN CONTACT: Wash skin with soap and water for 15 minutes. Get medical aid if symptoms persist.

FIRST AID - EYE CONTACT: In case of contact, immediately flush eyes with large quantities of water for at least 15 minutes until irritation subsides. Get medical attention immediately.

FIRST AID - INGESTION: If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately.

5. Fire-fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: 465 <undefined>

SPECIAL FIREFIGHTING PROCEDURES: Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam

6. Accidental Release Measures

ENVIRONMENTAL MEASURES: No Information

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations.

7. Handling and Storage

HANDLING: KEEP OUT OF REACH OF CHILDREN! DO NOT TAKE INTERNALLY. Use only with adequate ventilation. Ensure fresh air entry during application and drying. Do not breathe dust. Removal of this product after use will result in the generation of Dust. If dry-sanded, exposure to dust may result in the build-up of material in eyes, ears, nose, and mouth which may cause irritation. While dry sanding, use of a NIOSH-approved dust mask is recommended. Wash thoroughly after handling.

STORAGE: Avoid excessive heat and freezing. Do not store at temperatures above 120 degrees F. Store away from caustics and oxidizers. Keep containers tightly closed.

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
Limestone	N.E.	N.E.	15 mg/m ³ TWA total dust, 5 mg/m ³ TWA respirable fraction	N.E.
Attapulgite Clay	N.E. 2 mg/m ³ TWA particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	N.E. N.E.	15 mg/m ³ TWA total dust, 5 mg/m ³ TWA respirable fraction	N.E. N.E.
Quartz	0.025 mg/m ³ TWA respirable fraction	N.E.	N.E.	N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation
Sk = Skin Sensitizer N.E. = Not Established

Personal Protection



RESPIRATORY PROTECTION: When concentrations exceed the exposure limits specified, use of a NIOSH-approved dust, mist and fume respirator is recommended. Where the protection factor of the respirator may be exceeded, use of a full facepiece, supplied air, or Self Contained Breathing Apparatus (SCBA) may be necessary. If concentrations exceed the exposure limits specified, use of a NIOSH-approved supplied air respirator is recommended. Where the protection factor is exceeded, use of a Self Contained Breathing Apparatus (SCBA) may be necessary. Use an approved NIOSH/OSHA respirator if dry sanded. National Institute for Occupational Safety and Health (NIOSH) has recommended that the permissible exposure limit be changed to 50 micrograms respirable free silica per cubic meter of air (0.05 mg/m³) as determined by a full shift sample up to 10-hour work shift. A respiratory protection program that meets the OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.



SKIN PROTECTION: Wear protective gloves.



EYE PROTECTION: Safety glasses with side-shields.



OTHER PROTECTIVE EQUIPMENT: Not required under normal use.



HYGIENIC PRACTICES: Remove and wash contaminated clothing before re-use.

9. Physical and Chemical Properties

Appearance:	White to Off-White	Physical State:	Paste
Odor:	Slight	Odor Threshold:	Not Established
Density, g/cm³:	1.77 - 1.78	pH:	Between 7.0 and 12.0
Freeze Point, °C:	Not Established	Viscosity (mPa.s):	Not Established
Solubility in Water:	Not Established	Partition Coeff., n-octanol/water:	Not Established
Decomposition Temperature, °C:	Not Established	Explosive Limits, %:	N.I. - N.I.
Boiling Range, °C:	N.I. - N.I.	Auto-Ignition Temperature, °C	Not Established
Minimum Flash Point, °C:	93.3	Vapor Pressure, mmHg:	No Information
Evaporation Rate:	Slower Than n-Butyl Acetate	Flash Method:	Seta Closed Cup
Vapor Density:	Heavier Than Air	Flammability:	No Information
Combustibility:	Does not support combustion		

(See "Other information" Section for abbreviation legend)

(If product is an aerosol, the flash point stated above is that of the propellant.)

10. Stability and Reactivity

STABILITY: Stable under normal conditions.

CONDITIONS TO AVOID: Do not breathe dust. Avoid dust formation in confined areas. Excessive heat and freezing.

INCOMPATIBILITY: Incompatible with strong bases and oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Normal decomposition products, i.e., CO_x, NO_x.

11. Toxicological Information

EFFECT OF OVEREXPOSURE - INHALATION: Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes). Prolonged, repeated, or high exposures may cause irritation to the respiratory tract (nose, mouth, mucous membranes). Dust from dry sanding may cause eye, skin, nose, throat and respiratory tract irritation.

EFFECT OF OVEREXPOSURE - SKIN CONTACT: Under normal use conditions, this product is not expected to cause adverse health effects. Prolonged or repeated contact with skin may cause mild irritation. May cause skin irritation in susceptible persons.

EFFECT OF OVEREXPOSURE - EYE CONTACT: Under normal use conditions, this product is not expected to cause adverse health effects. Direct eye contact may cause irritation. May cause eye irritation.

EFFECT OF OVEREXPOSURE - INGESTION: Under normal use conditions, this product is not expected to cause adverse health effects. Single dose oral toxicity is very low. Amounts ingested incidental to industrial handling are not likely to cause injury; however, ingestion of large amounts may cause injury. Ingestion may result in obstruction when material hardens.

CARCINOGENICITY: No Information

EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS: Contains Crystalline Silica which has been determined to be carcinogenic to humans (1) by IARC when in respirable form. Risk of cancer depends upon duration and level of inhalation exposure to dust from sanding the dried paint or spray mist. The International Agency for Research on Cancer (IARC) has determined that crystalline silica in the form of quartz or cristobalite that is inhaled from occupational sources is carcinogenic to humans (Group 1- carcinogenic to humans). Refer to IARC Monograph 68, Silica, Some Silicates and Organic Fibres (published in June 1997) in conjunction with the use of these materials. The National Toxicology Program (NTP) classifies respirable crystalline silica as "known to be a human carcinogen". Refer to the 9th Report on Carcinogens (2000). The American Conference of Governmental Industrial Hygienists (ACGIH) classifies crystalline silica, quartz, as a suspected human carcinogen (Group A2). Breathing dust containing respirable crystalline silica may not cause noticeable injury or illness even though permanent lung damage may be occurring. Inhalation of dust may have the following serious chronic health effects: Excessive inhalation of respirable dust can cause pneumoconiosis, a respiratory disease, which can result in delayed, progressive, disabling and sometimes fatal lung injury. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness and reduced pulmonary function. Smoking exacerbates this disease. Individuals with pneumoconiosis are predisposed to develop tuberculosis. There is some evidence that breathing respirable crystalline silica or the disease silicosis is associated with an increased incidence of significant disease endpoints such as scleroderma (an immune system disorder manifested by fibrosis of the lungs, skin and other internal organs) and kidney disease. Prolonged or repeated inhalation of dust may cause lung damage.

PRIMARY ROUTE(S) OF ENTRY: Inhalation, Skin Absorption, Skin Contact

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
1317-65-3	Limestone	6450 mg/kg Rat	>2000 mg/kg	>20 mg/L
12174-11-7	Attapulgite	N.I.	N.I.	20 mg/kg
1332-58-7	Clay	>5000 mg/kg Rat	>5000 mg/kg Rat	>20 mg/L
14808-60-7	Quartz	500 mg/kg Rat	>2000 mg/kg	>20 mg/L

N.I. = No Information

12. Ecological Information

ECOLOGICAL INFORMATION: Ecological injuries are not known or expected under normal use.

13. Disposal Information

DISPOSAL INFORMATION: This product does not meet the definition of a hazardous waste according to U.S. EPA Hazardous Waste Management Regulation, 40 CFR Section 261. Dispose as hazardous waste according to all local, state, federal and provincial regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste.

14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No Information

DOT UN/NA Number:	N.A.
DOT Proper Shipping Name:	Not Regulated.
DOT Technical Name:	N.A.
DOT Hazard Class:	N.A.
Hazard SubClass:	N.A.
Packing Group:	N.A.

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Acute Health Hazard, Chronic Health Hazard

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

TOXIC SUBSTANCES CONTROL ACT:

All ingredients in this product are either on TSCA inventory list, or otherwise exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

CALIFORNIA PROPOSITION 65 CARCINOGENS AND REPRODUCTIONAL TOXINS**CALIFORNIA PROPOSITION 65:** No Information**International Regulations: As follows -****CANADIAN WHMIS:**

This SDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class Consumer Commodity**16. Other Information****Revision Date:** 6/19/2015 **Supersedes Date:** New MSDS**Reason for revision:** HazCom2012/GHS Conversion**Datasheet produced by:** Regulatory Department**HMIS Ratings:**

Health:	1	Flammability:	1	Reactivity:	0	Personal Protection:	X
----------------	---	----------------------	---	--------------------	---	-----------------------------	---

VOC Less Water Less Exempt Solvent, g/L:24.7

VOC Material, g/L:12

VOC as Defined by California Consumer Product Regulation, Wt/Wt%:0.0

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H270 May cause or intensify fire; oxidiser.
H302 Harmful if swallowed.
H332 Harmful if inhaled.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS03



GHS07



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

DAP believes the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS. Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.