



# Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224  
Phone: 410-675-2100 or 800-543-3840

Revised: 6/15/2005

## DAP®/Bondex® Spackling Paste

- Ready to use
- Sands easily
- Interior use

**Packaging:** 1/2 pint tub, 1 pint tub, 1 quart tub, 1 gallon tub  
**Color:** White  
**UPC Numbers:** 10200, 10202, 10204, 10205

### Company Identification:

**Manufacturer:** DAP Inc., 2400 Boston St., Baltimore, Maryland 21224  
**Usage Information:** DAP HELPLINE: 888-DAP-TIPS, 9:00 am to 7:00 pm EST.  
**Order Information:** 800-327-3339  
**Fax Number:** 410-534-2650  
Also, visit the DAP website at [www.dap.com](http://www.dap.com).

### Product Description:

DAP®/Bondex® Spackling Paste is a ready mixed, easy-to-use professional grade, patching material used to fill holes and cracks and treat surfaces prior to painting. The product has a smooth working consistency, dries quickly, is non-shrinking and sands easily. Recommended for interior use only.

### Suggested Uses:

Ideal for filling and concealing small cracks, nail holes and blemishes in:

- Plaster
- Wallboard
- Wood

### Surface Preparation & Application:

- Surface must be clean, dry and free of dust and particles. Use sandpaper to dull glossy surfaces before repairing.
- Stir thoroughly before use. Apply with a clean putty knife.
- For a smoother finish, dip putty knife in water and lightly smooth spackling.
- For repairs deeper than 1/4", apply two or more layers allowing to dry between applications.
- Spackling Paste can be sanded or painted 1-5 hours after application, depending on temperature, humidity and depth of fill. Wet sanding is recommended to avoid generation of dust.
- Clean tools immediately with water.

**Physical & Chemical Characteristics:**

Consistency:	Paste
Vehicle:	Vinyl acetate latex polymer
Volatile:	Water
Filler:	Inert filler
Odor:	Slight acetate
Weight/Gallon:	14.8 +/- .2 pounds
Solids:	70.5 +/- 1% by weight
Application Temperature:	50°F Minimum
Service Temperature:	0°F to 150°F
Shelf Life:	1 Year
Freezing:	Freeze/Thaw stable 5 cycles
Drying Time:	1 to 5 hours depending on temperature, relative humidity and depth of fill.
Painting:	Takes either oil or latex-base paint.
MSDS No.:	71080

**Clean Up:**

Wash tools immediately after use with water. Be sure container is closed and tightly sealed. Store in a cool, dry place.

**Safety:**

See product label and Material Safety Data Sheet (MSDS) for safety information. You can request an MSDS by visiting our website at [www.dap.com](http://www.dap.com) or by calling 888-DAP-TIPS.

**Warranty Information:**

If you are not satisfied with this product's performance when used as directed, return used container and sales receipt to DAP Inc., Technical Customer Service, 2400 Boston Street, Suite 200, Baltimore, MD 21224 for product replacement or sales price refund. DAP will not be liable for incidental or consequential damages.