



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## DAP® PLASTIC WOOD-X™ ALL PURPOSE WOOD FILLER with DRYDex® Dry Time Indicator

### PRODUCT DESCRIPTION

DAP® PLASTIC WOOD-X™ All Purpose Wood Filler with DRYDex® Dry Time Indicator goes on pink and dries natural for an invisible repair. It is a high quality, latex-based wood filler formulated to create a surface and body that looks and acts like real wood. It can be used to repair cracks, gouges, holes and other surface defects on furniture, woodwork, molding, cabinets, paneling, plywood, windows, doors and painted surfaces. This easy-to-use filler is low in odor and cleans up with water. The thick, knife-grade formula can be molded and sculpted making it ideal for corners, vertical and unsupported surfaces. It offers easy handling by spreading smoothly and evenly. When dry, DAP PLASTIC WOOD-X All Purpose Wood Filler can be sanded, cut, planed, drilled, nailed or screwed, stained and painted. It is shrink, crack and crumble resistant and provides strong nail and screw anchoring. Interior/exterior use.



PACKAGING	COLOR	UPC
5.5 oz	Natural	7079800540
8 oz	Natural	7079800541
16 oz	Natural	7079800542
32 oz	Natural	7079800543
Kit	Natural	7079800596

### KEY FEATURES & BENEFITS

- Goes on PINK and dries NATURAL
- Easy-to-use, latex-based formula
- Water clean-up & low odor
- Looks and acts like real wood
- Can be sanded, planed, cut, drilled, screwed & nailed
- Shrink, crack and crumble resistant
- Thick, knife-grade formula can be molded & sculpted
- Ideal for corners and vertical surfaces
- Easy handling – spreads smoothly and evenly
- Stainable & paintable



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

- **Strong nail & screw anchoring**
- **Interior/Exterior use**

## SUGGESTED USES

For filling nail holes, gouges, cracks, scratches & imperfections on furniture, woodwork, molding, cabinets, paneling, plywood, windows, doors and painted surfaces.

## APPLICATION

1. Surface must be clean, dry and free of dirt, oil and loose material. De-gloss surface if necessary for best adhesion.
2. Surface, wood filler and air temperature should be above 40°F.
3. If staining, test wood filler with desired stain on scrap wood before filling to ensure desired stain color. Stain before filling with wood filler, then use stain to develop desired final finish.
4. Stir product with putty knife before application.
5. Apply wood filler into area to be filled. Press firmly into place using a putty knife or tool.
6. Avoid overspreading filler on surrounding surfaces. Overfill slightly to allow for sanding and settling. Most repairs require just one fill. Larger and deeper holes may require more than one application.
7. For larger and deeper holes, apply thin layers to build up thick sections. Allow wood filler to dry before applying next layer.
8. Allow to dry thoroughly before sanding: approximately 2 to 6 hours for shallow fills up to 1/8" and 36 hours for deeper fills 1/4" and over. Sand with medium sandpaper.
9. May be painted with latex-based paint immediately after sanding, or after 12 hours if using an oil-based paint.
10. Exterior applications must be coated with latex or oil-based paint or solid color stain.
11. If wood is to be stained, stain before filling with wood filler. Then use stain to develop desired final finish.
12. Reseal container tightly with lid.
13. Keep from freezing.

## TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Consistency	Stiff Paste
Vehicle	Latex Polymer
Filler	Inert Pigment
Volatile	Water



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

Solids	80% by weight
Odor	Mild
Shelf Life	12 months
Application Temperature	Above 40°F
Dry Time	Depending on temperature and humidity: 2 to 6 hours in shallow fills up to 1/8"; up to 36 hours in deep fills 1/4" and over

## CLEAN UP & STORAGE

Wipe off excess filler from surface and tools with a damp cloth before material dries. Dried wood filler must be sanded or scraped away. Reseal tightly with lid after each use. Store in a cool, dry place away from extreme heat or cold

## SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at [dap.com](http://dap.com) or by calling **888-DAP-TIPS**.

## WARRANTY

### Limited Warranty:

If product fails to perform as directed, within one year from the date of purchase, call 888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP Products Inc. will not be responsible for incidental or consequential damages.

## COMPANY IDENTIFICATION

**Manufacturer:** DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

**Usage Information:** Call **888-DAP-TIPS** or visit [dap.com](http://dap.com) & click on "Ask the Expert"

**Order Information:** 800-327-3339 or [orders@dap.com](mailto:orders@dap.com)

**Fax Number:** 410-558-1068

**Also, visit the DAP website at [dap.com](http://dap.com)**