

2 15/32<sup>1</sup> (62 mm) 5 11/32" (136 mm) \*1/2\*-14 threaded tub spout with slip-on adapter included

Full Spray 2.0 GPM Max.


RP70537▲

3 23/32"

(95 mm)

- 6 3/32"-(155 mm)

▲ Designate Proper Finish Suffix



## **TUB/SHOWER FAUCET**

■ Lever Handle TubShower, model P188775

# **STANDARD SPECIFICATIONS**

- Slip-on tub spout
- Tub/Shower. Requires 1 1/2" wall cavity
- Valve has back-to-back installation capability
- Forged brass body
- Field adjustable means to limit handle rotation into hot water zone
- Temperature control to rotate a maximum of 120° from full cold to the maximum temperature
- Single Handle
- Pressure Balance
- Temperature Only Controlled with Handle

## **WARRANTY**

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes; or, for commercial users, for 5 years from the date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.

## **COMPLIES WITH:**

- ASME A112.18.1 / CSA B125.1
- Indicates compliance to ICC/ANSI A117.1 Valve control only
- ASSE 1016

