



GREAT STUFF™ MULTIPURPOSE BLACK INSULATING FOAM SEALANT

MULTIPURPOSE SOLUTION FOR INDOOR,
OUTDOOR, MARINE & AUTOMOTIVE USE



GREAT STUFF™ Multipurpose Black¹ is a ready-to-use, minimal expansion polyurethane insulating foam sealant that fills, seals and insulates gaps up to 3/4 inch. It expands to take the shape of gaps and cracks, creating a long-lasting, airtight and water-resistant seal.

Black in color, it naturally blends into the surrounding environment and is specifically formulated for both indoor and outdoor use.² This multipurpose formulation can be used to fill gaps and cracks around the home, and in marine and automotive applications.

GREAT STUFF™ Multipurpose Black Insulating Foam Sealant is a simple, inexpensive way to minimize unwanted air flow and reduce condensation, and it can be used in many applications.



¹ Read all instructions and (Material) Safety Data Sheet ((M)SDS) carefully before use.

² Skin of cured foam can discolor if exposed to natural light. Paint or coat foam for best results.

³ 70°F ± 5°F and 50 ± 5% RH, 1 inch bead diameter, 6 inch length. Cure rate is dependant on temperature, humidity and size of foam bead.

Features and benefits at a glance

- Multipurpose Interior/Exterior Use²
- Fills, seals and insulates gaps up to 3/4 inch
- Black color blends naturally into the surrounding environment
- Allows cured foam to hide well and not be noticeable in shadows
- Expands to take the shape of gaps, creating a long-lasting, airtight and water-resistant seal
- Helps improve energy efficiency by forming an airtight seal in gaps and cracks
- Helps reduce unwanted noise and vibration
- Is a simple way to minimize unwanted air flow and reduce condensation
- Adheres well to stone, eliminating the need for a caulk adhesive (depending on the project)
- Adheres well to rock, wood, metal, masonry, glass, and most plastics
- Cures quickly 5–15 minutes, trims in 60 minutes (moisture-cured)³
- All-direction dispensing
- Paintable, stainable, sandable
- UL Classified
- CCMC 13074-L

Where to use GREAT STUFF™ Black Multipurpose Insulating Foam Sealant:

- Interior and exterior air sealing projects – including, but not limited to, insulation board joints, stud penetrations, plumbing penetrations, foundation/sill junctions, chimney bases⁴ and eaves
- Small gaps and cracks in the attic or garage
- Air conditioning lines, refrigerant lines, gas lines – service penetrations
- Repair of masonry walls, sidewalks, and porches
- Outdoor landscaping applications
- RV and vehicle undercarriages
- HVAC applications
- Trailer/transportation repairs
- Marine sealing applications



RV applications



Marine applications



Around gas lines



Around HVAC

Note: GREAT STUFF™ Insulating Foam Sealants are not for use in aviation, or food/beverage contact, or as structural support in marine applications.

⁴ Do not expose cured foam to temperatures above 240°F (116°C).

Greatness comes in many forms

Did you know that the average U.S. home has a 1/2 mile of gaps and cracks?^{**} Seal them with GREAT STUFF™

Each GREAT STUFF™ Insulating Foam Sealant* is specially formulated to seal gaps and cracks to block air, moisture and even pests. Our comprehensive line of ready-to-use sealants is a simple, inexpensive money-saving solution for any do-it-yourself homeowner.

- **GREAT STUFF™ Gaps & Cracks*** — Insulating foam sealant that expands to seal and insulate gaps up to one inch.
- **GREAT STUFF™ Window & Door*** — Minimally expanding foam that seals between a window or door frame and its rough opening.
- **GREAT STUFF™ Fireblock*** — Impedes spread of fire and smoke through service penetrations.^{***}
- **GREAT STUFF™ Big Gap Filler*** — Insulating foam sealant that expands to seal and insulate gaps up to three inches.
- **GREAT STUFF™ Pestblock*** — Blocks pests out of the home by eliminating points of entry.
- **GREAT STUFF™ Black*** — Multipurpose foam fills gaps and cracks up to 3/4 inch.



In the U.S.
The Dow Chemical Company
 Dow Building Solutions
 200 Larkin Center
 Midland, MI 48674

In Canada
Dow Chemical Canada ULC
Dow Building Solutions
 2400, 215 – 2 Street S.W.
 Calgary, Alberta T2P 1M4

For Technical Information:
1-866-583-BLUE (2583) (English)
1-800-363-6210 (French)

www.dowgreatstuff.com
www.dowbuildingsolutions.com

For Sales Information:
1-800-232-2436 (English)
1-800-565-1255 (French)

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. **NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.** The buyer assumes all risks as to the use of the material. Buyer's exclusive remedy or any claim (including without limitations, negligence, strict liability, or tort) shall be limited to the refund of the purchase price of the material. Failure to strictly adhere to any recommended procedures shall release The Dow Chemical Company, and its subsidiaries, of all liability with respect to the materials or the use thereof. The information herein is not intended for use by non-professional designers, applicators or other persons who do not purchase or utilize this product in the normal course of their business.

Dow Polyurethane Foam Insulation and Sealants

CAUTION: When cured, these products are combustible and will burn if exposed to open flame or sparks from high-energy sources. Do not expose to temperatures above 240°F (116°C). For more information, consult (Material) Safety Data Sheets ((M)SDS), call Dow at 1-866-583-BLUE (2583) or contact your local building inspector. In an emergency, call 1-989-636-4400 in the U.S. or 1-519-339-3711 in Canada. When air sealing buildings, ensure that combustion appliances, such as furnaces, water heaters, wood burning stoves, gas stoves and gas dryers are properly vented to the outside. See website: <http://www.epa.gov/iaq/homes/hjp-ventilation.html>. In Canada visit: <http://archive.nrc-cnrc.gc.ca/eng/ibp/irc/bsi/83-house-ventilation.html>.

GREAT STUFF™ Insulating Foam sealant and adhesive products contain isocyanate and a flammable blowing agent. Read all instructions and (Material) Safety Data Sheet ((M)SDS), carefully before use. Eliminate all sources of ignition before use. Cover all skin. Wear long sleeves, gloves, and safety glasses or goggles. Not for use in aviation, or food/beverage contact, or as structural support in marine applications. Provide adequate ventilation or wear proper respiratory protection. Contents under pressure. Not to be used for filling closed cavities or voids such as behind walls and under tub surrounds; improper use of the product could result in the accumulation of flammable vapors and/or uncured material. Failure to follow the warnings and instructions provided with the product, and/or all applicable rules and regulations, can result in injury or death.

Building and/or construction practices unrelated to building materials could greatly affect moisture and the potential for mold formation. No material supplier including Dow can give assurance that mold will not develop in any specific system.

* Read all instructions and (Material) Safety Data Sheet ((M)SDS) carefully before use.

** www.energystar.gov

*** Intended for use in residential application to maintain the continuity of an approved fire block material.