

4' Strip Light, Linkable

LED 54573161

45 W 5000 Im Strip Light

Specifications




The ETi 4' Linkable LED Strip Light offers exceptional performance as a high quality replacement for traditional fluorescent light sources. Lasting more than 5 times longer than fluorescent alternatives, these strip lights reduce energy and maintenance costs. A special benefit of these ETi Strip Lights is the linking feature - multiple fixtures can be connected using a linking cable or end-to-end connector, both included. Engineered to be installed as either a plug-in or direct wire fixture, an optional mounting plate (Item 54657102) is also available. The strip lights are 120v, UL listed for use in damp locations, and suitable for installations from -4° F to 95° F. Warranty 5 years.

KEY FEATURES & BENEFITS

- Installation as Portable/Plug In or Direct Wire
- 5000 Lumens & 45 Watts
- Linkable via cable or end-to-end-connector
- 120-277 Volt, 5000K, 80 CRI
- cULus Listed for Damp Locations
- Rated life 50,000 hours (45.6 years)

FIXTURE DIMENSIONS



This light source meets restrictions on hazardous substances.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, please see www.etissl.com/fcc15b

APPLICATION INFORMATION

Designed to be used anywhere a traditional fluorescent fixture is used. Typically used in workshops, garages and utility rooms. Other common applications in commercial, office, retail, restaurants, schools, hospitals and hotel/motel locations.



855 -384 -7754 www.etissl.com

4' Strip Light, Linkable

LED
54573161

SPECIFICATION DATA

Project _____

Item Number _____

Prepared by _____ Date _____

ORDERING INFORMATION

| Item Number | Description | Wattage | Input Voltage (VAC) | Average Rated Life ¹ | Typical Lumens ² | CCT ³ | CRI ⁴ | Power Factor | R9 | Duv | CBCP | Beam | Operating Frequency |
|-------------|-----------------|---------|---------------------|---------------------------------|-----------------------------|------------------|------------------|--------------|----|--------|--------|-------|---------------------|
| 54573161 | LED STRIP LIGHT | 45 | 120-277 | 50,000 | 5000 | 5000K | 80 | 0.976 | 18 | 0.0011 | 1219.8 | 109.4 | 50/60Hz |

¹ Hours lifetime with 70% lumen maintenance

² Thermally stable typical lumens ($\pm 10\%$)

³ Thermally stable CCT ($\pm 10\%$)

⁴ Color rendering index/Ra

SHIPPING INFORMATION

| Item Number | Item UPC | Item Dimensions (L x W x H) | Item Weight (lbs) | Inner Pack Qty | Inner Carton Bar Code | Inner Carton Dimensions (L x W x H) | Inner Pack Weight (lbs) | Master Pack Qty | Master Carton Bar Code | Master Dimensions (H x L x W) | Master Pack Weight (lbs) |
|-------------|--------------|-----------------------------|-------------------|----------------|-----------------------|-------------------------------------|-------------------------|-----------------|------------------------|-------------------------------|--------------------------|
| 54573161 | 849489002804 | 2.28" x 48.03" x 1.81" | 2.82 | N/A | N/A | N/A | N/A | 12 | 50849489002809 | 9.53" x 50.24" x 8.31" | 36.33 |



ETI Solid State Lighting
720 Corporate Woods Parkway
Vernon Hills, IL 60061

855 -384 -7754 www.etissl.com