## Heavy duty grade power receptacles

Product description

3-pole, 3-wire non-grounding
20A, 125/250V/AC
60A, 125/250V/AC

10-20R

Design features

- Heavy gauge galvanized steel mounting strap for corrosion resistance
- For use with copper wire
- Accepts #14 - #10 AWG wire

805

Flush power receptacles (UL) (CSA) NOM 426

Rating A	V/AC	NEMA	Description	Color	Catalog no.		
20	125/250	10-20R	Flush mount power receptacle, side wire, matching plug 2836	V	☐ 805V	•	•

Listed to UL498, file no. E15058; CSA certified to CSA C22.2, no. 42; NOM certified

Heavy duty grade power receptacles

Product description

3-pole, 4-wire grounding
60A, 125/250V/AC

14-60R

Design features

- For use with copper or aluminum wire
- Accepts #4 - #10 AWG wire

60

Panel power receptacles (UL) (CSA) NOM 426

Rating A	V/AC	NEMA	Description	Color	Catalog no.		
60	125/250	14-60R	Panel mount power receptacle, matching plug S20	BK	☐ 60	•	•

Listed to UL498, file no. E15058; CSA certified to C22.2, no. 42; NOM certified

Compatible wallplates / standard size for panel mount power receptacles c(UL)us

Description	Color suffix	Catalog no.		
Nylon 2-Gang wallplate for one power receptacle	V, W	☐ 5169__	•	•
Stainless steel 2-Gang wallplate for one power receptacle	Stainless Steel	☐ 93223	•	•

Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: BK (Black), V (Ivory), Stainless Steel, W (White)

BK	V		W
(Black)	(Ivory)	(Stainless Steel)	(White)

Dimensional information: B-70 **Specification information:** Please visit www.eaton.com/wiringdevices
Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page G-21   RoHS compliant - Page G-21