





300 S. DAYTON ST. DAVISON, MI 48423 PH: 810-653-9626 FAX:810-654-2616

*This Part requires two clamps, part numbers 080-300 & 088-300. See additional drawings for information on these clamps.

Min/Max Temp.	-30/140 Degrees F	.X=
Pressure Tested	4.3 PSI	
Material	Flexible PVC 60 Duro Shore A	
Installation Torque	60" Lbs.	UNLESS
Conforms to ASTM	D5926, C1173	
Box Quantity	20	UNITS: INCH
Clamps used	300 Series	
		3RD AN

0.83 lbs.

DESCRIPTION: **TOLERANCES:** X= Fractional ± $.XX = \pm .060$ $.XXX = \pm .032$ $ANG. = \pm 0.5^{\circ}$ SS OTHERWISE SPECIFIED

Coupling 4" Plastic Socket x 4" Plastic/Cast Iron

1059-44

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FERNCO, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF FERNCO, INC. IS PROHIBITED.

DESIGNER: SCALE not to scale D. Brady ANGLE PROJECTION CHECKER: DATE: 3/31/2009 SHEET 1 OF 1 DO NOT SCALE DRAWING