



SysLite DUO - Because light quality is reflected in the quality of your work.



Jobsite lighting is more than just putting light in a room; it is about truly seeing the surface you are working on in the correct color without hot spots in the center. The Syslite DUO is a hardwired AC lighting solution with 8000 Lumens projecting an evenly diffused light over 180° with a color temperature of 5000 Kelvin. Designed for the jobsite, the Syslite DUO is impact and water resistant meeting IP 55 standards for dust and water intrusion. Optional tripod, ST DUO 200, provides a firm and stable base that is designed to withstand years of service in the field. Couple that with the LED service life of 10,000 hours, the Syslite DUO will provide unmatched lighting for many years to come

Illumination – Even and wide diffusion (180°) with a color temperature of 5,000 Kelvin brings the closest thing to natural light to the jobsite. 8,000 Lumens of dark-shattering light is provided by two 40 LED banks (80 LED total) rated for 10,000 hours (over 5 years of work (250 days (30 8 hours per day)).

Durability – IP 55 rating against dust and water intrusion coupled with a robust and tough exterior shell and more than ample interior sealing and heat shielding helping to ensure a jobsite-ready and tough light for years to come. All backed by the Festool-exclusive Service All-Inclusive warranty.

Flexibility – Compact, light, and equipped with top handle for easy transport, the Syslite DUO can be used on the floor, nearly any horizontal surface, hung off a nail or screw or project light with the optional adjustable tripod. Provided with a Systainer 3 to integrate with other Festool products or to be transported alone with maximum protection.







Specifications Illuminating Power 8,000 Lumens Color Temperature 5,000 Kelvin Color Rendering Index (CRI) 80 Light Diffusion Range 180° Housing Safety Class IP 55 Maximum Output 112 watts (120 V AC) LED Service Life 10,000 hours Cable Length 15.7 ft (4.8 m)		Syslite DU0
Color Temperature 5,000 Kelvin Color Rendering Index (CRI) 80 Light Diffusion Range 180° Housing Safety Class IP 55 Maximum Output 112 watts (120 V AC) LED Service Life 10,000 hours	Specifications	
Color Rendering Index (CRI) Light Diffusion Range Housing Safety Class IP 55 Maximum Output LED Service Life 80 180° 112 watts (120 V AC) 112 watts (120 V AC)	Illuminating Power	8,000 Lumens
Light Diffusion Range Housing Safety Class Maximum Output LED Service Life 180° IP 55 Maximum Output 112 watts (120 V AC) LED Service Life	Color Temperature	5,000 Kelvin
Housing Safety Class IP 55 Maximum Output 112 watts (120 V AC) LED Service Life 10,000 hours	Color Rendering Index (CRI)	80
Maximum Output 112 watts (120 V AC) LED Service Life 10,000 hours	Light Diffusion Range	180°
LED Service Life 10,000 hours	Housing Safety Class	IP 55
in the second se	Maximum Output	112 watts (120 V AC)
Cable Length 15.7 ft (4.8 m)	LED Service Life	10,000 hours
3	Cable Length	15.7 ft (4.8 m)
Weight 8.6 lbs (3.9 kg)	Weight	8.6 lbs (3.9 kg)

Syslite DUO	
Launch	September 12, 2016
Item number	769967
Price	\$300.00
Includes:	Systainer SYS 3 TLOC

Syslite DUO Set	
Launch	September 12, 2016
Item number	574657
Price	\$435.00
Includes:	ST DUO 200 Tripod (200038) Systainer SYS 3 TLOC

ACCESSORIES



Tripod ST DUO 200

Project light to the level you need with up to over 6.5' (2.0 m) of stand height with the robust and durable SYSLITE DUO Tripod. Features a tool-free, easy-on mounting fixture and adjustable cord management loop.

\$199.00 200 038





