


Safety Data Sheet

Revision Date: 1/15/2010



Health	1
Flammability	0
Physical hazards	0
Personal protection	

1. Product and company identification

Product name	Solder Wire, Flo-Temp "Lead Free" 1/8"
Forney SKUs	38050, 38051, 38052
Manufacturer	Forney Industries, Inc. 2057 Vermont Drive Fort Collins, CO 80525 Phone: 1-800-521-6038 Email: customerservice@forneyind.com Emergency Response Phone: 1-800-535-5053 International Emergency Response Phone: 352-323-3500

2. Hazards identification

Physical state	Solid.
Odor	None.
OSHA/HCS status	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Emergency overview	WARNING! Harmful if swallowed. Irritating to eyes, respiratory system and skin. Do not ingest. Avoid contact with eyes, skin and clothing. Contains material that may cause target organ damage, based on animal data. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.
Routes of entry	Inhalation. Ingestion.
<u>Potential acute health effects</u>	
Inhalation	Irritating to respiratory system.
Ingestion	Harmful if swallowed. Can cause target organ damage. Ingestion may cause gastrointestinal irritation and diarrhea.
Skin	Irritating to skin. Skin inflammation is characterized by itching, scaling, reddening or, occasionally, blistering.
Eyes	Irritating to eyes. Adverse symptoms may include the following: redness, itching, swelling, pain

2. Hazards identification (continued)

Potential chronic health effects

Chronic effects	Contains material that can cause target organ damage. Adverse symptoms may include the following: Tin: Prolonged or repeated exposure may cause benign pneumoconiosis (Stannosis). Copper: Other adverse effects: metal fume fever, coughing, headache, shortness of breath/breathing difficulty, anemia. Chronic effects: jaundice, ulcerations.
Target organs	Contains material which may cause damage to the following organs: kidneys, liver, upper respiratory tract, skin, eyes.
Carcinogenicity Mutagenicity	Not classified or listed by IARC, NTP, OSHA, EU and ACGIH. No conclusive data is available to indicate product or any component present at greater than 0.1% may cause heritable genetic effects.
Developmental effects	No conclusive data is available to indicate product or any component present at greater than 0.1% may cause developmental abnormalities.
Fertility effects	No conclusive data is available to indicate product or any component present at greater than 0.1% may impair fertility.
Medical conditions aggravated by over- exposure	Pre-existing digestive disorders and disorders involving any other target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

3. Composition/information on ingredients

<u>Name</u>	<u>CAS number</u>	<u>% by weight</u>
Tin	7440-31-5	80-100
Copper	7440-50-8	1-5

Any ingredient not listed in Section 3 is non-regulated or present in the product in concentrations below legal disclosure limits.

4. First aid measures

Eye contact	Check for and remove any contact lenses. Get medical attention if irritation occurs. Immediately flush eyes with running water for at least 30 minutes, keeping eyelids open.
Skin contact	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 15 minutes. Get medical attention if symptoms occur. Wash contaminated clothing before reuse. Clean shoes thoroughly before reuse. Seek medical attention if irritation persists. In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Inhalation	Get medical attention immediately. Move exposed person to fresh air. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Ingestion	Get medical attention immediately. Wash out mouth with water. Remove dentures if any. Move exposed person to fresh air. Keep person warm and at rest. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

4. First aid measures (continued)

Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wear suitable protective clothing, gloves and eye/face protection. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus.
-----------------------------------	---

5. Fire-fighting measures

Flammability of the product	No specific fire or explosion hazard.
Extinguishing media	
Suitable	Use an extinguishing agent suitable for the surrounding fire.
Not suitable	None known.
Special exposure hazards	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Hazardous combustion products	Metal oxide/oxides
Special remarks on fire hazards	Flammable in the presence of the following materials or conditions: open flames, sparks and static discharge and heat.
Special remarks on explosion hazards	Explosive in the presence of the following materials or conditions: open flames, sparks and static discharge and heat.
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Large spill	Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see section 1 for emergency contact information and section 13 for waste disposal.
Small spill	Move containers from spill area. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

7. Handling and storage

Handling	Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Avoid contact with eyes, skin and clothing. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or approved alternative container. Containers should be kept closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
-----------------	---

7. Handling and storage (continued)

Storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).

8. Exposure controls/personal protection

Product name

CAS number

Exposure limits

Tin	7440-31-5	<p>OSHA PEL (United States, 9/2005). TWA: 2 mg/m³ 8 hour(s).</p> <p>ACGIH TLV (United States, 1/2008). TWA: 2 mg/m³ 8 hour(s).</p> <p>NIOSH REL (United States, 6/2008). Notes: Note: The REL and PEL also apply to other inorganic tin compounds (as Sn) except tin oxides. TWA: 2 mg/m³ 10 hour(s).</p>
Copper	7440-50-8	<p>OSHA Final Rule (United States, 1989). Notes: As copper TWA: 1 mg/m³ 8 hour(s). Form: TWA: 0.1 mg/m³ 8 hour(s). Form:</p> <p>NIOSH REL (United States, 6/2008). Notes: Note: The REL and PEL also apply to other copper compounds (as Cu) except Copper fumes. TWA: 1 mg/m³ 10 hour(s). Form: Dusts and Mists</p> <p>OSHA PEL (United States, 11/2006). TWA: 1 mg/m³ 8 hour(s). Form: Dusts and Mists TWA: 0.1 mg/m³ 8 hour(s). Form: Fume</p> <p>OSHA PEL 1989 (United States, 3/1989). Notes: as Cu TWA: 1 mg/m³, (as Cu) 8 hour(s). Form: Dusts and Mists TWA: 0.1 mg/m³, (as Cu) 8 hour(s). Form: Fume</p> <p>ACGIH TLV (United States, 1/2008). Notes: as Cu TWA: 1 mg/m³, (as Cu) 8 hour(s).</p> <p>ACGIH TLV (United States, 1/2008). Notes: Substances for which the TLV is higher than the OSHA Permissible Exposure Limit (PEL) and/or the NIOSH Recommended Exposure Limit (REL). See CFR 58(124) :36338-33351, June 30, 1993, for revised OSHA PEL. Adopted Values enclosed are those for which changes are proposed. Consult the Notice of Intended Changes for current proposal. See Notice of Intended changes. TWA: 0.2 mg/m³ 8 hour(s). Form: Fume</p>

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Engineering measures

Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Processes should be designed to minimize airborne and skin exposure to hazardous substances.

8. Exposure controls/personal protection (continued)

Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Remove/Take off immediately all contaminated clothing. Contaminated work clothing should not be allowed out of the workplace.
Personal protection	
Respiratory	Use a properly fitted, air-purifying or air-fed respirator complying with NIOSH if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Hands	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Eyes	Avoid contact with eyes. Safety eyewear should be used when there is a likelihood of exposure.
Skin	Avoid contact with skin and clothing. Wear protective clothing. Body garments used should be based upon the task being performed (e.g., lab coat, chemical resistant protective suit, sleevelets, synthetic apron, gauntlets) to avoid exposed skin surfaces. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. Physical and chemical properties

Physical state	Solid.
Flash point	Not available.
Auto-ignition temperature	Not available.
Flammable limits	Not available.
Color	Gray.
Odor	None.
pH	Not available.
Boiling/condensation point	Not available.
Melting/freezing point	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Odor threshold	Not available.
Evaporation rate	Not available.
VOC	0 g/l
Solubility	Insoluble in the following materials: cold water and hot water.

10. Stability and reactivity

Stability	The product is stable.
Conditions to avoid	No specific data.
Incompatibility with various substances	Reactive with oxidizing agents, reducing agents, acids, alkalis, chlorine, peroxides.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Other Hazardous decomposition products	metal oxides, toxic. fumes
Hazardous polymerization	Under normal conditions of storage and use, hazardous polymerization will not occur.

11. Toxicological information

Forney Industries has not conducted specific studies on the toxicity of this product.

12. Ecological information

Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
Copper	Acute EC50 9.2 ug/L Fresh water	Crustaceans - Bosmina longirostris - Juvenile (Fledgling, Hatchling, Weanling) - <48 hours	48 hours
	Acute EC50 1.6 ug/L Fresh water	Daphnia - Ceriodaphnia dubia - Neonate - <24 hours - 0.25 mm	48 hours
	Acute LC50 9.4 to 11.5 ug/L Fresh water	Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling) - <1 months	96 hours
	Chronic NOEC 11.7 ug/L Fresh water	Fish - Oncorhynchus tshawytscha	96 hours

13. Disposal considerations

Waste disposal	The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
-----------------------	---

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG* Label	Additional information
DOT Classification	Not regulated.	-	-	-	

PG* : Packing group

15. Regulatory information

United States

HCS Classification

Irritating material
Target organ effects

U.S. Federal regulations

All ingredients comply with applicable rules or orders under United States TSCA.
All components are listed or exempted.
TSCA 5(a)2 proposed significant new use rules: No products were found.
TSCA 5(a)2 final significant new use rules: No products were found.
TSCA 12(b) one-time export: No products were found.

SARA 313

	Product name	CAS number	Concentration
Form R - Reporting requirements	Copper	7440-50-8	1-5
Supplier notification	Copper	7440-50-8	1-5

Canada

WHMIS (Canada) Canada inventory

Not controlled under WHMIS (Canada).
All components are listed or exempted.

International lists

China inventory (IECSC) Europe inventory Australia inventory (AICS) Japan inventory (ENCS) Korea inventory (KECI) Philippines inventory (PICCS)

All components are listed or exempted.
All components are listed or exempted.
All components are listed or exempted.
All components are listed or exempted.
All components are listed or exempted.
All components are listed or exempted.

16. Other information

Definition of Terms

ACGIH	American Conference of Governmental Industrial Hygienists
Ceiling	Maximum exposure limit defined by OSHA
CAS	Chemical Abstract Service
IARC	International Agency for Research on Cancer
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
REL	Recommended Exposure Limit
RTK	Right to Know
SARA	Superfund Amendments and Reauthorization Act
STEL	Short Term Exposure Limit
TLV	ACGIH Threshold Limit Value
TLV-C	ACGIH Threshold Limit Value, Ceiling
TRADE SECRET	Claimed as allowed under 29CFR§1910.1200
TSCA	Toxic Substances Control Act
PPE	Personal Protection Equipment
CEPA	Canadian Environmental Protection Act
DSL	Domestic Substance List
NDSL	Non-Domestic Substance List
NSN	New Substance Notification Rules

Disclaimer

16. Other information (continued)

The information contained herein is based on data considered accurate. However, no warranty is expressed of implied regarding the accuracy of these data or the results to be obtained from the use thereof. Additionally, Forney Industries assumes no responsibility for injury to the vendee or third persons proximately caused by the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

END OF SAFETY DATA SHEET.