
FORNEY INDUSTRIES

SERVING SMALL BUSINESS, FARM & RANCH, HOME WORKSHOPS, AUTOMOTIVE AFTERCARE & THE INDUSTRIAL MARKETS SINCE 1932







FORNEY INDUSTRIES ALL BUSINESS IS LOCAL

FIVE WAYS TO ORDER

Web: www.forneyind.com Phone: 800-521-6038 Fax: 970-498-9505 Mail: Forney Industries

2057 Vermont Drive Fort Collins, CO 80525

Email: sales@forneyind.com

U.S. Warehouses:

- Fort Collins, CO
- Tipp City, OH

Forney Industries Promise

We deliver tailored solutions to address your specific problem or opportunity. We will staff and equip ourselves to deliver to you the personal service you desire and deserve. We are committed to your success regardless of location, size or needs. We understand it is your goal to get the job done right, and we are ready to help you do just that.

President's Message

Dear Valued Customer,

For more than 80 years, Forney Industries has been committed to offering products that make your life easier. Whether you are a seasoned welder, rancher or someone who simply enjoys working in the garage, we offer more than 5,000 products based on what you need, not on what we want to sell.

Our passion is bringing new and enhanced products to you. This combined with our unparalleled service sets us apart. In fact, All Business is Local is our mantra and that commitment hasn't changed over the years. We treat our customers with the same undivided, personal attention that we offered decades ago but offer the convenience of 24-hour electronic fulfillment services, too.

Your satisfaction begins with our employees. We pride ourselves on securing a remarkable staff that understands the products we sell and knows how important those products are to you. It's simple. Our employees are passionate about what you do.

As a family-owned company, please trust that we will continue to focus on you and your success. While you are busy working at your craft, we are researching and developing the next, best product that will make you increasingly more successful. After all, we aren't successful until you are.

Thank you for your continued business,

STEVEN G. ANDERSON, President & CEO Forney Industries

Copyright® 2017 Forney Industries, Inc. All rights reserved. Unauthorized reproduction and/or distribution is subject to U.S. copyright laws.



TABLE OF CONTENTS

AIR FITTINGS

8

Tru-Flate® Plugs & Couplers Industrial /Milton® (I/M®) Compatible 7 Plugs & Couplers

Aro® Compatible Plugs & Couplers

Universal Couplers

Lincoln® Compatible Plugs & Couplers 9

Blow Guns 10 Air Chucks 12

13 Pressure Gauges, Valves & Repair Kits

Brass Fittings — Barbed, Couplings, Reducers, Adapters & Bushings 15

Brass Fittings — Tees, Crosses 16

& Manifolds

18 Air Drain Cocks, Pressure Gauges, Pressure Switches & Safety Valves

Air Hose — PVC, Nylon, Rubber & 19 Polyurethane Flex Hose & Repair Parts

Air Filters, Regulators & Lubricators 22

Pneumatic (Air) Tools 24

CABLE TIES & TOOLS

Ultra Light-Duty 28

Releasable Standard Duty Standard Duty 28

29

30 Heavy-Duty

Extra Heavy-Duty 30

Super Heavy-Duty 30

31

Light-Duty Screw Mount Standard Duty Screw Mount 31

Heavy-Duty Screw Mount 31 Arrowhead Push Mount 31

Cable Tie Mounts 32

Cable Tie Tools 32

CHAIN & ACCESSORIES

Wire Rope Accessories 34

Clevis, Slip & Eye Hooks 35

38

Linking Center — Cold Shuts, Repair Links, Quick Links & Clevis Links

39 Swivels and Anchor Shackles

Hooks 41

Turnbuckles, Eye Bolts, & Screw Hooks 42

Pins — Hitch, Lynch, Bent & Take-Off 43

Chain — Grade 70, Grade 30, Linked 44

& Looped

Cable, Chain & Bolt Cutters 45

47 Wire Rope

Ratchet Tie Down Straps & Chain Binders 47

ELECTRICAL

50 Battery Chargers & Jump Starters

53 Battery Jumper Cables & Bumper

Jumper Kit

54

Battery & Tune Up Clamps Battery Terminals — Universal, Marine, 54

Top, Post & Side

56 Wire Connectors & Tools

59 Electrical Multi-Testers & Test Clips

Cable Lugs — Premium Copper 60

61 **Butt Connectors**

OPENING INVENTORIES, DISPLAYS & ACCESSORIES

Opening Inventories, Displays & Accessories

PLUMBERS & ROOFERS TORCH KITS & WEED BURNERS

Plumbers & Roofers Torch Kits **76**

& Accessories 77 Weedburners

PRESSURE WASHER PARTS

Screw Couplings & Nipples 80

81

Quick Connect Couplers, Plugs & Sockets Sewer & Multi-Regulator Nozzles Pressure Washer Fitting Guide 82

83

Quick Connect Spray Nozzles 85

Spray Guns, Lances & Strainers 86

87 High Pressure Hose

SOLDER, SOLDERING IRONS & FLUX

Solder, Soldering Irons & Flux

STEEL & ALUMINUM

Aluminum — Round, Square, 100

Flat, Tube & Angled

Sheet Metal & Expanded Metal 102

Steel — Rolled, Round, Square, Flat 103

Key Stock — Round, Square & Rolled Reinforced Steel Bar (Rebar) 108

109

Threaded Rod 109

WORK SHOP TOOLS

Paint Markers 112

112 Window Markers

113 Insert Bits

115 Power Bits

Double Ended Bits, Quick Change 117 Connectors & Magnetic Nutsetters

Silver & Deming Black & Gold Drill Bits 119

Fractional, Wire Gauge & Metric Drill 120 Gauges & Indexes

Drill Bit Sets

120

121 Files — Bastard, Slim Taper & Chain Saw

Tape Measures 122

Magnetic Jigs, Levels & Magnetizer/Demagnetizers 123

124 Power Tools & Hand Tools

Marking Pencils, Scribes & Soapstone Hacksaws & Hacksaw Blades 125


127

127 Wire Extension Springs

129 Wire Compression Springs

INDEX

Product Index by CAT# 131



TRU-FLATE® COMPATIBLE PLUGS & COUPLERS

Tru-Flate® compatible plugs and couplers. Intended for use on compressed air lines only. Maximum working pressure: 300 PSI.

BULK CAT#	CARDED CAT#	DESCRIPTION	SIZE (IN.)	MALE / FEMALE	IMAGE
75215	75590 2-pack	Steel plug	1/4" X 1/4" NPT	Male	
75220	75592 2-pack	Steel plug	1/4" X 1/4" NPT	Female	= 33
75224	75475	Steel plug	3/8" X 1/4" NPT	Male	
75228	75306	Steel plug	3/8" X 3/8" NPT	Male	
_	75322	Steel plug	3/8" X 1/4" NPT	Female	
	75398	Steel plug	1/4" X 3/8" NPT	Female	
	75399	Steel plug	1/4" X 3/8" NPT	Male	00.510
	75476	Steel plug	3/8" X 3/8" NPT	Female	
75217	75309	Brass coupler	1/4" X 1/4" NPT	Male	
75222	75315	Brass coupler	1/4" X 1/4" NPT	Female	
75226	75320	Steel coupler	3/8" X 3/8" NPT	Female	
75230	75485	Steel coupler	3/8" X 1/4" NPT	Female	
	75401	Brass coupler	1/4" X 3/8" NPT	Female	
	75484	Steel coupler	3/8" X 3/8" NPT	Male	





CAT# 75326

5-PIECE TRU-FLATE® COMPATIBLE 1/4 IN. PLUG & COUPLER VALUE PACK

Includes 1-each F-NPT coupler and F-NPT plug and 3-each M-NPT plug.





CAT# 75519

TRU-FLATE® COMPATIBLE 1/4 IN. MALE NPT PLUG X 1/4 IN. FEMALE NPT COUPLER SET

Plug (Forney® CAT# 75590) with 1/4" (6.35mm) male national pipe thread (NPT) and coupler (Forney® CAT# 75315) with 1/4" (6.35mm) female NPT. Steel construction. Intended for use on compressed air lines only. Maximum working pressure: 300 PSI.

INDUSTRIAL/MILTON® (I/M®) COMPATIBLE PLUGS & COUPLERS

Industrial/Milton® compatible plugs and couplers. Intended for use on compressed air lines only. Maximum working pressure: 300 PSI.

BULK CAT#	CARDED CAT#	DESCRIPTION	SIZE (IN.)	MALE / FEMALE	IMAGE
75238	75602 2-pack	Steel plug	1/4" X 1/4" NPT	Female	
75234	75600 2-pack	Steel plug	1/4" X 1/4" NPT	Male	
75242	75471	Steel plug	1/4" X 3/8" NPT	Male	
75246	75323	Steel plug	3/8" X 1/4" NPT	Male	
75248	75307	Steel plug	3/8" X 3/8" NPT	Male	
	75324	Steel plug	3/8" X 1/4" NPT	Female	
_	75472	Steel barbed plug	1/4" X 1/4" barb	_	
	75474	Steel plug	3/8" X 3/8" NPT	Female	
75240	75317	Brass coupler	1/4" X 1/4" NPT	Female	
75244	75479	Brass coupler	1/4" X 3/8" NPT	Female	
75247	<i>7</i> 5321	Steel coupler	3/8" X 3/8" NPT	Female	(C)
75236	<i>7</i> 5316	Brass coupler	1/4" X 1/4" NPT	Male	
	75480	Brass barbed coupler	1/4" X 1/4" barb	_	=====
	75483	Steel coupler	3/8" X 3/8" NPT	Male	0
	75520	Steel push coupler	1/4" X 1/4" NPT	Female	
	75521	Steel push coupler	1/4" X 1/4" NPT	Male	





CAT# 75305

I/M® COMPATIBLE 1/4 IN. X 1/4 IN. PLUG & COUPLER SET

Plug (Forney® CAT# 75600) with 1/4" (6.35mm) male national pipe thread (NPT), steel construction and coupler (Forney® CAT# 75317) with 1/4" (6.35mm) female NPT, brass construction. Intended for use on compressed air lines only. Maximum working pressure: 300 PSI.



CAT# 75325

5-PIECE I/M® COMPATIBLE 1/4 IN. PLUG & COUPLER VALUE PACK

Includes 1-each female NPT coupler & female NPT plug and 3-each male NPT plugs.

AIR FITTINGS 7

ARO® COMPATIBLE PLUGS & COUPLERS

Aro® compatible plugs and couplers. Intended for use on compressed air lines only. Maximum working pressure: 300 PSI.

BULK CAT#	CARDED CAT#	DESCRIPTION	SIZE (IN.)	MALE / FEMALE	IMAGE
75250	75303	Steel plug	1/4" X 1/4" NPT	Male	
75254	75473	Steel plug	1/4" X 1/4" NPT	Female	
75252	75318	Brass coupler	1/4" X 1/4" NPT	Female	
_	75482	Brass coupler	1/4" X 1/4" NPT	Male	

UNIVERSAL COUPLERS

Fits the three most popular air line plugs: Tru-Flate®, Industrial/Milton® and Aro® compatible 1/4" plugs. Not for Lincoln® or Lincoln® compatible plugs. Intended for use on compressed air lines only. Maximum working pressure: 300 PSI.

BULK CAT#	CARDED CAT#	DESCRIPTION	SIZE (IN.)	MALE / FEMALE	IMAGE
75260	75527	Brass coupler	1/4" X 1/4" NPT	Female	9)3
	75526	Brass coupler	1/4" X 1/4" NPT	Male	(P





AIR PLUG & COUPLER IDENTIFICATION TEST BAR

Makes identification of an unknown plug or coupler quick and easy. There is one 1/4" (6.35mm) plug from each of the main manufacturers (Tru-Flate®, Industrial/Milton®, Aro® and Lincoln®) clearly marked and securely fastened to the metal base. The customer simply holds their plug up next to the sample or connects their coupler to the appropriate plug to find the perfect fit — every time.



CAT# 75522

ARO® COMPATIBLE 1/4 IN. MALE NPT PLUG X 1/4 IN. FEMALE NPT COUPLER SET


Air Fittings Plug/Coupler Set, 1/4" (6.35mm) Aro® compatible. Plug (Forney® CAT# 75303) with 1/4" (6.35mm) male national pipe thread (NPT) and coupler (Forney® CAT# 75318) with 1/4" (6.35mm) female NPT. Steel and brass construction. Intended for use on compressed air lines only. Max working pressure: 300 PSI.

8 AIR FITTINGS

LINCOLN® COMPATIBLE PLUGS & COUPLERS

Lincoln® compatible plugs and couplers. Intended for use on compressed air lines only. Maximum working pressure: 300 PSI.

CARDED CAT#	DESCRIPTION	SIZE (IN.)	MALE / FEMALE	IMAGE
75304	Steel plug	1/4" X 1/4" NPT	Male	
75524	Steel plug	1/4" X 1/4" NPT	Female	
75319	Steel coupler	1/4" X 1/4" NPT	Female	• (1)
75525	Steel coupler	1/4" X 1/4" NPT	Male	





SIPHON SPRAY BLOW GUN

Combination of a standard blow gun and the siphon spray nozzle. Barbed siphon inlet fits 1/4" (6.35mm) inside diameter hose or tubing. For use on a regulated air line with a pressure setting not to exceed 30 PSI.



CAT# 75331

LEVER-TYPE BLOW GUN

Vented nozzle to relieve the compressed air pressure should the nozzle become plugged or accidentally obstructed. Inlet pressure: 150 PSI with 1/4" (6.35mm) female national pipe thread (NPT) inlet. Meets OSHA 100-1 for 30 PSI "dead head" pressure.



CAT# 75332

LEVER-TYPE BLOW GUN (STUBBY)

Vented nozzle to relieve the compressed air pressure should the nozzle become plugged or accidentally obstructed. Inlet pressure: 150 PSI with 1/4" (6.35mm) female national pipe thread (NPT) inlet. Meets OSHA 100-1 for 30 PSI "dead head" pressure. Standard size version is Forney® CAT# 75331.



CAT# 75334

I/M® COMPATIBLE ADJUSTABLE POCKET BLOW GUN

Industrial/Milton® compatible 1/4" (6.35mm) adjustable pocket. Extremely handy and easy to use. Just twist the knurled nozzle to adjust from a whisper of air to full 30 PSI volume flow. OSHA regulation 100-1 compliant.



CAT# 75336

LEVER-TYPE BLOW GUN WITH 2 FT. EXTENSION

Air blow gun with 2' extension, rubber safety tip and 1/4" female NPT inlet. Recommended working pressure: 90 PSI. Maximum working pressure: 150 PSI. Blow gun is zinc alloy with blue zinc coating. 2' (0.61m) extension is aluminum with oxidized finish, 8.5mm inner diameter and 12mm outer diameter.



CAT# 75337

LEVER-TYPE BLOW GUN WITH 4 FT. EXTENSION

Air blow gun with 4' (1.22m) extension, rubber safety tip and 1/4" female NPT inlet. Recommended working pressure: 90 PSI. Max working pressure: 150 PSI. Blow gun is zinc alloy with blue zinc coating. 4' (1.22m) extension is aluminum with oxidized finish, 8.5mm inner diameter and 12mm outer diameter.



CAT# 75352

BLOW GUN REDUCER/ADAPTER, 1/4 IN. TO 1/8 IN. NPT

Used to adapt Forney® CAT#'s 75355 and 75356 or any similar sized nozzles, tips and needles, to Forney® CAT#'s 75330, 75331, 75332, 75494 and 75495 blow guns or any similar blow guns with 1/8" (3.18mm) female NPT outlet.



CAT# 75353

STANDARD AIR NOZZLE WITH 1/8 IN. MALE NPT

Replacement nozzle for Forney® CAT#'s 75330, 75331, 75332, 75494, 75495 and 75529 blow guns or any similar blow gun with a 1/8" (3.18mm) female NPT nozzle outlet. POWERFUL AIR STREAM. DO NOT AIM DIRECTLY AT ANY PERSON, ANIMAL OR DELICATE FIXTURE.



CAT# 75354

RUBBER TIPPED BLOW GUN SAFETY AIR NOZZLE

1/8" (3.18mm) male NPT. OSHA compliant. Rubber tip provides a leak proof seal for cleaning out oil passages and fuel lines. Replacement nozzle for Forney® CAT#'s 75330, 75331, 75332, 75494, 75495 and 75529 blow guns or any similar blow gun with a 1/8" female NPT nozzle outlet.



CAT# 75355

TAPERED TIP BLOW GUN INFLATION NOZZLE & ADAPTER

1/8" (3.18mm) male NPT. 2-pack. Made of aluminum. Nozzle and adapter fit Forney® CAT#'s 75330, 75331, 75332, 75494 and 75495 blow guns or similar blow guns with 1/8" (3.18mm) female NPT outlets.



CAT# 75495

BUTTON-TYPE BLOW GUN

Vented nozzle to relieve the compressed air pressure should the nozzle become plugged or accidentally obstructed. Inlet pressure: 150 PSI with 1/4" (6.35mm) NPT inlet. Meets OSHA regulation 100-1 for 30 PSI "dead head" pressure.



CAT# 75356

AIR INFLATOR NEEDLE & ADAPTER

1/8" (3.18mm) male NPT. 2-pack. Made of steel. Needle and adapter fit Forney® CAT#'s 75330, 75331, 75332, 75494 and 75495 blow guns or similar blow guns with 1/8" (3.18mm) female NPT outlets.



CAT# 75529

6-PIECE DELUXE BLOW GUN KIT


All-purpose deluxe blow gun kit with four interchangeable nozzles for cleaning and deflating. Complete with standard nozzle, rubber tip nozzle, tapered nozzle and ball inflator. For use on a regulated air line with a pressure setting not to exceed 30 PSI.



CAT# 75494

RUBBER TIPPED BLOW GUN

Oil resistant, soft replaceable tip. Will not mark delicate surfaces. Leak proof seal against oil passages, fuel lines, etc., when air pressure is needed for cleaning. Complete with hang-up hook and 1/4" (6.35mm) female NPT inlet. For use on a regulated air line with a pressure setting not to exceed 30 PSI.







DIRECT LINE AIR CHUCK WITH SHUT-OFF

Direct line air chuck with built-in shut-off valve and 1/4" (6.35mm) female national pipe thread (NPT). Max air line pressure: 150 PSI. NOT FOR USE ON INFLATOR GAUGES.



CAT# 75349

HEAVY-DUTY 6 IN. DUAL FOOT AIR CHUCK

6" direct air line dual foot chuck with built-in shut-off valve and 1/4" (6.35mm) female national pipe thread (NPT). Max air line pressure: 150 PSI. For servicing trucks, buses and RVs with dual wheels. NOT FOR USE ON INFLATOR GAUGES.



CAT# 75350

HEAVY-DUTY 18 IN. DUAL FOOT AIR CHUCK

18" (457.2mm) dual foot air chuck with 1/4" (6.35mm) female national pipe thread (NPT). 150 PSI maximum air line pressure. Made from steel and zinc alloy. Includes built-in shut-off valve. Ideal for servicing trucks, buses and RVs with dual wheels. NOT FOR USE ON INFLATOR GAUGES.



CAT# 75487

DIRECT LINE AIR CHUCK WITH SNAP-ON CLIP

Direct line air chuck with built-in clip shut-off valve and 1/4" (6.35mm) female national pipe thread (NPT). Max air line pressure: 150 PSI. NOT FOR USE ON INFLATOR GAUGES.

CAT# 75488

SNAP-ON AIR CHUCK CLIP


Converts any single foot chuck to a clipon chuck. Fits Forney® CAT# 75340. Replacement clip for Forney® CAT# 75487.

CAT# 75489

DIRECT LINE AIR CHUCK

Direct line steel air chuck with built-in shut-off valve and 1/4" (6.35mm) inside diameter hose barb. Max air line pressure: 150 PSI.

NOT FOR USE ON INFLATOR GAUGES.



PRESSURE GAUGES

Precision manufactured providing long life, accuracy and performance for the most demanding applications. These items are carded.

CAT#	PSI	DESCRIPTION	IMAGE
75344	0 – 20	Low pressure tire gauge perfect for garden tractors, golf carts, ATV's, etc. Calibrated in 1/2 lb. increments.	0
75345	10 – 50	Standard tire gauge great for automobiles, vans, light trucks. Calibrated in 1 lb. increments.	
75346	20 – 120	Truck tire gauge — use for higher pressure applications such as half ton trucks to two and a half ton trucks. Calibrated in 2 lb. increments.	Se la
75347	10 – 150	Dual foot tire gauge designed for heavy-duty use required at the service level. Ideal for dual wheels and other difficult to reach valves on pick-up trucks. Calibrated 10 – 150 PSI in 2 PSI increments and 100 – 1,040 kPa in 20 kPa increments. 6" (152.4mm) extension metal construction.	
75348	5 – 45	Air/liquid tractor tire gauge. Calibrated in 1 lb. increments. Use on air or liquid filled tires; for farm or heavy construction equipment.	
<i>754</i> 91	10 – 50	Angled tire gauge, economical. Great for automobiles, vans, light trucks. Calibrated in 1 lb. increments. Calibrated on two sides with plastic casing and metal pocket clip.	
75492	20 - 120	Angled tire gauge, economical. Use for higher applications such as half ton trucks to two and a half ton trucks. Calibrated in 2 lb. Increments. Calibrated two sides with plastic casing and metal pocket clip.	
75493	10 – 120	Heavy-duty tire inflator & gauge. Rugged zinc casting with rubber bumper guard to protect against damage if dropped. Easy to read recessed sight glass with 12" (304.8mm) hose and dual foot chuck. Calibrated in 2 PSI increments.	
75496	10 – 120	Standard (econo model) tire inflator & gauge. Rugged zinc casting with rubber bumper guard to protect against damage if dropped. Easy to read recessed sight glass with 12" (304.8mm) hose and dual foot chuck. Calibrated in 2 PSI increments.	
75528	10 – 60	Dial tire gauge. Professional-type dial in drawn steel casing with a nickel plated brass chuck. Easy to read dial calibrated in 1 PSI increments. Includes automatic reset and pressure release valve.	

AIR FITTINGS 13



CAT# 75370

4-WAY TIRE VALVE REPAIR TOOL

Repairs core and stem threads. Features core screw driver and broken core extractor. Carded.



CAT# 75380

SCREWDRIVER VALVE CAPS, 4-PACK

All purpose caps with screwdriver top for removing or inserting valve cores. Fits .305" – 32" thread on standard type valves. 4-pack.



CAT# 75381

PLASTIC DOME VALVE CAPS, 4-PACK

Black flexible plastic valve caps. Caps do not have a sealing unit. 4-pack. Carded.



CAT# 75509

HEAVY-DUTY EMERGENCY TIRE REPAIR KIT

Emergency tire repair kit for all bias ply and non-speed rated tires. Contains a probe, open-eyed tool, .30 fluid ounces of universal cement and 5 radial inserts. Carded.





BRASS DUAL BARBED AIR HOSE SPLICERS

Dual-barbed hose splicer for air hose. All brass construction. Resists rust and will not corrode as easily as other materials. Use with hose clamps or ferrules

CARDED CAT#	DESCRIPTION	SIZE (IN.)	MALE / FEMALE	IMAGE
75357	Dual barbed hose splicer	3/8" to 3/8"	N/A	
75361	Dual barbed hose splicer	1/4" to 1/4"	N/A	

BRASS BARBED AIR HOSE ENDS

All-brass air hose end with barbed end. Resists rust and will not corrode as easily as other materials. Use with hose clamps or ferrules.

CARDED CAT#	DESCRIPTION	SIZE (IN.)	MALE / FEMALE	IMAGE
75358	Female national pipe thread (NPT) and barbed ends for air hose	1/4" NPT for 3/8" hose	Female	
75359	Male national pipe thread (NPT) and barbed ends for air hose	1/4" NPT for 3/8" hose	Male	
75360	Male national pipe thread (NPT) and barbed ends for air hose	1/4" NPT for 1/4" hose	Male	
75362	Female national pipe thread (NPT) and barbed ends for air hose	1/4" NPT for 1/4" hose	Female	
75530	Female national pipe thread (NPT) and barbed ends for air hose	3/8" NPT for 3/8" hose	Female	

BRASS HOSE COUPLINGS

All-brass air hose couplings. Resists rust and will not corrode as easily as other materials.

CARDED CAT#	DESCRIPTION	SIZE (IN.)	MALE / FEMALE	IMAGE
75448	Brass air hose coupling with 1/4" (6.35mm) male national pipe thread (NPT) ends for 1/4" (6.35mm) air hose.	1/4" NPT for 1/4" air hose	Male	
75532	Brass air hose coupling with 1/4" (6.35mm) female national pipe thread (NPT) ends for 1/4" (6.35mm) air hose.	1/4" NPT for 1/4" air hose	Female	

BRASS HOSE REDUCERS

All-brass hose reducers. Resists rust and will not corrode as easily as other materials. Use to connect 3/8" (9.52mm) air hose to 1/4" (6.35mm) air hose.

CARDED CAT#	DESCRIPTION	SIZE (IN.)	MALE / FEMALE	IMAGE
75447	Brass hose reducer with 3/8" (9.52mm) female national pipe thread (NPT) and 1/4" (6.35mm) male NPT ends.	3/8" NPT to 1/4" NPT	Female/Male	@
75533	Brass hose reducer with 3/8" (9.52mm) male national pipe thread (NPT) and 1/4" (6.35mm) male NPT ends.	3/8" NPT to 1/4" NPT	Male/Male	

AIR FITTINGS 15

BRASS BUSHINGS

All-brass air hose bushing with female national pipe thread (NPT) and male NPT ends. Resists rust and will not corrode as easily as other materials.

CAT#	DESCRIPTION	SIZE (IN.)	MALE / FEMALE	IMAGE
75534	Brass air hose bushing	1/8" NPT to 1/4" NPT	Female/Male	
75535	Brass air hose bushing	1/4" NPT to 3/8" NPT	Female/Male	
75536	Brass air hose bushing	3/8" NPT to 1/2" NPT	Female/Male	



BRASS TEES

All-brass construction air line accessories. Resists rust and will not corrode as easily as other materials. Female national pipe thread (NPT) ends. Working pressure: 150 PSI.

CAT#	DESCRIPTION	SIZE (IN.)	MALE / FEMALE	IMAGE
75363	Brass tee	1/4" NPT	Female	4
75364	Brass tee	3/8" NPT	Female	•

BRASS CROSSES

All-brass construction air line accessories. Resists rust and will not corrode as easily as other materials. Female national pipe thread (NPT) ends. Working pressure: 150 PSI.

CAT#	DESCRIPTION	SIZE (IN.)	MALE / FEMALE	IMAGE
75365	Brass cross	1/4" NPT	Female	×
75366	Brass cross	3/8" NPT	Female	**

BRASS TRIPOD MANIFOLDS

3-in-1 brass tripod manifolds. Supplies three air tools from one source. No need to disconnect/connect to use different tools. Includes three (3) female national pipe thread (NPT) outlets and a single female NPT inlet. All-brass construction resists rust and will not corrode as easily as other materials.

CAT#	DESCRIPTION	SIZE (IN.)	MALE / FEMALE	IMAGE
75558	3-in-1 brass tripod manifold	1/4" NPT inlet 3x 1/4" NPT outlets	Female	*
75559	3-in-1 brass tripod manifold	3/8" NPT inlet 3x 1/4" NPT outlets	Female	•



CAT# 75537

BRASS BALL END ADAPTER

All-brass air hose ball end adapter with ball socket and 1/4" (6.35mm) male national pipe thread (NPT) x 1/4" (6.35mm) male nominal pipe size (NPS) ends. Resists rust and will not corrode as easily as other materials.



CAT# 75542

AIR/WATER ADAPTER

Fluid adapter for ballast. Screws onto .482" – 26 threads of all air/liquid valves. Has a bushing to fit .305" – 32 valve cap threads of standard tire valves. Includes additional bushing to fit .406" – 26 threads of old-style air liquid valves.



CAT# 75543

SCHRAEDER® COMPATIBLE TANK VALVE

Use with compressed air tanks for rapid filling or deflation of air tanks and air lines. 1/8" (3.18mm) male national pipe thread (NPT) fitting. Maximum pressure of 200 PSI. Includes cap and core.



CAT# 75549

TANK MANIFOLD FOR AIR COMPRESSORS

Air compressor manifold with 1/2" (12.7mm) male national pipe thread (NPT) inlet and 1/4" (6.35mm) male NPT outlet. Gauge port is 1/4" (6.35mm) male NPT. Pressure switch mount is 1/4" (6.35mm) NPT. Safety valve: 125 – 150 PSI. Suitable for compressors up to 3 HP.



CAT# 75550

TANK MANIFOLD FOR CARRY TANKS

Carry tank manifold with 1/2" (12.7mm) male national pipe thread (NPT) inlet and 1/4" (6.35mm) female NPT outlet. Gauge port is 1/4" (6.35mm) female NPT. Safety valve: 150 PSI.




CAT# 75560

BRASS 3-IN-1 FLAT MANIFOLD

Supplies three air tools from one source. No need to disconnect/connect to use different tools. Includes three (3) 1/4" (6.35mm) female national pipe thread (NPT) outlets and a single 1/4" (6.35mm) female NPT inlet. All-brass construction resists rust and will not corrode as easily as other materials.





COMPRESSER TANK DRAIN COCKS

All brass construction. Resists rust and will not corrode as easily as other materials.

CARDED CAT#	DESCRIPTION	SIZE (IN.)	MALE / FEMALE	IMAGE
75367	Compressor tank drain cock with male national pipe thread (NPT).	1/4"	Male	
75368	Compressor tank drain cock with male national pipe thread (NPT).	1/8″	Male	(=



CAT# 75553

2 IN. AIR PRESSURE GAUGE

2" (50.8mm) air line pressure gauge with 1/4" (6.35mm) national pipe thread (NPT). Calibration range of 0 – 160 PSI (0 – 1,100 kPa). Rear mount. **NOT SUITABLE FOR LIQUIDS OR OTHER GASES.**



CAT# 75554

2-1/4 IN. AIR PRESSURE GAUGE

2-1/4" (57.15mm) pressure gauge with 1/4" (6.35mm) national pipe thread (NPT). Calibration range of 0 – 160 PSI (0 – 1,100 kPa). Bottom mount. **NOT SUITABLE FOR LIQUIDS OR OTHER GASES.**



CAT# 75565

1-1/2 IN. AIR PRESSURE GAUGE

Air line pressure gauge with 1/8" (3.18mm) national pipe thread (NPT). Rear mount. Calibration range of 0 – 160 PSI (0 – 1,100 kPa). NOT SUITABLE FOR LIQUID OR OTHER GASES.



CAT# 75555

AIR PRESSURE SWITCH

1-1/2 HP @ 115V; 2 HP @ 230V; 1 PH, 80 – 100 PSI. Includes unloader valve, adjustable 25 – 100 PSI and 20 – 40 PSI differential.

NOT SUITABLE FOR LIQUIDS OR OTHER GASES.



CAT# 75556

AIR PRESSURE SWITCH

1-1/2 HP @ 115V; 2 HP @ 230V; 1 PH, 95 – 125 PSI. Includes unloader valve, adjustable 40 – 150 PSI and 30 – 40 PSI differential. NOT SUITABLE FOR LIQUIDS OR OTHER GASES.



CAT# 75570

AIR PRESSURE SWITCH WITH AUTO-OFF LEVER

1-1/2 HP @ 115V; 2 HP @ 230V; 1 PH; 95 – 125 PSI. Includes unloader valve, adjustable 40 – 150 PSI, 30 – 40 differential and disconnect (off) lever. **NOT SUITABLE FOR LIQUID OR OTHER GASES.**



CAT# 75501

POLYURETHANE FLEX AIR HOSE STRAIN RELIEF FITTINGS

Strain relief fittings used to repair polyurethane flex air hose. Reusable nickel-plated swivel fitting with male national pipe thread (NPT) and integral bend restrictor. Sold individually as one fitting plus restrictor.

CAT#	DESCRIPTION	SIZE
75501	Strain relief fitting for 1/4" polyurethane flex air hose	1/4" male NPT fittings
75502	Strain relief fitting for 3/8" polyurethane flex air hose	1/4" male NPT fittings
75503	Strain relief fitting for 3/8" polyurethane flex air hose	3/8" male NPT fittings



POLYURETHANE FLEX AIR HOSES

Lightweight polyurethane braided flex air hose with reusable nickel-plated swivel fittings and integral bend restrictors on each end. Abrasion and oil resistant. Maintains excellent flexibility in hot and cold temperatures with a working pressure of 210 PSI at 70° (21.1° C). Temperature range: -40° F to 165° F (-40° C to 73.9° C).

CAT#	DESCRIPTION	LENGTH
75442		1/4" ID x 50'
75443		1/4" ID x 100'
75444	1/4" (6.35mm) reusable nickel-plated	3/8" ID x 50'
75445	, and the second	3/8" ID x 100'
75450		1/4" ID x 25'



3/8 ID RUBBER AIR HOSES

General purpose rubber hose. 3/8" ID x 25' with 3/8" Male NPT fittings on both ends. Excellent for air, water or agricultural chemicals. Resists heat, sunlight, ozone and weathering. Features 250 PSI work load limit and 1,000 PSI burst pressure. Temperature range: -40° F (-40° C) to 180° F (82.2° C).

CAT#	DESCRIPTION	LENGTH
75435	3/8" male NPT fittings on both ends	3/8" ID x 25'
75436	3/8" male NPT fittings on both ends	3/8" ID x 50'
75437	1/4" male NPT fittings on both ends	3/8" ID x 25'
75438	1/4" male NPT fittings on both ends	3/8" ID x 50'

AIR FITTINGS 19

PVC AIR HOSES

PVC air hose. Male NPT fittings on both ends. Designed for a variety of uses such as: carpentry, painting, automotive and home repair. 300 PSI work pressure and 1,200 PSI burst pressure. Lighter in weight than rubber hose. Temperature range: 25° F (-3.9° C) to 150° F (65.6° C).

CAT#	DESCRIPTION	LENGTH
75406	1/4" male NPT fittings on both ends	1/4" ID x 25'
75407	1/4" male NPT fittings on both ends	1/4" ID x 50'
75408	3/8" male NPT fittings on both ends	3/8" ID x 25'
75409	3/8" male NPT fittings on both ends	3/8" ID x 50'
<i>7</i> 5410	1/4" male NPT fittings on both ends	3/8" ID x 25'
<i>7</i> 5411	1/4" male NPT fittings on both ends	3/8" ID x 50'
75414	1/4" male NPT fittings on both ends	1/4" ID x 100'
75415	1/4" male NPT fittings on both ends	3/8" ID x 100



CAT# 75406

NYLON RECOIL AIR HOSES

Nylon recoil air hose. Male NPT fittings (1 swivel end). Made of tough abrasion resistant nylon. Extends to 25 times its stored length. Conveniently coils when not in use. Includes swivel assembly. Working pressure: 200 PSI. Temperature range: 20° F (-6.7° C) to 175° F (79.4° C). Bright yellow.

CAT#	DESCRIPTION	LENGTH
75417	1/4" male NPT fittings (1 swivel end)	1/4" ID x 12'
75418	1/4" male NPT fittings (1 swivel end)	1/4" ID x 25'
75425	3/8" male NPT fittings (1 swivel end)	3/8" ID x 25'



CAT# 75417

1/4" ID RUBBER HOSE

General purpose 1/4" (6.35mm) ID rubber hose with 1/4" male national pipe thread (NPT) fittings on both ends. Excellent for air, water or agricultural chemicals. Resists heat, sunlight, ozone and weathering. Features 250 PSI work load limit and 1,000 PSI burst pressure. Temperature range: -40° F (-40° C) to 180° F (82.2° C).

CAT#	DESCRIPTION	LENGTH
75430	1/4" male NPT fittings on both ends	1/4" ID x 25'
75431	1/4" male NPT fittings on both ends	1/4" ID x 50'



CAT# 75430

POLYURETHANE FLEX AIR HOSE SPLICERS

Brass hose splicer for polyurethane flex air hose. Designed to repair damaged hose or to attach two hoses together. Splicer is a reusable compression design. Sold individually.

CAT#	DESCRIPTION	SIZE (IN.)	IMAGE
75498	Brass hose splicer for 1/4" (6.35mm) polyurethane flex air hose.	1/4" (6.35mm)	() saiges ()
75499	Brass hose splicer for 3/8" (9.52mm) polyurethane flex air hose.	3/8" (9.52mm)	MED D

SAFETY VALVES

American Society of Mechanical Engineers (ASME) standard brass safety valve with 1/4" (6.35mm) male national pipe thread (NPT). 2" (50.8mm) height. Silicone pad bubble tight within +/- 10%. Zinc plated music wire spring. "UV" "NB" stamped.

CAT#	DESCRIPTION	SIZE (IN.)	IMAGE
75551	Rated for 150 PSI/136 Standard Cubic Feet per Minute (SCFM)	1/4" (6.35mm) male NPT	
75552	Rated for 125 PSI/116 Standard Cubic Feet per Minute (SCFM)	1/4" (6.35mm) male NPT	0



AIR FITTINGS 21

FORNEY INDUSTRIES



CAT# 75500

18 IN. SNUBBER (LEADER) HOSE

1/4" (6.35mm) male national pipe thread (NPT). Absorbs the intermittent shock loads produced by air powered tools to the air hose coupler. Use leader hose to eliminate premature failure of the coupler. Maximum working pressure: 300 PSI. AIR ONLY. NOT **SUITABLE FOR LIQUID OR** OTHER GASES.



CAT# 75561

90° AIRLINE SWIVEL

Eliminates kinked/twisted air line hose by swiveling 90°. All brass construction resists rust and will not corrode as easily as other materials. 1/4" (6.35mm) male national pipe thread (NPT) fitting \times 1/4" (6.35mm) female NPT fitting.



CAT# 75546

AIR LINE MINI-REGULATOR WITH 1/4 IN. FEMALE NPT

16 cubic feet per minute (CFM) at 300 PSI, 5 to 125 PSI at outlets. Unbalanced poppet standard. Solid control piston with lip seal for extended life. Compact: 3.08" (78mm) high by 1.65" (42mm) wide. Max inlet pressure: 250 PSIG; Max operating temperature: 125° F (51.67° C). Suitable for use with 1/2 HP to 6 HP compressors.



CAT# 75540

360° AIRLINE SWIVEL

Eliminates kinked/twisted air line hose by swiveling a full 360°. Max working pressure: 150 PSI. 1/4" (6.35mm) male national pipe thread (NPT) fitting \times 1/4" (6.35mm) female NPT fitting. Perfect for the compressor-to-air line connection.



CAT# 75562

360° UNIVERSAL SWIVEL

360° universal swivel. Prevents hoses from kinking. For use in pneumatic applications. 1/4" (6.35mm) male national pipe thread (NPT) and 1/4" (6.35mm) female NPT. Max pressure: 125 PSI.



CAT# 75547

AIR LINE MINI-LUBRICATOR WITH 1/4 IN. FEMALE NPT

Mini-lubricator with 1/4" (6.35mm) national pipe thread (NPT). 12 cubic feet per minute (CFM) at 150 PSI. Generates oil particles of 5 micron and smaller downstream. Ideal for low and high flow applications with changing air flow. Removable drip control knob for tamper resistance. Max temperature: 125° (51.67° C).



CAT# 75541

6-PIECE AIR HOSE REPAIR KIT

Contains all parts necessary to repair a direct air line hose assembly. Includes: single foot air chuck, male hose end, hose splicer and three (3) band-style hose clamps. Fits 1/4" (6.35mm) inside diameter hose.



CAT# 75545

AIR LINE MINI-FILTER

Mini-filter with 1/4" (6.35mm) national pipe thread (NPT). Unique deflector plate creates swirling of the air stream ensuring maximum water and dirt separation. Max inlet pressure: 150 PSIG. Max operating temperature: 125° F (51.67° C). 5 micron filter element. Use with Forney® CAT# 75574, mounting bracket and Forney® CAT# 75578, replacement element.



CAT# 75574

MOUNTING BRACKET

Mounting bracket for Forney® CAT# 75545, mini-filter and Forney® CAT# 75546, miniregulator. Includes panel mount nut.

FORNEY INDUSTRIES



CAT# 75575

MOUNTING BRACKET

Mounting bracket for Forney® CAT# 75547, mini-lubricator.



CAT# 75576

MOUNTING BRACKET

Mounting bracket for Forney® CAT#'s 75580, full-size filter and 75582, full-size lubricator.



CAT# 75577

MOUNTING BRACKET

Mounting bracket for Forney® CAT# 75581, full-size regulator. Includes panel mount nut.



CAT# 75578

REPLACEMENT MINI-FILTER ELEMENT

Mini-filter replacement element for Forney® CAT# 75545, mini-filter. 5 micron.



CAT# 75579

REPLACEMENT FILTER ELEMENT

Full-size replacement element for Forney® CAT# 75580, full-size filter. 40 micron.



CAT# 75580

FULL SIZE AIR FILTER WITH 3/8 IN. FEMALE NPT

Unique deflector plate and shroud creates a swirling of the air stream, ensuring maximum water and dirt separation. Large filter element surface guarantees low pressure drop and increased element life. Max inlet pressure: 150 PSIG. Max operating temperature: 125° F (51.67° C). Manual twist drain.



CAT# 75581

FULL SIZE AIR REGULATOR WITH 3/8 IN. FEMALE NPT

80 cubic feet per minute (CFM) at 250 PSI, 5 to 150 PSI. Rolling diaphragm for extended life. Removable non-rising knob for panel mounting and tamper resistance. Reverse flow. Max inlet pressure: 250 PSI. Max operating temperature: 175° F (79.4° C). Suitable for use with compressors up to 10 HP.



CAT# 75582

FULL SIZE AIR LUBRICATOR WITH 3/8 IN. FEMALE NPT

Sends 5 micron (or smaller) oil particles downstream to lubricate complex systems. Ideal for low and high flow applications with changing air flow. Removable drip control knob for tamper resistance. Max inlet pressure: 150 PSIG. Max operating temperature: 125° F (51.67° C).



1/2 IN. DRIVE AIR IMPACT WRENCH

1/2" drive with built-in regulator allows for four torque settings: 230, 215, 194 and 150 ft-lbs. of torque. Push-pull reversing lever for easy operation. 7" (177.8mm) overall length. 5 lbs. (2.27Kg) net weight. Works best with 3/8" (9.52mm) inside diameter hose.

SPECIFICATIONS

WORKING AIR PRESSURE: 90 PSI BOLT CAPACITY: 5/8" (15.88mm) AIR INLET: 1/4" (6.35mm) NPT

ANVIL: 1" (25.4mm)

AIR CONSUMPTION: 4.5 CFM MAX TORQUE: 230 ft-lbs.



CAT# 1990

3/8 IN. AIR DRILL

Contoured handle expels exhaust air away from work. 1/4" national pipe thread (NPT) inlet. 18,000 RPM motor reduced to 2,200 RPM chuck speed through planetary idler gears producing even torque. Ball bearing construction. Ideal for all general purpose drilling. Includes 3/8" (9.52mm) U.S. Jacobs® chuck. 2.2 lbs. (0.998 kg) net weight. Best with 3/8" (9.52mm) inside diameter hose.

SPECIFICATIONS

WORKING AIR PRESSURE: 90 PSI

FREE SPEED: 2,200 RPM
AIR INLET: 1/4" (6.35mm) NPT
CHUCK SIZE: 3/8" (9.52mm) NPT
AIR CONSUMPTION: 4.0 CFM
SPINDLE THREAD: 3/8" – 24 UNF



CAT# 1989

3/8 IN. DRIVE AIR RATCHET WRENCH

3/8" drive with ball bearing construction and fully hardened gearing and precision machined moving parts. Fast 150 RPM run down delivers up to 50 ft-lbs. of torque. Hardened yoke and ball detent retainer. 10" (254mm) overall length. 2.6 lbs. (1.18 kg) net weight. Works best with 3/8" (9.52mm) inside diameter hose.

SPECIFICATIONS

WORKING AIR PRESSURE: 90 PSI BOLT CAPACITY: 3/8" (9.52mm) AIR INLET: 1/4" (6.35mm) NPT FREE SPEED: 160 RPM AIR CONSUMPTION: 4.0 CFM MAX TORQUE: 50 ft-lbs.



CAT# 1992

6 IN. HEAVY-DUTY DUAL ACTION AIR SANDER

6" heavy-duty professional quality. 1/4" (6.35mm) national pipe thread (NPT) inlet. Quiet, random sanding action assures patternfree finish. Pad and head move in different directions for uniform surface contact; ensuring minimal heat build-up and abrasive loading. Built-in regulator allows power control. Works best with 3/8" (9.52mm) inside diameter hose. 6" (152.4mm) replacement orbital sander backing pad is Forney® CAT# 72435.

SPECIFICATIONS

WORKING AIR PRESSURE: 90 PSI FREE SPEED: 10,000 RPM AIR INLET: 1/4" (6.35mm) NPT AIR CONSUMPTION: 6.0 CFM

PAD SIZES: 6" (152.4mm) or 5" (127mm) **ORBITAL STROKE:** 3/16" (4.76mm)



HIGH SPEED MINI AIR DIE GRINDER

Comes with 1/8" (3.18mm) and 1/4" (6.35mm) collets. 1/4" (6.35mm) national pipe thread (NPT) inlet. Accepts most major brand bits. Lever throttle for positive speed control. All ball bearing for smooth operation and long life. Suitable for most grinding operations. 5-1/2" (139.7mm) overall length. 1.0 lbs. (0.453 kg) net weight. Works best with 3/8" (9.52mm) inside diameter hose.

SPECIFICATIONS

WORKING AIR PRESSURE: 90 PSI

FREE SPEED: 18,000 RPM AIR INLET: 1/4" (6.35mm) NPT AIR CONSUMPTION: 3.0 CFM

COLLET (INCLUDED): 1/8" (3.18mm) & 1/4" (6.35mm)



CAT# 1997

16 GAUGE AIR NIBBLER

16 gauge, ultralight tool under 2 lbs. (0.91 kg). 1/4" (6.35mm) national pipe thread (NPT) inlet. Cuts through 16 gauge mild steel without deforming the sheet or leaving a burr. Die adjusts for cutting forward, right or left. Ideal tool for metal fabrication. Works best with 3/8" (9.52mm) inside diameter hose.

SPECIFICATIONS

WORKING AIR PRESSURE: 90 PSI

FREE SPEED: 3,500 RPM AIR INLET: 1/4" (6.35mm) NPT AIR CONSUMPTION: 4.0 CFM

CUTTING CAPACITY: 1/16" (1.6mm) steel;

5/64" (1.98mm) aluminum



CAT# 1994

UTILITY AIR CUT-OFF AIR TOOL

Heavy-duty 3" (76.2mm) diameter wheel cutter with 1/4" (6.35mm) national pipe thread (NPT) inlet. Cuts through muffler clamps, hangers, sheet metal, radiator hose clamps, rusted bumper bolts and steel rods up to 3/4" (19.05mm) thick. Includes 3" (76.2mm) disc and independent power regulator. Features hand guard trigger. 5" (127mm) overall length. 2.5 lbs. (1.13 kg) net weight. Works best with 3/8" (9.35mm) inside diameter hose.

SPECIFICATIONS

WORKING AIR PRESSURE: 90 PSI

FREE SPEED: 20,000 RPM

AIR INLET: 1/4" (6.35mm) NPT

AIR CONSUMPTION: 4.0 CFM

WHEEL DIAMETER: 3" (76.2mm)



CAT# 1998

150MM AIR HAMMER WITH FOUR CHISELS

Contoured 1-piece polished aluminum housing with 1/4" (6.35mm) national pipe thread (NPT) inlet. Positive action trigger and built-in regulator for easy speed and power control. Quick change spring for chisel changes. Includes punch, ripping chisel, cold chisel and panel cutter. 5-1/4" (133.35mm) overall length. 3.6 lbs. (1.63 kg) net weight. Works best with 3/8" (9.52mm) inside diameter hose.

SPECIFICATIONS

WORKING AIR PRESSURE: 90 PSI BLOWS PER MINUTE: 4,500 RPM AIR INLET: 1/4" (6.35mm) NPT AIR CONSUMPTION: 4.0 CFM STROKE: 1-5/8" (41.28mm) BORE LENGTH: 3/4" (19.05mm)



HIGH PRESSURE AIR SPRAY GUN

Professional spray gun with 1/4'' (6.35mm) national pipe thread (NPT) inlet. For use at work, in the shop, around the house and on the farm or ranch for any spray job. 2.6 Lbs. (1.18 kg) net weight with canister. Works best with 3/8'' (9.52mm) inside diameter hose.

SPECIFICATIONS

WORKING AIR PRESSURE: 50 – 60 PSI **AIR INLET:** 1/4" (6.35mm) NPT

AIR CONSUMPTION: 4.0 – 7.0 CFM FLUID NOZZLE SIZE: 1.8mm BORE LENGTH: 3/4" (19.05mm)




CAT# 75583

PNEUMATIC (AIR) TOOL OIL (10W), 8 OZ.

Highly blended premium 10 weight (10W) pneumatic (air) tool oil. 8 oz (.237 L). Lubricates all pneumatic tools, compressed air motors and Forney® CAT#'s 75547 and 75582 lubricators. Good maintenance prolongs pneumatic (air) tool life. **DO NOT USE IN COMPRESSORS REQUIRING 30 WEIGHT (30W) OIL.**







18 LBS. TENSILE STRENGTH ULTRA LIGHT-DUTY CABLE TIES

CAT#	PACKAGE QUANTITY	APPROXIMATE LENGTH	WIDTH	THICKNESS	BUNDLE DIAMETER	COLOR
62001	100	4" / 100mm	.10" / 2.5mm	.04" / 1.0mm	.75" / 19.0mm	Natural
62002	100	4" / 100mm	.10" / 2.5mm	.04" / 1.0mm	.75" / 19.0mm	Black
62003	100	4" / 100mm	.10" / 2.5mm	.04" / 1.0mm	.75" / 19.0mm	Red
62004	100	4" / 100mm	.10" / 2.5mm	.04" / 1.0mm	.75" / 19.0mm	Yellow
62005	100	4" / 100mm	.10" / 2.5mm	.04" / 1.0mm	.75" / 19.0mm	Green
62006	100	4" / 100mm	.10" / 2.5mm	.04" / 1.0mm	.75" / 19.0mm	Blue
62007	100	4" / 100mm	.10" / 2.5mm	.04" / 1.0mm	.75" / 19.0mm	Orange
62008	100	4" / 100mm	.10" / 2.5mm	.04" / 1.0mm	.75" / 19.0mm	Purple
62009	100	4" / 100mm	.10" / 2.5mm	.04" / 1.0mm	.75" / 19.0mm	Brown
62010	100	4" / 100mm	.10" / 2.5mm	.04" / 1.0mm	.75" / 19.0mm	Gray
62011	100	8" / 200mm	.10" / 2.5mm	.05" / 1.3mm	2" / 50.8mm	Natural
62012	100	8" / 200mm	.10" / 2.5mm	.05" / 1.3mm	2" / 50.8mm	Black



50 LBS. TENSILE STRENGTH RELEASABLE STANDARD DUTY CABLE TIES

CAT#	PACKAGE QUANTITY	APPROXIMATE LENGTH	WIDTH	THICKNESS	BUNDLE DIAMETER	COLOR
62055	25	8" / 200mm	.19" / 4.8mm	.06" / 1.5mm	2" / 50.8mm	Natural
62056	25	8" / 200mm	.19" / 4.8mm	.06" / 1.5mm	2" / 50.8mm	Black
62057	100	8" / 200mm	.19" / 4.8mm	.06" / 1.5mm	2" / 50.8mm	Natural
62058	100	8" / 200mm	.19" / 4.8mm	.06" / 1.5mm	2" / 50.8mm	Black
62059	100	8" / 200mm	.19" / 4.8mm	.06" / 1.5mm	2" / 50.8mm	Assorted
62060	25	11" / 280mm	.19" / 4.8mm	.06" / 1.5mm	3" / 76.2mm	Natural
62061	25	11" / 280mm	.19" / 4.8mm	.06" / 1.5mm	3" / 76.2mm	Black
62062	100	11" / 280mm	.19" / 4.8mm	.06" / 1.5mm	3" / 76.2mm	Natural
62063	100	11" / 280mm	.19" / 4.8mm	.06" / 1.5mm	3" / 76.2mm	Black
62064	100	11" / 280mm	.19" / 4.8mm	.06" / 1.5mm	3" / 76.2mm	Assorted
62065	100	50 each: 8" / 200mm 11" / 280mm	.19" / 4.8mm	.06" / 1.5mm	_	Assorted



CAT#	PACKAGE QUANTITY	APPROXIMATE LENGTH	WIDTH	THICKNESS	BUNDLE DIAMETER	COLOR
62013	25	8" / 200mm	.19" / 4.8mm	.06" / 1.5mm	2" / 50.8mm	Natural
62014	25	8" / 200mm	.19" / 4.8mm	.06" / 1.5mm	2" / 50.8mm	Black
62015	100	8" / 200mm	.19" / 4.8mm	.06" / 1.5mm	2" / 50.8mm	Natural
62016	100	8" / 200mm	.19" / 4.8mm	.06" / 1.5mm	2" / 50.8mm	Black
62017	100	8" / 200mm	.19" / 4.8mm	.06" / 1.5mm	2" / 50.8mm	Red
62018	100	8" / 200mm	.19" / 4.8mm	.06" / 1.5mm	2" / 50.8mm	Yellow
62019	100	8" / 200mm	.19" / 4.8mm	.06" / 1.5mm	2" / 50.8mm	Green
62020	100	8" / 200mm	.19" / 4.8mm	.06" / 1.5mm	2" / 50.8mm	Blue
62021	100	8" / 200mm	.19" / 4.8mm	.06" / 1.5mm	2" / 50.8mm	Orange
62022	100	8" / 200mm	.19" / 4.8mm	.06" / 1.5mm	2" / 50.8mm	Purple
62023	100	8" / 200mm	.19" / 4.8mm	.06" / 1.5mm	2" / 50.8mm	Brown
62024	100	8" / 200mm	.19" / 4.8mm	.06" / 1.5mm	2" / 50.8mm	Gray
62025	100	8" / 200mm	.19" / 4.8mm	.06" / 1.5mm	2" / 50.8mm	Assorted
62026	25	12" / 300mm	.19" / 4.8mm	.06" / 1.5mm	3" / 76.2mm	Natural
62027	25	12" / 300mm	.19" / 4.8mm	.06" / 1.5mm	3" / 76.2mm	Black
62028	100	12" / 300mm	.19" / 4.8mm	.06" / 1.5mm	3" / 76.2mm	Natural
62029	100	12" / 300mm	.19" / 4.8mm	.06" / 1.5mm	3" / 76.2mm	Black
62030	100	12" / 300mm	.19" / 4.8mm	.06" / 1.5mm	3" / 76.2mm	Red
62031	100	12" / 300mm	.19" / 4.8mm	.06" / 1.5mm	3" / 76.2mm	Yellow
62032	100	12" / 300mm	.19" / 4.8mm	.06" / 1.5mm	3" / 76.2mm	Green
62033	100	12" / 300mm	.19" / 4.8mm	.06" / 1.5mm	3" / 76.2mm	Blue
62034	100	12" / 300mm	.19" / 4.8mm	.06" / 1.5mm	3" / 76.2mm	Orange
62035	100	12" / 300mm	.19" / 4.8mm	.06" / 1.5mm	3" / 76.2mm	Purple
62036	100	12" / 300mm	.19" / 4.8mm	.06" / 1.5mm	3" / 76.2mm	Brown
62037	100	12" / 300mm	.19" / 4.8mm	.06" / 1.5mm	3" / 76.2mm	Gray
62038	100	12" / 300mm	.19" / 4.8mm	.06" / 1.5mm	3" / 76.2mm	Assorted
62039	25	14.5" / 370mm	.19" / 4.8mm	.06" / 1.5mm	4" / 101.6mm	Natural
62040	25	14.5" / 370mm	.19" / 4.8mm	.06" / 1.5mm	4" / 101.6mm	Black
62041	100	14.5" / 370mm	.19" / 4.8mm	.06" / 1.5mm	4" / 101.6mm	Natural
62042	100	14.5" / 370mm	.19" / 4.8mm	.06" / 1.5mm	4" / 101.6mm	Black
62043	100	14.5" / 370mm	.19" / 4.8mm	.06" / 1.5mm	4" / 101.6mm	Red
62044	100	14.5" / 370mm	.19" / 4.8mm	.06" / 1.5mm	4" / 101.6mm	Yellow
62045	100	14.5" / 370mm	.19" / 4.8mm	.06" / 1.5mm	4" / 101.6mm	Blue
62046	100	14.5" / 370mm	.19" / 4.8mm	.06" / 1.5mm	4" / 101.6mm	Orange
62047	100	14.5" / 370mm	.19" / 4.8mm	.06" / 1.5mm	4" / 101.6mm	Purple
62048	100	14.5" / 370mm	.19" / 4.8mm	.06" / 1.5mm	4" / 101.6mm	Brown
62049	100	14.5" / 370mm	.19" / 4.8mm	.06" / 1.5mm	4" / 101.6mm	Gray
62050	100	14.5" / 370mm	.19" / 4.8mm	.06" / 1.5mm	4" / 101.6mm	Assorted
62051	100	17" / 430mm	.19" / 4.8mm	.06" / 1.5mm	4" / 101.6mm	Natural
62052	100	17" / 430mm	.19" / 4.8mm	.06" / 1.5mm	4" / 101.6mm	Black
62053	100	20" / 500mm	.19" / 4.8mm	.06" / 1.5mm	5.9" / 149.9mm	Natural
62054	100	20" / 500mm	.19" / 4.8mm	.06" / 1.5mm	5.9" / 149.9mm	Black

CABLE TIES & TOOLS 29



120 LBS. TENSILE STRENGTH HEAVY-DUTY CABLE TIES

CAT#	PACKAGE QUANTITY	APPROXIMATE LENGTH	WIDTH	THICKNESS	BUNDLE DIAMETER	COLOR
62066	100	8" / 200mm	.29" / 7.4mm	.07" / 1.8mm	2" / 50.8mm	Natural
62067	100	8" / 200mm	.29" / 7.4mm	.07" / 1.8mm	2" / 50.8mm	Black
62068	100	12" / 300mm	.29" / 7.4mm	.07" / 1.8mm	3" / 76.2mm	Natural
62069	100	12" / 300mm	.29" / 7.4mm	.07" / 1.8mm	3" / 76.2mm	Black
62070	100	14.5" / 370mm	.29" / 7.4mm	.07" / 1.8mm	4" / 101.6mm	Natural
62071	100	14.5" / 370mm	.29" / 7.4mm	.07" / 1.8mm	4" / 101.6mm	Black
62077	50	18" / 450mm	.29" / 7.4mm	.07" / 1.8mm	5.2" / 132.0mm	Natural
62078	50	18" / 450mm	.29" / 7.4mm	.07" / 1.8mm	5.2" / 132.0mm	Black



175 LBS. TENSILE STRENGTH EXTRA HEAVY-DUTY CABLE TIES

CAT#	PACKAGE QUANTITY	APPROXIMATE LENGTH	WIDTH	THICKNESS	BUNDLE DIAMETER	COLOR
62079	50	18" / 450mm	.35" / 8.9mm	.08" / 2mm	5.2" / 132.1mm	Natural
62080	50	18" / 450mm	.35" / 8.9mm	.08" / 2mm	5.2" / 132.1mm	Black
62081	25	25.5" / 650mm	.35" / 8.9mm	.08" / 2mm	7" / 117.8mm	Natural
62082	25	25.5" / 650mm	.35" / 8.9mm	.08" / 2mm	7" / 117.8mm	Black
62085	10	36" / 900mm	.35" / 8.9mm	.08" / 2mm	10.7" / 271.8mm	Natural
62086	10	36" / 900mm	.35" / 8.9mm	.08" / 2mm	10.7" / 271.8mm	Black
62089	10	48" / 1220mm	.35" / 8.9mm	.08" / 2mm	15" / 381mm	Natural
62090	10	48" / 1220mm	.35" / 8.9mm	.08" / 2mm	15" / 381mm	Black
	<u> </u>		<u>:</u>	<u> </u>		- E



250 LBS. TENSILE STRENGTH SUPER HEAVY-DUTY CABLE TIES

CAT#	PACKAGE QUANTITY	APPROXIMATE LENGTH	WIDTH	THICKNESS	BUNDLE DIAMETER	COLOR
62096	25	22" / 560mm	.50" / 12.7mm	.09" / 2.3mm	6" / 152.4mm	Natural
62097	25	22" / 560mm	.50" / 12.7mm	.09" / 2.3mm	6" / 152.4mm	Black
62098	10	40" / 1020mm	.50" / 12.7mm	.09" / 2.3mm	12.1" / 307.3mm	Natural
62099	10	40" / 1020mm	.50" / 12.7mm	.09" / 2.3mm	12.1" / 307.3mm	Black



40 LBS, TENSILE STRENGTH LIGHT-DUTY SCREW MOUNT CABLE TIES

CAT#	PACKAGE QUANTITY	APPROXIMATE LENGTH	WIDTH	THICKNESS	BUNDLE DIAMETER	COLOR
62102	100	6.5" / 170mm	.14" / 3.6mm	.07" / 1.8mm	1.44" / 36.6mm	Natural
62103	100	6.5" / 170mm	.14" / 3.6mm	.07" / 1.8mm	1.44" / 36.6mm	Black



50 LBS. TENSILE STRENGTH STANDARD DUTY SCREW MOUNT CABLE TIES

CAT#	PACKAGE QUANTITY	APPROXIMATE LENGTH	WIDTH	THICKNESS	BUNDLE DIAMETER	COLOR
62104	25	8.0" / 200mm	.19" / 4.8mm	.06" / 1.5mm	2.0" / 50.8mm	Natural
62105	25	8.0" / 200mm	.19" / 4.8mm	.06" / 1.5mm	2.0" / 50.8mm	Black
62106	100	8.0" / 200mm	.19" / 4.8mm	.06" / 1.5mm	2.0" / 50.8mm	Natural
62107	100	8.0" / 200mm	.19" / 4.8mm	.06" / 1.5mm	2.0" / 50.8mm	Black
62108	100	15.0" / 380mm	.19" / 4.8mm	.06" / 1.5mm	4.0" / 101.6mm	Natural
62109	100	15.0" / 380mm	.19" / 4.8mm	.06" / 1.5mm	4.0" / 101.6mm	Black



120 LBS. TENSILE STRENGTH HEAVY-DUTY SCREW MOUNT CABLE TIES

CAT#	PACKAGE QUANTITY	APPROXIMATE LENGTH	WIDTH	THICKNESS	BUNDLE DIAMETER	COLOR
62110	25	15" / 380mm	.29" / 7.4mm	.07" / 1.8mm	4" / 101.6mm	Natural
62111	25	15" / 380mm	.29" / 7.4mm	.07" / 1.8mm	4" / 101.6mm	Black



40 LBS. TENSILE STRENGTH ARROWHEAD PUSH MOUNT CABLE TIES

CAT#	PACKAGE QUANTITY	APPROXIMATE LENGTH	WIDTH	THICKNESS	BUNDLE DIAMETER	COLOR
62112	25	6" / 150mm	.15" / 3.8mm	.06" / 1.5mm	1.5" / 38.1mm	Natural
62113	25	6" / 150mm	.15" / 3.8mm	.06" / 1.5mm	1.5" / 38.1mm	Black
62114	100	6" / 150mm	.15" / 3.8mm	.06" / 1.5mm	1.5" / 38.1mm	Natural
62115	100	6" / 150mm	.15" / 3.8mm	.06" / 1.5mm	1.5" / 38.1mm	Black



CABLE TIE MOUNTS

Fits tie sizes 18 – 50 lbs. To mount, peel and stick adhesive or use #6 – #8 screw.

CAT#	PACKAGE QUANTITY	LENGTH	WIDTH	HEIGHT	COLOR
62116	25	1"	1"	0.22"	Natural
62117	25	1"	1"	0.22"	Black
62118	50	1"	1"	0.22"	Natural
62119	50	1"	1"	0.22"	Black
62120	100	1"	1"	0.22"	Natural
62121	100	1"	1"	0.22"	Black




CAT# 62122

TENSION TOOL FOR NYLON CABLE TIES

General use tension tool for nylon cable ties. Tool for tension adjustment and cutting of 18 to 50 lbs. nylon cable ties (up to .19" wide). Ideal for electricians, car repair or hard to reach areas.







GALVANIZED WIRE ROPE CLIPS

Drop-forged galvanized wire rope (aircraft cable) clips. **NOT SUITABLE FOR OVERHEAD LIFTING.**

CAT#	DESCRIPTION	SIZE
61010	Wire rope (aircraft cable) clips	1/8" (3.18mm)
61011	Wire rope (aircraft cable) clips	3/16" (4.76mm)
61012	Wire rope (aircraft cable) clips	1/4" (6.35mm)
61013	Wire rope (aircraft cable) clips	5/16" (7.94mm)
61014	Wire rope (aircraft cable) clips	3/8" (9.52mm)
61015	Wire rope (aircraft cable) clips	7/16" (11.11mm)
61016	Wire rope (aircraft cable) clips	1/2" (12.7mm)



ZINC PLATED WIRE ROPE CLIPS

Zinc plated malleable wire rope (aircraft cable) clips. **NOT SUITABLE FOR OVERHEAD LIFTING.**

CAT#	DESCRIPTION	SIZE
61019	Wire rope (aircraft cable) clips	1/16" (1.59mm)
61020	Wire rope (aircraft cable) clips	1/8" (3.18mm)
61021	Wire rope (aircraft cable) clips	3/16" (4.76mm)
61022	Wire rope (aircraft cable) clips	1/4" (6.35mm)
61023	Wire rope (aircraft cable) clips	5/16" (7.94mm)
61024	Wire rope (aircraft cable) clips	3/8" (9.52mm)
61025	Wire rope (aircraft cable) clips	1/2" (12.7mm)



CAT# 61019

ZINC PLATED WIRE ROPE THIMBLES

Standard duty zinc plated wire rope (aircraft cable) thimbles. **NOT SUITABLE FOR OVERHEAD LIFTING.**

CAT#	DESCRIPTION	SIZE
61029	Wire rope thimble	1/16" (1.59mm)
61030	Wire rope thimble	1/8" (3.18mm)
61031	Wire rope thimble	3/16" (4.76mm)
61032	Wire rope thimble	1/4" (6.35mm)
61033	Wire rope thimble	5/16" (7.94mm)
61034	Wire rope thimble	3/8" (9.52mm)
61035	Wire rope thimble	1/2" (12.7mm)



CAT# 61029



4-PACK ALUMINUM STOPS & FERRULES FOR WIRE ROPE

Aluminum stops and ferrules (cable sleeves) for wire rope (aircraft cable). Two (2) stops and two (2) ferrules per package. **NOT SUITABLE FOR OVERHEAD LIFTING.**

CAT#	DESCRIPTION	SIZE
61036	4-pack aluminum stops & ferrules	1/16" (1.59mm)
61037	4-pack aluminum stops & ferrules	1/8" (3.18mm)
61038	4-pack aluminum stops & ferrules	3/16" (4.76mm)
61039	4-pack aluminum stops & ferrules	1/4" (6.35mm)



CAT# 61040

CLEVIS GRAB HOOKS

High test. Drop forged and galvanized. Used to connect lifting and rigging attachments. **NOT SUITABLE FOR OVERHEAD LIFTING.**

CAT#	SIZE	WORK LOAD LIMIT
	1/4" (6.35mm)	2,600 lbs. (1,179.34 kg)
61041	5/16" (7.94mm)	3,900 lbs. (1,769.01 kg)
61042	3/8" (9.52mm)	5,400 lbs. (2,449.40 kg)
61043	7/16" (11.11mm)	7,200 lbs. (3,265.87 kg)
	1/2" (12.7mm)	9,200 lbs. (4,173.05 kg)



GRADE 70 CLEVIS GRAB HOOKS

Grade 70 (yellow zinc) clevis grab hooks. Drop forged and galvanized. Used to connect lifting and rigging attachments. **NOT SUITABLE FOR OVERHEAD LIFTING.**

CAT#	SIZE	WORK LOAD LIMIT
61046	5/16" (7.94mm)	4,500 lbs. (2,041.17 kg)
61047	3/8" (9.52mm)	6,600 lbs. (2,993.71 kg)

CLEVIS SLIP HOOKS

Clevis slip hooks. High test. Drop forged and galvanized. Used to connect lifting and rigging attachments. **NOT SUITABLE FOR OVERHEAD LIFTING.**

CAT#	SIZE	WORK LOAD LIMIT
	1/4" (6.35mm)	1,950 lbs. (884.51 kg)
61051	5/16" (7.94mm)	2,875 lbs. (1,304.08 kg)
61052	3/8" (9.52mm)	4,000 lbs. (1,814.37 kg)
61053	7/16" (11.11mm)	5,000 lbs. (2,267.96 kg)
61054	1/2" (12.7mm)	6,500 lbs. (2,948.35 kg)



CAT# 61050

EYE GRAB HOOKS

Eye grab hook. High test. Drop forged and galvanized. Used to connect lifting and rigging attachments. **NOT SUITABLE FOR OVERHEAD LIFTING.**

CAT#	SIZE	WORK LOAD LIMIT
	1/4" (6.35mm)	2,600 lbs. (1,179.34 kg)
61061	5/16" (7.94mm)	3,900 lbs. (1,769.01 kg)
61062	3/8" (9.52mm)	5,400 lbs. (2,449.40 kg)
61063	7/16" (11.11mm)	7,000 lbs. (3,175.15 kg)
61064	1/2" (12.7mm)	9,200 lbs. (4,173.05 kg)



EYE SLIP HOOKS

Eye slip hook. High test. Drop forged and galvanized. Used to connect lifting and rigging attachments. **NOT SUITABLE FOR OVERHEAD LIFTING.**

CAT#	SIZE	WORK LOAD LIMIT
	1/4" (6.35mm)	1,950 lbs. (884.51 kg)
61071	5/16" (7.94mm)	2,875 lbs. (1,304.08 kg)
61072	3/8" (9.52mm)	4,000 lbs. (1,814.37 kg)
61073	7/16" (11.11mm)	5,000 lbs. (2,267.96 kg)
61074	1/2" (12.7mm)	6,500 lbs. (2,948.35 kg)



CAT# 61070



CLEVIS SLIP HOOKS WITH LATCH

Clevis slip hooks with latch. High test. Drop forged and galvanized. Used to connect lifting and rigging attachments. **NOT SUITABLE FOR OVERHEAD LIFTING.**

CAT#	SIZE	WORK LOAD LIMIT
	1/4" (6.35mm)	1,950 lbs. (1,247.38 kg)
61081	5/16" (7.94mm)	2,875 lbs. (1,950.45 kg)
61082	3/8" (9.52mm)	4,000 lbs. (2,381.36 kg)
61083	7/16" (11.11mm)	5,000 lbs. (3,175.15 kg)
	1/2" (12.7mm)	6,500 lbs. (4,082.33 kg)



CAT# 61086

GRADE 70 CLEVIS SLIP HOOK WITH LATCH

Grade 70 (yellow zinc) clevis slip hooks with latch. Drop forged and galvanized. Used to connect lifting and rigging attachments. **NOT SUITABLE FOR OVERHEAD LIFTING.**

CAT#	SIZE	WORK LOAD LIMIT
61086	5/16" (7.94mm)	4,300 lbs. (1,950.45 kg)
61087	3/8" (9.52mm)	5,250 lbs. (2,381.36 kg)



EYE SNAP HOOK WITH LATCH

Eye snap hook with latch. High test. Drop forged and galvanized. Used to connect lifting and rigging attachments. **NOT SUITABLE FOR OVERHEAD LIFTING.**

CAT#	SIZE	WORK LOAD LIMIT
61085	7/16" (11.11mm)	750 lbs. (340.19 kg)

COLD SHUTS

Cold shuts. Zinc plated. Use to repair broken grade 30 proof coil chain or high test chain. NOT SUITABLE FOR OVERHEAD LIFTING.

CAT#	DESCRIPTION	SIZE
	For grade 30 proof coil or high test chain	3/16″
	For grade 30 proof coil or high test chain	1/4″
	For grade 30 proof coil or high test chain	5/16″
	For grade 30 proof coil or high test chain	3/8″
61095	For grade 30 proof coil or high test chain	1/2″



CAT# 61090

COLD SHUT REPAIR LINKS

Cold shut repair links. Galvanized. Use to repair broken grade 30 proof coil chain or high test chain. NOT SUITABLE FOR OVERHEAD LIFTING.

CAT#	DESCRIPTION	SIZE
61110	Use to repair broken grade 30 proof coil chain or high test chain.	3/16″
61111	Use to repair broken grade 30 proof coil chain or high test chain.	1/4″
61112	Use to repair broken grade 30 proof coil chain or high test chain.	5/16"
61113	Use to repair broken grade 30 proof coil chain or high test chain.	3/8″



QUICK LINKS

Quick links. Galvanized. Use to repair broken grade 30 proof coil chain or high test chain. NOT SUITABLE FOR OVERHEAD LIFTING.

CAT#	DESCRIPTION	SIZE
	For grade 30 proof coil or high test chain	3/16″
	For grade 30 proof coil or high test chain	1/4″
	For grade 30 proof coil or high test chain	5/16″
	For grade 30 proof coil or high test chain	3/8″
	For grade 30 proof coil or high test chain	1/2″



CAT# 61120



TWIN CLEVIS LINKS

Galvanized twin clevis links for grade 30 proof coil chain or high test chain. **NOT SUITABLE FOR OVERHEAD LIFTING.**

CAT#	SIZE	WORK LOAD LIMIT
61130	1/4" (6.35mm) to 5/16" (7.94mm)	4,700 lbs. (2,131.88 kg)
61131	3/8" (9.52mm)	6,600 lbs. (2,993.71 kg)
61132	7/16" (11.11mm) to 1/2" (12.7mm)	11,250 lbs. (5,102.91 kg)



REGULAR SWIVELS

Regular swivel. Made from forged heat treated steel and galvanized. **NOT SUITABLE FOR OVERHEAD LIFTING.**

CAT#	SIZE	WORK LOAD LIMIT
	1/4" (6.35mm)	850 lbs. (385.55 kg)
61141	5/16" (7.94mm)	1,250 lbs. (566.99 kg)
61142	3/8" (9.52mm)	2,250 lbs. (1,020.58 kg)
	1/2" (12.7mm)	3,600 lbs. (1,632.93 kg)



JAW END SWIVELS

Jaw end swivel. Made from forged heat treated steel and galvanized. **NOT SUITABLE FOR OVERHEAD LIFTING.**

CAT#	SIZE	WORK LOAD LIMIT
	1/4" (6.35mm)	850 lbs. (385.55 kg)
	5/16" (7.94mm)	1,250 lbs. (566.99 kg)
61152	3/8" (9.52mm)	2,250 lbs. (1,020.58 kg)
61153	1/2" (12.7mm)	3,600 lbs. (1,632.93 kg)

SCREW PIN ANCHOR SHACKLES

Anchor shackle with screw pin. Made from forged heat treated steel and galvanized. Pins are alloy steel. **NOT SUITABLE FOR OVERHEAD LIFTING.**

CAT#	SIZE	WORK LOAD LIMIT
	3/16" (4.76mm)	666 lbs. (302.09 kg)
61161	1/4" (6.35mm)	1,000 lbs. (453.59 kg)
61162	5/16" (7.94mm)	1,500 lbs. (680.39 kg)
61163	3/8" (9.52mm)	2,000 lbs. (907.14 kg)
61164	7/16" (11.11mm)	3,000 lbs. (1,360.78 kg)
61165	1/2" (12.7mm)	4,000 lbs. (1,814.37 kg)



CAT# 61160

CLEVIS PIN ANCHOR SHACKLES

Anchor shackles with clevis pin. Made from forged heat treated steel and galvanized. Pins are alloy steel. **NOT SUITABLE FOR OVERHEAD LIFTING.**

CAT#	SIZE	WORK LOAD LIMIT
	3/16" (4.76mm)	666 lbs. (302.09 kg)
61171	1/4" (6.35mm)	1,000 lbs. (453.59 kg)
61172	5/16" (7.94mm)	1,500 lbs. (680.39 kg)
61173	3/8" (9.52mm)	2,000 lbs. (907.14 kg)
61174	7/16" (11.11mm)	3,000 lbs. (1,360.78 kg)
61175	1/2" (12.7mm)	4,000 lbs. (1,814.37 kg)



CAT# 61170

DOUBLE ROUND EYE SWIVELS

Double round eye swivel, zinc plated. Made from forged heat treated steel and galvanized. **NOT SUITABLE FOR OVERHEAD LIFTING.**

CAT#	DESCRIPTION	SIZE	
	Double round eye swivel	1/2" x 1/2"	
61288	Double round eye swivel	5/8" x 5/8"	
61289	Double round eye swivel	3/4" x 3/4"	
61290	Double round eye swivel	1" x 1"	





DOUBLE SQUARE EYE SWIVEL

Double square eye swivel, zinc plated. Made from forged heat treated steel and galvanized. **NOT SUITABLE FOR OVERHEAD LIFTING.**

CAT#	DESCRIPTION	SIZE
	Double square eye swivel	1" x 1"



ROUND EYE SNAP HOOK

Die cast plated zinc alloy with nickel plating. Used to connect lifting and rigging attachments. **NOT SUITABLE FOR OVERHEAD LIFTING.**

CAT#	EYE SIZE	PIN SIZE
61264	3-1/2"	5/8″



SPRING HOOKS

Die cast plated zinc alloy with nickel plating with universal snap. Used to connect lifting and rigging attachments. **NOT SUITABLE FOR OVERHEAD LIFTING.**

CAT#	HOOK SIZE	PIN SIZE
	50mm	5mm
61303	60mm	6mm
61304	80mm	8mm
61305	90mm	9mm
61306	100mm	10mm

HOOK & EYE TURNBUCKLES

Forged steel body and steel hook and eye turnbuckle. Observe all maximum WWL limits. Overhead lifting or support of human weight requires special chain and accessories.

CAT#	SIZE		
	5/16" (7.94mm) x 4-1/2" (114.3mm)		
61322	3/8" (9.52mm) x 6" (152.40mm)	1,000 lbs. (453.59 kg)	
61323	1/2" (12.7mm) x 6" (152.40mm)	1,500 lbs. (680.39 kg)	
61324	1/2" (12.7mm) x 9" (228.60mm)	1,500 lbs. (680.39 kg)	
	5/8" (15.88mm) x 6" (152.40mm)		



SCREW EYE BOLTS WITH SHOULDER

Screw eye bolts with shoulder. Hot dipped, galvanized.

CAT#	DESCRIPTION	SIZE
61360	Screw eye bolt with shoulder	2" with 1/4" eye size
61363	Screw eye bolt with shoulder	2" with 5/16" eye size
61369	Screw eye bolt with shoulder	3-1/4" with 1/2" eye size



CAT# 61360

MACHINE EYE BOLT WITH NUTS

Machine eye bolt with nut. Hot dipped, galvanized.

CAT#	DESCRIPTION	SIZE
61373	Machine eye bolt with nut	2" with 1/4" eye size
61378	Machine eye bolt with nut	2-1/4" with 5/16" eye size
61381	Machine eye bolt with nut	4-1/4" with 5/16" eye size
61383	Machine eye bolt with nut	2-1/2" with 3/8" eye size
61385	Machine eye bolt with nut	4-1/2" with 3/8" eye size
61386	Machine eye bolt with nut	6" with 3/8" eye size
61388	Machine eye bolt with nut	3-1/4" with 1/4" eye size
61389	Machine eye bolt with nut	6" with 1/2" eye size





STRAIGHT HITCH PINS WITH CLIP

Yellow zinc hitch pins.

CAT#	DESCRIPTION	SIZE
	Yellow zinc hitch pin	5/8" x 4-1/2"
61332	Yellow zinc hitch pin	3/4" x 6-1/4"
	Yellow zinc hitch pin	7/8" x 6-1/4"



ZINC PLATED LYNCH PINS

Zinc plated lynch pins.

CAT#	DESCRIPTION	SIZE
61352	Lynch pin	1/4"
61353	Lynch pin	5/16"



CAT# 61340

5/8 IN. BENT HITCH PIN WITH CLIP

5/8" zinc plated bent hitch pin with clip.



CAT# 61345

1/4 IN. SQUARE POWER TAKE-OFF HITCH PIN

Zinc plated 1/4" square power take-off pin.



CAT# 61357

1/8 IN. REPLACEMENT "R" CLIP FOR HITCH PINS

Zinc plated 1/8" replacement "R" clip.

GRADE 70 BINDER CHAIN WITH CLEVIS GRAB HOOKS

DOT approved grade 70 binder chain with clevis grab hooks.

CAT#	BULK CAT#	SIZE & LENGTH	WORK LOAD LIMIT	
70397	*70400	5/16" x 20'	4,700 lbs.	
70398	*70401	3/8" x 14'	6,600 lbs.	
70399	**70402	3/8" x 20'	6,600 lbs.	

^{*} Barrel of 20 pieces



CAT# 70397

GRADE 70 YELLOW ZINC CHAIN

Chain by the bucket. Grade 70 yellow zinc transport chain. 100 Lbs. (45.36 Kg) bucket. Approved by the Department of Transportation (DOT). **NOT SUITABLE FOR OVERHEAD LIFTING.**

CAT#	SIZE & LENGTH	WORK LOAD LIMIT
70403	92′ X 5/16″	4,700 lbs.
70404	66′ X 3/8″	6,600 lbs.



CAT# 70403

GRADE 30 PROOF COIL CHAIN

Chain by the bucket. Grade 30 proof coil, zinc plated. Hot galvanized. **NOT SUITABLE FOR OVERHEAD LIFTING.**

CAT#	SIZE & LENGTH	WORK LOAD LIMIT
70410	250' x 3/16"	750 lbs.
70411	141' x 1/4"	1,250 lbs.
70412	92′ x 5/16″	1,900 lbs.
70413	63' x 3/8"	2,650 lbs.



CAT# 70410

^{**} Barrel of 15 pieces



CAT# 70420

#2/0 X 175 FT. DOUBLE LOOP CHAIN

Double loop chain, 175' (53.34m) x #2/0 zinc plated double loop chain on plastic reel. 255 lbs. (115.67 kg) work load limit (WLL). NOT SUITABLE FOR OVERHEAD LIFTING.



CAT# 70421

#3 X 100 FT. DOUBLE LOOP CHAIN

Double loop chain 100' (30.48m) x #3 zinc plated double loop chain on plastic reel. 90 lbs. (40.82 kg) work load limit (WLL). **NOT SUITABLE FOR OVERHEAD LIFTING.**



CAT# 70425

#2/0 X 125 FT. STRAIGHT LINK COIL CHAIN

Straight link coil chain, 125' (38.1m) x #2/0 zinc plated straight link coil chain on plastic reel. 520 lbs. (235.88 kg) work load limit (WLL). NOT SUITABLE FOR

OVERHEAD LIFTING.



CAT# 70426

#2/0 X 110 FT. TWIST LINK CHAIN

Twist link machine chain, 110' (33.53m) x #2/0 zinc plated twist link machine chain on plastic reel. 495 lbs. (224.53 kg) work load limit (WLL). NOT SUITABLE FOR OVERHEAD LIFTING.



CAT# 70408

3/64 IN. - 3/16 IN. CABLE CUTTER

Wire & cable cutter, 8" (203.2mm) 3/64" (1.19mm) to 3/16" (4.76mm). hand-held cable cutter. Industrial class quality with drop forged blades and induction quenched cutting edges.



CAT# 70409

36 IN. BOLT CUTTER

36" bolt cutter. Sturdy, economical cutting tool for Forney® and similar chain. 36" (914.4mm) long. Designed to cut up to 3/8" grade 30 proof coil. Use Forney® CAT# 70407 for larger and/or harder chain.



STRUGGLING WITH BOLT CUTTERS?

LET A HYDRAULIC CHAIN CUTTER DO THE WORK FOR YOU!

CAT# 70407

HYDRAULIC CHAIN/CABLE CUTTER

Heavy-duty hydraulic chain and cable cutter. Drop-ship (D.S.) only.

CAPACITIES:

- 3/8" (9.52mm) alloy chain (Grade 70) 1/2" (12.7mm) high test (proof chain)
- 3/8" (9.52mm) wire rope (aircraft cable)





CAT# 70445

GALVANIZED WIRE ROPE (AIRCRAFT CABLE)

Galvanized wire rope (aircraft cable) spool. 7x7 small diameter construction wire rope is not intended for aircraft use but is designed for industrial and marine applications. 7x19 rotation resistant wire ropes are designed to resist the tendency to spin or rotate under load and are ideal for general purpose use on single-part crane lines to lift a free load or where rotation resistance is crucial. NOT SUITABLE FOR OVERHEAD LIFTING.

CAT#	TYPE	SIZE & LENGTH	BREAKING STRENGTH	WORK LOAD LIMIT
70445	7x7	500' (152.4m) x 1/16" (1.59mm)	480 lbs. (217.72 kg)	96 lbs. (43.5 kg)
70446	7x7	500' (152.4m) x 1/8" (3.18mm)	1,700 lbs. (771.11 kg)	340 lbs. (154.2 kg)
70447	7x7	250' (76.2m) x 3/16" (4.76mm)	3,700 lbs. (1,678.29 kg)	740 lbs. (335.7 kg)
70448	7x19	250' (76.2m) x 1/4" (6.35mm)	7,000 lbs. (3,175.15 kg)	1400 lbs. (635 kg)

GALVANIZED (7X7) VINYL COATED WIRE ROPE (AIRCRAFT CABLE)

Vinyl coated wire rope (aircraft cable) spool. Small diameter construction wire rope is not intended for aircraft use but is designed for industrial and marine applications. NOT SUITABLE FOR OVERHEAD LIFTING.

CAT#	TYPE	SIZE & LENGTH	BREAKING STRENGTH	WORK LOAD LIMIT
70450	7x7	500' (152.4m) x 1/16"- 3/32" (1.59mm-2.38mm)	480 lbs. (217.72 kg)	96 lbs. (43.5 kg)
70451	7x7	250' (76.2m) x 3/32"- 3/16" (2.38mm-4.76mm)	920 lbs. (417.30 kg)	184 lbs. (83.5 kg)
70452	7x7	250' (76.2m) x 1/8"- 3/16" (3.18mm-4.76mm)	1,700 lbs. (771.11 kg)	340 lbs. (154.2 kg)
70453		250' (76.2m) x 3/16"- 1/4" (4.76mm-6.35mm)	4,200 lbs. (1,905.09 kg)	840 lbs. (381 kg)



CAT# 70450



RATCHET TIE DOWN STRAP WITH FLAT HOOKS

2" (50.8mm) x 27' (8.23m) ratchet tie down with flat hooks and wide handle ratchet. Made with 12,000 lbs. (5,443.11 kg) webbing. Assembly rated capacity 10,000 lbs. (4,535.92 kg) and work load limit (WLL) of 3,335 lbs. (1,512.73 kg).



CAT# 70465

RATCHET TIE DOWN STRAP WITH "S" HOOKS

1'' (25.4mm) x 16' (4.88m) ratchet tie down with coated "S" hooks. Made with 2,400 lbs. rated capacity (2,041.17 kg) polyester webbing.



CAT# 70467

GRADE 70 RATCHET CHAIN BINDER

Ratchet load binder for use on 5/16" (7.94mm) grade 70 chain to 3/8" (9.52mm) grade 43 chain. 5,400 lbs. (2,449.40 kg) work load limit (WLL). Forged and painted. Department of Transportation (DOT) approved for truck tie-down use.







FORNEY® BATTERY/TRICKLE CHARGER, 1.5 AMP, 12 VOLT

1.5 amps, 12 volts. Includes automatic over-charging protection, short protection, reverse hook-up protection, overheat protection, LED indicator and instruction manual. Ideal for keeping batteries charged while in storage. ETL certified. 5-3-1 warranty with "advanced replacement."



INDUSTRY LEADING 5/3/1 WARRANTY

CAT# 52721

FORNEY® BATTERY/TRICKLE CHARGER, 2/6 **AMP, 6/12 VOLT**

2 amp trickle charge at 6 volts and 12 volts. 6 amp medium charge at 12 volts. Automatic operation. Includes over-charging protection at 12 Volts, reverse hook-up protection, short circuit protection, overheat protection, instruction manual and easy-to-read ammeter. ETL certified. 5-3-1 warranty with "advanced replacement."



INDUSTRY LEADING 5/3/1 WARRANTY

CAT# 52722

FORNEY® BATTERY CHARGER, 10 AMP, 12 **VOLT, FULLY AUTOMATIC**

10 amp, 12 volt. Fully automatic and manually selectable. Includes overcharging protection in automatic mode, reverse hook-up protection, short circuit protection, overheat protection, instruction manual and easy-to-read ammeter. ETL certified. 5-3-1 warranty with "advanced replacement."



INDUSTRY LEADING 5/3/1 WARRANTY

CAT# 52723

FORNEY® BATTERY CHARGER, 2/10/50 AMP, 12 VOLT, 50 AMP EMERGENCY START

2 amp trickle charge, 10 amp fast charge, and 50 amp for emergency engine starting. Made for 12 volt batteries. Fully automatic. Includes over-charging protection, reverse hook-up protection, short protection, overheat protection, instruction manual and ammeter with LED indicator. ETL certified. 5-3-1 warranty with "advanced replacement."



INDUSTRY LEADING 5/3/1 WARRANTY



INDUSTRY LEADING 5/3/1 WARRANTY

WWW.FORNEYIND.COM

CAT# 52725

FORNEY® WHEELED BATTERY CHARGER WITH 200 AMP ENGINE START, 2/10/40/200 AMP, 6/12 VOLT

2 amp slow charge, 10 amp fast charge, 40 amp fast charge, 200 amp for emergency engine start. Made for both 6 and 12 volt batteries. Manual operation. Fan cooled. Includes reverse hook-up protection, short protection, overheat protection, hold position on timer switch for continuous charging, rotary switch for ease of use and accuracy, and instruction manual. ETL certified. 5-3-1 Warranty with "Advanced Replacement."

CAT# 52726

FORNEY® WHEELED BATTERY CHARGER WITH 300 AMP ENGINE START, 2/30/60/300 AMP, 6/12 VOLT

2 amp trickle charge, 30 amp fast charge, 60 amp rapid charge, 300 amp for emergency engine start. Made for both 6 volt and 12 volt batteries. Manual operation. Fan cooled. Includes reverse hook-up protection, short protection, overheat protection, hold position on timer switch for continuous charging, rotary switch for ease of use and accuracy, and instruction manual. ETL certified. 5-3-1 Warranty with "Advanced Replacement."



INDUSTRY LEADING 5/3/1 WARRANTY

CAT# 52730

FORNEY® JUMP START, 7AH, 12V, 400PA

7 amp-hour, 12 volt. Sealed lead-acid battery. Includes 8-gauge booster cable, wall charger and 12 volt cigarette lighter/charger, one (1) 12 volt outlet with 15 amp overload protector, overheat protection, LED battery status indicator and instruction manual. CE Certified. 1 year/90 day limited warranty with "advanced replacement."

COLD CRANKING: 90 – 150 amps **NORMAL CRANKING (CA):** 150 amps

PEAK (PA): 400 amps



INDUSTRY LEADING 5/3/1 WARRANTY

CAT# 52731

FORNEY® JUMP START, 18AH, 12V, 800PA

18 amp-hour, 12 volt. Sealed lead-acid battery. Includes 6-gauge booster cable, wall charger and 12 volt cigarette lighter/charger, two (2) 12 volt outlets with 15 amp overloading protector, 5 volt DC USB port, safety on/off switch, overcharging protection, ultrabright LED work light, LED battery status indicator and instruction manual. CE certified. 1 year/90 day limited warranty with "advanced replacement."

COLD CRANKING: 150 – 210 amps

NORMAL CRANKING (CA): 250 - 300 amps

PEAK (PA): 800 amps





FORNEY® JUMP START WITH AIR COMPRESSOR, 18AH, 12V, 800PA

Forney® jump start with 120 PSI air compressor. 18 amp-hour, 12 volt. Sealed lead-acid battery. Includes 6-gauge booster cable, 120 PSI air compressor, wall charger and 12 volt cigarette lighter/charger, 5 volt DC USB port, two (2) 12 volt outlets with 15 amp overloading protection, safety on-off switch, overcharging protection, ultra-bright LED light, LED battery status indicator and instruction manual. CE certified. 1-year/90-day limited warranty with "advanced replacement."

COLD CRANKING: 150 – 210 amps

NORMAL CRANKING (CA): 250 - 300 amps

PEAK (PA): 800 amps







CAT# 52865





CAT# 52880



HEAVY-DUTY BATTERY JUMPER CABLES

Heavy-duty battery jumper cables. Made with premium copper welding cable. Super heavy-duty 500 amp clamps used on both ends of cable Forney® CAT# 54722 are replacement 500 amp clamps. This may be the last jumper cable you'll ever have to buy!

CAT#	DESCRIPTION	LENGTH
52865	#4 premium copper welding cable	12′ (3.66m)
52866	#4 premium copper welding cable	16′ (4.88m)
52867	#4 premium copper welding cable	20' (6.1m)
52868	#4 premium copper welding cable	25' (7.62m)
52870	#4 twin premium copper welding cable	12′ (3.66m)
52871	#4 twin premium copper welding cable	16′ (4.88m)
52872	#4 twin premium copper welding cable	20' (6.1m)
52873	#4 twin premium copper welding cable	25' (7.62m)
52875	#2 premium copper welding cable	12′ (3.66m)
52876	#2 premium copper welding cable	16′ (4.88m)
52877	#2 premium copper welding cable	20' (6.1m)
52878	#2 premium copper welding cable	25' (7.62m)

BATTERY BOOSTER CABLES

Made of copper coated aluminum. Recommended 200 amp maximum use.

CAT#	DESCRIPTION	LENGTH
52880	#8 gauge cables with 400 amp clamps	12' (3.66m)
52881	#6 gauge cables with 400 amp clamps	16′ (4.88m)
52882	#4 gauge cables with 500 amp clamps	20′ (6.1m)

CAT# 52841

BUMPER JUMPER KIT BY FORNEY®

The bumper jumper kit includes output jack, retaining knobs, insulating washers and bumper plate. Simply mount between bumper and service unit battery. Use with Forney® CAT#'s 57901 and 57902 male sure-grip plugs on bumper plate end of jumper cables. Excellent for service stations, auto dealers, garages, trucking firms, contractors, farmers and ranchers.

FORNEY INDUSTRIES



CAT# 54705

500 AMP HEAVY-DUTY BATTERY CHARGER CLAMPS

500 amp heavy-duty insulated battery charger clamps with alligator-style copper plated jaws. Includes positive and negative clamps. Accepts up to #2 gauge cable. Heavy-duty construction and easy grip handles.



CAT# 54717

200 AMP MEDIUM-DUTY BATTERY CHARGER CLAMPS

200 amp medium-duty copper plated battery charger clamps with heavy spring for positive clamping action. Includes positive and negative clamps. Heavy-duty construction and easy grip handles.



CAT# 54722

500 AMP COMMERCIAL BATTERY CHARGER CLAMPS

500 amp commercial grade battery charger clamps with parrot-style zinc plated jaws. Includes positive and negative clamps. Accepts up to #2 gauge cable. Heavy-duty construction and easy grip handles.



CAT# 54727

50 AMP TUNE-UP CLAMPS

50 amp copper plated tune-up clamps. Fine quality, copper plated battery and tune-up replacement clip. With red and black insulators.



CAT# 54732

80 AMP STANDARD DUTY CLAMPS

80 amp standard duty copper plated battery clamps. Includes positive and negative clamps. Accepts up to #8 gauge cable. Heavy-duty construction and easy grip handles.



CAT# 60348

BATTERY & CHARGER ELECTRICAL TEST CLIP 2-PACK

General purpose battery and charger electrical test clip with insulator, 25 amp (2-pack).



CAT# 54770

UNIVERSAL TOP POST BATTERY TERMINAL

High quality battery terminal ends for many applications and uses. Fits wire sizes #8 gauge – #4/0. Meets S.A.E. standards. Designed to restore worn battery cables to original configuration or to convert from one battery style to another. Forney® CAT# 54785 is 10-pack.



CAT# 54771

UNIVERSAL SIDE POST BATTERY TERMINAL

High quality battery terminal ends for many applications and uses. Fits wire sizes #8 gauge – #4/0. Meets S.A.E. standards. Designed to restore worn battery cables to original configuration or to convert from one battery style to another. Forney® CAT# 54788 is 8-pack.



CAT# 54772

HEAVY-DUTY UNIVERSAL TOP POST BATTERY TERMINAL

High quality heavy duty battery terminal ends for many applications and uses. Fits wire sizes #1 gauge – #4/0. Meets S.A.E. standards. Designed to restore worn battery cables to original configuration or to convert from one battery style to another. Forney® CAT# 54786 is 10-pack.

FORNEY INDUSTRIES



CAT# 54773

MARINE POST BATTERY TERMINAL

Lead-type marine post battery terminal with wing nut and 5/16" (7.94mm) stud. Fits wire sizes #8 gauge – #4/0. Meets S.A.E. standards. Designed to restore worn battery cables to original configuration or to convert from one battery style to another. Forney® CAT# 54787 is 10-pack.



CAT# 54774

SIDE POST BATTERY TERMINAL (2-PACK)

Side post battery terminal adapter, 2-pack. Converts top post to side terminal application. High quality terminal ends for many applications and uses. Fits wire sizes #8 gauge – #4/0. Meets or exceeds S.A.E. standards. Proven in rigorous testing.



CAT# 54775

SIDE TERMINAL CONVERSION POSTS (2-PACK)

Side terminal conversion posts, 2-pack. Converts side terminal to top post. High quality terminal ends for many applications and uses. Fits wire sizes #8 gauge – #4/0. Meets or exceeds S.A.E. standards. Proven in rigorous testing.



CAT# 54785

UNIVERSAL TOP POST BATTERY TERMINAL

10-each Forney® CAT# 54770 regular duty universal top post terminals. Fits wire sizes #8 gauge – #4/0. Meets S.A.E. standards. Designed to restore worn battery cables to original configuration or to convert from one battery style to another.



CAT# 54786

HEAVY-DUTY UNIVERSAL TOP POST BATTERY TERMINAL

10-each Forney® CAT# 54772 heavy-duty universal top post batter terminals. Fits wire sizes #1 gauge – #4/0. Meets S.A.E. standards. Designed to restore worn battery cables to original configuration or to convert from one battery style to another.



CAT# 54787

MARINE POST BATTERY TERMINAL

10-each Forney® CAT# 54778 lead-type marine post battery terminals with wing nut and 5/16" (7.94mm) stud. Fits wire sizes #8 gauge – #4/0. Meets S.A.E. standards. Proven in rigorous testing. Designed to restore worn battery cables to original configuration or to convert from one battery style to another.



CAT# 54781

BOLT & NUT FOR BATTERY TERMINALS

5/16" (7.94mm) x 1-1/4" (31.75mm) plated bolt and nut for battery terminals. Bulk. Forney® CAT# 60156 is carded 2-pack.



CAT# 54782

SIDE TERMINAL BOLT FOR BATTERY TERMINALS

3/8" (9.52mm) x 5/16" (7.94mm) side battery terminal flanged bolt for battery terminals. Bulk. Forney® CAT# 60157 is carded 2-pack.



CAT# 54788

UNIVERSAL SIDE POST BATTERY TERMINAL

8-each Forney® CAT# 54771, universal side post battery terminals. High quality terminal ends for many applications and uses. Fits wire sizes #8 gauge – #4/0. Meets SAE standards. Designed to restore worn battery cables to original configuration or to convert from one battery style to another.

CRIMP & SEAL HEAT SHRINK CONNECTOR RING TERMINALS

Sealed crimp connector ring terminal. Seam is brazed together with a solder alloy for outstanding wire contact, increased current flow and superior tensile strength. This ensures less voltage drops which prevents wiring failures and reduces equipment downtime. May be used with solid or stranded wire and can be crimped on any side of the barrel without opening the seam.

FEATURES:

1.800.521.6038

- Translucent, adhesive-lined polyolefin tubing that allows visual inspection, prevents wire corrosion and provides a waterproof seal;
- Conforms to automotive manufacturer's specifications for wiring repairs (necessary for maintaining electrical warranties);
- Brazed seam ring terminals prevent opening of connector barrel;
- Color-coded tubing with wire gauge imprint provides easy identification of the correct part for the job.

CAT#	DESCRIPTION	QUANTITY
54810	10 – 12 AWG, #10 stud	5-pack
	14 – 16 AWG, #10 stud	5-pack
	14 – 16 AWG, 1/4" stud	5-pack



CAT# 54810

CRIMP & SEAL HEAT SHRINK BUTT CONNECTOR

Sealed crimp butt connector. The barrel is created from one seamless piece of metal that eliminates the problem of the barrel opening. Provides outstanding wire contact, increased current flow and superior tensile strength. This ensures less voltage drop, prevents wiring failures and reduces equipment downtime. May be used with solid or stranded wire.

FEATURES:

- Translucent, adhesive-lined polyolefin tubing that allows visual inspection, prevents wire corrosion and provides a waterproof seal;
- Conforms to automotive manufacturer's specifications for wiring repairs (necessary for maintaining electrical warranties);
- Seamless butt connectors prevent opening of connector barrel;
- Color-coded tubing with wire gauge imprint provides easy identification of the correct part for the job.

CAT#	DESCRIPTION	QUANTITY
	10 – 12 AWG	5-pack
54814	14 – 16 AWG	5-pack
	18 – 20 AWG	5-pack
	10 – 12 AWG	25-pack
54826	14 – 16 AWG	25-pack
	18 – 20 AWG	25-pack



CAT# 54813





FULLY INSULATED SLIP-ON CRIMP & SEAL HEAT SHRINK CONNECTOR

Fully insulated slip-on crimp & seal heat shrink connector, 14-16 AWG, .250" male, blue, 2 hump butted seam, 5-pack. Blue color coded with butted seam and .250" (6.35mm) tab. The butted seam is formed when metal is stamped, rolled and butted to create the connector barrel. Should only be used with stranded wire and must be crimped in the proper place to avoid opening the seam.

FEATURES:

- Translucent, adhesive-lined polyolefin tubing that allows visual inspection, prevents wire corrosion and provides a waterproof seal;
- Conforms to automotive manufacturer's specifications for wiring repairs (necessary for maintaining electrical warranties);
- Color-coded tubing with wire gauge imprint provides easy identification of the correct part for the job.

CAT#	DESCRIPTION	QUANTITY
54816	14-16 AWG, .250" male tab, blue	5-pack
54817	14-16 AWG, .250" female tab, blue	5-pack



CAT# 54818

HIGH-ADHESIVE FLOW SHRINK TUBING

Made of all weather polyolefin tubing with a very active adhesive lining. Excellent for sealing multiple wires. Puncture resistant and provides superior strain relief.

CAT#	DESCRIPTION	QUANTITY
54818	.300" ID, clear/red, 6" long, 4:1 shrink ratio	2-pack
54819	.450" ID, clear/yellow, 6" long, 4:1 shrink ratio	2-pack



MULTI-PURPOSE CRIMPER & CUTTER

The tool has two precision ground wire cutters and four crimping dies for 22-10 American Wire Gauge (AWG) insulated terminals. It also has bolt cutters for 6-32, 8-32, 10-32, 10-24 and 4-40 screws, which also can be used to rethread these bolts. The wire stripper can neatly strip stranded wire in 22-10 AWG and solid wire from 18-8 AWG series. 8-3/8" (212.73mm) length. Handles are red with Forney® imprint.



CAT# 54821

ECONOMY MULTI-PURPOSE CRIMPER & CUTTER

Economical multi-purpose hand tool that crimps, cuts and strips wire with ease.



FORNEY® ALL-PURPOSE SELF-IGNITING BUTANE TORCH, 2,500°F

Gas adjustment wheel provides adjustable, long blue torch flame with temperatures up to 2,500°F/1,300°C. Self-igniting piezo electric ignition is easy to start and eliminates the need for lighter or matches. Incorporates "trigger" switch with "pulldown" lock to meet Consumer Products Safety Commission (CPSC) Child Safety Requirements. "Hands-free" slide lock for continuous use and instant off operation. Ergonomic handle design ensures a non-slip grip. Removable base for table-top or hand-held use. 60 minutes continuous run time with a full charge. Durable self-contained, refillable plastic fuel tank. Refill with Forney® CAT# 54822 butane for best performance. Unique shutter lever to easily extinguish ignition flame if using optional soldering or hot air tip attachments. Use to heat parts, ignite materials, melt plastic, shrink tubing, solder and desolder, terminate specialty connectors and more. CSA-US and GS-TUV certified.

DIMENSIONS: 5.5'' (139.7mm) H x 3.8'' (96.52mm) L x 1.3'' (33.02mm) W

APPROX. RUN TIME: One hour

APPROX. FLAME TEMPERATURE: 2,500° F (1,300° C)

SHIPPED EMPTY

RECOMMENDED FUEL: Forney® CAT# 54821 Butane

FUEL TANK: Plastic, built-in, refillable
NET WEIGHT: 6.4 oz (181.44g)
SHIPPING WEIGHT: 1 lbs. (0.45 kg)





CAT# 54823

FORNEY® BUTANE MINI-TORCH WITH ADJUSTABLE FLAME, 2,500°F

Compact palm size is perfect for tool kits and field service kits. Produces an adjustable, wind resistant flame with temperatures up to 2,500°F/1,300°C, perfect for many microtorch applications. Built-in safety lock with improved easy-to-use self-ignition system. Meets Consumer Products Safety Commission (CPSC) Requirements. Powered by refillable "fuel cell" (included) with flame adjustment lever. Built-in fuel level viewing window. Use with Forney® CAT# 54822 butane for best performance. Pinpoint flame is perfect for soldering, desoldering, heat shrinking and terminating, heating, lighting and many other applications.

DIMENSIONS: 2.65" (67.31mm) L x 1.05" (26.67mm) W x 4.60" (116.84mm) H

FUEL TANK: "Refillable Fuel" Cell

RECOMMENDED FUEL: Forney® CAT# 54821 Butane **APPROX. FLAME TEMP:** 2,500° F (1,300° C) blue flame

APPROX. RUN TIME: 20 minutes (full charge)

NET WEIGHT: 2.9 oz (82g)

SHIPPING WEIGHT: 1 lbs. (0.45 kg)



CAT# 54822

FORNEY® BUTANE REFILL, 1.0 OZ (28.35G)

Butane refill in 1.0 oz (28.35g) 39mm x 97mm lined aluminum tube. 12-pack. A-28 butane with universal precision refill tip. Use to refill Forney® CAT# 54823 and 54824 butane torches and all other similar butane torches.



7 FUNCTION, 14-RANGE DIGITAL MULTI-TESTER, POCKET SIZE

Digital 7 function multi-tester. Choose from 7 functions and 14 measuring ranges to test DC voltage, DC current, resistance, diodes, audible continuity, transistors and battery strength. Includes a 9-volt battery and complete instructions.



CAT# 57301

5-FUNCTION, 14-RANGE MULTI-TESTER VOLT-OHMMETER, POCKET SIZE

Pocket-sized 5 function volt ohmmeter multi-tester. Choose from 5 functions and 14 measuring ranges to test DC/AC voltage, DC current, resistance and battery strength. Compact with wide open dial and clear markings. Includes battery and complete instructions.



CAT# 60343

GENERAL PURPOSE ELECTRICAL TEST CLIP

General purpose electrical test clip with insulator, 5 amp (2-pack).



CAT# 60344

ALLIGATOR ELECTRICAL TEST CLIP

Crocodile electrical test clip with insulator, 5 amp (2-pack).



CAT# 60345

PEE WEE ELECTRICAL TEST CLIP

Pee wee electrical test clip with insulator, 5 amp (2-pack).



CAT# 60346

ELECTRIXCAL TEST CLIP WITH INSULATOR

Econo electrical test clip with insulator, 10 amp (2-pack).



CAT# 60347

HIGH GRADE ELECTRICAL TEST CLIP

High grade electrical test clip with insulator, 20 amp (2-pack).



CAT# 57637

CABLE LUG CRIMPING CRIMPING TOOL

Cable lug crimping tool, #6 AWG to #3/0 AWG. Hammer type cable lug crimping tool that is reversible and spring loaded. Crimps cable lugs from #6 American Wire Gauge (AWG) to #3/0 AWG.



PREMIUM COPPER CABLE LUGS

Carefully manufactured for sound, solid connections and trouble-free service. Easily crimped or swaged. Made from electrolytic copper rated for 100% conductivity.

CAT#	BULK CAT# (5-PACK)	DESCRIPTION	QUANTITY
60096	57651	#1/0 Cable x 3/8" Stud Premium Copper Cable Lug (Carded)	2-pack
60097	57652	#1/0 Cable x 1/2" Stud Premium Copper Cable Lug (Carded)	2-pack
60095	57650	#1 Cable x 3/8" Stud Premium Copper Cable Lug (Carded)	2-pack
60107	57662	#1 Cable x 1/2" Stud Premium Copper Cable Lug (Carded)	2-pack
60098	57653	#2/0 Cable x 3/8" Stud Premium Copper Cable Lug (Carded)	2-pack
60099	57654	#2/0 Cable x 1/2" Stud Premium Copper Cable Lug (Carded)	2-pack
60094	57649	#2 Cable x 5/16" Stud Premium Copper Cable Lug (Carded)	2-pack
60105	57660	#2 Cable x 3/8" Stud Premium Copper Cable Lug (Carded)	2-pack
60106	57661	#2 Cable x 1/2" Stud Premium Copper Cable Lug (Carded)	2-pack
60100	57655	#3/0 Cable x 1/2" Stud Premium Copper Cable Lug (Carded)	2-pack
60101	57656	#4/0 Cable x 1/2" Stud Premium Copper Cable Lug (Carded)	2-pack
60092	57647	#4 Cable x 5/16" Stud Premium Copper Cable Lug (Carded)	2-pack
60093	57648	#4 Cable x 3/8" Stud Premium Copper Cable Lug (Carded)	2-pack
60104	57659	#4 Cable x 1/2" Stud Premium Copper Cable Lug (Carded)	2-pack
60091	57646	#6 Cable x 1/4" Stud Premium Copper Cable Lug (Carded)	2-pack
60103	57658	#6 Cable x 3/8" Stud Premium Copper Cable Lug (Carded)	2-pack
60090	57645	#8 Cable x #10 Stud Premium Copper Cable Lug (Carded)	2-pack
60102	57657	#8 Cable x 3/8" Stud Premium Copper Cable Lug (Carded)	2-pack





PREMIUM COPPER BUTT CONNECTORS

Carefully engineered and manufactured for sound connections and trouble-free service. Easily crimped or swaged. Made from electrolytic copper rated for 100% conductivity.

CAT#	BULK CAT# (5-PACK)	DESCRIPTION	QUANTITY
60108	57663	Premium all-copper, zinc plated butt connectors for #8 cable.	2-pack
60109	57664	Premium all-copper, zinc plated butt connectors for #6 cable.	2-pack
60110	57665	Premium all-copper, zinc plated butt connectors for #4 cable.	2-pack
60111	57666	Premium all-copper, zinc plated butt connectors for #2 cable.	2-pack
60112	57667	Premium all-copper, zinc plated butt connectors for #1/0 cable.	2-pack
60113	57668	Premium all-copper, zinc plated butt connectors for #2/0 cable.	2-pack



ELECTRICAL 61

DESIGNED NEVER DUPLICATED.



START TO FINISH.

GET IT DONE WITH FORNEY

RESEARCH

We engineer Forney welding machines, accessories and consumables with the features today's welders expect.

LISTEN

We focus on understanding your assortment, inventory turn and profit goals within the welding category.

DESIGN

We craft the best welding and metalworking category and marketing plantailored to your business goals.

SUCCESS

Contact us at sales@forneyind.com to take your welding category to new heights of success.





11-PIECE PNEUMATIC (AIR) TOOL & OIL ASSORTMENT

11-piece pneumatic (air) tool and oil assortment. Includes 1-each of Forney® CAT#'s 01988, 01989, 01990, 01992, 01993, 01994, 01997, 01998 and 01999; 2-each 75583.

CAT# 49198

35-PIECE STOCK & SHEET METAL ALUMINUM OPENING INVENTORY

35-piece round, square stock, round and square tube, flat, angle stock and sheet metal aluminum assortment. Includes 1-each Forney® CAT#'s 49200, 49201, 49204, 49205, 49210, 49211, 49212, 49213, 49220, 49221, 49222, 49223, 49224, 49225, 49234, 49235, 49236, 49237, 49238, 49239, 49240, 49241, 49250, 49251, 49252, 49253, 49260, 49261, 49262, 49263, 49264, 49265, 49270, 49274 and 49276•

CAT# 49199

105-PIECE STOCK & SHEET METAL ALUMINUM OPENING INVENTORY

105-piece round, square stock, round and square tube, flat, angle stock and sheet metal aluminum opening inventory. Includes 3-each Forney® CAT#'s 49200, 49201, 49204, 49205, 49210, 49211, 49212, 49213, 49220, 49221, 49222, 49223, 49224, 49225, 49234, 49235, 49236, 49237, 49238, 49239, 49240, 49241, 49250, 49251, 49252, 49253, 49260, 49261, 49262, 49263, 49264, 49265, 49270, 49274 and 49276.

CAT# 49303

268-PIECE STEEL OPENING INVENTORY

268-piece cold rolled and hot rolled rounds, round tubing, zinc plated rounds, flat plated, square tubing, hot rolled plate, flat stock, slotted angle and flat galvanized, angle stock, all-thread, threaded rod couplers, hot and cold rolled round and square key stock, sheet metal and reinforced steel bar (re-bar) steel opening inventory. Includes 1-each Forney® CAT#'s 49320, 49321, 49322, 49323, 49324, 49326, 49327, 49330, 49331, 49425, 49426, 49427, 49428, 49429, 49430, 49439, 49440, 49441, 49442, 49449, 49450, 49451, 49452, 49453, 49454, 49455, 49456, 49478, 49481, 49484, 49485, 49486, 49487, 49488, 49489, 49490, 49491, 49492, 49493, 49494, 49495, 49496, 49497, 49498, 49499, 49500, 49501, 49525, 49526, 49527, 49528, 49529, 49530, 49531, 49540, 49541, 49542, 49543, 49544, 49546, 49547, 49548, 49549, 49550, 49570, 49575, 49584, 49585, 49600, 49611, 49612, 49613, 49614, 49620, 49640, 49641, 49642, 49645, 49646, 49647, 49650, 49651, 49652, 49674, 49675, 49676, 49677, 49678, 49685, 49686, 49687, 49688, 49689, 49690, 49691, 49692, 49695, 49696, 49697, 49698, 49699, 49700, 49701, 49702, 49711, 49712, 49713, 49714, 49715, 49716, 49717, 49728, 49730, 49731 and 49732; 2-each 49350, 49351, 49352, 49353, 49354, 49355, 49356, 49357, 49358, 49359, 49360, 49361, 49380, 49381, 49382, 49383, 49381, 49382, 49383, 49391, 49392, 49400, 49402, 49410, 49411, 49412, 49413, 49414, 49415, 49416, 49417, 49418, 49419, 49420, 49421, 49422, 49423, 49424, 49431, 49432, 49433, 49434, 49435, 49436, 49437, 49488, 49660, 49667, 49671 and 49672.

CAT# 49305

130-PIECE STEEL OPENING INVENTORY

130-piece hot rolled rounds, hot rolled square keystock, flat stock, angle stock, square and round tubing, sheet metal, hot rolled plate, zinc plated round, flat plated, and slotted angle and flat galvanized steel assortment. Includes 1-each Forney® CAT#'s 49350, 49351, 49352, 49353, 49354, 49355, 49356, 49357, 49358, 49359, 49360, 49361, 49400, 49402, 49410, 49411, 49412, 49413, 49414, 49415, 49416, 49417, 49418, 49419, 49420, 49421, 49422, 49423, 49424, 49425, 49426, 49427, 49428, 49429, 49430, 49431, 49432, 49433, 49434, 49435, 49436, 49437, 49438, 49439, 49440, 49441, 49442, 49445, 49446, 49447, 49449, 49450, 49451, 49452, 49453, 49456, 49470, 49471, 49472, 49473, 49474, 49475, 49476, 49477, 49478, 49479, 49480, 49481, 49482, 49483, 49484, 49485, 49486, 49487, 49488, 49489, 49490, 49491, 49492, 49493, 49494, 49495, 49496, 49497, 49498, 49499, 49500, 49501, 49520, 49521, 49522, 49523, 49524, 49525, 49526, 49527, 49528, 49529, 49530, 49531, 49540, 49541, 49542, 49543, 49544, 49570, 49575, 49584, 49585, 49600, 49611, 49612, 49613, 49614, 49620, 49625, 49630, 49632, 49634, 49640, 49641, 49642, 49645, 49646, 49647, 49650, 49651 and 49652.

171-PIECE STEEL ROD ASSORTMENT

171-piece 3' and 6' all-thread grade 2 steel rod assortment. Includes 3-each Forney® CAT#'s 49677 and 49678; 5-each 49674, 49675 and 49676; 10-each 49666, 49669 and 49672; 20-each 49660, 49662, 49663, 49665, 49668 and 49669.

CAT# 49315

280-PIECE STEEL ROD ASSORTMENT

280-piece 1' and 2' all-thread grade 2 steel rod assortment. Includes 10-each Forney® CAT#'s 49691, 49692, 49701 and 49702; 20-each 49685, 49686, 49687, 49688, 49689, 49690, 49695, 49696, 49697, 49698, 49699 and 49700.

CAT# 49316

55-PIECE STOCK STEEL ASSORTMENT

55-piece cold rolled (hardened) squared plated key stock steel assortment. Includes 5-each Forney® CAT#'s 49715, 49716 and 49717; 10-each 49711, 49712, 49713 and 49714.

CAT# 49725

50-PIECE GRADE 2 COUPLER ASSORTMENT

50-piece galvanized grade 2 steel threaded rod coupler assortment. Includes 10-each Forney® CAT#'s 49728, 49729, 49730, 49731 and 49732.

CAT# 52711

17-PIECE BATTERY CHARGER AND JUMP START ASSORTMENT

17-piece battery charger and jump start assortment. Includes 4-each Forney® CAT#'s 52720; 3-each 52721, 52722, 52723, 52725, 52726, 52731 and 52732.

CAT# 54801

45-PIECE ASSORTMENT

45-piece crimp and seal heat shrink connectors, tubing, crimper and butane torch assortment. Includes 1-each Forney® CAT#'s 54824; 2-each 54810, 54811, 54812, 54813, 54814, 54815, 54816, 54817, 54818, 54819, 54820, 54821, 54823, 54825, 54826 and 54827; 12-each 54822.

CAT# 57640

104-PIECE COPPER CABLE LUG DISPLAY

104-piece premium copper cable lug display. Includes 4-each Forney® CAT#'s 57654, 57655 and 57656; 6-each 57650, 57651, 57652 and 57653; 12-each 57645, 57646 and 57649; 16-each 57647 and 57648; PLUS FREE 1-EACH 10483.

CAT# 57643

60-PIECE PREMIUM COPPER CABLE LUGS & BUTT CONNECTORS DISPLAY

60-piece premium copper cable lugs and butt connectors display. Includes 5-each Forney® 57657, 57658, 57659, 57660, 57661, 57662, 57663, 57664, 57665, 57666, 57667 and 57668; PLUS FREE 1-EACH 10482.

CAT# 60089

24-PIECE PREMIUM COPPER CABLE LUGS & BUTT CONNECTORS ASSORTMENT

24-piece premium copper cable lugs and butt connectors assortment. Includes 1-each Forney® CAT#'s 60090, 60091, 60092, 60093, 60094, 60095, 60096, 60097, 60098, 60099, 60100, 60101, 60102, 60103, 60104, 60105, 60106, 60107, 60108, 60109, 60110, 60111, 60112 and 60113.

13-PIECE PAINT MARKER ASSORTMENT

13-piece paint marker assortment (carded). Includes 2-each Forney® CAT#'s 60314 and 60315; 3-each 60310, 60312 and 60313.

CAT# 60340

30-PIECE ELECTRICAL TEST CLIP ASSORTMENT

30-piece electrical test clip assortment. Includes 5-each Forney® CAT#'s 60343, 60344, 60345, 60346, 60347 and 60348.

CAT# 60792

144-PIECE CHAIN AND HARDWARE OPENING INVENTORY

144-piece (small) chain and hardware opening inventory (with Lozier® metal bin shelf). Includes 1-each Forney® CAT#'s 70397, 70398, 70399, 70408, 70409, 70410, 70411, 70412, 70413, 70447 and 70448; 2-each 61024, 61025, 61030, 61031, 61032, 61042, 61046, 61047, 61050, 61051, 61052, 61081, 61082, 61086 and 61087; 3-each 61110, 61111, 61112, 61264, 61340; 4-each 61020, 61021, 61022, 61023, 61040, 61041, 61080, 61121, 61122, 61123, 61161, 61162, 61163, 61302, 61303, 61304, 61305, 61306, 61345, 61352, 61353 and 61357; **PLUS FREE 1-EACH 10245.**

CAT# 60793

225-PIECE CHAIN AND HARDWARE OPENING INVENTORY

225-piece (medium) chain and hardware opening inventory (with Lozier® metal bin shelves). Includes 1-each Forney® CAT#'s 70398, 70408, 70409, 70410, 70411, 70412, 70413, 70420, 70421, 70425, 70446, 70447, 70448, 70460, 70465 and 70467; 2-each 61024, 61025, 61030, 61031, 61032, 61036, 61037, 61038, 61042, 61046, 61047, 61050, 61051, 61052, 61082, 61086, 61087, 61125, 61130, 61131, 61164, 61165, 61321, 61322, 61323, 61330, 61332, 70397, 70399; 3-each 61090, 61091, 61092, 61093, 61110, 61111, 61112, 61113, 61161, 61162, 61163, 61264 and 61340; 4-each 61019, 61020, 61021, 61022, 61023, 61040, 61041, 61080, 61081, 61120, 61121, 61122, 61123, 61302, 61303, 61304, 61305, 61306, 61345, 61352, 61353, 61357, 61369, 61378, 61383, 61386, 61388 and 61389; PLUS FREE 2-EACH 10245.

CAT# 60794

281-PIECE CHAIN AND HARDWARE OPENING INVENTORY

281-piece (large) chain and hardware opening inventory (with Lozier® metal bin shelves). Includes 1-each Forney® CAT#'s 70398, 70408, 70409, 70410, 70411, 70412, 70413, 70420, 70421, 70425, 70426, 70445, 70446, 70447, 70448, 70460, 70465 and 70467; 2-each 61024, 61025, 61033, 61036, 61037, 61038, 61039, 61042, 61046, 61047, 61050, 61051, 61052, 61080, 61081, 61082, 61085, 61086, 61087, 61093, 61095, 61125, 61130, 61131, 61132, 61140, 61141, 61142, 61164, 61165, 61321, 61322, 61323, 61324, 61326, 61330, 61332, 61334, 70397 and 70399; 3-each 61090, 61091, 61092, 61110, 61111, 61112, 61113, 61264 and 61340; 4-each 61019, 61020, 61021, 61022, 61023, 61029, 61030, 61031, 61032, 61040, 61041, 61120, 61121, 61122, 61123, 61160, 61161, 61162, 61163, 61302, 61303, 61305, 61306, 61345, 61352, 61353, 61357, 61360, 61363, 61369, 61373, 61378, 61381, 61383, 61385, 61386, 61388 and 61389; PLUS FREE 2-EACH 10245.

CAT# 60795

284-PIECE CHAIN AND HARDWARE OPENING INVENTORY

284-piece (large) chain and hardware opening inventory (with Lozier® metal bin shelves). Includes 1-each Forney® CAT#'s 70397, 70398, 70399, 70403, 70404, 70407, 70408, 70409, 70410, 70411, 70412, 70413, 70420, 70421, 70425, 70426, 70445, 70446, 70447, 70448, 70460, 70465 and 70467; 2-each 61024, 61025, 61033, 61036, 61037, 61038, 61039, 61042, 61046, 61047, 61050, 61051, 61052, 61082, 61085, 61086, 61087, 61093, 61095, 61125, 61130, 61131, 61132, 61140, 61141, 61142, 61164, 61165, 61321, 61322, 61323, 61324, 61326, 61330, 61332 and 61334; 3-each 61080, 61081, 61090, 61091, 61092, 61110, 61111, 61112, 61113, 61264 and 61340; 4-each 61019, 61020, 61021, 61022, 61023, 61029, 61030, 61031, 61032, 61040, 61041, 61120, 61121, 61122, 61123, 61160, 61161, 61162, 61163, 61302, 61303, 61304, 61305, 61306, 61345, 61352, 61353, 61357, 61360, 61363, 61369, 61373, 61378, 61381, 61383, 61385, 61386, 61388 and 61389; **PLUS FREE 2-EACH 10245.**

144-PIECE (SMALL) CHAIN, WIRE ROPE AND ACCESSORIES OPENING INVENTORY

144-piece (small) chain, wire rope and accessories opening inventory. Includes 1-each Forney® CAT#'s 70397, 70398, 70399, 70408, 70409, 70410, 70411, 70412, 70413, 70447 and 70448; 2-each 61024, 61025, 61030, 61031, 61032, 61042, 61046, 61047, 61050, 61051, 61052, 61081, 61082, 61086 and 61087; 3-each 61110, 61111, 61112, 61264 and 61340; 4-each 61020, 61021, 61022, 61023, 61040, 61041, 61080, 61121, 61122, 61123, 61161, 61162, 61163, 61302, 61303, 61304, 61305, 61306, 61345, 61352, 61353 and 61357.

CAT# 60797

225-PIECE (MEDIUM) CHAIN, WIRE ROPE AND ACCESSORIES OPENING INVENTORY

225-piece (medium) chain, wire rope and accessories opening inventory. Includes 1-each Forney® CAT#'s 70398, 70408, 70409, 70410, 70411, 70412, 70413, 70420, 70421, 70425, 70446, 70447, 70448, 70460, 70465 and 70467; 2-each 61024, 61025, 61030, 61031, 61032, 61036, 61037, 61038, 61042, 61046, 61047, 61050, 61051, 61052, 61082, 61086, 61087, 61125, 61130, 61131, 61164, 61165, 61321, 61322, 61323, 61330, 61332, 70397 and 70399; 3-each 61090, 61091, 61092, 61093, 61110, 61111, 61112, 61113, 61161, 61162, 61163, 61264 and 61340; 4-each 61019, 61020, 61021, 61022, 61023, 61040, 61041, 61080, 61081, 61120, 61121, 61122, 61123, 61302, 61303, 61304, 61305, 61306, 61345, 61352, 61353, 61357, 61369, 61378, 61383, 61386, 61388 and 61389; PLUS FREE 1-EACH 10302.

CAT# 60798

281-PIECE (LARGE) CHAIN, WIRE ROPE AND ACCESSORIES OPENING INVENTORY

281-piece (large) chain, wire rope and accessories opening inventory. Includes 1-each Forney® CAT#'s 70398, 70408, 70409, 70410, 70411, 70412, 70413, 70420, 70421, 70425, 70426, 70445, 70446, 70447, 70448, 70460, 70465 and 70467; 2-each 61024, 61025, 61033, 61036, 61037, 61038, 61039, 61042, 61046, 61047, 61050, 61051, 61052, 61080, 61081, 61082, 61085, 61086, 61087, 61093, 61095, 61125, 61130, 61131, 61132, 61140, 61141, 61142, 61164, 61165, 61321, 61322, 61323, 61324, 61326, 61330, 61332, 61334, 70397 and 70399; 3-each 61090, 61091, 61092, 61110, 61111, 61112, 61113, 61264 and 61340; 4-each 61019, 61020, 61021, 61022, 61023, 61029, 61030, 61031, 61032, 61040, 61041, 61120, 61121, 61122, 61123, 61160, 61161, 61162, 61163, 61302, 61303, 61304, 61305, 61306, 61345, 61352, 61353, 61357, 61360, 61363, 61369, 61373, 61378, 61381, 61383, 61385, 61386, 61388 and 61389; PLUS FREE 1-EACH 10308.

CAT# 60799

284-PIECE CHAIN, WIRE ROPE AND ACCESSORIES OPENING INVENTORY

284-piece (large) chain, wire rope and accessories with hydraulic chain cutter opening inventory. Includes 1-each Forney® CAT#'s 70398, 70403, 70404, 70407, 70408, 70409, 70410, 70411, 70412, 70413, 70420, 70421, 70425, 70426, 70445, 70446, 70447, 70448, 70460, 70465 and 70467; 2-each 61024, 61025, 61033, 61036, 61037, 61038, 61039, 61042, 61046, 61047, 61050, 61051, 61052, 61080, 61081, 61082, 61085, 61086, 61087, 61093, 61095, 61125, 61130, 61131, 61132, 61140, 61141, 61142, 61164, 61165, 61321, 61322, 61323, 61324, 61326, 61330, 61332, 61334, 70397 and 70399; 3-each 61090, 61091, 61092, 61110, 61111, 61112, 61113, 61264 and 61340; 4-each 61019, 61020, 61021, 61022, 61023, 61029, 61030, 61031, 61032, 61040, 61041, 61120, 61121, 61122, 61123, 61160, 61161, 61162, 61163, 61302, 61303, 61304, 61305, 61306, 61345, 61352, 61353, 61357, 61360, 61363, 61369, 61373, 61378, 61381, 61383, 61385, 61386, 61388 and 61389; PLUS FREE 1-EACH 10308.

CAT# 60880

375-PIECE CHAIN & UTILITY HARDWARE OPENING INVENTORY

375-piece chain and utility hardware opening inventory. Includes 1-each Forney® CAT#'s 61324, 61326, 70403, 70404, 70408, 70410, 70411, 70412, 70413, 70420, 70421, 70425, 70426, 70446, 70446, 70447, 70448, 70450, 70451, 70452, 70453, 70465 and 70467; 2-each 61025, 61035, 61042, 61044, 61052, 61053, 61054, 61082, 61083, 61084, 61085, 61087, 61090, 61091, 61095, 61130, 61131, 61132, 61140, 61141, 61142, 61143, 61150, 61151, 61152, 61153, 61164, 61165, 61264, 61321, 61322, 61323, 61330, 61332, 61334, 61345, 70397, 70398, 70399 and 70460; 3-each 61036, 61037, 61038, 61039, 61050, 61051, 61080, 61081, 61086, 61092, 61093, 61110, 61111, 61112, 61113, 61160, 61161, 61162, 61163, 61360, 61363, 61369, 61373, 61378, 61381, 61383, 61385, 61386, 61388 and 61389; 5-each 61023, 61024, 61029, 61030, 61031, 61032, 61034, 61040, 61041, 61046, 61047, 61123, 61125, 61302, 61303, 61304, 61305, 61352, 61353 and 61357; 10-each 61019, 61020, 61021, 61022, 61120, 61121 and 61122; PLUS FREE 1-EACH 10252 AND 10318; 4-EACH 10249.

18-PIECE CHAIN & WIRE ROPE OPENING INVENTORY

18-piece chain and wire rope assortment. Includes 1-each Forney® CAT#'s 70400, 70401, 70402, 70403, 70404, 70410, 70411, 70412, 70413, 70420, 70445, 70446, 70447, 70448, 70450, 70451, 70452 and 70453.

CAT# 60992

30-PIECE SMALL (1/4 IN. – 3/8 IN.) HOOK ASSORTMENT

30-piece small (1/4" – 3/8") hook assortment. Includes 2-each Forney® CAT#'s 61040, 61041, 61042, 61050, 61051, 61052, 61060, 61061, 61062, 61070, 61071, 61072, 61080, 61081 and 61082.

CAT# 60993

10-PIECE LARGE (7/16 IN. – 1/2 IN.) HOOK ASSORTMENT

10-piece large (7/16" – 1/2") hook assortment. Includes 1-each Forney® CAT#'s 61043, 61044, 61053, 61054, 61063, 61064, 61073, 61074, 61083 and 61084.

CAT# 60991

190-PIECE UTILITY HARDWARE (SMALL) OPENING INVENTORY

190-piece utility hardware (small) opening inventory. Includes 1-each Forney® CAT#'s 61015, 61016, 61019, 61025, 61029, 61035, 61036, 61037, 61038, 61039, 61043, 61044, 61053, 61054, 61063, 61064, 61073, 61074, 61083, 61084, 61085, 61086, 61087, 61095, 61125, 61130, 61131, 61132, 61140, 61141, 61142, 61143, 61150, 61151, 61152, 61153, 61165, 61175, 61302, 61303, 61304, 61305, 61306, 61326, 61330, 61332, 61334, 61340, 61345, 61352, 61353, 61357, 61360, 61363, 61369, 61373, 61378, 61381, 61383, 61385, 61386, 61388, 61389, 70460, 70465 and 70467; 2-each 61010, 61011, 61012, 61013, 61014, 61020, 61021, 61022, 61023, 61024, 61030, 61031, 61032, 61033, 61034, 61040, 61041, 61042, 61050, 61051, 61052, 61060, 61061, 61062, 61070, 61071, 61072, 61080, 61081, 61082, 61090, 61091, 61092, 61093, 61110, 61111, 61112, 61113, 61114, 61120, 61121, 61122, 61123, 61124, 61160, 61161, 61162, 61163, 61164, 61170, 61171, 61172, 61173, 61174, 61264, 61287, 61288, 61289, 61290, 61293, 61321, 61322, 61323 and 61324.

CAT# 60995

33-PIECE CLEVIS LINKS-SHACKLES & SWIVELS ASSORTMENT

33-piece clevis links, shackles and swivels assortment. Includes 1-each Forney® CAT#'s 61130, 61131, 61132, 61140, 61141, 61142, 61143, 61150, 61151, 61152, 61153, 61165 and 61175; 2-each 61160, 61161, 61162, 61163, 61164, 61170, 61171, 61172, 61173 and 61174

CAT# 60994

70-PIECE LINKING ASSORTMENT

70-piece linking assortment. Includes 1-each Forney® CAT#'s 61015, 61016, 61019, 61025, 61029, 61035, 61095 and 61125; 2-each 61010, 61011, 61012, 61013, 61014, 61020, 61021, 61022, 61023, 61024, 61030, 61031, 61032, 61033, 61034, 61036, 61037, 61038, 61039, 61090, 61091, 61092, 61093, 61110, 61111, 61112, 61113, 61120, 61121, 61122 and 61123.

CAT# 61001

55-PIECE SMALL (1/4 IN. – 3/8 IN.) HOOK ASSORTMENT

55-piece small (1/4" – 3/8") hook assortment. Includes 3-each Forney® CAT#'s 61042, 61052, 61062, 61072 and 61082; 4-each 61040, 61041, 61050, 61051, 61060, 61061, 61071, 61071, 61080 and 61081.

CAT# 61002

20-PIECE LARGE (7/16 IN. – 1/2 IN.) HOOK ASSORTMENT

20-piece large (7/16" – 1/2") hook assortment. Includes 2-each Forney® CAT#'s 61043, 61044, 61053, 61054, 61063, 61064, 61073, 61074, 61083 and 61084.

CAT# 61003

159-PIECE LINKING ASSORTMENT

159-piece linking assortment. Includes 2-each Forney® CAT#'s 61015, 61016, 61019, 61025, 61029, 61035, 61036, 61037, 61038, 61039, 61095 and 61125; 3-each 61013, 61014, 61023, 61024, 61033, 61034, 61093, 61113 and 61123; 6-each 61010, 61011, 61012, 61020, 61021, 61022, 61030, 61031, 61032, 61090, 61091, 61092, 61110, 61111, 61112, 61120, 61121 and 61122.

CAT# 61004

72-PIECE CLEVIS LINKS, SHACKLES & SWIVELS ASSORTMENT

72-piece clevis links, shackles and swivels assortment. Includes 2-each Forney® CAT#'s 61130, 61131, 61132, 61140, 61141, 61142, 61143, 61150, 61151, 61152, 61153, 61165 and 61175; 3-each 61164 and 61174; 4-each 61162, 61163, 61172 and 61173; 6-each 61160, 61161, 61170 and 61171.

56-PIECE BASIC SOLDER OPENING INVENTORY

56-piece basic solder opening inventory. Includes 1-each Forney® CAT#'s 38051, 38052, 38061, 38110, 38111, 38116, 59020, 59021, 60300, 60301, 60303, 61400, 61401, 61402, 61403, 61409, 61419, 61420, 61421, 61422, 61426, 61427, 61428, 61429, 61430, 61435, 61437, 61438, 61440, 61441, 61455, 61464, 61466, 61467, 61468, 61470, 61473, 61479, 61480, 61485, 61486, 61489, 61490, 61503, 61510, 61511, 61512, 61532, 61533, 61534, 61535, 61536, 61537, 61538, 61539 and 61542.

CAT# 61393

24-PIECE LEAD-FREE PLUMBING SOLDER ASSORTMENT

24-piece lead-free plumbing solder assortment. Includes 1-each Forney® CAT#'s 38050, 38051, 38052, 38060, 38061, 38062, 60300, 60301, 60303, 61435, 61437, 61463, 61464, 61467, 61468, 61508, 61509, 61510, 61511, 61532, 61533, 61539 and 61542.

CAT# 61394

46-PIECE ELECTRICAL SOLDER ASSORTMENT

46-piece electrical solder assortment. Includes 1-each Forney® CAT#'s 38070, 59020, 59021, 60300, 60301, 60303, 61419, 61420, 61421, 61422, 61423, 61425, 61426, 61427, 61428, 61429, 61430, 61444, 61445, 61447, 61449, 61455, 61456, 61458, 61459, 61466, 61470, 61472, 61473, 61474, 61475, 61476, 61477, 61478, 61479, 61480, 61499, 61503, 61512, 61528, 61529, 61530, 61534, 61535, 61539 and 61542.

CAT# 61391

81-PIECE ADVANCED SOLDER OPENING INVENTORY

81-piece advanced solder opening inventory. Includes 1-each Forney® CAT#'s 38050, 38051, 38052, 38060, 38061, 38072, 38073, 38102, 38103, 38108, 38109, 38110, 38111, 38116, 59020, 59021, 60300, 60301, 60303, 61400, 61401, 61402, 61403, 61404, 61407, 61409, 61419, 61420, 61421, 61422, 61425, 61426, 61427, 61428, 61429, 61430, 61435, 61437, 61438, 61440, 61441, 61450, 61460, 61464, 61466, 61467, 61468, 61470, 61472, 61473, 61474, 61476, 61477, 61478, 61479, 61480, 61481, 61483, 61484, 61485, 61489, 61490, 61499, 61503, 61509, 61510, 61511, 61512, 61528, 61529, 61530, 61532, 61533, 61534, 61535, 61536, 61537, 61538, 61539 and 61542.

CAT# 61392

108-PIECE PROFESSIONAL SOLDER OPENING INVENTORY

108-piece professional solder opening inventory. Includes 1-each Forney® CAT#'s 38050, 38051, 38052, 38060, 38061, 38062, 38070, 38072, 38073, 38101, 38102, 38103, 38106, 38108, 38109, 38110, 38111, 38116, 38141, 59020, 59021, 60300, 60301, 60303, 61400, 61401, 61402, 61403, 61404, 61405, 61406, 61407, 61409, 61412, 61419, 61420, 61421, 61422, 61423, 61425, 61426, 61427, 61428, 61429, 61430, 61435, 61437, 61438, 61440, 61441, 61444, 61445, 61447, 61449, 61450, 61452, 61454, 61455, 61456, 61459, 61459, 61460, 61461, 61463, 61464, 61466, 61467, 61468, 61469, 61470, 61471, 61472, 61473, 61474, 61475, 61476, 61477, 61478, 61479, 61480, 61481, 61482, 61483, 61484, 61485, 61486, 61489, 61491, 61499, 61503, 61508, 61509, 61510, 61511, 61512, 61528, 61529, 61530, 61532, 61533, 61534, 61535, 61536, 61537, 61538, 61539 and 61542.

CAT# 61395

36-PIECE GENERAL PURPOSE SOLDER ASSORTMENT

36-piece general purpose solder assortment. Includes 1-each Forney® CAT#'s 38050, 38101, 38102, 38103, 38106, 38108, 38109, 38110, 38111, 60300, 60301, 60303, 61400, 61401, 61402, 61403, 61404, 61405, 61406, 61407, 61409, 61450, 61452, 61454, 61481, 61482, 61483, 61484, 61485, 61486, 61511, 61536, 61537, 61538, 61539 and 61542.

CAT# 61396

27-PIECE SMALL SOLDER OI AUTOMOTIVE

27-piece small solder OI automotive. Includes 1-each Forney® CAT#'s 38116, 59021, 60300, 60301, 60303, 61400, 61402, 61419, 61429, 61430, 61440, 61473, 61479, 61480, 61485, 61510, 61511, 61512, 61528, 61529, 61530, 61534, 61535, 61536, 61538, 61539 and 61542.

CAT# 61397

41-PIECE LARGE SOLDER OI AUTOMOTIVE

41-piece large solder OI automotive. Includes 1-each Forney® CAT#'s 38070, 38072, 38073, 38101, 38103, 38109, 38110, 38116, 59021, 60300, 60301, 60303, 61400, 61402, 61419, 61423, 61426, 61429, 61430, 61440, 61472, 61473, 61474, 61477, 61478, 61479, 61480, 61484, 61485, 61510, 61511, 61512, 61528, 61529, 61530, 61534, 61535, 61536, 61538, 61539, and 61542.

34-PIECE SOLDER ASSORTMENT

34-piece solder assortment. Includes 1-each Forney® CAT#'s 38052, 38062, 38070 and 38101; 2-each 38050, 38051, 38060, 38061, 38072, 38073, 38102, 38103, 38108, 38109, 38110, 38116, 59021, 60300 and 60303.

CAT# 70310

18-PIECE MACHINIST FILES ASSORTMENT

18-piece machinist files, assorted styles/sizes, opening inventory. Includes 1-each Forney® CAT#'s 70320, 70321, 70322, 70323, 70324, 70325, 70326, 70327, 70328, 70330, 70331, 70332, 70334, 70335, 70340, 70341, 70342 and 70343.

CAT# 70727

93-PIECE OPENING INVENTORY (BULK)

93-piece insert bit, power bit, magnetic nutsetter, magnetic bit holder and magnetic socket opening inventory (bulk). Includes 1-each Forney® CAT#'s 70752; 2-each 70730, 70735, 70738, 70739, 70740, 70742, 70743, 70756 and 70762; 3-each 70731, 70733, 70734, 70741 and 70758; 4-each 70736 and 70755; 5-each 70776; 8-each 70757 and 70763; 10-each 70770, 70771 and 70773; PLUS FREE 1-EACH 10378 AND 10587.

CAT# 70816

48-PIECE PAINT MARKER DISPLAY

48-piece paint marker display. Includes 6-each Forney® CAT#'s 70824 and 70825; 8-each 70820 and 70822; 10-each 70818 and 70819; **PLUS FREE 6-CHAMBER DISPLAY.**

CAT# 70817

24-PIECE PAINT MARKER DISPLAY

24-piece paint marker display. Includes 3-each Forney® CAT#'s 70824 and 70825; 4-each 70820 and 70822; 5-each 70818 and 70819; PLUS FREE PAINT CAN DISPLAY.

CAT# 70827

15-PIECE X-LARGE PAINT MARKER DISPLAY

15-piece x-large paint marker display. Includes 2-each Forney® CAT#'s 70830, 70831 and 70835; 3-each 70828, 70829 and 70832; **PLUS FREE 6-CHAMBER DISPLAY.**

CAT# 70859

9-PIECE WINDOW MARKER DISPLAY

9-piece window marker display. Includes 1-each Forney® CAT#'s 70854, 70855 and 70857; 2-each 70853, 70856 and 70858; PLUS FREE DISPLAY.

CAT# 72499

20-PIECE WIRE COMPRESSION & EXTENSION SPRINGS ASSORTMENT

20-piece wire compression and extension springs assortment. Includes 1-each Forney® CAT#'s 72514, 72523, 72538, 72545, 72546, 72547, 72566, 72568, 72569, 72570, 72571, 72577, 72586, 72589, 72596, 72597, 72599, 72623, 72636 and 72661.

CAT# 70727

93-PIECE OPENING INVENTORY (BULK)

93-piece insert bit, power bit, magnetic nutsetter, magnetic bit holder and magnetic socket opening inventory (bulk). Includes 1-each Forney® CAT#'s 70752; 2-each 70730, 70735, 70738, 70739, 70740, 70742, 70743, 70756 and 70762; 3-each 70731, 70733, 70734, 70741 and 70758; 4-each 70736 and 70755; 5-each 70776; 8-each 70757 and 70763; 10-each 70770, 70771 and 70773; PLUS FREE 1-EACH 10378 AND 10587.

63-PIECE HACKSAW FRAME & BLADE ASSORTMENT

63-piece hacksaw frame and blade assortment. Includes 3-each Forney® CAT#'s 73000; 2-each 72005, 72006 and 72007;

PLUS FREE 1-EACH 10232 AND 10626; 2-EACH 10248.

CAT# 75100

80-PIECE PRESSURE WASHER PARTS & ACCESSORIES OPENING INVENTORY

80-piece pressure washer parts and accessories (large) opening inventory. Includes 1-each Forney® CAT#'s 75161, 75167, 75172, 75173, 75176 and 75196; 2-each 75106, 75107, 75108, 75109, 75114, 75115, 75116, 75117, 75118, 75123, 75126, 75127, 75128, 75129, 75134, 75135, 75136, 75137, 75148, 75149, 75150, 75153, 75154, 75155, 75156, 75157, 75160, 75166, 75168, 75169, 75180, 75183, 75185, 75186, 75193, 75194 and 75195; PLUS FREE 1-EACH 10260 AND 10589.

CAT# 75101

39-PIECE PRESSURE WASHER PARTS & ACCESSORIES OPENING INVENTORY

39-piece pressure washer parts and accessories (medium) opening inventory. Includes 1-each Forney® CAT#'s 75106, 75107, 75108, 75109, 75114, 75115, 75116, 75117, 75118, 75123, 75126, 75127, 75128,75129, 75134, 75135, 75136, 75137, 75148, 75149, 75150, 75153, 75154, 75155, 75156, 75157, 75160, 75166, 75167, 75168, 75169, 75176, 75180, 75183, 75185, 75186, 75193, 75194, 75195 and 75196; PLUS FREE 1-EACH 10260 AND 10589.

CAT# 70838

100-PIECE INSERT BIT, POWER BIT, POWER BIT EXTENSIONS, DOUBLE ENDED BIT, MAGNETIC NUTSETTER, MAGNETIC BIT HOLDER AND SOCKET ADAPTER OPENING INVENTORY (CARDED)

100-piece insert bit, power bit, hex bit set, power bit extensions, double ended bit, magnetic nutsetter, magnetic bit holder and socket adapter opening inventory (carded). Includes 1-each Forney® CAT#'s 70893, 70894, 70895, 70896, 70897, 70898 and 70962; 2-each 70840, 70841, 70842, 70845, 70846, 70847, 70860, 70861, 70862, 70863, 70864, 70865, 70875, 70876, 70877, 70878, 70886, 70887, 70901,70903, 70908, 70912, 70917, 70940, 70941, 70946, 70947, 70948, 70951, 70955, 70956 and 70960; 3-each 70890 and 70891; 4-each 70942 and 70952; 5-each 70902, 70905 and 70915.

CAT# 72498

74-PIECE WIRE COMPRESSION & EXTENSION SPRINGS OPENING INVENTORY

74-piece wire compression and extension springs assortment. Includes 1-each Forney® CAT#'s 72506, 72507, 72508, 72509, 72511, 72512, 72513, 72514, 72519, 72520, 72521, 72522, 72523, 72529, 72530, 72531, 72532, 72533, 72534, 72535, 72536, 72537, 72538, 72542, 72543, 72544, 72545, 72546, 72547, 72548, 72549, 72550, 72554, 72555, 72556, 72557, 72558, 72559, 72560, 72562, 72563, 72564, 72566, 72569, 72570, 72573, 72575, 72576, 72577, 72586, 72587, 72588, 72592, 72594, 72596, 72597, 72599, 72600, 72621, 72623, 72631, 72633, 72635, 72636, 72637, 72640, 72642, 72643, 72644, 72645, 72647, 72648, 72649 and 72651.

CAT# 72497

163-PIECE WIRE COMPRESSION & EXTENSION SPRINGS OPENING INVENTORY

163-piece wire compression and extension springs opening inventory. Includes 1-each Forney® CAT#'s 72506, 72507, 72508, 72509, 72510, 72511, 72512, 72513, 72514, 72515, 72516, 72517, 72518, 72519, 72520, 72521, 72522, 72523, 72524, 72525, 72526, 72527, 72528, 72529, 72530, 72531, 72532, 72533, 72534, 72535, 72536, 72537, 72538, 72538, 72539, 72540, 72541, 72542, 72543, 72544, 72545, 72546, 72547, 72548, 72549, 72550, 72551, 72552, 72553, 72554, 72555, 72556, 72557, 72558, 72559, 72560, 72561, 72562, 72563, 72564, 72565, 72566, 72567, 72568, 72569, 72570, 72571, 72572, 72573, 72574, 72575, 72576, 72577, 72578, 72579, 72580, 72581, 72582, 72583, 72584, 72585, 72586, 72587, 72588, 72589, 72590, 72591, 72592, 72593, 72594, 72595, 72596, 72597, 72599, 72600, 72601, 72602, 72603, 72604, 72605, 72606, 72607, 72608, 72609, 72610, 72611, 72612, 72613, 72614, 72615, 72618, 72618, 72619, 72620, 72621, 72622, 72623, 72644, 72645, 72646, 72647, 72648, 72649, 72649, 72650, 72651, 72652, 72653, 72654, 72655, 72656, 72657, 72658, 72659, 72660, 72661, 72662, 72663, 72664, 72665, 72666, 72667, 72668, and 72669.

29-PIECE PRESSURE WASHER PARTS & ACCESSORIES OPENING INVENTORY

29-piece pressure washer parts and accessories opening inventory. Includes 1-each Forney® CAT#'s 70854, 70855 and 70857; 2-each 70853, 70856 and 70858; PLUS FREE DISPLAY.

CAT# 75103

32-PIECE PRESSURE WASHER PARTS & ACCESSORIES TABLE TOP DISPLAY

32-piece pressure washer parts and accessories counter top display. Includes 2-each Forney® CAT#'s 75108, 75117, 75127, 75128, 75129, 75134, 75136, 75137, 75148, 75149, 75153, 75155, 75156, 75157, 75166 and 75180; PLUS FREE 1-EACH 10589.

CAT# 75104

75-PIECE PRESSURE WASHER QUICK CONNECT SPRAY NOZZLE ASSORTMENT

75-piece quick connect spray nozzle assortment. Includes 10-each Forney® CAT#'s 75143 and 75147; 15-each 75144; 20-each 75145 and 75146; **PLUS FREE LABELED DISPLAY BOX.** Display measurements are: 7" Wide x 10" Deep x 10-1/4" Tall.

CAT# 75210

170-PIECE AIR FITTINGS OPENING INVENTORY (BULK)

170-piece air fittings opening inventory (bulk). Includes 5-each Forney® CAT#'s 75217, 75222, 75226, 75236, 75240, 75247, 75252 and 75260; 10-each 75215, 75220, 75224, 75238, 75230, 75234, 75238, 75242, 75244, 75246, 75248, 75250 and 75254;

PLUS FREE 1-EACH 10263, 10264, 10265 AND 10266; 8-EACH 10489.

CAT# 75280

30-PIECE ACCESSORIES ASSORTMENT

30-piece pvc air hose, polyurethane flex air hose, rubber hose and accessories assortment. Includes 1-each Forney® CAT#'s 75406, 75407, 75408, 75409, 75410, 75411, 75414, 75415, 75425, 75430, 75431, 75435, 75436, 75437, 75438, 75442, 75443, 75444, 75445, 75450, 75498, 75499, 75500, 75501, 75502, 75503, 75540, 75541, 75561 and 75562.

CAT# 75281

18-PIECE I/M® COMPATIBLE AIR FITTINGS ASSORTMENT (CARDED)

18-piece Industrial/Milton® compatible fittings assortment (carded). Includes 1-each Forney® CAT#'s 75305, 75307, 75316, 75317, 75321, 75323, 75324, 75325, 75471, 75472, 75474, 75479, 75480, 75483, 75520, 75521, 75600 and 75602.

CAT# 75284

23-PIECE FILTERS, REGULATORS, LUBRICATORS, GAUGES, SWITCHES & SAFETY VALVES ASSORTMENT

23-piece filters, regulators, lubricators, gauges, switches and safety valve assortment. Includes 1-each Forney® CAT#'s 75367, 75368, 75545, 75546, 75547, 75551, 75552, 75553, 75554, 75555, 75556, 75565, 75570, 75574, 75575, 75576, 75577, 75578, 75579, 75580, 75581, 75582 and 75583.

CAT# 75282

16-PIECE TRU-FLATE® COMPATIBLE ASSORTMENT

16-piece Tru-flate® compatible assortment (carded). Includes 1-each Forney® CAT#'s 75306, 75309, 75315, 75320, 75322, 75326, 75398, 75399, 75401, 75475, 75476, 75484, 75485, 75519, 75590 and 75592.

CAT# 75283

11-PIECE LINCOLN® / ARO® COMPATIBLE & UNIVERSAL FITTINGS ASSORTMENT

11-piece Lincoln® and Aro® compatible and universal fittings assortment (carded). Includes 1-each Forney® CAT#'s 75303, 75304, 75318, 75319, 75473, 75482, 75522, 75524, 75525, 75526 and 75527.

CAT# 75285

33-PIECE BLOW GUNS & CHUCKS ASSORTMENT

33-piece blow guns and chucks assortment. Includes 1-each Forney® CAT#'s 75330, 75331, 75332, 75334, 75488, 75489 and 75495; 2-each 75336, 75337, 75340, 75349, 75350, 75352, 75353, 75354, 75355, 75356, 75487, 75494 and 75529.

14-PIECE TIRE GAUGES & VALVES ASSORTMENT

14-piece tire gauges and valves assortment. Includes 1-each Forney® CAT#'s 75344, 75345, 75346, 75347, 75348, 75370, 75380, 75381, 75491, 75492, 75493, 75496, 75509 and 75528.

CAT# 75287

26-PIECE BRASS FITTINGS, AIR/WATER ADAPTER, TANK VALVE & TANK MANIFOLD ASSORTMENT (CARDED)

26-piece brass fittings, air/water adapter, tank valve and tank manifold assortment (carded). Includes 1-each Forney® CAT#'s 75357, 75358, 75359, 75360, 75361, 75362, 75363, 75364, 75365, 75366, 75447, 75448, 75530, 75532, 75533, 75534, 75535, 75536, 75537, 75542, 75543, 75549, 75550, 75558, 75559 and 75560.

CAT# 75288

17-PIECE RECOIL AIR HOSE & ACCESSORIES ASSORTMENT

17-piece recoil air hose and accessories assortment. Includes 1-each Forney® CAT#'s 75363, 75364, 75365, 75366, 75417, 75418, 75425, 75500, 75540, 75541, 75543, 75554, 75558, 75560, 75561, 75562 and 75565.

CAT# 75292

361-PIECE AIR HOSE, FITTINGS & ACCESSORIES OPENING INVENTORY (CARDED)

361-piece air hose, fittings and accessories opening inventory (carded). Includes 1-each Forney® CAT#'s 75334, 75385, 75407, 75408, 75409, 75414, 75415, 75418, 75425, 75430, 75431, 75435, 75436, 75437, 75442, 75443, 75444, 75445, 75450, 75488, 75493, 75498, 75499, 75501, 75502, 75503, 75541, 75542, 75543, 75549, 75550, 75559, 75574, 75575, 75576 and 75577; 2-each 75318, 75319, 75325, 75326, 75330, 75331, 75336, 75337, 75344, 75345, 75346, 75347, 75348, 75350, 75352, 75353, 75354, 75355, 75356, 75365, 75366, 75368, 75370, 75380, 75381, 75406, 75410, 75411, 75417, 75438, 75472, 75474, 75480, 75482, 75489, 75495, 75500, 75509, 75509, 75521, 75525, 75526, 75527, 75528, 75540, 75546, 75546, 75547, 75551, 75552, 75553, 75555, 75556, 75558, 75560, 75561, 75562, 75570, 75578, 75579, 75580, 75581 and 75582; 3-Each 75303, 75304, 75306, 75307, 75309, 75315, 75316, 75317, 75320, 75321, 75322, 75323, 75324, 75332, 75349, 75357, 75358, 75359, 75360, 75361, 75362, 75363, 75364, 75367, 75398, 75399, 75401, 75447, 75448, 75471, 75473, 75475, 75476, 75479, 75483, 75484, 75485, 75487, 75491, 75492, 75494, 75522, 75524, 75529, 75530, 75532, 75533, 75534, 75535, 75536, 75537, 75554, 75565 and 75583; 5-each 75305, 75340, 75519, 75590, 75592, 75600 and 75602.

CAT# 75295

115-PIECE AIR FITTING & HOSE OPENING INVENTORY

115-piece air fitting and hose opening inventory. Includes 1-each Forney® CAT#'s 75385, 75406, 75411, 75417, 75418, 75496, 75546, 75570, 75581; 2-each 75303, 75307, 75309, 75315, 75318, 75321, 75323, 75324, 75325, 75326, 75349, 75357, 75359, 75360, 75361, 75363, 75367, 75399, 75448, 75471, 75475, 75479, 75483, 75485, 75487, 75491, 75492, 75494, 75519, 75522, 75527, 75529, 75532, 75533, 75535, 75543, 75554, 75565, 75583, 75590, 75592; 4-each 75305, 75316, 75317, 75340, 75600, 75602.

CAT# 75293


240-PIECE AIR HOSE, FITTINGS & ACCESSORIES OPENING INVENTORY (CARDED)

240-piece air hose, fittings and accessories opening inventory (carded). Includes 1-each Forney® CAT#'s 75318, 75319, 75330, 75331, 75334, 75336, 75337, 75344, 75345, 75346, 75347, 75348, 75350, 75352, 75353, 75354, 75355, 75356, 75365, 75366, 75368, 75381, 75385, 75407, 75408, 75409, 75410, 75411, 75414, 75415, 75417, 75418, 75425, 75430, 75431, 75435, 75436, 75437, 75442, 75443, 75444, 75445, 75450, 75472, 75474, 75480, 75482, 75488, 75489, 75493, 75498, 75499, 75500, 75501, 75502, 75503, 75509, 75520, 75521, 75525, 75528, 75540, 75541, 75542, 75543, 75547, 75549, 75551, 75552, 75553, 75555, 75556, 75558, 75559, 75560, 75562, 75570, 75574, 75575, 75576, 75577, 75578, 75579, 75580, 75581 and 75582; 2-each 75303, 75304, 75306, 75307, 75309, 75315, 75316, 75317, 75320, 75321, 75322, 75323, 75324, 75325, 75326, 75332, 75340, 75349, 75357, 75358, 75359, 75360, 75361, 75362, 75363, 75364, 75367, 75370, 75380, 75399, 75399, 75401, 75406, 75438, 75447, 75448, 75471, 75473, 75475, 75476, 75479, 75483, 75484, 75485, 75487, 75491, 75492, 75494, 75496, 75522, 75524, 75526, 75527, 75529, 75530, 75532, 75533, 75534, 75535, 75536, 75537, 75545, 75546, 75554, 75565 and 75583; 3-each 75305, 75519, 75590, 75592, 75600 and 75602.

161-PIECE AIR HOSE, FITTINGS & ACCESSORIES OPENING INVENTORY (CARDED)

161-piece air hose, fittings and accessories opening inventory (carded). Includes 1-each Forney® CAT#'s 75303, 75304, 75305, 75306, 75307, 75309, 75315, 75316, 75317, 75318, 75319, 75320, 75321, 75322, 75323, 75324, 75325, 75326, 75330, 75331, 75332, 75334, 75336, 75337, 75340, 75344, 75345, 75346, 75347, 75348, 75349, 75350, 75352, 75353, 75354, 75355, 75356, 75357, 75358, 75359, 75360, 75361, 75362, 75363, 75364, 75365, 75366, 75367, 75368, 75370, 75380, 75381, 75385, 75398, 75399, 75401, 75406, 75407, 75408, 75409, 75410, 75411, 75414, 75415, 75417, 75418, 75425, 75430, 75431, 75435, 75436, 75437, 75438, 75442, 75443, 75444, 75445, 75447, 75448, 75450, 75471, 75472, 75473, 75474, 75475, 75476, 75479, 75480, 75482, 75483, 75484, 75485, 75487, 75488, 75491, 75492, 75493, 75494, 75495, 75496, 75498, 75499, 75500, 75501, 75502, 75503, 75509, 75519, 75520, 75521, 75522, 75524, 75525, 75526, 75527, 75528, 75553, 75554, 75555, 75556, 75558, 75559, 75560, 75561, 75562, 75565, 75570, 75574, 75575, 75576, 75577, 75578, 75579, 75580, 75581, 75582, 75583, 75590, 75592, 75600 and 75602.







PLUMBERS AIR-ACETYLENE TORCH KIT

Compact, light-duty air acetylene plumber's torch kit for plumbing, heating and refrigeration use. Heat, solder and braze pipe, tubing and thin gauge metals. Features a feather brush flame, interchangeable screw-in tips (sold separately), heavy-duty torch and a UL listed brass regulator. "A" fittings on 3/16" (4.76mm) hose. Kit includes 12'-1/2" (3.81m) hose and torch igniter.



CAT# 1721

PLUMBERS AIR-PROPANE/ PROPYLENE TORCH KIT

Compact, light-duty air propane plumbers torch kit for plumbing, heating and refrigeration use. Heat, solder and braze pipe, tubing and thin gauge metals. Features a hot turbine flame, heavy-duty torch and a UL listed brass regulator. "A" fittings on 1/4" (6.35mm) hose. Kit includes 10' (3.05m) hose and torch igniter.



CAT# 1725

ROOFERS PILOT VALVE TYPE TORCH KIT

Roofers torch kit, pilot valve type. 300,000 BTUs. Features high temperature tips, on/off brass needle valves, UL listed components and adjustable flame. 25' (7.62m) hose and igniter included. Perfect for roofing, heating, agricultural and industrial applications. Engineered for efficient heating.



CAT# 88064

AIR-ACETYLENE FUEL REGULATOR (400 PSI)

Air acetylene fuel regulator, 400 PSI. For Forney® CAT# 1720 plumbers torch kit, or other similar air acetylene compatible torches.



CAT# 88066

3/16 IN. X 12-1/2 FT. ACETYLENE HOSE

12-1/2' (3.81m) replacement air acetylene hose with 3/16" (4.76mm) "A" fittings. Fits Forney® CAT# 1720, plumbers torch kit, or other similar air acetylene compatible torch kits.



CAT# 88067

AIR-ACETYLENE TORCH HANDLE

Replacement acetylene torch handle. Fits Forney® CAT# 1720 plumbers torch kit, or other similar air acetylene compatible torch kits.



AIR-ACETYLENE SOLDERING, BRAZING, & HEATING TIPS

For Forney® CAT# 1720 plumbers torch kit, or other similar air acetylene compatible torches.

CAT#	DESCRIPTION
88061	Air acetylene soldering, brazing and heating tip #1
88062	Air acetylene soldering, brazing and heating tip #3
88063	Air acetylene soldering, brazing and heating tip #5



FORNEY® FIREMAN™ WEED BURNER AND ICE MELTER (500,000 BTUS)

Features a brass control knob that will not lock or freeze during use, an all-steel torch handle and torch head construction. 10' (3.05m) hose with POL safety valve and universal CGA-510 L.P. connection. UL listed. Striker included for proper ignition. Hundreds of practical uses: burn weeds, melt ice, repair asphalt, etc. Hooks up to a standard 20 lbs. (9.07 kg) barbecue grill-type liquid propane tank. Easy to ignite using the flint lighter included with the kit. POL valve prevents excess flow of L.P. gas if hose is cut or melted. 36" (914.4mm) all-steel handle and torch head.

CAT#	DESCRIPTION	QUANTITY
1723	Weed Burner	Single
1724	Weed Burner – 3-Pack	3-Pack
1726	Weed Burner – 6-Pack with Display Box	6-Pack



CAT# 86231


REPLACEMENT HOSE FOR WEEDBURNER

Replacement 1/4 in. x 10 ft. weedburner hose for Forney® CAT# 1723, CSA certified, CGA 510 POL, 9/16 in. - 18 lh. 350 PSI max pressure.











M22F X 1/4 IN. FEMALE SCREW COUPLING

M22F to 1/4" female NPT. Used anywhere high pressure connections are frequently assembled and disassembled. Connects to all of the most common 1/4" (6.35mm) pressure washer equipment in the industry and converts M22 metric thread size to standard thread size. 300° F (148.9° C) and 5.800 PSI.



CAT# 75109

M22F X 3/8 IN. MALE SCREW COUPLING

M22F to 3/8" male NPT. Used anywhere high pressure connections are frequently assembled and disassembled. Connects to all of the most common 3/8" (9.52mm) pressure washer equipment in the industry and converts M22 metric thread size to standard thread size. 300° F (148.9° C) and 5,800 PSI.



CAT# 75116

M22M X 3/8 IN. FEMALE SCREW NIPPLE

M22M x 3/8" female NPT. Used anywhere high pressure connections are frequently assembled and disassembled, in combination with screw couplers. Connects to both male and female 3/8" (9.52mm) fittings and converts M22 metric thread size to standard thread size. 300° F (148.9° C) and 5,800 PSI.



CAT# 75107

M22F X 1/4 IN. MALE SCREW COUPLING

M22F to 1/4" male NPT. Used anywhere high pressure connections are frequently assembled and disassembled. Connects to all of the most common 1/4" (6.35mm) pressure washer equipment in the industry and converts M22 metric thread size to standard thread size. 300° F (148.9° C) and 5,800 PSI.



CAT# 75114

M22M X 1/4 IN. FEMALE SCREW NIPPLE

M22M to 1/4" female NPT. Used anywhere high pressure connections are frequently assembled and disassembled, in combination with screw couplers. Connects to both male and female 1/4" (6.35mm) fittings and converts M22 metric thread size to standard thread size. 300° F (148.9° C) and 5,800 PSI.



CAT# 75117

M22M X 3/8 IN. MALE SCREW NIPPLE

M22M x 3/8" male NPT. Used anywhere high pressure connections are frequently assembled and disassembled, in combination with screw couplers. Connects to both male and female 3/8" (9.52mm) fittings and converts M22 metric thread size to standard thread size. 300° F (148.9° C) and 5,800 PSI.



CAT# 75108

M22F X 3/8 IN. FEMALE SCREW COUPLING

M22F to 3/8" female NPT. Used anywhere high pressure connections are frequently assembled and disassembled. Connects to all of the most common 3/8" (9.52mm) pressure washer equipment in the industry and converts M22 metric thread size to standard thread size. 300° F (148.9° C) and 5,800 PSI.



CAT# 75115

M22M X 1/4 IN. MALE SCREW NIPPLE

M22M to 1/4" male NPT. Used anywhere high pressure connections are frequently assembled and disassembled, in combination with screw couplers. Connects to both male and female 1/4" (6.35mm) fittings and converts M22 metric thread size to standard thread size. 300° F (148.9° C) and 5,800 PSI.



CAT# 75118

M22M X 1/4 IN. FEMALE LONG SCREW NIPPLE

M22M x 1/4" male NPT. Used anywhere high pressure connections are frequently assembled and disassembled, in combination with screw couplers. Connects to both male and female 1/4" (6.35mm) fittings and converts M22 metric thread size to standard thread size. 300° F (148.9° C) and 5,800 PSI.



M22F X 1/4 IN. QUICK COUPLER PLUG (5,800 PSI)

1/4" (6.35mm) quick coupler plug x M22F converter coupling. 300° F (148.9° C). 5.800 PSI.



CAT# 75128

3/8 IN. MALE QUICK COUPLER SOCKET (4,200 PSI)

3/8" (9.52mm) male, brass socket quick coupler. Used anywhere high pressure connections are frequently assembled and disassembled. These quick couplers connect to all of the most common pressure washer equipment in the industry. 4,200 PSI.



CAT# 75135

1/4 IN. FEMALE QUICK CONNECT PLUG (5,500 PSI)

1/4" (6.35mm) F-NPT, plated steel quick connect plug. Used in combination with quick couplers anywhere high pressure connections are frequently assembled and disassembled. Ideal for quick exchange of spray nozzles and spray guns. These quick connect plugs connect to all of the most common pressure washer equipment in the industry. 5,500 PSI.



CAT# 75126

1/4 IN. MALE QUICK COUPLER SOCKET (5,500 PSI)

1/4" (6.35mm) male, brass socket quick coupler. Used anywhere high pressure connections are frequently assembled and disassembled. These quick couplers connect to all of the most common pressure washer equipment in the industry. 5,500 PSI.



CAT# 75129

3/8 IN. FEMALE QUICK COUPLER SOCKET (4,200 PSI)


3/8" (9.52mm) female, brass socket quick coupler. 4,200 PSI. Used anywhere high pressure connections are frequently assembled and disassembled. These quick couplers connect to all of the most common pressure washer equipment in the industry.



CAT# 75136

3/8 IN. MALE QUICK CONNECT PLUG (4,200 PSI)

3/8" (9.52mm) M-NPT, plated steel quick connect plug. Used in combination with quick couplers anywhere high pressure connections are frequently assembled and disassembled. Ideal for quick exchange of spray nozzles and spray guns. These quick connect plugs connect to all of the most common pressure washer equipment in the industry. 4,200 PSI.



CAT# 75127

1/4 IN. FEMALE QUICK COUPLER SOCKET (5,500 PSI)

1/4" (6.35mm) female, brass socket quick coupler. Used anywhere high pressure connections are frequently assembled and disassembled. These quick couplers connect to all of the most common pressure washer equipment in the industry. 5,500 PSI.



CAT# 75134

1/4 IN. MALE QUICK CONNECT PLUG (5,500 PSI)

1/4" (6.35mm) M-NPT, plated steel quick connect plug. Used in combination with quick couplers anywhere high pressure connections are frequently assembled and disassembled. These quick connect plugs connect to all of the most common pressure washer equipment in the industry. 5,500 PSI.



CAT# 75137

3/8 IN. FEMALE QUICK CONNECT PLUG (4,200 PSI)

3/8" (9.52mm) F-NPT, plated steel quick connect plug. Used in combination with quick couplers anywhere high pressure connections are frequently assembled and disassembled. Ideal for quick exchange of spray nozzles and spray guns. These quick connect plugs connect to all of the most common pressure washer equipment in the industry. 4,200 PSI.



CAT# 75140

1/4 IN. FNPT X 4.5MM SEWER NOZZLE

Female national pipe thread (F-NPT) x 4.5mm orifice stainless steel sewer nozzle. Slides easily into drain pipes and sewer lines. Forward and backward ports in the nozzle blasts into the clogged pipe, breaking up the debris while pulling the hose through the pipe. Made of corrosion resistant stainless steel. 4.200 PSI.



CAT# 75160

4.5MM ROTATING TURBO NOZZLE

4.5mm rotating turbo nozzle with 1/4" F-NPT inlet. Increases cleaning efficiency by more than 200% over a 25° spray nozzle by using a 0° rotating tearing action. This nozzle is ideal for hard surface cleaning such as removing graffiti and caked on mud on equipment. 212° F (100° C). 3,600 PSI.



CAT# 75176

1/4 IN. MNPT X 1/4 IN. QUICK CONNECT TURBO FILTER

Turbo nozzle filter with 4.5mm orifice and 1/4" (6.35mm) male x 1/4" (6.35mm) quick connect. Used in combination with Forney® CAT# 75160 and 75161 Turbo Nozzles to protect the nozzles from damage by preventing debris from getting into the nozzle. 190° F (87.8° C). 5,800 PSI.



CAT# 75141

1/8 IN. FNPT X 4.5MM SEWER NOZZLE

Female national pipe thread (F-NPT) x 4.5mm orifice stainless steel sewer nozzle. Slides easily into drain pipes and sewer lines. Backward ports in the nozzle blasts into the clogged pipe, breaking up the debris while pulling the hose through the pipe. Made of corrosion resistant stainless steel. 4,200 PSI.



CAT# 75161

4.5MM ROTATING TURBO NOZZLE

4.5mm high-pressure rotating turbo nozzle with 1/4" F-NPT inlet. Increases the cleaning efficiency by more than 200% over a 25° spray nozzle by using a 0° rotating tearing action. This nozzle is ideal for hard surface cleaning such as removing graffiti and caked on mud on equipment. 212° F (100° C). 5,100 PSI.



CAT# 75142

1/4 IN. FNPT X 5.5MM ROTATING SEWER NOZZLE

1/4" (6.35mm) female national pipe thread (F-NPT) x 5.5mm orifice stainless steel rotating sewer nozzle. Slides easily into drain pipes and sewer lines. Backward ports drive the nozzle forward and flush debris. Made of corrosion resistant stainless steel. 4,000 PSI.



CAT# 75166

1/4 IN. FNPT X 3.5MM ADJUSTABLE SPRAY NOZZLE

1/4" (6.35mm) female national pipe thread (F-NPT) inlet. 3.5mm orifice multi regulator nozzle. This nozzle easily switches between a solid or flat spray pattern without having to change nozzles. The spray pattern adjusts from a solid 0° to a flat 80° spray pattern with a twist of the nozzle head. 300° F (148.9° C). 3,200 PSI.



PRESSURE WASHER FITTING GUIDE

The orifice size of the nozzle determines the operating pressure of your machine. As a rule, the smaller the orifice, the greater the restriction of water flowing through the machine. This causes the pressure to increase. Choosing a nozzle with too small of an orifice will limit water flow and possibly create an excessive load on the machine. Too large and it will reduce operating pressure.



WHITE 40° NOZZLE

This is a wash nozzle. Its wide spray pattern disperses the water pressure over a large area and is recommended for rinsing and moderate washing.

COMMON USES:

- Washing aluminum siding
- Cleaning windows
- Washing vehicles
- Spraying sidewalks, driveways and patios



YELLOW 15° NOZZLE

This is a chiseling nozzle. The spray should be directed at a 45° angle to the surface and be used like a scraper to remove paint, grease and dirt

COMMON USES:

- Surface preparation (removing peeling paint and mildew stains)
- Cleaning windows
- Cleaning gutters and downspouts
- Cleaning bugs from trucks



GREEN 45° NOZZLE

This is a flushing nozzle. With a narrower spray pattern than the 40° nozzle and with more concentrated spray pressure, this nozzle is best suited for flushing dirt, mud and grime.

COMMON USES:

- Wet sweeping leaves from sidewalks or driveways
- Cleaning barn or garage floors
- Washing swimming pool bottoms
- Cleaning barbecue grills



RED 0° NOZZLE

This is a blasting nozzle. It delivers a very concentrated stream of water. Care should be used to avoid gouging wood or damaging fragile surfaces.

COMMON USES:

- Removing weeds from sidewalk or driveway cracks
- Removing stubborn mineral stains from concrete, masonry, aluminum and steel
- Removing caked mud from equipment
- Cleaning the underside of lawn mowers



BLACK 65° NOZZLE

This is a soap nozzle. Its wide angle spray pattern disperses soap or chemicals over a large area.

COMMON USES:

- Applying soap or chemicals
- Automotive, home and farm

Use the table below to select the proper size for your machine. Match the operating pressure (PSI) of your machine to the gallons per minute (GPM).

Noz:	zle								POU	INDS PEI	r squai	RE INCH	(PSI)							
orifice	size	500	600	700	800	1000	1500	2000	2500	3000	3500	4000	4500	5000	5500	6000	6500	7000	7500	8000
2		0.71	0.77	0.84	0.89	1	1.2	1.4	1.6	1.7	1.9	2	2.1	2.2	2.3	2.4	2.5	2.6	2.7	2.8
2.5		0.9	1	1	1.1	1.3	1.6	1.8	2	2.2	2.3	2.5	2.7	2.8	2.9	3.1	3.2	3.3	3.4	3.5
3		1.1	1.2	1.3	1.4	1.5	1.8	2.1	2.4	2.6	2.8	3	3.2	3.4	3.5	3.7	3.8	4	4.1	4.2
3.5		1.3	1.4	1.5	1.6	1.8	2.2	2.5	2.8	3.1	3.3	3.5	3.7	3.9	4.1	4.3	4.5	4.6	4.8	4.9
4		1.4	1.6	1. <i>7</i>	1.8	2	2.5	2.8	3.2	3.5	3.7	4	4.2	4.5	4.7	4.9	5.1	5.3	5.5	5.7
4.5	<u> </u>	1.6	1. <i>7</i>	1.9	2	2.3	2.8	3.2	3.6	3.9	4.2	4.5	4.8	5	5.3	5.5	5.7	6	6.2	6.4
5	<u>ත</u>	1.8	1.9	2.1	2.2	2.5	3.1	3.5	4	4.3	4.7	5	5.3	5.6	5.9	6.1	6.4	6.6	6.8	7.1
5.5	PER MINUTE (GPM)	1.9	2.1	2.3	2.5	2.8	3.4	3.9	4.1	4.8	5.1	5.5	5.8	6.2	6.4	6.7	7	7.3	7.5	7.8
6	R MI	2.1	2.3	2.5	2.7	3	3.7	4.2	4.7	5.2	5.6	6	6.4	6.7	7	7.3	7.6	7.9	8.2	8.5
6.5	S PE	2.3	2.5	2.7	2.9	3.3	4	4.6	5.1	5.6	6.1	6.5	6.9	7.3	7.6	8	8.3	8.6	8.9	9.2
7	GALLONS	2.5	2.7	2.9	3.1	3.5	4.3	4.9	5.5	6.1	6.5	7	7.4	7.8	8.2	8.6	8.9	9.3	9.6	9.9
7.5	GAL	2.7	2.9	3.1	3.4	3.8	4.6	5.3	5.9	6.5	7	7.5	8	8.4	8.8	9.2	9.6	9.9	10.3	10.6
8		2.8	3.1	3.4	3.6	4	4.9	5.7	6.3	6.9	7.5	8	8.5	8.9	9.4	9.8	10.2	10.6	11	11.3
9		3.2	3.5	3.8	4	4.5	5.5	6.4	<i>7</i> .1	7.8	8.4	9	9.6	10.1	10.6	11	11.5	11.9	12.3	12.7
10	_	3.5	3.9	4.2	4.5	5	6.1	7.1	7.9	8.6	9.4	10	10.6	11.2	11. <i>7</i>	12.2	12.7	13.2	13.7	14.1
12		4.2	4.6	5	4.2	6	7.3	8.5	9.5	10.4	11.2	12	12.7	13.4	14.1	14.7	15.3	15.9	16.4	17
15		5.3	5.8	6.3	6.7	7.5	9.2	10.6	11.9	13	14.1	15	15.9	16.8	17.6	18.4	19.1	19.8	20.5	21.2



QUICK CONNECT SPRAY NOZZLES

CAT#	BULK CAT#	NAME	DESCRIPTION	IMAGE
75150	75143 (10-pack)	Quick Connect Spray Nozzle, 65° x 4.0mm, Black	Soap and chemical spray nozzle designed for a 1/4" (6.35mm) quick coupler. Ideal for quick exchange of spray nozzle and spray guns. It delivers a wide spray angle that allows an even and broad application of the soap or chemicals. Connects to all of the most common pressure washer equipment in the industry. 300° F (148.9° C). 4,000 PSI.	6
75153	75144 (10-pack)	Quick Connect Chiseling Nozzle, 15° x 4.5mm, Yellow	Chiseling nozzle designed for a 1/4" (6.35mm) quick coupler. Ideal for quick exchange of spray nozzles and spray guns. The spray should be directed at a 45° angle to the surface and be used like a scraper to remove paint, grease and dirt. Uses: Surface preparation (removing peeling paint and mildew stains), cleaning gutters and downspouts and bugs from trucks. Connects to all of the most common pressure washer equipment in the industry. 4,000 PSI.	9
75154	_	Quick Connect Chiseling Nozzle, 15° x 5.5mm, Yellow	Chiseling nozzle designed for a 1/4" (6.35mm) quick coupler. Ideal for quick exchange of spray nozzles and spray guns. The spray should be directed at a 45° angle to the surface and be used like a scraper to remove paint, grease and dirt. Uses: Surface preparation (removing peeling paint and mildew stains), cleaning gutters and downspouts and bugs from trucks. Connects to all of the most common pressure washer equipment in the industry. 4,000 PSI.	9
75155	75145 (10-pack)	Quick Connect Flushing Nozzle, 25° x 4.5mm, Green	Flushing nozzle designed for a 1/4" (6.35mm) quick coupler. Ideal for quick exchange of spray nozzles and spray guns. This nozzle is best suited for flushing dirt, mud and grime. Uses: Wet sweeping leaves from walks, curbs and driveways, cleaning stable floors, washing swimming pool bottoms and cleaning barbecue grills. Connects to all of the most common pressure washer equipment in the industry. 4,000 PSI.	-(0
75156	75146 (10-pack)	Quick Connect Wash Nozzle, 40° x 4.5mm, White	Wash nozzle designed for a 1/4" (6.35mm) quick coupler. Ideal for quick exchange of spray nozzles and spray guns. Its wide spray pattern disperses the water pressure over a large area and is recommended for rinsing and moderate washing. Uses: Washing down aluminum siding, cleaning windows, washing vehicles, spraying sidewalks, driveways and patios. Connects to all of the most common pressure washer equipment in the industry. 4,000 PSI.	€ 0
75157	75147 (10-pack)	Quick Connect Blasting Nozzle, 0° x 4.5mm, Red	Blasting nozzle designed for a 1/4" (6.35mm) quick coupler. Ideal for quick exchange of spray nozzles and spray guns. It delivers a very concentrated stream of water. Care should be used to avoid gouging wood or damaging fragile surfaces. Uses: Removing weeds from sidewalk cracks, stubborn mineral stains and chewing gum from concrete, masonry, aluminum and steel, caked mud from equipment and cleaning lawn mower undersides. Connects to all of the most common pressure washer equipment in the industry. 4,000 PSI.	6
<i>7</i> 5148	_	Spray Nozzle Assortment, 4.0mm, 5-Piece	Spray nozzle assortment 4.0mm, five (5) pack of orifice quick connect spray nozzles. Includes 0° blasting (red), 15° chiseling (yellow), 25° flushing (green), 40° washing (white) and 65° soap (black) nozzles. Designed for a 1/4" (6.35mm) quick coupler and ideal for quick exchange of spray nozzle and spray guns. Connects to all of the most common pressure washer equipment in the industry. 300° F (148.9° C). 4,000 PSI.	3 8 8 8 8
75149	_	Spray Nozzle Assortment, 4.5mm, 5-Piece	Spray nozzle assortment 4.5mm, five (5) pack of orifice quick connect spray nozzles. Includes 0° blasting (red), 15° chiseling (yellow), 25° flushing (green), 40° washing (white) and 65° soap (black) nozzles. Designed for a 1/4" (6.35mm) quick coupler and ideal for quick exchange of spray nozzle and spray guns. Connects to all of the most common pressure washer equipment in the industry. 300° F (148.9° C). 4,000 PSI.	5 5 8 4 4

















SIDE HANDLE FOR LANCE

Lance side handle is used on any 1/4" (6.35mm) pressure washer lance and can be adjusted to the perfect position needed by the user. The lance handle reduces user fatigue. Fits Forney® CAT# 75168, 36" (914.4mm) Molded Lance, or other similar 1/4" (6.35mm) lances.



CAT# 75172

SOAP STRAINER FOR 1/4 IN. & 3/8 IN. HOSES

Chemical strainer with built-in stainless steel check valve. The soap enters through the strainer preventing debris from entering the pump. The strainer is designed with a step down hose barb to accept both 1/4" (6.35mm) and 3/8" (9.52mm) hoses.

CAT# 75168

36 IN. LANCE WITH MOLDED GRIP

36" (914.4mm) molded lance with 1/4" (6.35mm) male national pipe threads (M-NPT). The grip is molded directly to the lance to provide protection and strength. 300° F (148.9° C). Forney® CAT# 75167, Side Handle for Lance, can be purchased separately. 5,800 PSI.



CAT# 75173

1/2 IN. FNPT X 1/2 IN. MNPT INLET WATER STRAINER

Inlet water strainer. Placed between the garden hose and the pressure washer to prevent debris from entering the pressure washer from the water source. 1/2" (12.7mm) female national pipe thread (NPT) x 1/2" (12.7mm) male NPT. 145 PSI. 140° F (60° C).

CAT# 75169

36 IN. LANCE WITH MOLDED GRIP & SIDE HANDLE

36" (914.4mm) molded lance with side handle and 1/4" (6.35mm) male national pipe threads (NPT). The grip is molded directly to the lance to provide protection and strength. The side handle can be adjusted and helps reduce fatigue. 300° F (148.9° C). Replacement side handle is Forney® CAT# 75167. 5.800 PSI.



CAT# 75180

SPRAY GUN, 3/8 IN. FNPT INPUT X 1/4 IN. FNPT

3/8" (9.52mm) female national pipe thread (F-NPT) x 1/4" (6.35mm) female NPT output spray gun with forged brass housing. Industry standard and well suited for all pressure washing applications. Specially designed heat and chemical resistant seals allow for optimum performance even in the harshest of environments. 300° F (149° C). 4,000 PSI.





3/8 IN. X 50 FT. HIGH PRESSURE HOSE

Hose, 3/8" (9.52mm) x 50' (15.24m) high pressure hose with 3/8" (9.52mm) male national pipe thread (NPT) solid and swivel screw couplings and bend protectors. 250° F (121.1° C). Smooth rubber cover. Resistant to cleaning detergents. Perfect hose for medium-duty pressure washers. 4,000 PSI.



CAT# 75193

CONCENTRATED PRESSURE WASHER DETERGENT CLEANER

Premium pressure washer detergent with excellent cleaning properties. Strong enough to remove the heaviest of dirt and grime without harming waxed or painted surfaces. Pre-measured for proper dilution ratio. Biodegradable and safe for most applications. Formulated specifically for use with pressure washers. Just empty contents of bag in a 5 gallon bucket of water, mix and it's ready for use.



CAT# 75185

1/4 IN. X 50 FT. HIGH PRESSURE HOSE

Hose, 1/4" (6.35mm) x 50' high pressure hose with M22 x M22 female quick screw couplings and bend protectors. 140° F (60° C). Smooth rubber cover. Resistant to cleaning detergents. Perfect hose for medium-duty pressure washers. 3,000 PSI.



CAT# 75195

1/2 IN. X 260 IN. TEFLON PIPE THREAD TAPE

1/2" (12.7mm) wide x 260" (6,604mm) long Teflon® tape used to wrap the threaded ends of pipe to provide a leak free connection.



CAT# 75186

1/4 IN. X 25 FT. HIGH PRESSURE HOSE

Hose, 1/4'' (6.35mm) × 25' high pressure hose with M22 × M22 female quick screw couplings and bend protectors. 140° F (60° C). Smooth rubber cover. Resistant to cleaning detergents. Perfect hose for medium-duty pressure washers. 3,000 PSI.



CAT# 75196

UPSTREAM DETERGENT INJECTOR

Pressure washer upstream detergent injector for high PSI soap applications. Includes hose and strainer, adjustable chemical flow and garden hose connections. Designed to introduce detergents into the water upstream from the pump for high pressure applications. 140 PSI, 160° F (71.1° C), 3/4" (19.05mm) F-NPT (garden hose) Inlet, 3/4" (19.05mm) M-NPT (garden hose) Outlet, 1.5 – 4.0 GPM and 48" (1,219.2mm) Hose Length.

O-RINGS

CAT#	DESCRIPTION	IMAGE
75190	10-pack replacement screw coupler o-rings (Viton®). Fits Forney® CAT# 75106, 75107, 75108 and 75109 screw couplings.	0
<i>7</i> 5191	10-pack replacement 1/4" (6.35mm) quick coupler o-rings (Buna®). Fits Forney® CAT# 75126 and 75127, 1/4" (6.35mm) socket quick couplers.	0
75192	10-pack replacement 3/8" (9.52mm) quick coupler o-rings (Buna®). Fits Forney® CAT# 75128 and 75129, 3/8" (9.52mm) socket quick couplers.	0
75194	Five (5) each of the three (3) most common pressure washer replacement o-rings, Forney® CAT# 75190, Viton® compatible screw coupler o-rings, 75191, 3/8" (9.52mm) Buna® compatible quick coupler o-rings and 75192, 1/4" (6.35mm) Buna® compatible quick coupler o-rings. Used to replace worn o-rings in screw couplers and quick couplers.	[%] %%


START TO FINISH GET IT DONE WITH FORNEY



GET THE JOB DONE RIGHT

Tested and trusted for 85 years, Forney Industries' complete Shop Tools, Abrasive and Safety product lines will ensure you get the job done right. Our products provide the best combination of price and performance. Forney Industries offers more than 5,000 products serving the automotive, hardware, farm & ranch, industrial and do-it-yourself markets.







PLUMBING



GENERAL PURPOSE

SPECIALTY





LEAD FREE SOLDER OPTIONS

- » Better for the environment» Required for potable water
- » Reliable
- » Safe

SOLDERING IRONS, GUNS & TORCHES

Forney Industries' soldering line features high quality, industry standard products to accomplish any job. The materials are consistent and reliable, allowing precise metal fusing and better results. The all-inclusive line offers lead free options suitable for various applications.







CAT# 59020

25W SOLDERING IRON

25W soldering iron, 120V/680°F. Lightweight with replaceable pointed tip. Ideal for light-duty repairs.

CAT# 59021

30W SOLDERING IRON

30W soldering iron, 120V/734°F. Lightweight with replaceable pointed tip. Ideal for light-duty repairs and hobbyist.

CAT# 61512

40W SOLDERING IRON

40W soldering iron, 120V/842°F. Lightweight with replaceable pointed tip. Ideal for light-duty repairs, hobbyist and general shop use.





60W SOLDERING IRON

60W soldering iron, 120V/896°F. Light weight with replaceable pointed tip. Ideal for general shop use, hobbyist and heavy-duty applications.



CAT# 61529

8W BATTERY POWERED SOLDERING IRON

8W battery powered soldering iron with LED, 4.5V/840°F. Light weight with replaceable pointed tip. Ideal for light-duty repairs and hobbyist.



CAT# 61503

30W WOODBURNING SOLDERING IRON

30W wood burning/soldering iron, 120V/750°F with standard tip and 5 additional burning tips for multiple usage.

90





100W 450°F/230°C SOLDERING GUN

Ideal for home or hobby applications, 120V/450°F. Single output from instant-heat gun. Ready to solder in 6 – 8 seconds. Includes solder, paste flux and extra tips.



CAT# 61530

200W ADJUSTABLE TEMP SOLDERING GUN

Fast heating, convenient and useful for normal to heavy-duty soldering. Temperature range of 160°F to 930°F. Includes solder, paste flux and extra tips.



CAT# 61539

PENCIL FLAME TORCH

Pencil flame propane torch, adjustable flame knob for control and economy. Solid brass valve body for durability.



CAT# 61542

SELF-IGNITING TORCH

Self-igniting trigger torch, adjustable flame control knob, instant on/off trigger igniter, simple one-handed operation and lock button keeps torch lit for finger-free use.



FORNEY INDUSTRIES FULL SOLDERING LINE PROVIDES EVERYTHING YOU NEED TO GET THE JOB DONE RIGHT.

DOES YOUR SOLDER DISPLAY LOOK LIKE THIS?



...WHEN IT SHOULD LOOK LIKE THIS?



INCLUDES

- SOLDER
 - BULK
 - CARDED
 - LEAD FREE OPTIONS
- BRUSHES & FLUX
- GUNS
- IRONS
- TORCHES









	ELECTRICAL SOLDER								
CAT#	DESCRIPTION	LEAD FREE	DIAMETER	WEIGHT	ALLOY	PACKAGE			
38070	Electrical Repair Rosin Core Solder	_	1/8"	16 oz.	94.5% Lead / 3.3% Tin / 2.2% Antimony	Bulk			
38072	Electrical Repair Rosin Core Solder	_	1/16"	4 oz.	40% Tin / 60% Lead	Bulk			
38073	Electrical Repair Rosin Core Solder		1/16"	4 oz.	60% Tin / 40% Lead	Bulk			
61419	Electrical Repair Rosin Core Solder	<u> </u>	1/16"	.75 oz.	40% Tin / 60% Lead	Card			
61420	Lead Free Electrical Repair Rosin Core Solder	LEAD FREE	1/16"	.75 oz.	97% Tin / 2.75% Copper / 0.25% Silver	Card			
61421	Lead Free Electrical Repair Rosin Core Solder	LEAD FREE	1/32"	0.35 oz.	96% Tin / 4% Silver	Card			
61422	Lead Free Electrical Repair Rosin Core Solder	LEAD FREE	1/16"	.3 oz.	96% Tin / 4% Silver	Card			
61423	Electrical Repair Rosin Core Solder	_	1/8"	16 oz.	40% Tin / 60% Lead	Bulk			
61425	Lead Free Electrical Repair Rosin Core Solder	LEAD FREE	1/16"	8 oz.	97% Tin / 2.75% Copper / 0.25% Silver	Bulk			
61426	Electrical Repair Rosin Core Solder	<u> </u>	1/32"	4 oz.	60% Tin / 40% Lead	Card			
61427	Lead Free Electrical Repair Rosin Core Solder	LEAD FREE	1/16"	4 oz.	97% Tin / 2.75% Copper / 0.25% Silver	Card			
61428	Lead Free Electrical Repair Rosin Core Solder	LEAD FREE	1/16"	4 oz.	95% Tin / 5 % Antimony	Card			
61429	Electrical Repair Rosin Core Solder	_	1/20"	.3 oz.	60% Tin / 40% Lead	Card			
61430	Electrical Repair Rosin Core Solder	_	1/32"	.3 oz.	60% Tin / 40% Lead	Card			
61444	Lead Free Electrical Repair Rosin Core Solder	LEAD FREE	1/16"	16 oz.	97% Tin / 2.75% Copper / 0.25% Silver	Bulk			
61445	Lead Free Electrical Repair Rosin Core Solder	LEAD FREE	1/32"	16 oz.	97% Tin / 2.75% Copper / 0.25% Silver	Bulk			
61447	Lead Free Electrical Repair Rosin Core Solder	LEAD FREE	1/20"	16 oz.	97% Tin / 2.75% Copper / 0.25% Silver	Bulk			
61449	Lead Free Electrical Repair Rosin Core Solder	LEAD FREE	1/8"	16 oz.	97% Tin / 2.75% Copper / 0.25% Silver	Bulk			
61455	Electrical Repair Rosin Core Solder	_	1/16"	16 oz.	60% Tin / 40% Lead	Bulk			
61456	Electrical Repair Rosin Core Solder	_	1/32"	16 oz.	60% Tin / 40% Lead	Bulk			
61458	Electrical Repair Rosin Core Solder	_	1/8"	16 oz.	60% Tin / 40% Lead	Bulk			
61459	Electrical Repair Rosin Core Solder	_	1/16"	16 oz.	40% Tin / 60% Lead	Bulk			
61471	Electrical Repair Rosin Core Solder	_	1/8"	80 oz.	60% Tin / 40% Lead	Bulk			
61472	Electrical Repair Rosin Core Solder		1/16"	8 oz.	60% Tin / 40% Lead	Bulk			
61473	Electrical Repair Rosin Core Solder	-	1/16"	.75 oz.	60% Tin / 40% Lead	Card			
61474	Electrical Repair Rosin Core Solder		1/16"	8 oz.	40% Tin / 60% Lead	Bulk			
61475	Lead Free Electrical Repair Rosin Core Solder	LEAD FREE	1/16"	16 oz.	95% Tin / 5% Antimony	Bulk			
61476	Lead Free Electrical Repair Rosin Core Solder	LEAD FREE	1/16"	8 oz.	95% Tin / 5% Antimony	Bulk			
61477	Electrical Repair Rosin Core Solder	_	1/32"	8 oz.	60% Tin / 40% Lead	Bulk			
61478	Lead Free Electrical Repair Rosin Core Solder	LEAD FREE	1/32"	8 oz.	97% Tin / 2.75% Copper / 0.25% Silver	Bulk			
61479	Lead Free Electrical Repair Rosin Core Solder	LEAD FREE	1/32"	4 oz.	97% Tin / 2.75% Copper / 0.25% Silver	Card			
61480	Lead Free Electrical Repair Rosin Core Solder	LEAD FREE	1/32"	.3 oz.	97% Tin / 2.75% Copper / 0.25% Silver	Card			
61534	Electrical Repair Rosin Core Solder		1/16"	4 oz.	40% Tin / 60% Lead	Card			
61535	Electrical Repair Rosin Core Solder	_	1/16"	4 oz.	60% Tin / 40% Lead	Card			






	PLUMBING SOLDER								
CAT#	DESCRIPTION	LEAD FREE	DIAMETER	WEIGHT	ALLOY	PACKAGE			
38050	Lead Free plumbing repair solid core solder		1/8"	4 oz.	97% Tin / 2.75% Copper / 0.25% Silver	Bulk			
38051	Lead Free plumbing repair solid core solder	LEAD FREE	1/8"	8 oz.	97% Tin / 2.75% Copper / 0.25% Silver	Bulk			
38052	Lead Free plumbing repair solid core solder	LEAD FREE	1/8"	16 oz.	97% Tin / 2.75% Copper / 0.25% Silver	Bulk			
38060	Lead Free plumbing repair solid core solder	LEAD FREE	1/8"	4 oz.	95% Tin / 5% Antimony	Bulk			
38061	Lead Free plumbing repair solid core solder	LEAD FREE	1/8"	8 oz.	95% Tin / 5% Antimony	Bulk			
38062	Lead Free plumbing repair solid core solder		1/8"	16 oz.	95% Tin / 5% Antimony	Bulk			
61412	Solid bar plumbers solder	LEAD FREE	3/8" x 3/4" x 3"	4 oz.	97% Tin / 3% Copper	Bulk			
61435	Lead Free plumbing repair solid core solder kit	lead free	1/8"	.75 oz.	96% Tin / 3.9% Copper / 0.1% Silver	Card			
61437	Lead Free plumbing repair solid core solder kit		1/8"	3 oz.	96% Tin / 3.9% Copper / 0.1% Silver	Card			
61491	Lead Free plumbing repair solid core solder kit		1/8"	80 oz.	97% Tin / 2.75% Copper / 0.25% Silver	Bulk			
61532	Lead Free plumbing repair solid core solder	LEAD FREE	1/8"	4 oz.	97% Tin / 2.75% Copper / 0.25% Silver	Card			
61533	Lead Free plumbing repair solid core solder		1/8"	4 oz.	95% Tin / 5% Antimony	Card			





	GENERAL PURPOSE SOLDER								
CAT#	DESCRIPTION	LEAD FREE	DIAMETER	WEIGHT	ALLOY	PACKAGE			
38101	General Purpose Repair Acid Core Solder	-	1/8"	16 oz.	94.5% Lead / 3.3% Tin / 2.2% Antimony	Bulk			
38102	General Purpose Repair Acid Core Solder	<u> </u>	1/8"	8 oz.	40% Tin / 60% Lead	Bulk			
38103	General Purpose Repair Acid Core Solder	<u> </u>	1/8"	4 oz.	40% Tin / 60% Lead	Bulk			
38106	General Purpose Repair Solid Core Solder	<u> </u>	1/8"	16 oz.	40% Tin / 60% Lead	Bulk			
38108	General Purpose Repair Solid Core Solder	<u> </u>	1/8"	4 oz.	40% Tin / 60% Lead	Bulk			
38109	General Purpose Repair Solid Core Solder	-	1/8"	4 oz.	50% Tin / 50% Lead	Bulk			
38110	General Purpose Repair Solid Core Solder	-	1/8"	8 oz.	50% Tin / 50% Lead	Bulk			
38111	General Purpose Repair Solid Core Solder	<u> </u>	1/8"	16 oz.	50% Tin / 50% Lead	Bulk			
38116	General Purpose Repair Acid Core Solder Kit	-	1/16"	.9 oz.	94% Tin / 6% Silver	Card			
61400	General Purpose Repair Acid Core Solder	<u> </u>	1/8"	.75 oz.	40% Tin / 60% Lead	Card			
61401	Lead Free General Purpose Repair Acid Core Solder	€ LEAD FREE	1/8"	4 oz.	95% Tin / 5 % Antimony	Card			
61402	General Purpose Repair Acid Core Solder	_	1/16"	.75 oz.	40% Tin / 60% Lead	Card			
61403	Lead Free General Purpose Repair Acid Core Solder	lead free	1/16"	.75 oz.	97% Tin / 2.75% Copper / 0.25% Silver	Card			
61404	Lead Free General Purpose Repair Acid Core Solder	lead free	1/16"	8 oz.	97% Tin / 2.75% Copper / 0.25% Silver	Bulk			
61405	Lead Free General Purpose Repair Acid Core Solder		1/16"	16 oz.	97% Tin / 2.75% Copper / 0.25% Silver	Bulk			
61406	Lead Free General Purpose Repair Acid Core Solder		1/8"	16 oz.	97% Tin / 2.75% Copper / 0.25% Silver	Bulk			
61407	Lead Free General Purpose Repair Acid Core Solder		1/8"	8 oz.	97% Tin / 2.75% Copper / 0.25% Silver	Bulk			
61409	Lead Free General Purpose Repair Acid Core Solder		1/8"	4 oz.	97% Tin / 2.75% Copper / 0.25% Silver	Bulk			
61450	General Purpose Repair Solid Core Solder	<u> </u>	1/8"	8 oz.	40% Tin / 60% Lead	Bulk			
61452	General Purpose Acid Core Solder	<u> </u>	1/8"	16 oz.	40% Tin / 60% Lead	Bulk			
61454	General Purpose Acid Core Solder	-	1/16"	16 oz.	40% Tin / 60% Lead	Bulk			
61481	General Purpose Repair Acid Core Solder		1/8"	8 oz.	3.3% Tin / 94.5% Lead / 2.2% Antimony	Bulk			
61482	Lead Free General Purpose Repair Acid Core Solder	€ LEAD FREE	1/8"	16 oz.	95% Tin / 5% Antimony	Bulk			
61483	Lead Free General Purpose Repair Acid Core Solder	lead free	1/8"	8 oz.	95% Tin / 5% Antimony	Bulk			
61484	General Purpose Repair Acid Core Solder	<u> </u>	1/16"	8 oz.	40% Tin / 60% Lead	Bulk			
61485	General Purpose Repair Acid Core Solder	<u> </u>	1/16"	4 oz.	40% Tin / 60% Lead	Card			
61486	Lead Free General Purpose Repair Acid Core Solder	€ LEAD FREE		4 oz.	97% Tin / 2.75% Copper / 0.25% Silver	Card			
61536	General Purpose Repair Acid Core Solder	<u> </u>	1/8"	4 oz.	40% Tin / 60% Lead	Card			
61537	General Purpose Solid Core Solder	<u> </u>	1/8"	4 oz.	40% Tin / 60% Lead	Card			
61538	General Purpose Repair Solid Core Solder	<u> </u>	1/8"	4 oz.	50% Tin / 50% Lead	Card			





	SPECIALTY SOLDER						
CAT#	DESCRIPTION	LEAD FREE	DIAMETER	WEIGHT	ALLOY	PACKAGE	
61438	Lead Free Specialty Brazing Solid Core Solder Kit		1/32"	.21 oz.	44% Tin / 56% Silver	Card	
61440	Lead Free Aluminum Brazing Solid Core Solder Kit		1/16″	.3 oz.	100% Aluminum	Card	
61441	Lead Free Specialty Repair Silver Solder	LEAD FREE	1/16"	.75 oz.	96% Tin / 4% Silver	Card	
61489	Lead Free Specialty Repair Solid Core Solder	LEAD FREE	1/8"	8 oz.	96% Tin / 3.9% Copper / .1% Silver	Card	
61490	Lead Free Specialty Repair Solid Core Solder	LEAD FREE	1/8"	4 oz.	96% Tin / 3.9% Copper / .1% Silver	Card	



	REPLACEMENT TIPS					
CAT#	DESCRIPTION					
61513	Replacement soldering tip for Forney CAT# 59020/59021 25W & 30W soldering irons					
61514	Replacement soldering tip for Forney CAT# 61499 60W soldering iron					
61515	Replacement soldering tip for Forney CAT# 61512 40W soldering iron					
61516	Replacement soldering tip for Forney CAT# 61529 8W battery powered soldering iron					
61517	Replacement chisel tip for Forney CAT# 61503 30W woodburning soldering iron					
61518	Replacement long point tip for Forney CAT# 61503 30W woodburning soldering iron					
61519	Replacement short point tip for Forney CAT# 61503 30W woodburning soldering iron					
61520	Replacement knife point tip for Forney CAT# 61503 30W woodburning soldering iron					
61521	Replacement solder point tip for Forney CAT# 61503 30W woodburning soldering iron					
61522	Replacement soldering tip for Forney CAT# 61528 100W soldering gun					
61523	Replacement soldering tip for Forney CAT# 61530 200W soldering gun					
61543	Replacement cutting tip for Forney CAT# 61528 100W soldering gun					
61544	Replacement cutting tip for Forney CAT# 61530 200W soldering gun					

	FLUX LIQUIDS AND PASTES
CAT#	DESCRIPTION
61460	Acid & petrolatum-based paste flux, petrolatum-based soldering paste that contains zinc chloride and ammonium chloride. The petrolatum helps protect the solder joint against corrosive attack and the paste form insures that the flux stays put until soldering. 2 oz.
61461	Acid & petrolatum-based paste flux, petrolatum-based soldering paste that contains zinc chloride and ammonium chloride. The petrolatum helps protect the solder joint against corrosive attack and the paste form insures that the flux stays put until soldering. 16 oz.
61464	Acid & petrolatum-based paste flux kit, petrolatum-based soldering paste that contains zinc chloride and ammonium chloride. The petrolatum helps protect the solder joint against corrosive attack and the paste form insures that the flux stays put until soldering. 2 oz.
61508	Acid tinning paste flux, water-soluble flux, contains tin powder, enabling it to coat solder area with thin layer of tin, thus aiding the soldering process.16 oz.
61509	Acid tinning cream flux, water-soluble flux, contains tin powder, enabling it to coat solder area with thin layer of tin, thus aiding the soldering process. 4 oz.
37025	Aluminum welding flux 1/4 lb. jar
37250	Brazing flux 1/2 lb.
38120	Rubyfluid™ liquid flux for soldering, 2 oz. (bulk)
38125	Rubyfluid™ paste flux for soldering, 2 oz. (bulk)
60301	Rubyfluid™ liquid flux for soldering, 2 oz.
60303	Rubyfluid™ paste flux for soldering, 2 oz.
61466	Rosin core solder liquid flux, 3 oz.
61463	Water soluble paste flux, formulated specifically for use in plumbing applications where copper and copper-alloy tubes are being soldered. It is also an excellent choice for copper pipes used in heating, air-conditioning, mechanical and fire sprinkler systems. 8 oz.
61467	Water soluable paste flux with brush, formulated specifically for use in plumbing applications where copper and copper-alloy tubes are being soldered. It is also an excellent choice for copper pipes used in heating, air-conditioning, mechanical and fire sprinkler systems. 2 oz.
61468	Water soluble paste flux, formulated specifically for use in plumbing applications where copper and copper-alloy tubes are being soldered. It is also an excellent choice for copper pipes used in heating, air-conditioning, mechanical and fire sprinkler systems. 2 oz.
61469	Water soluble paste flux, formulated specifically for use in plumbing applications where copper and copper-alloy tubes are being soldered. It is also an excellent choice for copper pipes used in heating, air-conditioning, mechanical and fire sprinkler systems. 16 oz.

	ADDITIONAL ACCESSORIES					
CAT#	DESCRIPTION					
38140	Tin handle horsehair acid brush for solder flux, $4-3/4'' \times 3/8''$ (min order quantity of 12)					
38141	Tin handle horsehair acid brush for solder flux, 4-3/4" x 3/8" (order in quantity of 144, gross)					
60300	Tin handle horsehair acid brush for solder flux, 4-3/4" x 3/8" (3-pack)					
61510	4-in-1 long lasting high carbon steel brush for cleaning the i.D. And o.D. of 1/2" and 3/4" copper tube and fittings					
61470	Sal-ammoniac, quickly cleans any carbon build-up that collects on the tip of a soldering iron. 4 oz.					
61511	Premium grade emery cloth, 1" x 6' 120 grit. Hand sanding (dry) and cleaning of metal, wood and pipe ends. Aluminum oxide coating. Open grain prevents loading.					

STEEL & ALUMINUM



ALUMINUM ROUND ROD 6063-T5

Suitable for most light- and medium-duty projects. Can be welded using Forney® or similar aluminum MIG wire, arc rod or gas welding specialty rods.

CAT#	APPROXIMATE LENGTH	DIAMETER
49200	3′	1/4″
49201	4'	1/4″
49204	3′	1/2″
49205	4'	1/2″



ALUMINUM SQUARE STOCK 6063-T5

Suitable for most light- and medium-duty projects. Can be welded using Forney® or similar aluminum MIG wire, arc rod or gas welding specialty rods.

CAT#	APPROXIMATE LENGTH	DIAMETER
49210	3′	1/4"
49211	4'	1/4"
49212	3′	1/2"
49213	4′	1/2"



ALUMINUM FLAT STOCK 6063-T5


Suitable for most light- and medium-duty projects. Can be welded using Forney® or similar aluminum MIG wire, arc rod or gas welding specialty rods.

CAT#	APPROXIMATE LENGTH	WIDTH	THICKNESS
49220	3′	3/4"	1/8″
49221	4′	3/4"	1/8″
49222	3′	1″	1/8″
49223	4′	1″	1/8″
49224	3′	1-1/2″	1/8″
49225	4′	1-1/2″	1/8″



ALUMINUM ANGLE STOCK

Suitable for most light- and medium-duty projects. Can be welded using Forney® or similar aluminum MIG wire, arc rod or gas welding specialty rods.







ALUMINUM SQUARE TUBING 6063-T5

Suitable for most light- and medium-duty projects. Can be welded using Forney® or similar aluminum MIG wire, arc rod or gas welding specialty rods.

CAT#	APPROXIMATE LENGTH	SIDE 1 WIDTH	SIDE 2 WIDTH	WALL THICKNESS
49250	3′	3/4"	3/4"	1/16″
49251	4'	3/4"	3/4"	1/16″
49252	3′	1"	1"	1/16″
49253	4′	1″	1″	1/16″



Suitable for most light- and medium-duty projects. Can be welded using Forney® or similar aluminum MIG wire, arc rod or gas welding specialty rods.



CAT# 49250

CAT#	APPROXIMATE LENGTH	DIAMETER	WALL THICKNESS
49260	3′	1/2″	0.050"
49261	3′	3/4"	0.050"
49262	4′	1/2″	0.050″
49263	4′	3/4"	0.050″
49264	6′	1/2″	0.062"
49265	6′	3/4"	0.062"

5052 ALUMINUM 16 GAUGE SHEET METAL

Suitable for most light- and medium-duty projects. Can be welded using Forney® or similar aluminum MIG wire, arc rod or gas welding specialty rods.

CAT#	APPROXIMATE LENGTH	WIDTH	GAUGE
49270	18″	6"	16
49274	18"	12"	16
49276	12″	24"	16



MILD STEEL SHEET METAL

A36 mild carbon steel alloy. Common structural steel in U.S.A. Minimum yield of 36,000 PSI (250 MPa) and ultimate tensile strength of 58,000 to 80,000 PSI (400 – 550 MPa).

CAT#	APPROXIMATE LENGTH	WIDTH	GAUGE
49570	18"	6"	16
49575	12″	24"	16
49584	12″	18"	22
49585	12″	24"	22



CAT# 49570

GALVANIZED MILD STEEL SHEET

Galvanized mild steel sheet metal, 26 gauge, grade 60 mild steel sheet metal.

CAT#	APPROXIMATE LENGTH	WIDTH	GAUGE
49600	24"	36"	26



13 GAUGE EXPANDED METAL


Made from A36 mild carbon steel alloy. Common structural steel in U.S.A. Minimum yield: 36,000 PSI (250 MPa). Ultimate tensile strength: 58,000 to 80,000 PSI (400 – 550 MPa).


CAT#	APPROXIMATE LENGTH	WIDTH	THICKNESS
49611	24"	24"	3/4"
49612	12"	24"	3/4"
49613	16"	32"	1/2″
49614	24"	24"	1/2″



COLD ROLLED STEEL ROUNDS


A36 mild carbon steel alloy. Common structural steel in U.S.A. Minimum yield of 36,000 PSI (250 MPa) and ultimate tensile strength of 58,000 to 80,000 PSI (400 -550 MPa). Cold rolled steel is tough and tight grained.





HOT ROLLED STEEL ROUNDS

A36 mild carbon steel alloy. Common structural steel in U.S.A. Minimum yield of 36,000 PSI (250 MPa) and ultimate tensile strength of 58,000 to 80,000 PSI (400 -550 MPa). Hot rolled steel is versatile and economical.









FLAT STOCK MILD STEEL

A36 mild carbon steel alloy. Common structural steel in U.S.A. Minimum yield of 36,000 PSI (250 MPa) and ultimate tensile strength of 58,000 to 80,000 PSI (400 - 550 MPa).

CAT#	APPROXIMATE LENGTH	WIDTH	THICKNESS
49410	3′	1/2″	1/8″
49411	4′	1/2″	1/8″
49412	6′	1/2″	1/8″
49413	3′	3/4″	1/8″
49414	4′	3/4″	1/8″
49415	6′	3/4″	1/8″
49416	3′	1″	1/8″
49417	4′	1″	1/8″
49418	6′	1″	1/8″
49419	3′	1-1/4″	1/8″
49420	4′	1-1/4″	1/8″
49421	6′	1-1/4″	1/8″
49422	3′	1-1/2"	1/8″
49423	4′	1-1/2″	1/8″
49424	6′	1-1/2″	1/8″
49425	3′	2″	1/8″
49426	4′	2″	1/8″
49427	6′	2″	1/8″
49428	3′	3″	1/8″
49429	4′	3″	1/8″
49430	6′	3″	1/8″
49431	3′	3/4"	3/16″

CAT#	APPROXIMATE LENGTH	WIDTH	THICKNESS
49432	4'	3/4"	3/16"
49433	3′	1″	3/16″
49434	4'	1″	3/16″
49435	3′	1-1/4"	3/16″
49436	4'	1-1/4″	3/16″
49437	3′	1-1/2"	3/16″
49438	4'	1-1/2″	3/16″
49439	3′	2″	3/16″
49440	4'	2″	3/16″
49441	3′	3″	3/16″
49442	4'	3″	3/16″
49445	3′	1″	1/4″
49446	4'	1″	1/4″
49447	6′	1″	1/4″
49449	3′	1-1/2″	1/4″
49450	4'	1-1/2"	1/4″
49451	6′	1-1/2″	1/4″
49452	4'	2″	1/4″
49453	4′	3″	1/4″
49454	4'	2″	3/8″
49455	4′	3″	3/8″
49456	4'	2″	1/2″



14 GAUGE SLOTTED ANGLE GALVANIZED MILD STEEL

Mild steel slotted angle, oval holes (slots). 14 gauge thickness (5/64").

CAT#	APPROXIMATE LENGTH	LEG WIDTH	LEG WIDTH
49645	3′	1-1/2"	1-1/2"
49646	4′	1-1/2"	1-1/2"
49647	6′	1-1/2"	1-1/2"
19650	3′	1-1/2"	2-1/4"
19651	4′	1-1/2"	2-1/4"
19652	6′	1-1/2″	2-1/4"



SLOTTED FLAT GALVANIZED MILD STEEL

Galvanized mild steel slotted flat with 3/8'' (9.52mm) holes (slots). 14 gauge thickness (5/64'').

CAT#	APPROXIMATE LENGTH	WIDTH	THICKNESS
49640	3′	1-3/8″	14 gauge (5/64")
49641	4′	1-3/8″	14 gauge (5/64")
49642	6′	1-3/8″	14 gauge (5/64")

SQUARE TUBING MILD STEEL

A36 mild carbon steel alloy with 16 gauge walls. Common structural steel in U.S.A. Minimum yield of 36,000 PSI (250 MPa) and ultimate tensile strength of 58,000 to 80,000 PSI (400 - 550 MPa).



CAT#	APPROXIMATE LENGTH	DIAMETER	
49520	3′	1/2″	
49521	4′	1/2″	
49522	6′	1/2"	
49523	3′	3/4"	
49524	4′	3/4"	
49525	6′	3/4"	
49526	3′	1"	
49527	4′	1"	
49528	6′	1"	
49529	3′	1-1/4"	
49530	4′	1-1/4"	***************************************
49531	6′	1-1/4"	




ANGLE STOCK MILD STEEL

A36 mild carbon steel alloy. Common structural steel in U.S.A. Minimum yield of 36,000 PSI (250 MPa) and ultimate tensile strength of 58,000 to 80,000 PSI (400 - 550 MPa).

CAT#	APPROXIMATE LENGTH	LEG 1 WIDTH	LEG 2 WIDTH	THICKNESS
49470	3′	1/2″	1/2″	1/8″
49471	4'	1/2″	1/2″	1/8″
49472	6′	1/2″	1/2″	1/8″
49473	3′	3/4"	3/4"	1/8″
49474	4′	3/4″	3/4"	1/8″
49475	6′	3/4"	3/4"	1/8″
49476	3′	1″	1″	1/8″
49477	4'	1″	1″	1/8″
49478	6′	1″	1″	1/8″
49479	3′	1-1/4″	1-1/4″	1/8″
49480	4′	1-1/4″	1-1/4″	1/8″
49481	6′	1-1/4″	1-1/4″	1/8″
49482	3′	1-1/2″	1-1/2″	1/8″
49483	4′	1-1/2″	1-1/2″	1/8″
49484	6′	1-1/2″	1-1/2″	1/8″
49485	3′	2″	2″	1/8″

CAT#	APPROXIMATE LENGTH	LEG 1 WIDTH	LEG 2 WIDTH	THICKNESS
49486	4'	2″	2″	1/8″
49487	6′	2″	2″	1/8″
49488	3′	1-1/2″	1-1/2″	3/16″
49489	4'	1-1/2″	1-1/2″	3/16″
49490	6′	1-1/2″	1-1/2″	3/16″
49491	3′	2″	2″	3/16″
49492	4′	2″	2″	3/16″
49493	6′	2″	2″	3/16″
49494	3′	1-1/2″	1-1/2″	1/4″
49495	4'	1-1/2″	1-1/2″	1/4″
49496	6′	1-1/2″	1-1/2″	1/4″
49497	3′	2″	2″	1/4″
49498	4′	2″	2″	1/4″
49499	6′	2″	2″	1/4″
49500	3′	3″	3″	1/4″
49501	4′	3″	3″	1/4″





ROUND TUBING MILD STEEL

A36 mild carbon steel alloy with 16 gauge walls. Common structural steel in U.S.A. Minimum yield of 36,000 PSI (250 MPa) and ultimate tensile strength of 58,000 to 80,000 PSI (400 – 550 MPa).

CAT#	APPROXIMATE LENGTH	DIAMETER
49540	3′	1/2"
49541	3′	3/4"
49542	3′	1″
49543	3′	1-1/4"
49544	3′	1-1/2″



HOT ROLLED PLATE

Hot rolled mild steel plate. A36 mild carbon steel alloy. 12" (304.80mm) length \times 4" (101.6mm) width \times 1/4" (6.35mm) thickness. Common structural steel in U.S.A. Minimum yield of 36,000 PSI (250 MPa) and ultimate tensile strength of 58,000 to 80,000 PSI (400 – 500 MPa). Hot rolled mild steel is versatile and economical.

CAT#	APPROXIMATE LENGTH	WIDTH	THICKNESS
49620	12"	4"	1/4"



FLAT PLATED MILD STEEL

 $3/4'' \times 1/8'' \times 3''$ Plated Mild Steel Flat. 12 gauge A36 mild carbon steel alloy. Common structural steel in U.S.A. Minimum yield of 36,000 PSI (250 MPa) and ultimate tensile strength of 58,000 to 80,000 PSI (400 – 500 MPa).

CAT#	APPROXIMATE LENGTH	WIDTH	THICKNESS
49625	3′	3/4"	1/8″



ROUND ZINC PLATED MILD STEEL

A36 mild carbon steel alloy. Common structural steel in U.S.A. Minimum yield of 36,000 PSI (250 MPa) and ultimate tensile strength of 58,000 to 80,000 PSI (400-500 MPa).

CAT#	APPROXIMATE LENGTH	WIDTH
49630	3′	1/4″
49632	3′	5/16″
49634	3′	3/8″

ROUND KEY STOCK COLD ROLLED

Cold rolled round key stock made of 1018 grade mild steel carbon steel used worldwide as it is easily machined, welded and fabricated. Minimum yield strength of 53,700 PSI and ultimate tensile strength of 63,800 PSI. Cold rolled steel is tough with tight grain.

CAT#	APPROXIMATE LENGTH	DIAMETER
49380	3′	1/8″
49381	4′	1/8″
49382	3′	3/16"
49383	4'	3/16"



SQUARE KEY STOCK COLD ROLLED

Cold rolled square key stock made of 1018 grade mild steel carbon steel used world-wide as it is easily machined, welded and fabricated. Minimum yield strength of 53,700 PSI and ultimate tensile strength of 63,800 PSI. Cold rolled steel is tough with tight grain.

CAT# APPROXIMATE LENGTH		DIAMETER
49391	3′	3/16"
49392	3′	1/4"



SQUARE KEY STOCK HOT ROLLED

Hot rolled square key stock made of 1018 grade mild steel carbon steel used worldwide as it is easily machined, welded and fabricated. Minimum yield strength of 53,700 PSI and ultimate tensile strength of 63,800 PSI. Hot rolled steel is versatile and economical.

CAT# APPROXIMATE LENGTH		DIAMETER
49400	3′	3/8″
49402	3′	1/2"



SQUARE KEY STOCK HOT ROLLED

Plated/hardened cold rolled square key stock made of 1018 grade mild steel carbon steel used world-wide as it is easily machined, welded and fabricated. Minimum yield strength of 53,700 PSI and ultimate tensile strength of 63,800 PSI. Cold rolled steel is tough with tight grain.

CAT#	APPROXIMATE LENGTH	DIAMETER	
49711	1′	3/16"	
49712	1′	1/4"	
49713	1′	5/16"	
49714	1′	3/8″	
49715	1′	1/2″	
49716	1′	5/8"	
49717	1′	3/4"	





RE-INFORCED STEEL BAR (REBAR) FOR CONCRETE

Grade 60 mild steel re-enforced steel bar (rebar). Superior grade for reinforcing concrete.

CAT#	APPROXIMATE LENGTH	DIAMETER
49546	3/8″	4′
49547	3/8″	6′
49548	1/2″	3′
49549	1/2″	4'
49550	1/2″	6′



ALL-THREAD ROD GRADE 2

All-thread rod. Grade 2. Hot dipped galvanized. General purpose.

CAT#	APPROXIMATE LENGTH	THREAD SIZE		
49660	3′	10-4		
49662	3′	1/4″-20		
49663	6′	1/4″-20		
49665	3′	5/16″-18		
49666	6′	5/16″-18		
49668	3′	3/8″-16		
49669	6′	3/8″-16		
49671	3′	1/2″-13		
49672	6′	1/2″-13		
49674	3′	5/8″-11		
49675	6′	5/8″-11		
49676	3′	3/4″-10		
49677 3'		7/8″-9		
49678	3′	1″-8		
49685	1′	6-32		

CAT#	APPROXIMATE LENGTH	THREAD SIZE	
49686	1′	8-32	
49687	1′	10-24	
49688	1′	10-32	
49689	1′	1/4″-20	
49690	1′	5/16″-18	
49691	1′	3/8″-16	
49692	3′	10-24	
49695	2′	8/32	
49696	2′	8/32	
49697	2′	10-24	
49698	2′	10-32	
49699	2′	1/4″-20	
49700	2′	5/16″-18	
49701	2′	3/8″-16	
49702	2′	1/2″-13	


THREADED ROD COUPLERS GRADE 2

Grade 2 galvanized steel general purpose threaded rod couplers.

CAT#	THREAD SIZE
49728	1/4″-20
49729	5/16"-18
49730	3/8″-16
49731	1/2″-13
49732	5/8″-11







PAINT MARKERS

Multiple colors are available in two sizes - regular and x-large. Both sizes are oil-based paint markers for permanent marking on most surfaces. Intense, highly visible, quick drying colors are water and weather resistant. Precision valve regulates paint flow.


COLOR	CAT# – REGULAR	CAT# – CARDED	CAT# – EXTRA LARGE
White	70818	60312	70828
Black	70819	60313	70829
Red	70820	60314	70830
Blue	70821	<u> </u>	70831
Yellow	70822	60315	70832
Green	70823	_	70833
Silver	70824		70834
Orange	70825	_	70835
Black/White 2-Pack	_	60310	_



CAT# 70826

PAINT MARKER REPLACEMENT NIBS (12-PACK)

Replacement nibs for Forney® CAT#'s 70818 through 70825 (bulk) and 60312 through 60315 (carded) regular paint markers. 12-pack.



WINDOW MARKERS

Made in U.S.A. Great for indoor or outdoor holiday decorating, announcing special events, advertising vehicles for sale and many other uses. Temporary window marker for use on glass, metal and most other non-porous surfaces. Vibrant color is weather resistant, dries quickly and removes easily. To remove paint, spray with an all-purpose cleaner, briefly soak and rub vigorously with a wet cloth or paper towel. Use only as directed. Not intended for use on clothing, convertibles or car paint, rubber, textiles, paper and other porous surfaces. May stain clothing.


COLOR	CAT#
White	70853
Black	70854
Red	70856
Blue	70855
Green	70858
Yellow	70857



INSERT & POWER BITS

POWER BITS Power bits are designed to be used in a power drill. They're manufactured from S2 modified tool steel and heat treated to 58 - 62 rc. Bits are tested during the manufacturing process for gauge fit, tolerance and specification accuracy. Torque tested at final stages to 120 - 150% above ANSI standards.

INSERT BITS Insert bits are designed to be used with screwdriver type hand tools. They're manufactured from S2 modified tool steel and heat treated to 58 - 62 rc. Bits are tested during the manufacturing process for gauge fit, tolerance and specification accuracy. Torque tested at final stages to 120 - 150% above ANSI standards.



SAFETY WARNINGS

When working with power or hand tools, always make sure you are wearing the appropriate eye, face, head, hand, feet and hearing safety equipment for the tool and the job. Read all instructions thoroughly before you begin work and make sure your equipment is properly grounded. Some products in this catalog may contain chemicals known to the State of California to cause cancer or other reproductive harm (California Proposition 65). Wash hands after use.







SQUARE RECESS INSERT BITS

CARDED CAT#	BULK CAT#	LENGTH	POINT SIZE	MINIMUM BULK ORDER QUANTITY	QUANTITY PER CARDED PACK
70840	70730	1"	#1	Multiples of 10	2
70841	70731	1″	#2	Multiples of 10	2
70842		1″	#3	_	2





PHILLIPS INSERT BITS

CARDED CAT#	BULK CAT#	LENGTH	POINT SIZE	MINIMUM BULK ORDER QUANTITY	QUANTITY PER CARDED PACK
70901	70756	1″	#1	10	2
70905	70757, 70754	1″	#2	10 (70757) 100 (70754)	2
70908	70758	1"	#3	10	2





PHILLIPS DRYWALL INSERT BITS

CARDED CAT#	LENGTH	POINT SIZE	QUANTITY PER CARDED PACK
70902	1"	#2	2
70903	1″	#2	4





PHILLIPS REDUCED DIAMETER INSERT BITS

BULK CAT#	LENGTH	POINT SIZE	MINIMUM BULK ORDER QUANTITY
70752	1"	#1	10
70753, 70755	1"	#2	10 (70755) 100 (70753)





TORX INSERT BITS

CARDED CAT#	BULK CAT#	LENGTH	POINT SIZE	MINIMUM BULK ORDER QUANTITY	QUANTITY PER CARDED PACK
70860	70738	1"	Т10	Multiples of 5	2
70861	70739	1″	T15	Multiples of 5	2
70862	70740	1″	T20	Multiples of 5	2
70863	70741	1″	T25	Multiples of 5	2
70864	_	1″	T27	_	2
70865	70742	1″	T30	Multiples of 5	2
_	70743	1″	T40	Multiples of 5	_





PHILLIPS POWER BITS

CARDED CAT#	BULK CAT#	LENGTH	POINT SIZE	MINIMUM BULK ORDER QUANTITY	QUANTITY PER CARDED PACK
70915	70733	2″	#2	Multiples of 10	2
_	70734	3″	#2	Multiples of 10	_
_	70762	1-15/16"	#1	Multiples of 10	_
_	70763	1-15/16"	#2	Multiples of 10	_
70912	_	2″	#1	_	2
70917	_	2″	#3	_	2





SQUARE POWER BITS

BULK CAT#	LENGTH	POINT SIZE	MINIMUM BULK ORDER QUANTITY
70735	1-15/16"	#1	Multiples of 10
70736	1-15/16″	#2	Multiples of 10





SQUARE RECESS POWER BITS

CARDED CAT#	LENGTH	POINT SIZE	QUANTITY PER CARDED PACK
70845	2"	#1	2
70846	2"	#2	2
70847	2"	#3	2
70955	6"	#1	1
70956	6"	#2	1





LIMITED CLEARANCE SLOTTED POWER BITS

CARDED CAT#	LENGTH	POINT SIZE	QUANTITY PER CARDED PACK
70886	6"	7/32" (6 – 8)	1
70887	6"	1/4" (8 – 0)	1





SLOTTED POWER BITS

CARDED CAT#	LENGTH	POINT SIZE	QUANTITY PER CARDED PACK
70875	2"	3/16" (4 – 5)	2
70876	2"	7/32" (6 – 8)	2
70877	2"	1/4" (8 – 10)	2
70878	2"	9/32" (10 – 12)	2







TORX POWER BITS

CARDED CAT#	LENGTH	POINT SIZE	QUANTITY PER CARDED PACK
70893	2"	T10	2
70894	2"	T15	2
70895	2"	T20	2
70896	2"	T25	2
70897	2"	T27	2
70898	2"	T30	2





HEX MAGNETIC NUTSETTERS

CARDED CAT#	BULK CAT#	LENGTH	NUT SIZE	MINIMUM ORDER QUANTITY	QUANTITY PER CARDED PACK
_	70770	1-3/4″	1/4"	1	<u> </u>
_	70771	1-3/4″	5/16	1	_
	70776	2-9/16″	1/4″	1	_
70946	_	2″	1/4″	_	1
70947		2"	5/16″	_	1
70948		2″	3/8″	<u> </u>	1



MAGNETIC BIT HOLDERS

CARDED CAT#	BULK CAT#	LENGTH	NUT SIZE	MINIMUM ORDER QUANTITY	QUANTITY PER CARDED PACK
_	70773	3″	1/4″	1	_
70942	_	2-1/2"	1/4″	1	1
70952	_	4"	1/4″	1	1





SLOTTED & PHILLIPS DOUBLE ENDED BIT

Doubled ended bit. Includes 1/4'' (6.35mm) (8 – 10) slotted end and #2 Phillips end. 2'' (50.8mm) overall length.

CAT#	DESCRIPTION
70890	Doubled Ended Bit, 1/4" (8 – 10) Slotted & #2 Phillips







SLOTTED/PHILLIPS DOUBLE ENDED BIT COMBO

3-piece slotted & phillips double ended bits combo pack. Includes 3/16" (4.76mm) slotted & #1 Phillips bit, 1/4" (6.35mm) slotted and #2 Phillips bit and 9/32" (7.14mm) slotted & #3 Phillips bit. All three bits are 2" (50.8mm) overall length.

CAT#	DESCRIPTION
70891	Slotted & Phillips Double Ended Bits Combo Pack, 3-Piece



QUICK RELEASE POWER BIT EXTENSIONS

Quick release bit extension designed for working in hard-to-reach areas. Quick release function provides for fast bit changes.

CAT#	DESCRIPTION	
70960	Quick Release Power Bit Extension, 2-3/4"	
70962	Quick Release Power Bit Extension, 6"	









SOCKET ADAPTERS

CAT#	DESCRIPTION	
70940	Socket Adapter, 1/4" Hex to 1/4" Square Drive x 1" Long	
70941	Socket Adapter, 1/4" Hex to 1/4" Square Drive x 2" Long	



3-PIECE MAGNETIC NUTSETTER SET

CAT#	DESCRIPTION	
70951	Nutsetter Set, Magnetic, 3-Piece (Carded)	





HEX EXTENSION

Hex extension — 2'' (50.8mm) x 1/4'' (6.35mm) hex extension square drive for power driving 1/4'' (6.35mm) drive sockets.

CAT#	DESCRIPTION	
70767	Hex Extension, 2" x 1/4"	




SILVER & DEMING BLACK & GOLD DRILL BITS

1/2" (12.7mm) shank, 3" (76.2mm) flute length, 6" (152.4mm) overall length. Three flats on shank do not allow spinning in chuck. 118° split point so drills do not "walk" when drilling. Black and gold finish to enhance lubricity. Suitable for stainless steel and high temperature alloys.

CAT#	DESCRIPTION	
	9/16" x 6" with 1/2" Shank	
70692	5/8" x 6" with 1/2" Shank	
70693	3/4" x 6" with 1/2" Shank	
	7/8" x 6" with 1/2" Shank	
	1" x 6" with 1/2" Shank	

DRILL GAUGE

CAT#	DESCRIPTION	
21300	Fractional drill gauge. 29-pieces. Includes drill gauges for sizes 1/16" (1.59mm) to 1/2" (12.7mm) by 32nds fractional drills.	
21302	Drill gauge for #1 to #60 wire gauge drills.	



CAT# 21300

METAL DRILL INDEX

Empty metal drill index.

CAT#	DESCRIPTION	CAPACITY
21285	Grey Metal	13-Piece
21286	Black Metal	13-Piece
21287	Grey Metal	15-Piece
21288	Grey Metal	21-Piece
21289	Grey Metal	29-Piece
21292	Grey Metal	29-Piece "Stubby"
21294	#1 – #60 Wire Gauge Metal Index	60-Piece



CAT# 21285

29-PIECE INDUSTRIAL SPLIT POINT DRILL SET

Industrial quality drill bit set with 135° split points and black and gold finish. Includes drill bits size 1/16" (1.59mm) to 1/2" (12.7mm) by 64ths. Suitable for steel, cast iron and stainless steel. Split point reduces walking and the black and gold finish enhances lubricity.



CAT# 70720



ROUND BASTARD MACHINIST FILE

Round double cut, coarse bastard cut file for use with moderate stock removal and finishing of sharp inside corners on steel and other iron-based metals.

CAT#	DESCRIPTION
70330	Hand File, 6" Round Bastard Machinist File
70331	Hand File, 8" Round Bastard Machinist File
70332	Hand File, 10" Round Bastard Machinist File

SLIM TAPER MACHINIST FILE

Slim taper single cut file for use in general stock removal of steel and other ironbased metals.

CAT#	DESCRIPTION	
70334	Hand File, 7" Slim Taper Machinist File	
70335	Hand File, 6" Slim Taper Machinist File	

CHAIN SAW FILE

Round and smooth files with spiral cut. Use for the smooth finishing of chainsaw teeth.

CAT#	DESCRIPTION
	Hand File, Chain Saw File, 1/8" x 6"
70341	Hand File, Chain Saw File, 5/32" x 6"
70342	Hand File, Chain Saw File, 3/16" x 8"
70343	Hand File, Chain Saw File, 7/32" x 8"



CAT# 70340



HALF-ROUND BASTARD MACHINIST FILE

Half-round double cut, coarse bastard cut file. Use for moderate stock removal and finishing of sharp inside corners on steel.

CAT#	THREAD SIZE
70326	Hand File, 6" Half-Round Bastard Machinist File
70327	Hand File, 8" Half-Round Bastard Machinist File
70328	Hand File, 10" Half-Round Bastard Machinist File



FLAT BASTARD MACHINST FILE

Flat mill double cut, coarse bastard cut file for use with general stock removal of steel and other iron-based metals.

CAT#	THREAD SIZE
70320	Hand File, 8" Flat Bastard Machinist File
70321	Hand File, 10" Flat Bastard Machinist File
70322	Hand File, 12" Flat Bastard Machinist File



MILL BASTARD MACHINIST FILE

Flat mill single cut, coarse bastard cut file for use with general stock removal of steel and other iron-based metals.

CAT#	THREAD SIZE
70323	Hand File, 8" Mill Bastard Machinist File
70324	Hand File, 10" Mill Bastard Machinist File
70325	Hand File, 12" Mill Bastard Machinist File



RETRACTABLE TAPE MEASURE

Professional grade measuring tape with easy slide thumb lock and quick auto return with cushioned brake. Impact resistant housing with non-slip grip.

CAT#	THREAD SIZE
70305	Tape Measure, Retractable, 1/2" x 12'
70306	Tape Measure, Retractable, 3/4" x 16'
70307	Tape Measure, Retractable, 1" x 25'





CAT# 21305

MAGDEMAG™ MAGNETIZER & DEMAGNETIZER

MagDeMag™ magnetizer/demagnetizer. Specially designed to magnetize or demagnetize screwdrivers, insert bits, retrieval tools and other small tools.



CAT# 21313

36-PIECE MAGDEMAG™ ASSORTMENT

36-piece MagDeMag™ refill. Includes 36-each Forney® CAT# 21305, MagDeMag™.



CAT# 70221

8 IN. MAGNETIC LEVEL WITH 3 VIALS

8" (203.2mm) non-switchable magnetic level with 3 vials for leveling.



CAT# 70715

LARGE MAGNETIC SUPPORT JIG

Magnetic welding jig with center hole, lifts up to 75 lbs. Strong non-switchable magnetic that sticks to any iron object. Includes 45°, 90° and 135° angles. Excellent "3rd hand" for welding, soldering, assembly, pipe installation, marking, floating and separating thin metal stacks.



CAT# 70716

SMALL MAGNETIC SUPPORT JIG

Magnetic welding jig, small. Strong nonswitchable magnetic that sticks to any iron object. Includes 45°, 90° and 135° angles. Excellent "3rd hand" for welding, soldering, assembly, pipe installation, marking, floating and separating thin metal stacks.



CAT# 70717

MEDIUM MAGNETIC SUPPORT JIG

Magnetic welding jig with center hole, medium, lifts up to 50 lbs. Strong nonswitchable magnetic that sticks to any iron object. Includes 45°, 90° and 135° angles. Excellent "3rd hand" for welding, soldering, assembly, pipe installation, marking, floating and separating thin metal stacks.







CAT# 1901

4-1/2 IN. ANGLE GRINDER

Professional grade angle grinder with precise metal ball-bearing gears. Includes spindle wrench and a two-position side handle ISO 9001 certified.

TECHNICAL DATA

RATED VOLTAGE: 120V/60HZ
RATED WATTAGE: 900 W
RATED AMPERAGE: 7.2 amps
NO LOAD SPEED: 11,000 RPM
WHEEL SIZE: 4-1/2" (114.3mm)

SPINDLE: 5/8"-11 **ARBOR:** 7/8" (22.22mm)



CAT# 70710


EASY 4-WAY PICK REPAIR KIT

4-piece general purpose repair kit containing one (1) each easy-pick hook (o-ring remover), easy-pick 90° scribe, easy-pick double scribe and easy-pick straight scribe.



SOAPSTONE HOLDER REFILLS

#1 select natural white soapstone pencil refill. Uniform texture and size. Won't contaminate welds.





MARKING SCRIBE


Premium scribe, useful marking tool featuring a handy pocket clip, knurled aluminum handle and tungsten carbide tip. Cuts glass.

CAT#	DESCRIPTION
70714	Premium Scribe
70718	Premium Scribe with Alnico Retrieval Magnet



THINLINE MARKING PENCIL & REFILLS

Marks on dry, wet and oily surfaces. Visible when hot. Resists flame and heat. Use on stainless steel, plastic, aluminum, lumber, tile, glass and more. Shatter resistant and stays sharp.





CAT# 70795

Control of the second s

CAT# 70811

YELLOW COLD SURFACE MARKER

For permanent marking of oily, icy, wet, dry, sleek, smooth or rough metal surfaces. Weatherproof and will not fade. Also marks wet, dry, green or creosote lumber, plastics, ceramics, rubber and glass. Contains no lead or zinc compounds.

CAT#	DESCRIPTION
70811	Yellow Cold Surface Marker (Carded), 2-Pack
70812	Yellow Cold Surface Marker (Bulk)





CAT# 70794

SILVER LEAD PENCIL (2-PACK)

Silver lead pencil, 2-pack. Writes on both smooth and rough surfaces such as wood, tile, metal and plastic. Waterproof.

CAT# 70802

FLAT SOAPSTONE HOLDER, STEEL

Ruggedly constructed flat steel soapstone holder comes with a channel case design and convenient spring pocket clip. Easily indexable, this holder is designed for onehanded operation. Proven and superior design features that are widely used and preferred in the welding industry.

CAT# 70806

ROUND SOAPSTONE HOLDER, METAL

Round metal soapstone pencil holder, constructed with an inner sleeve collet to separate the soapstone for maximum grip and protection. Slim line brass holder with a convenient deluxe pocket clip. Easily adjustable.



CAT# 70807

ROUND SOAPSTONE PENCIL HOLDER, 1/4 IN. ALUMINUM

1/4" round aluminum soapstone pencil holder, constructed with an inner sleeve collet to separate the soapstone for maximum grip and protection. Slim line brass holder with a convenient deluxe pocket clip. Easily adjustable.





CAT# 73000

ADJUSTABLE HACKSAW BLADE FRAME

Hacksaw frame, adjustable, standard duty sturdy, adjustable frame. Fits all standard length blades. Lightweight and strong for faster, smoother and quieter cutting.



CARBON HACKSAW BLADES

Standard American pattern saw file. Round, smooth single cut.



CAT#	DESCRIPTION
72005	Carbon Hacksaw Blade, 12" x 18T, 10-Pack
72006	Carbon Hacksaw Blade, 12" x 24T, 10-Pack
72007	Carbon Hacksaw Blade, 12" x 32T, 10-Pack



WIRE EXTENSION SPRINGS

Zinc plated steel wire extension spring. Baked for a rust resistant finish and heat treated for performance and longevity. Ideal for a wide variety of uses in homes, the shop, on the farm or ranch, small businesses or light industry such as screen doors, chaise lounges, toys, lawn and garden equipment, industrial and farm equipment, business machines, cars, trucks, boats, RVs, etc. Packs of 2.

CAT#	LENGTH	WIRE DIAMETER	OUTER DIAMETER	MAX LOAD (LBS.)	NUMBER IN PACKAGE
72506	1.5"	.015"	.125″	1.4 lbs.	2
72507	1.5"	.02"	.156″	2.7 lbs.	2
72508	1.5"	.023"	.218″	2.9 lbs.	2
72509	1.5"	.035″	.25″	8.4 lbs.	2
72510	1.5"	.025"	.281″	2.8 lbs.	2
<i>7</i> 2511	1.5"	.02″	.312″	1.4 lbs.	2
72512	1.5"	.028″	.343″	3.6 lbs.	2

CAT#	LENGTH	WIRE DIAMETER	OUTER DIAMETER	MAX LOAD (LBS.)	NUMBER IN PACKAGE
,	1.5"	.028″	.437"	2.5 lbs.	2
72514	1.5"	.047"	.437"	11 lbs.	2
72540	1.625"	.08″	.5"	35 lbs.	2
72515	1.875"	.014″	.125″	1.3 lbs.	2
72516	1.875"	.02″	.156″	2.2 lbs.	2
72517	1.875"	.02″	.25″	1.7 lbs.	2
	1.875"	.025"	.281″	4.7 lbs.	2

WIRE EXTENSION SPRINGS (CONTINUED)

CAT#	LENGTH	WIRE DIAMETER	OUTER DIAMETER	MAX LOAD (LBS.)	NUMBER IN PACKAGE	CAT#	LENGTH	WIRE DIAMETER	OUTER DIAMETER	MAX LOAD (LBS.)	NUMBER IN PACKAGE
72519	1.875"	.035"	.25"	8.4 lbs.	2	72559	4.75"	.091″	.687"	35 lbs.	2
72520	1.875"	.025"	.281″	4.7 lbs.	2	72553	5"	.035″	.25″	6 lbs.	2
72521	1.875"	.0.25"	.343″	2.3 lbs.	2	72558	5"	.072″	.5″	25 lbs.	2
72522	1.875"	.028″	.437"	2.5 lbs.	2	72579	5"	.035"	.375″	5.4 lbs.	2
72523	1.875"	.047"	.437"	11 lbs.	2	72580	5"	.032″	.312″	5.2 lbs.	2
72532	2"	.062″	.437"	19 lbs.	2	72581	5"	.035"	.312″	6.6 lbs.	2
72541	2"	.105″	.75″	60 lbs.	2	72569	5.5"	.12″	1.062"	49 lbs.	1
72542	2.25"	.105″	.75″	60 lbs.	2	72578	5.5"	.062"	.375″	23 lbs.	2
72543	2.437"	.105″	.75″	50 lbs.	2	72582	5.5"	.12″	1.062"	49 lbs.	1
72524	2.5"	.018″	.125″	2.5 lbs.	2	72560	6"	.072"	.562"	22 lbs.	2
72525	2.5"	.02″	.156″	2.7 lbs.	2	72561	6"	.035″	.25″	6 lbs.	2
72526	2.5"	.025"	.187″	4.2 lbs.	2	72562	6"	.028″	.312″	3.9 lbs.	2
72527	2.5"	.016″	.25″	0.87 lbs.	2	72570	6"	.091″	.875″	26 lbs.	1
72528	2.5"	.02″	.25″	1.7 lbs.	2	72563	6.5"	.047"	.375″	10 lbs.	2
72529	2.5"	.035″	.25″	8.4 lbs.	2	72564	6.5"	.054"	.625"	8.3 lbs.	2
72530	2.5"	.028″	.437"	2.5 lbs.	2	72572	6.5"	.162″	1.25"	100 lbs.	1
72531	2.5"	.047"	.437"	11 lbs.	2	72577	6.5"	.091″	6.5"	31 lbs.	1
72534	2.5"	.072″	.625"	19 lbs.	2	72571	7"	.105″	1.062"	33 lbs.	1
72544	2.625"	.105″	.75″	50 lbs.	2	72573	7"	.135″	1″	75 lbs.	1
72538	2.75"	.035″	.437"	3.3 lbs.	2	72576	7.5"	.091″	1.125″	20 lbs.	1
72545	2.875"	.072″	.562"	22 lbs.	2	72574	8.5"	.08″	1.062"	15 lbs.	1
72549	2.875"	.105″	.75″	60 lbs.	2	72575	8.5"	.148″	1.125″	87 lbs.	1
72535	3"	.054″	.562″	9.2 lbs.	2	72587	8.5"	.047"	5″	7.2 lbs.	1
72536	3"	.028″	.312″	3.5 lbs.	2	72588	8.5"	.047"	.437"	8.4 lbs.	1
72550	3.125"	.105″	.75″	50 lbs.	2	72589	8.5"	.091″	.625″	39 lbs.	1
72537	3.25"	.025″	.25″	3.1 lbs.	2	72590	8.5"	.054"	.562″	9.2 lbs.	1
72546	3.25"	.072″	.625″	19 lbs.	2	72591	8.5"	.062″	.625″	13 lbs.	1
72533	3.5"	.054″	.437″	12 lbs.	2	72592	8.5"	.08″	.625″	27 lbs.	1
72539	3.5"	.047"	8.4"	2 lbs.	2	72593	8.5"	.062″	.875″	8.8 lbs.	1
72548	3.5"	.062″	.75″	11 lbs.	2	72594	8.5"	.105″	.875″	41 lbs.	1
72551	3.75"	.105″	.75″	50 lbs.	2	72596	8.5"	.12″	1″	52 lbs.	1
72555	3.75"	.041″	.375″	6.5 lbs.	2	72595	9"	.135″	.875″	87 lbs.	1
72547	4"	.047"	.562″	6.5 lbs.	2	72597	10"	.148″	1.25″	77 lbs.	1
72552	4"	.035″	.375″	3.9 lbs.	2	72586	10.25"	.041″	.437"	5.5 lbs.	1
72568	4"	.12″	.812″	66 lbs.	2	72583	11.5"	.135″	1.5″	47 lbs.	1
72554	4.5"	.028″	.375″	2.9 lbs.	2	72584	12"	.105″	1″	35 lbs.	1
72556	4.5"	.041″	.468″	5.2 lbs.	2	72585	12"	.135″	1.062"	69 lbs.	1
72557	4.5"	.062″	.5″	16 lbs.	2	72565	16"	.105″	1.125″	31 lbs.	1
72567	4.5"	.091″	.812"	29 lbs.	2	72566	16.5"	.054"	.562"	9.2 lbs.	1



WIRE COMPRESSION SPRINGS

Zinc plated steel wire compression spring. Baked for a rust resistant finish and heat treated for performance and longevity. Ideal for a wide variety of uses in homes, the shop, on the farm or ranch, small businesses or light industry such as screen doors, chaise lounges, toys, lawn and garden equipment, industrial and farm equipment, business machines, cars, trucks, boats, RVs, etc.

CAT#	LENGTH	WIRE DIAMETER	OUTER DIAMETER	MAX LOAD (LBS.)	NUMBER IN PACKAGE	CAT#	LENGTH	WIRE DIAMETER	OUTER DIAMETER	MAX LOAD (LBS.)	NUMBER IN PACKAGE
72601	0.5"	.035"	.25″	6.2 lbs.	6	72633	1.5"	.041″	.625"	3.8 lbs.	2
72600	0.562"	.023"	.156″	4.5 lbs.	6	72636	1.5″	.041″	.5″	5.4 lbs.	2
72609	0.625"	.026"	.312″	3.1 lbs.	6	72624	1.75"	.013″	.218″	0.44 lbs.	4
72611	0.75"	.032"	.375″	3.2 lbs.	6	72626	1.75"	.016"	.312″	0.61 lbs.	4
72603	0.875"	.016″	.187″	0.81 lbs.	6	72629	1.75″	.035″	.375″	4.2 lbs.	4
72602	1″	.011″	.156″	0.57 lbs.	6	72640	1.75"	.062"	.5″	17 lbs.	2
72604	1″	.028″	.187″	6.3 lbs.	6	72631	2″	.047"	.312″	12 lbs.	4
72605	1″	.02″	.218″	2.2 lbs.	6	72641	2″	.054"	.437"	13 lbs.	2
72606	1″	.013″	.187″	0.78 lbs.	6	72646	2″	.08″	.75″	23 lbs.	2
72607	1″	.016″	.187″	1.3 lbs.	6	72647	2″	.08″	.937"	19 lbs.	2
72608	1″	.02"	.25″	1.9 lbs.	6	72630	2.125"	.032"	.437"	2.8 lbs.	4
72610	1″	.035″	.25″	8.9 lbs.	6	72632	2.25"	.041″	.437"	6.1 lbs.	2
72634	1″	.062"	.5″	17 lbs.	2	72639	2.25"	.062"	.375″	22 lbs.	2
72635	1″	.054"	.562″	9.5 lbs.	2	72644	2.5"	.08″	.625"	27 lbs.	2
72623	1.062"	.041″	.437"	6.1 lbs.	4	72654	2.5"	.135″	1.375″	55 lbs.	1
72622	1.125"	.041″	.375″	7 lbs.	4	72642	2.75"	.047"	.406″	9.7 lbs.	2
72621	1.25"	.041″	.312″	8.3 lbs.	4	72643	2.75"	.072"	.5″	25 lbs.	2
72638	1.25"	.091″	.687″	35 lbs.	2	72645	2.75"	.054"	.625″	9.1 lbs.	2
72612	1.375"	.014"	.125″	1.4 lbs.	6	72660	2.75"	.12"	1.187″	46 lbs.	2
72613	1.375″	.016″	.156″	1.6 lbs.	6	72649	3″	.054"	.562″	10 lbs.	2
72614	1.375"	.013″	.187″	0.78 lbs.	6	72650	3″	.08″	.625"	27 lbs.	2
72615	1.375″	.028″	.187″	6.3 lbs.	6	72651	3″	.105″	.875″	43 lbs.	2
72616	1.375″	.016″	.187″	1.3 lbs.	6	72658	3″	.12"	1.125"	34 lbs.	2
72617	1.375″	.02″	.218″	2.2 lbs.	4	72659	3″	.12"	1″	54 lbs.	2
72618	1.375"	.023"	.218″	3.3 lbs.	4	72653	3.25"	.148″	1.5″	67 lbs.	1
72619	1.375"	.02"	.25″	1.9 lbs.	4	72648	3.5"	.041"	.718″	3.8 lbs.	2
72620	1.375″	.028″	.281″	4.1 lbs.	4	72657	3.5"	.12"	1″	54 lbs.	2
72625	1.375″	.028"	.218″	5.5 lbs.	4	72662	3.5"	.08″	.75″	23 lbs.	2
72637	1.375″	.072″	.562″	22 lbs.	2	72655	4"	.12"	1.125"	48 lbs.	2
72627	1.5"	.047"	.343″	11 lbs.	4	72656	4"	.148″	.937"	103 lbs.	2
72628	1.5"	.026"	.375″	2.2 lbs.	4	72661	4"	.08″	.875″	20 lbs.	2

WORKSHOP TOOLS 129

WIRE COMPRESSION SPRINGS (CONTINUED)

CAT#	LENGTH	WIRE DIAMETER	OUTER DIAMETER	MAX LOAD (LBS.)	NUMBER IN PACKAGE	
72652	4.375"	.148″	1.375″	72 lbs.	1	
72663	5″	.091″	.625″	38 lbs.	2	
72664	6"	.091″	.75″	32 lbs.	2	
72665	6"	.072″	.687"	18 lbs.	2	

CAT#	LENGTH	WIRE DIAMETER	OUTER DIAMETER	MAX LOAD (LBS.)	NUMBER IN PACKAGE
72666	6″	.091″	.875″	28 lbs.	1
72667	6"	.12″	1.375"	40 lbs.	1
72669	7"	.162″	1.125"	111 lbs.	1
72668	9″	.08″	.625″	27 lbs.	1



CAT# 72599

100-PIECE MIXED WIRE COMPRESSION & EXTENSION SPRING ASSORTMENT

100-piece springs, extension and compression, mixed assortment.
Approximately 100 mixed zinc plated wire extension and compression springs.





CAT# INDEX

1720 76	38110 95	49305 64	49422 104	49483 106	49600 102
1721 76	38111 95	49314 65	49423 104	49484 106	49611 102
1723 77	38116 95	49315 65	49424 104	49485 106	49612 102
1724 77	38120 98	49316 65	49425 104	49486 106	49613 102
1725 76	38125 98	49320 103	49426 104	49487 106	49614 102
1726 77	38140 98	49321 103	49427 104	49488 106	49620 107
1901 124	38141 98	49322 103	49428 104	49489 106	49625 107
1955 64	49198 64	49323 103	49429 104	49490 106	49630 107
1988 24	49199 64	49324 103	49430 104	49491 106	49632 107
1989 24	49200 100	49326 103	49431 104	49492 106	49634 107
1990 24	49201 100	49327 103	49432 104	49493 106	49640 105
1992 24	49204 100	49330 103	49433 104	49494 106	49641 105
1993 25	49205 100	49331 103	49434 104	49495 106	49642 105
1994 25	49210 100	49350 103	49435 104	49496 106	49645 105
1997 25	49211 100	49351 103	49436 104	49497 106	49646 105
1998 25	49212 100	49352 103	49437 104	49498 106	49647 105
1999 26	49213 100	49353 103	49438 104	49499 106	49650 105
21285 120	49220 100	49354 103	49439 104	49500 106	49651 105
21286 120	49221 100	49355 103	49440 104	49501 106	49652 105
21287 120	49222 100	49356 103	49441 104	49520 105	49660 109
21288 120	49223 100	49357 103	49442 104	49521 105	49662 109
21289 120	49224 100	49358 103	49445 104	49522 105	49663 109
21292 120	49225 100	49359 103	49446 104	49523 105	49665 109
21294 120	49234 101	49360 103	49447 104	49524 105	49666 109
21300 120	49235 101	49361 103	49449 104	49525 105	49668 109
21302 120	49236 101	49380 108	49450 104	49526 105	49669 109
21305 123	49237 101	49381 108	49451 104	49527 105	49671 109
21313 123	49238 101	49382 108	49452 104	49528 105	49672 109
37025 98	49239 101	49383 108	49453 104	49529 105	49674 109
37250 98	49240 101	49391 108	49454 104	49530 105	49675 109
38050 94	49241 101	49392 108	49455 104	49531 105	49676 109
38051 94	49250 101	49400 108	49456 104	49540 107	49677 109
38052 94	49251 101	49402 108	49470 106	49541 107	49678 109
38060 94	49252 101	49410 104	49471 106	49542 107	49685 109
38061 94	49253 101	49411 104	49472 106	49543 107	49686 109
38062 94	49260 101	49412 104	49473 106	49544 107	49687 109
38070 93	49261 101	49413 104	49474 106	49546 109	49688 109
38072 93	49262 101	49414 104	49475 106	49547 109	49689 109
38073 93	49263 101	49415 104	49476 106	49548 109	49690 109
38101 95	49264 101	49416 104	49477 106	49549 109	49691 109
38102 95	49265 101	49417 104	49478 106	49550 109	49692 109
38103 95	49270 102	49418 104	49479 106	49570 102	49695 109
38106 95	49274 102	49419 104	49480 106	49575 102	49696 109
38108 95	49276 102	49420 104	49481 106	49584 102	49697 109
38109 95	49303 64	49421 104	49482 106	49585 102	49698 109

49699 109	54771 54	57658 60	60314 112	61036 35	61131 39
49700 109	54772 54	57659 60	60315 112	61037 35	61132 39
49701 109	54773 55	57660 60	60340 66	61038 35	61140 39
49702 109	54774 55	57661 60	60343 59	61039 35	61141 39
49711 108	54775 55	57662 60	60344 59	61040 35,37	61142 39
49712 108	54781 55	57663 61	60345 59	61041 35	61143 39
49713 108	54782 55	57664 61	60346 59	61042 35	61150 39
49714 108	54785 55	57665 61	60347 59	61043 35	61151 39
49715 108	54786 55	57666 61	60348 54	61044 35	61152 39
49716 108	54787 55	57667 61	60792 66	61046 35	61153 39
49717 108	54788 55	57668 61	60793 66	61047 35-36	61160 40
49725 65	54800	59020 90	60794 66	61050 36	61161 40
49728 110	54801 65	59021 90	60795 66	61051 36	61162 40
49729 110	54810 56	60089 65	60796 67	61052 36	61163 40
49730 110	54811 56	60090 60	60797 67	61053 36	61164 40
49731 110	54812 56	60091 60	60798 67	61054 36	61165 40
49732 110	54813 56	60092 60	60799 67	61060 36	61170 40
52711 65	54814 56	60093 60	60880 67	61061 36	61171 40
52720 50	54815 56	60094 60	60883 68	61062 36	61172 40
52721 50	54816 57	60095 60	60991 68	61063 36	61173 40
52722 50	54817 57	60096 60	60992 68	61064 36	61174 40
52723 50	54818 57	60097 60	60993 68	61070 36	61175 40
52725 51	54819 57	60098 60	60994 68	61071 36	61264 41
52726 51	54820 57	60099 60	60995 68	61072 36	61287 40
52730 51	54821 57	60100 60	61001 68	61073 36	61288 40
52731 51	54822 58	60101 60	61002 68	61074 36	61289 40
52732 52	54823 <mark>58</mark>	60102 60	61003 68	61080 37	61290 40
52841 53	54824 58	60103 60	61004 68	61081 37	61293 41
52865 53	54825 56	60104 60	61010 34	61082 37	61302 41
52866 53	54826 56	60105 60	61011 34	61083 37	61303 41
52867 53	54827 56	60106 60	61012 34	61084 37	61304 41
52868 53	57300 59	60107 60	61013 34	61085 37	61305 41
52870 53	57301 59	60108 61	61014 34	61086 37	61306 41
52871 53	57637 59	60109 61	61015 34	61087 37	61321 42
52872 53	57640 65	60110 61	61016 34	61090 38	61322 42
52873 53	57643 65	60111 61	61019 34	61091 38	61323 42
52875 53	57645 60	60112 61	61020 34	61092 38	61324 42
52876 53	57646 60	60113 61	61021 34	61093 38	61326 42
52877 53	57647 60	60156 55	61022 34	61095 38	61330 43
52878 53	57648 60	60157 55	61023 34	61110 38	61332 43
52880 53	57649 60	60300 98	61024 34	61111 38	61334 43
52881 53	57650 60	60301 98	61025 34	61112 38	61340 43
52882 53		60303 98	61029 34	61113 38	61345 43
54705 54	57652 60	60305 125	61030 34	61120 38	61352 43
54717 54	57653 60	60306 125	61031 34	61121 38	61353 43
54722 54	57654 60	60309 66	61032 34	61122 38	61357 43
54727 54	57655 60	60310 112	61033 34	61123 38	61360 42
54732 54	57656 60	60312 112	61034 34	61125 38	61363 42
54770 54	57657 60	60313 112	61035 34	61130 39	61369 42

132

61373 42	61454 95	61522 98	62034 29	62097 30	70399 44
61378 42	61455 93	61523 98	62035 29	62098 30	70400 44
61381 42	61456 93	61528 91	62036 29	62099 30	70401 44
61383 42	61458 93	61529 90	62037 29	62102 31	70402 44
61385 42	61459 93	61530 91	62038 29	62103 31	70403 44
61386 42	61460 98	61532 94	62039 29	62104 31	70404 44
61388 42	61461 98	61533 94	62040 29	62105 31	70407 46
61389 42	61463 98	61534 93	62041 29	62106 31	70408 45
61390 69	61464 98	61535 93	62042 29	62107 31	70409 45
61391 69	61466 98	61536 95	62043 29	62108 31	70410 44
61392 69	61467 98	61537 95	62044 29	62109 31	70411 44
61393 69	61468 98	61538 95	62045 29	62110 31	70412 44
61394 69	61469 98	61539 91	62046 29	62111 31	70413 44
61395 69	61470 98	61542 91	62047 29	62112 31	70420 45
61396 69	61471 93	61543 98	62048 29	62113 31	70421 45
61397 69	61472 93	61544 98	62049 29	62114 31	70425 45
61398 7 0	61473 93	62001 28	62050 29	62115 31	70426 45
61400 95	61474 93	62002 28	62051 29	62116 32	70445 47
61401 95	61475 93	62003 28	62052 29	62117 32	70446 47
61402 95	61476 93	62004 28	62053 29	62118 32	70447 47
61403 95	61477 93	62005 28	62054 29	62119 32	70448 47
61404 95	61478 93	62006 28	62055 28	62120 32	70450 47
61405 95	61479 93	62007 28	62056 28	62121 32	70451 47
61406 95	61480 93	62008 28	62057 28	62122 32	70452 47
61407 95	61481 95	62009 28	62058 28	70221 123	70453 47
61409 95	61482 95	62010 28	62059 28	70305 122	70460 47
61412 94	61483 95	62011 28	62060 28	70306 122	70465 47
61419 93	61484 95	62012 28	62061 28	70307 122	70467 47
61420 93	61485 95	62013 29	62062 28	70310 7 0	70691 119
61421 93	61486 95	62014 29	62063 28	70320 122	70692 119
61422 93	61489 96	62015 29	62064 28	70321 122	70693 119
61423 93	61490 9 6	62016 29	62065 28	70322 122	70694 119
61425 93	61491 94	62017 29	62066 30	70323 122	70695 119
61426 93	61499 90	62018 29	62067 30	70324 122	70710 124
61427 93	61503 90	62019 29	62068 30	70325 122	70714 125
61428 93	61508 98	62020 29	62069 30	70326 122	70715 123
61429 93	61509 98	62021 29	62070 30	70327 122	70716 123
61430 93	61510 98	62022 29	62071 30	70328 122	70717 123
61435 94	61511 98	62023 29	62077 30	70330 121	70718 125
61437 94	61512 90	62024 29	62078 30	70331 121	70720 120
61438 96	61513 98	62025 29	62079 30	70332 121	70727 70
61440 96	61514 98	62026 29	62080 30	70334 121	70730 114
61441 96	61515 98	62027 29	62081 30	70335 121	70731 114
61444 93	61516 98	62028 29	62082 30	70340 121	70733 115
61445 93	61517 98	62029 29	62085 30	70341 121	70734 115
61447 93	61518 98	62030 29	62086 30	70342 121	70735 115
61449 93	61519 98	62031 29	62089 30	70343 121	70736 115
61450 95	61520 98	62032 29	62090 30	70397 44	70738 115
61452 95	61521 98	62033 29	62096 30	70398 44	70739 115

70740 115	70834 112	70948 117	72542 128	72591 128	72641 129
70741 115	70835 112	70951 119	72543 128	72592 128	72642 129
70742 115	70838 71	70952 11 7	72544 128	72593 128	72643 129
70743 115	70840 114	70955 116	72545 128	72594 128	72644 129
70752 114	70841 114	70956 116	72546 128	72595 128	72645 129
70753 114	70842 114	70960 118	72547 128	72596 128	72646 129
70754 114	70845 116	70962 118	72548 128	72597 128	72647 129
70755 114	70846 116	72005 127	72549 128	72599 130	72648 129
70756 114	70847 116	72006 127	72550 128	72600 129	72649 129
70757 114	70853 112	72007 127	72551 128	72601 129	72650 129
70758 114	70854 112	72497 71	72552 128	72602 129	72651 129
70762 115	70855 112	72498 71	72553 128	72603 129	72652 130
70763 115	70856 112	72499 7 0	72554 128	72604 129	72653 129
70767 119	70857 112	72506 127	72555 128	72605 129	72654 129
70770 117	70858 112	72507 127	72556 128	72606 129	72655 129
70771 117	70859 7 0	72508 127	72557 128	72607 129	72656 129
70773 117	70860 115	72509 127	72558 128	72608 129	72657 129
70776 117	70861 115	72510 127	72559 128	72609 129	72658 129
70794 126	70862 115	72511 127	72560 128	72610 129	72659 129
70795 125	70863 115	72512 127	72561 128	72611 129	72660 129
70796 125	70864 115	72513 127	72562 128	72612 129	72661 129
70797 125	70865 115	72514 127	72563 128	72613 129	72662 129
70801 125	70875 116	72515 127	72564 128	72614 129	72663 130
70802 126	70876 116	72516 127	72565 128	72615 129	72664 130
70803 125	70877 116	72517 127	72566 128	72616 129	72665 130
70804 125	70878 116	72518 127	72567 128	72617 129	72666 130
70805 125	70886 116	72519 128	72568 128	72618 129	72667 130
70806 126	70887 116	72520 128	72569 128	72619 129	72668 130
70807 126	70890 118	72521 128	72570 128	72620 129	72669 130
70811 125	70891 118	72522 128	72571 128	72621 129	72999 71
70812 125	70893 117	72523 128	72572 128	72622 129	73000 127
70816 7 0	70894 117	72524 128	72573 128	72623 129	75100 71
70817 7 0	70895 117	72525 128	72574 128	72624 129	75101 71
70818 112	70896 117			72625 129	75102 72
70819 112	70897 117	72527 128	72576 128	72626 129	75103 72
70820 112	70898 117	72528 128		72627 129	75104 72
70821 112		72529 128		72628 129	75106 80
70822 112		72530 128	72579 128	72629 129	75107 80
70823 112				72630 129	75108 80
70824 112		72532 128		72631 129	75109 80
70825 112				72632 129	
70826 112				72633 129	75115 80
70827 7 0			72584 128		75116 80
70828 112				72635 129	75117 80
70829 112		72537 128		72636 129	
70830 112		72538 128		72637 129	75123 81
70831 112				72638 129	75126 81
70832 112		72540 127		72639 129	75127 81
70833 112	70947 117	72541 128	72590 128	72640 129	75128 81

75129 81	75230 6	75336 10	75437 19	75533 1 5
75134 81	75234 7	75337 10	75438 19	75534 16
75135 81	75236 7	75340 12	75442 19	75535 1 6
75136 81	75238 7	75344 13	75443 19	75536 1 6
75137 81	75240 7	75345 13	75444 19	75537 17
75140 82	75242 7	75346 13	75445 19	75540 22
75141 82	75244 7	75347 13	75447 15	75541 22
75142 82	75246 7	75348 13	75448 15	75542 17
75143 85	75247 7	75349 12	75450 19	75543 17
75144 85	75248 7	75350 12	75471 7	75545 22
75145 85	75250 8	75352 10	75472 7	75546 22
75146 85	75252 8	75353 10	75473 8	75547 22
75147 85	75254 8	75354 10	75474 7	75549 17
75148 85	75260 8	75355 11	75475 6	75550 17
75149 85	75280 72	75356 11	75476 6	75551 21
75150 85	75281 72	75357 15	75479 7	75552 21
75153 85	75282 72	75358 15	75480 7	75553 18
75154 85	75283 <mark>72</mark>	75359 1 5	75482 8	75554 18
75155 85	75284 72	75360 1 5	75483 7	75555 18
75156 85	75285 72	75361 1 5	75484 6	75556 18
75157 85	75286 73	75362 1 5	75485 6	75558 16
75160 82	75287 73	75363 1 6	75487 12	75559 16
75161 82	75288 73	75364 16	75488 12	75560 17
75166 82	75292 73	75365 1 6	75489 12	75561 22
75167 86	75293 73	75366 16	75491 13	75562 22
75168 86	75294 74	75367 18	75492 13	75565 18
75169 86	75295 73	75368 18	75493 13	75570 18
75172 86	75303 8	75370 14	75494 11	75574 22
75173 86	75304 9	75380 14	75495 11	75575 23
75176 82	75305 7	75381 14	75496 13	75576 23
75180 86	75306 6	75385 8	75498 21	75577 23
75183 87	75307 7	75398 6	75499 21	75578 23
75185 87	75309 6	75399 6	75500 22	75579 23
75186 87	75315 6	75401 6	75501 19	75580 23
75190 87	75316 7	75406 20	75502 19	75581 23
75191 87	75317 7	75407 20	75503 19	75582 23
75192 87	75318 8	75408 20	75509 14	75583 26
75193 87	75319 9	75409 20	75519 6	75590 6
75194 87	75320 6	75410 20	75520 7	75592 6
75195 87	75321 7	75411 20	75521 7	75600 7
75196 87	75322 6	75414 20	75522 8	75602 7
75210 72	75323 7	75415 20	75524 9	86231 77
75215 6	75324 7	75417 20	75525 9	88061 76,100
75217 6	75325 7	75418 20	75526 8	88062 7 6
75220 6	75326 6	75425 20	75527 8	88063 76
75222 6	75330 10	75430 20	75528 13	88064 76
75224 6	75331 10	75431 20	75529 11	88066 76
75226 6	75332 10	75435 19	75530 15	88067 7 6
75228 6	75334 10	75436 19	75532 15	

Our Mission:

To be a value added, service oriented, primary distributor providing tailored solutions.

FORNEY INDUSTRIES

All you gotta do is Direct to You All you gotta do is Solve to You All you Solve to You Solve to You All you Solve to You Solve to You All you Solve to You Sol







TURNKEY

Single-Source, Fit to Your Needs





We are committed to your success regardless of location, size or needs. We understand it is your goal to get the job done right and we are ready to help you do just that.

NOTES

VISIT FORNEYIND.COM FOR OUR FULL PRODUCT OFFERING!







FORNEY INDUSTRIES 2057 VERMONT DR. FORT COLLINS, CO 80525

1.800.521.6038
sales@forneyind.com
www.forneyind.com • www.askforney.com









