

Plastic Bottle, 12 fl. oz. 078698132419

Plastic Bottle, 32 fl. oz. 078698132440

Metal Drum, 54 gal. 078698132495

## DIESEL-TONE® DIESEL FUEL CONDITIONER

M2412, M2432, M2449

Diesel-Tone Diesel Fuel Conditioner is a new and improved diesel fuel conditioner formula for automotive and all diesel engine fuel systems. Designed to keep injectors clean, prevent rust and corrosion, restore proper combustion and dissolve gum and varnish. This diesel fuel additive complies with the federal low sulfur content requirements for use in diesel motor vehicles and non-road engines.

## **APPLICATIONS:**

- Dissolves Gum & Varnish
- Keeps Injectors Clean
- Restores Proper Combustion

**DIRECTIONS:** Pour contents into fuel tank when refueling. 12 ounces treats up to 20 gallons.

**STORAGE, HANDLING & DISPOSAL:** Use and dispose of product and residue in accordance with all local, state and federal laws and regulations.

**DANGER:** See MSDS for complete list of ingredients. Combustible. Use in well ventilated area away from sparks and flames. Eye and skin irritant. Avoid eye and skin contact and breathing of vapors. Harmful or fatal if swallowed. Vapor harmful.

**FIRST AID:** Eyes: Flush thoroughly with water for 15 minutes while lifting eyelids occasionally and get prompt medical attention. Skin: Wash with soap and water. If irritation persists, get prompt medical attention. Inhalation: Move to fresh air. If breathing becomes difficult, get prompt medical attention. Ingestion: If swallowed, DO NOT INDUCE VOMITING. Call Poison Control Center, Physician, or Hospital Emergency Room immediately.

## **KEEP AWAY FROM CHILDREN AND ANIMALS**

WARNING: This product contains a chemical known to the State of California to cause cancer or birth defects or other reproductive harm.

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.

