

# MATERIAL SAFETY DATA SHEET

NPCA

FOR COATINGS, RESINS AND RELATED MATERIALS  
(Approved by US Department of Labor Essentially Similar to Form OSHA 20)

Date Issued 03/30/06

## SECTION I

### MANUFACTURER'S NAME

GARDNER-GIBSON CORPORATION

### STREET ADDRESS

4161 E 7<sup>TH</sup> AVENUE

### EMERGENCY TELEPHONE NUMBER

1-800-424-9300

### PRODUCT CLASS

ROOF CEMENT MASTIC A/F/AKA PLASTIC RF  
CEMENT

### CITY, STATE, AND ZIP CODE

TAMPA, FL 33605

### MANUFACTURER'S CODE

### IDENTIFICATION

6220, 6230, 6233, 6234, 6235, 6212, 6222, 6223,  
6224, 6242, 6264, 6237

### TRADE NAME

BLACKJACK, ROOFTTTE

## SECTION II- HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	TLV PPM	TLV Mg/M3	LEL	VAPOR PRESSURE
PETROLEUM ASPHALT CAS # - 8052-42-4	<50%		0.5 Fume		
STODDARD SOLVENT CAS #- 8052-41-3	<25%	100			
CELLULOSE FIBER CAS #- 9004-34-6	<5%		10*		
INORGANIC FILLER CAS #- 1317-65-3	<30%		10*		
CAS #-					

ADDITIONAL INFORMATION- \* AS RESPIRABLE FRACTION OF DUST

### Hazardous Materials Identification System (HMIS)

Health  
1Flammability  
2Reactivity  
1Personal Protection  
C

## SECTION III – PHYSICAL DATA

BOILING RANGE: 300 °F - 390°F VAPOR DENSITY  HEAVIER  LIGHTER, THAN AIREVAPORATION RATE  FASTER  SLOWER, THAN  
ETHER PERCENT VOTILE BY VOLUME 22 % WEIGHT PER GALLON  
BY VOLUME 8.3 LBS

## SECTION IV – FIRE AND EXPLOSION HAZARD DATA

DOT CATEGORY - NA

FLASH POINT- 105°F Minimum

EXTINGUISHING MEDIA- CO2, FOAM, &amp; DRY CHEMICAL . DO NOT USE HALOGENATED EXTINGUISHING AGENTS.

UNUSUAL FIRE AND EXPLOSION HAZARDS- CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.  
PRODUCTS OF COMBUSTION MAY BE TOXIC.SPECIAL FIRE FIGHTING PROCEDURES- WEAR MSHA/NIOSH APPROVED POSITIVE BREATHING APPARATUS IS RECOMMENDED  
FOR FIREFIGHTERS. WATER MAY BE USED TO COOL CLOSED CONTAINERS, BUT MAY CAUSE FROTHING, APPLY CAUTIOUSLY.  
HIGH PRESSURE STREAM WILL SPREAD FIRE. DO NOT USE HALOGENATED EXTINGUISHING AGENTS!.

---

## SECTION V – REACTIVITY DATA

---

STABILITY:  UNSTABLE

STABLE

CONDITIONS TO AVOID: SPARK, FLAMES,  
ELECTRICAL AND STATIC DISCHARGE.

INCOMPATIBILITY (MATERIALS TO AVOID): STRONG OXIDIZERS, ACIDS, AND HALOGENATED CHEMICALS

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON DIOXIDE, CARBON MONOXIDE, NOX, SOX, H<sub>2</sub>S AND REACTIVE HYDROCARBONS

HAZARDOUS POLYMERIZATION:  MAY OCCUR

WILL NOT OCCUR

CONDITIONS TO AVOID: NONE

---

## SECTION VI-HEALTH HAZARD DATA

---

EFFECTS OF OVEREXPOSURE- ACUTE: SKIN: PROLONGED REPEATED CONTACT MAY CAUSE IRRITATION. EYES: CONTACT MAY CAUSE IRRITATION, BLURRED VISION, REDNESS. INHALATION: EXCESSIVE BREATHING OF HIGH VAPOR CONCENTRATION CAN CAUSE POSSIBLE UNCONSCIOUSNESS AND EVEN ASPHYXIATION. INGESTION: CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA. CARCINOGENICITY: MATERIAL CONTAINS PETROLEUM ASPHALT. IARC HAS DETERMINED THAT THERE IS AN ADEQUATE EVIDENCE THAT ASPHALT ALONE IS CARCINOGENIC TO HUMANS, IN SOLUTION, SOLVENT EXTRACTS CAN PRODUCE SKIN CANCER IN ANIMALS FOLLOWING PROLONGED AND REPEATED CONTACT. IARC HAS CONCLUDED THAT THERE IS SUFFICIENT EVIDENCE OF THE CARCINOGENICITY OF ASPHALT EXTRACTS. THEREFORE, CUTBACKS LIKE THIS PRODUCT MAY ALSO BE IMPLICATED AS POTENTIALLY CARCINOGENIC. PLEASE FOLLOW MSDS PRECAUTIONARY MEASURES. SYNERGISTIC MATERIALS: N/A. REPRODUCTIVE EFFECTS: ND. TERATOGENIC: NO. MUTAGENIC: NO.

**CALIF. PROP. 65 • CHEMICAL WARNING** (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ).

**WARNING:** This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. Read and follow label directions and information given on Material Safety Data Sheets and use care when handling or using all petroleum products.

EMERGENCY FIRST AID PROCEDURE- SKIN: WASH EXPOSED AREAS WITH SOAP AND WATER. EYES: FLUSH EYES WITH COPIOUS AMOUNTS OF WATER, IF SYMPTOMS PERSIST, CONSULT A PHYSICIAN. INHALATION: REMOVE PERSON TO FRESH AIR. IF BREATHING IS DIFFICULT ADMINISTER OXIGEN. IF BREATHING STOPS, GIVE ARTIFICIAL RESPIRATION. SEEK MEDICAL ATTENTION IMMEDIATELY. INGESTION: DO NOT INDUCE VOMITING.

---

## SECTION VII – SPILL OR LEAK PROCEDURES

---

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: SOAK UP SPILL WITH SAND OR OTHER ABSORBENT. REMOVE SOURCES OF IGNITION. PLACE IN CONTAINERS. WASH AREA.

WASTE DISPOSAL METHOD: DISPOSE IN ACCORDANCE WITH LOCAL, STATE OR FEDERAL REGULATIONS.

---

## SECTION VIII – SPECIAL PROTECTION INFORMATION

---

RESPIRATORY PROTECTION: NOT NORMALLY REQUIRED IN WELL VENTILATED AREA. IF TLV IS EXCEEDED, A NIOSH/MSHA APPROVED BREATHING APPARATUS IS RECOMMENDED.

VENTILATION: USE WITH ADEQUATE VENTILATION. MAINTAIN EXPOSURE BELOW TLV LEVEL.

PROTECTIVE GLOVES: RUBBER GLOVES SHOULD BE USED, AS WELL AS LONG SLEEVES.

EYE PROTECTION: FACE SHIELD AND SAFETY GOGGLES SHOULD BE USED.

OTHER PROTECTIVE EQUIPMENT: SOLVENT RESISTANT APRON AND BOOTS

---

## SECTION IX – REGULATORY INFORMATION

---

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: STORE IN COOL DRY AREA.

OTHER PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN AND AWAY FROM SOURCES OF IGNITION. AVOID CONTACT WITH SKIN OR CLOTHING. KEEP CONTAINER CLOSED. WASH THOROUGHLY AFTER USING.