SAFETY DATA SHEET

GC26104

Section 1. Identification Product name : Geocel® Pro Flex® Tripolymer Sealant Brown : GC26104 **Product code** Other means of : Not available. identification **Product type** : Liquid. Relevant identified uses of the substance or mixture and uses advised against Not applicable. Manufacturer : Geocel Products Group A Business Unit of the Sherwin-Williams Company 101 W. Prospect Avenue Cleveland, Ohio 44115 : Sherwin-Williams Canada Inc. National contact 180 Brunel Road Mississauga, Ontario L4Z 1T5 Canada **Emergency telephone** : US / Canada: (216) 566-2917 Mexico: SETIQ 01-800-00-214-00 / (52) 55-5559-1588 24 hours / 365 days a year number of the company **Product Information** : US / Canada: (800) 348-7615 **Telephone Number** Mexico: Not Available **Regulatory Information** : US / Canada: (216) 566-2902 **Telephone Number** Mexico: Not Available **Transportation Emergency** : US / Canada: (216) 566-2917 **Telephone Number** Mexico: SETIQ 01-800-00-214-00 / (52) 55-5559-1588 24 hours / 365 days a year

Section 2. Hazards identification

: SKIN CORROSION/IRRITATION - Category 2
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2B
CARCINOGENICITY - Category 1B
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract
irritation) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) -
Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
Percentage of the mixture consisting of ingredient(s) of unknown oral toxicity: 17.2% Percentage of the mixture consisting of ingredient(s) of unknown dermal toxicity: 64.8% Percentage of the mixture consisting of ingredient(s) of unknown inhalation toxicity: 64. 8%

Signal word

: Danger

Date of issue/Date	of revision	: 2/15/2018	Date of previous issue	: 2/13/2018	Version	:4.03
GC26104	Geocel® Pro Flex® T Brown	ripolymer Sealan	t		SHW-85-	NA-GHS

Section 2. Hazards identification

Hazard statements	 Causes skin and eye irritation. May cause cancer. May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.
Precautionary statements	
General	: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Wash hands thoroughly after handling.
Response	: Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

CAS number/other identifiers

Ingredient name	% by weight	CAS number
Tetrachloroethylene	47.59	127-18-4
Isobutylene Polymer	7.8	9003-27-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

: 2/13/2018

Section 4. First aid measures

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health e	fects
Eye contact	: Causes eye irritation.
Inhalation	 Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
Skin contact	: Causes skin irritation.
Ingestion	: Can cause central nervous system (CNS) depression.
Over-exposure signs/sy	<u>mptoms</u>
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
Indication of immediate r	nedical attention and special treatment needed, if necessary
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

3/12

Section 4. First aid measures

Protection of first-aiders No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds carbonyl halides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
Methods and materials for co	nt	ainment and cleaning up
Small anill		Stop look if without rick. Move containers from shill area. Dilute with water and men up

Small	spill

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Section 6. Accidental release measures

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	 Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name	Exposure limits
Tetrachloroethylene	ACGIH TLV (United States, 3/2016). TWA: 25 ppm 8 hours. TWA: 170 mg/m ³ 8 hours. STEL: 100 ppm 15 minutes. STEL: 685 mg/m ³ 15 minutes. OSHA PEL Z2 (United States, 2/2013). TWA: 100 ppm 8 hours. CEIL: 200 ppm
Isobutylene Polymer	AMP: 300 ppm 5 minutes.

Occupational exposure limits (Canada)

Ingredien	Ingredient name			Exposure limits			
Tetrachlo	roethylene			15 min OEL: 6 15 min OEL: 10 8 hrs OEL: 25 8 hrs OEL: 170) mg/m³ 8 hours. Imbia Provincial (Canada	3	
Date of issue/	Date of revision	: 2/15/2018	Date of previous issue	: 2/13/2018	Version : 4.03	5/12	
C26104 Geocel® Pro Flex® Tripolymer Sealant Brown		SHW-85-NA-GHS-C					

Section 8. Exposure controls/personal protection

STEL: 100 ppm 15 minutes. CA Ontario Provincial (Canada, 7/2015).
TWA: 25 ppm 8 hours.
STEL: 100 ppm 15 minutes.
CA Québec Provincial (Canada, 1/2014).
TWAEV: 25 ppm 8 hours.
TWAEV: 170 mg/m ³ 8 hours.
STEV: 100 ppm 15 minutes.
STEV: 685 mg/m ³ 15 minutes.
CA Saskatchewan Provincial (Canada,
7/2013).
STEL: 100 ppm 15 minutes.
TWA: 25 ppm 8 hours.

Occupational exposure limits (Mexico)

Ingredient name	Exposure limits
Tetrachloroethylene	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 25 ppm 8 hours. STEL: 100 ppm 15 minutes.

Appropriate engineering controls	: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection meas	<u>ures</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Date of issue/Date	e of revision	: 2/15/2018	Date of previous issue	: 2/13/2018	Version	: 4.03	6/12
GC26104	Geocel® Pro Flex® Brown	® Tripolymer Sealar	nt		SHW-85-	NA-GHS-CA	

Section 9. Physical and chemical properties

Appearance		
Physical state	1	Liquid.
Color	:	Not available.
Odor	:	Not available.
Odor threshold	1	Not available.
рН	:	Not available.
Melting point	:	Not available.
Boiling point	:	121°C (249.8°F)
Flash point	1	Closed cup: >93.3°C (>199.9°F)
Evaporation rate	1	2.59 (butyl acetate = 1)
Flammability (solid, gas)	1	Not available.
Lower and upper explosive (flammable) limits	:	Not available.
Vapor pressure	:	2.4 kPa (18 mm Hg) [at 20°C]
Vapor density	1	5.83 [Air = 1]
Relative density	1	1.2
Solubility	1	Not available.
Partition coefficient: n- octanol/water	:	Not available.
Auto-ignition temperature	:	Not available.
Decomposition temperature	1	Not available.
Viscosity	:	Kinematic (40°C (104°F)): <0.205 cm²/s (<20.5 cSt)
Molecular weight	:	Not applicable.
Aerosol product		
Heat of combustion	1	2.689 kJ/g

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity								
Product/ingredient name	Result	Species	Dose	Exposure				
Tetrachloroethylene	LD50 Oral	Rat	2629 mg/kg	-				

Irritation/Corrosion

Date of issue/Date	of revision	: 2/15/2018	Date of previous issue	: 2/13/2018	Version : 4	.03 7/12
GC26104	Geocel® Pro Flex® Ti Brown	ripolymer Sealar	ıt		SHW-85-NA-	GHS-CA

Section 11. Toxicological information

	Product/ingredient name	Result	Species	Score	Exposure	Observation	
	Tetrachloroethylene	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-	
		Eyes - Mild irritant	Rabbit	-	162 milligrams	-	
		Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-	
		Skin - Severe irritant	Rabbit	-	24 hours 810 milligrams	-	

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Tetrachloroethylene	-	2A	Reasonably anticipated to be a human carcinogen.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	• •	Route of exposure	Target organs
Tetrachloroethylene	Category 3		Respiratory tract irritation and Narcotic effects

Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
Tetrachloroethylene	Category 2	Not determined	Not determined

Aspiration hazard

Not available.

Information on the likely
routes of exposure: Not available.Potential acute health effectsEye contact: Causes eye irritation.Inhalation: Can cause central nervous system (CNS) depression. May cause drowsiness or
dizziness. May cause respiratory irritation.Skin contact: Causes skin irritation.

Ingestion : Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

Date of issue/Da	ate of revision	: 2/15/2018	Date of previous issue	: 2/13/2018	Version : 4.03	8/12
GC26104	Geocel® Pro Fle Brown	x® Tripolymer Seala	nt		SHW-85-NA-GHS-C	Α

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
Delayed and immediate effe	ects and also chronic effects from short and long term exposure

Short term exposure		
Potential immediate effects	: N	Not available.
Potential delayed effects	: N	Not available.
Long term exposure		
Potential immediate effects	: N	Not available.
Potential delayed effects	: N	Not available.
Potential chronic health ef	fects	<u>5</u>
Not available.		
General	: N	May cause damage to organs through prolonged or repeated exposure.
Carcinogenicity	: N	May cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: N	No known significant effects or critical hazards.
Teratogenicity	: N	No known significant effects or critical hazards.
Developmental effects	: N	No known significant effects or critical hazards.
Fertility effects	: N	No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates			
Route	ATE value		
Oral	4575.1 mg/kg		

Section 12. Ecological information

Product/ingredient name	Result	Species	Exposure
Tetrachloroethylene	Acute EC50 504 ppm Marine water Acute EC50 3.64 mg/l Fresh water Acute EC50 3.64 mg/l Fresh water Algae - Chlamydomonas reinhardtii - Exponential growth phase		96 hours 72 hours
	Acute EC50 7500 μg/l Fresh water Acute LC50 3.5 mg/l Marine water Acute LC50 4000 μg/l Fresh water	Daphnia - Daphnia magna - Instar Crustaceans - Elminius modestus Fish - Jordanella floridae - Juvenile (Fledgling, Hatchling, Weanling)	
	Chronic EC10 1.77 mg/l Fresh water	Algae - Chlamydomonas	72 hours
Date of issue/Date of revision	: 2/15/2018 Date of previous issue	: 2/13/2018 Version : 4.	03 9/12
GC26104 Geocel® Pro Fle Brown	ex® Tripolymer Sealant	SHW-85-NA-	GHS-CA

Section 12. Ecological information				
	Chronic NOEC 0.4 mg/l Fresh water	reinhardtii - Exponential growth phase Daphnia - Daphnia magna	21 days	
	Chronic NOEC 500 µg/l Fresh water	Fish - Pimephales promelas - Larvae	32 days	
Isobutylene Polymer	Acute LC50 >5600000 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours	

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Tetrachloroethylene		49	low
Isobutylene Polymer		314 to 1882	high

Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	UN1897	UN1897	UN1897	UN1897	UN1897
UN proper shipping name	Tetrachloroethylene mixture	Tetrachloroethylene mixture	Tetrachloroethylene mixture	Tetrachloroethylene mixture	Tetrachloroethylene mixture. Marine pollutant (Tetrachloroethylene)
Transport hazard class(es)	6.1	6.1	6.1	6.1	6.1
Packing group	111	111			
Date of issue/Date of rev GC26104 Geoc Brow	el® Pro Flex® Tripolymer Se		ssue : 2/13/2018		on : 4.03 10/12 -85-NA-GHS-CA

izards	No.	No.	No.	Yes. The environmentally hazardous substance mark is not required.	Yes.
dditional formation	-	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2. 26-2.36 (Class 6).	-	The environmentally hazardous substance mark may appear if required by other transportation regulations.	The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤ kg. <u>Emergency</u> <u>schedules</u> F-A, S A
	<u>ERG No.</u>	ERG No.	ERG No.		
	160	160	160		
ecial precaution	consid mode suitab prior t respon unload	der container sizes. T of transport (sea, air ly for that mode of tra o shipment, and com nsibility of the person	he presence of , etc.), does not ansport. All pack pliance with the offering the pro s must be traine	rided for informational pure a shipping description for indicate that the product (aging must be reviewed applicable regulations in oduct for transport. Peopled on all of the risks der mergency situations.	or a particular ot is packaged d for suitability s the sole ble loading and
nsport in bulk a Annex II of MARI IBC Code		ailable.			
		shipping name	: Not availa		
	Ship ty	·	: Not availa		
Annex II of MAR	POL and Proper Ship ty	shipping name		ble.	

Section 15. Regulatory information

SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Section 16. Other information

	Classification				
SKIN CORROSION/IRRIT/ SERIOUS EYE DAMAGE/ CARCINOGENICITY - Cat SPECIFIC TARGET ORG/ irritation) - Category 3 SPECIFIC TARGET ORG/ Category 3 SPECIFIC TARGET ORG/	Calculation method Calculation method Calculation method Calculation method Calculation method Calculation method				
History					
Date of printing	: 2/15/2018				
Date of issue/Date of revision	: 2/15/2018				
Date of previous issue	: 2/13/2018				
Version	: 4.03				
Key to abbreviations : ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)					

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by Sherwin-Williams, including but not limited to the incorporation of non Sherwin-Williams products or the use or addition of products in proportions not specified by Sherwin-Williams. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

UN = United Nations