

# ***ITASCA Marine*** **2-Cycle Outboard** **TC-W3<sup>®</sup> Engine Oil**



**Warren Oil Company**

Product Data Sheet

**ITASCA MARINE 2- CYCLE OUTBOARD TC-W3 ENGINE OIL** Is formulated from premium base stocks, along with ashless additives to provide outstanding protection against piston scuffing, bearing wear, ring sticking and rust in marine applications where a certified National Marine Manufacturer's Association (NMMA) TC-W3<sup>®</sup> lubricant is required.

**ITASCA MARINE 2- CYCLE OUTBOARD TC-W3 ENGINE OIL** is also recommended for use in applications where TC-W<sup>®</sup>, TC-WII<sup>®</sup>, TC-W3<sup>®</sup> and JASO FB and API TC two-cycle air-cooled category's are required.

It exceeds the warranty requirements of Evinrude<sup>®</sup>, Mercury<sup>®</sup>, Johnson<sup>®</sup>, Yamaha<sup>®</sup>, Mariner<sup>®</sup>, Suzuki<sup>®</sup> as well as all other makes and models of High Performance Outboard Engines and all two-cycle engines where a TC-W3<sup>®</sup> product is required. It may also be used in both oil-injected engines as well as those where the oil is mixed with the fuel.

**ITASCA MARINE 2- CYCLE OUTBOARD TC-W3 ENGINE OIL** is dyed BLUE for easy identification.

## **Benefits**

- Resistant to piston scuffing and ring sticking
- Minimizes engine deposits and port plugging
- Mixes readily with gasoline
- Dyed for easy identification
- Provides rust and corrosion protection

***Warren Oil Company, Inc.***

*Dunn, NC 28334 : Benton, AL 36758: San Antonio, TX 78210:  
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72303*

# ***ITASCA Marine***

## **2-Cycle Outboard TC-W3 Engine Oil**



**Warren Oil Company**

Product Data Sheet

### Fuel Mixing Table

Ounces of Oil to Gallon of Gasoline (U.S. Measure)

Ratio Gas to Oil	1 Gal. oz.	2 Gal. oz.	3 Gal. oz.	4 Gal. oz.	5 Gal. oz.	6 Gal. oz.
16:1	8	16	24	32	40	48
20:1	6	13	19	26	32	38
25:1	5	10	15	20	26	31
50:1	3	5	8	10	13	16
100:1	1.5	2.6	4	5	6.4	8

### Typical Characteristics

**ITASCA Outboard TC-W3 Motor Oils**

**Outboard TC-W3**

Gravity, API	32.0
pounds/gal.	7.21
Viscosity (typical)	
@40 Deg. C, cSt	45.0
@100 Deg. C, cSt	7.94
Viscosity Index	149
Pour Point Deg. F	-44
Ash, wt %	None
Appearance	Blue

Case Pallet Specifications:

702196	12/1 qt.	6 rows/14 count	84/pallet
702197	6/1 gal.	4 rows/9 count	36/pallet
702198	55 gal.	4 count	4/pallet

### ***Warren Oil Company, Inc.***

*Dunn, NC 28334 : Benton, AL 36758: San Antonio, TX 78210:  
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72303*