# SAFETY DATA SHEET.

Issuing date 07-May-2015 Revision Date 07-May-2015 Version 1

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name 57400 (109) WHITE LITHIUM GREA

Recommended use of the chemical

and restrictions on use

Product code F01460

Product Type Extremely flammable aerosol

Synonyms None

Supplier's details

Recommended Use Lubricant.

Uses advised against No information available

Manufactured For:

Kellogg's Professional Products

325 Pearl Street Sandusky, OH 44870

Emergency telephone number

**Chemical Emergency Phone** 

Number

Chemtrec 1-800-424-9300

# 2. HAZARDS IDENTIFICATION

# Classification

Skin corrosion/irritation	Category 2
Carcinogenicity	Category 2
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed Gas

# GHS Label elements, including precautionary statements

#### **Emergency Overview**

#### DANGER

#### **Hazard Statements**

Causes skin irritation

Suspected of causing cancer

Suspected of damaging fertility or the unborn child

May cause respiratory irritation. May cause drowsiness or dizziness

May cause damage to organs (Central Nervous System, Skin, and Respiratory System) through prolonged or repeated exposure.

May be fatal if swallowed and enters airways

Extremely flammable aerosol

Contains gas under pressure; may explode if heated



Appearance opaque Physical state Aerosol Odor Solvent

#### **Precautionary Statements - Prevention**

Obtain special instructions before use

Wear protective gloves/protective clothing/eye protection/face protection

Do not handle until all safety precautions have been read and understood

Wash face, hands and any exposed skin thoroughly after handling

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Do not spray on an open flame or other ignition source

Pressurized container: Do not pierce or burn, even after use

# **Precautionary Statements - Response**

If exposed or concerned: Get medical advice/attention

Specific treatment (see first aid on this label)

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash before reuse

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

#### **Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

# **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

None

#### Other information

0% of the mixture consists of ingredient(s) of unknown toxicity

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS # 64742-49-0, COMMERCIAL HEXANES, MAY BE SUBSTITUTED FOR CAS #110-54-3.

Chemical Name	CAS-No	Weight %*
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	10-20
HEXANE	64742-49-0	10-20
NAPHTHENIC OIL, SEVERLY HYDROT	64742-52-5	1-10
HYDROCARBON SOLVENT	64742-96-7	1-10
ZINC OXIDE	1314-13-2	0.1-1
TITANIUM DIOXIDE	13463-67-7	0.1-1

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. FIRST AID MEASURES

# First aid measures for different exposure routes

General advice Avoid contact with eyes, skin, and clothing. Avoid breathing, vapors, mist, or gas.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Seek immediate medical attention/advice.

**Skin contact** Wash off immediately with soap and plenty of water. Remove and wash contaminated

clothing before re-use. Get medical attention immediately if symptoms occur.

**Inhalation** Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped,

contact emergency medical services immediately.

Ingestion Do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to an

unconscious person. Risk of product entering the lungs on vomiting after ingestion.

# Most important symptoms/effects, acute and delayed

Main Symptoms Causes eye and skin irritation.Inhalation causing Central Nervous System effects.Harmful if

swallowed.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

# Suitable Extinguishing Media

Water fog.Dry chemical. Carbon dioxide (CO2). Cool containers/tanks with water spray.

Unsuitable Extinguishing Media Keep away from heat and sources of ignition. Cool containers / tanks with water spray.

# Specific hazards arising from the chemical

Extremely flammable. Keep product and empty container away from heat and sources of ignition. Risk of ignition. In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray.

#### **Explosion Data**

Sensitivity to Mechanical Impact none. Sensitivity to Static Discharge

# **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# 6. ACCIDENTAL RELEASE MEASURES

# Personal precautions, protective equipment and emergency procedures

Avoid contact with eyes, skin, and clothing. Avoid breathing vapors or mists. . Use with Personal precautions

adequate ventilation. Keep container away from heat, flames, and all other sources of ignition. Provide adequate ventilation. Do not get in eyes, on skin, or on clothing. Do not

taste or swallow. Wash thoroughly after handling. Ensure adequate ventilation.

**Environmental precautions** 

Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in **Environmental precautions** 

low areas. Prevent further leakage or spillage if safe to do so. Do not allow material to

contaminate ground water system. Prevent product from entering drains.

# Methods and materials for containment and cleaning up

**Methods for Containment** Prevent further leakage or spillage if safe to do so. Absorb or cover with dry earth, sand or

other non-combustible material and transfer to containers.

Methods for cleaning up Pick up and transfer to properly labeled containers. Soak up with inert absorbent material.

Clean contaminated surface thoroughly. After cleaning, flush away traces with water. Take

precautionary measures against static discharges.

# 7. HANDLING AND STORAGE

# Precautions for safe handling

Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not Advice on safe handling

puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top

of can.

# Conditions for safe storage, including any incompatibilities

Technical measures/Storage

conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out

of the reach of children. Store locked up.

Incompatible products Strong acids, alkalis, or oxidizing agents. 1

Aerosol Level

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# Control parameters

**Exposure Guidelines** 

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	74-98-6: TWA: 1000 ppm 106-97-8: STEL: 1000 ppm 75-28-5: STEL: 1000 ppm	74-98-6:TWA: 1000 ppm TWA: 1800 mg/m³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m³ 106-97-8: (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m³	74-98-6:IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m³ 106-97-8:TWA: 800 ppm TWA: 1900 mg/m³ 75-28-5:TWA: 800 ppm TWA: 1900 mg/m³
HEXANE 64742-49-0	TWA: 50 ppm Skin - potential significant contribution to overall exposure by the cutaneous route	TWA: 500 ppm TWA: 1800 mg/m³ (vacated) TWA: 50 ppm (vacated) TWA: 180 mg/m³	IDLH: 1100 ppm TWA: 50 ppm TWA: 180 mg/m³
ZINC OXIDE 1314-13-2	STEL: 10 mg/m³ respirable fraction TWA: 2 mg/m³ respirable fraction	TWA: 5 mg/m³ fume TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable fraction (vacated) TWA: 5 mg/m³ fume (vacated) TWA: 10 mg/m³ total dust (vacated) TWA: 5 mg/m³ respirable fraction (vacated) STEL: 10 mg/m³ fume	IDLH: 500 mg/m³ Ceiling: 15 mg/m³ dust TWA: 5 mg/m³ dust and fume STEL: 10 mg/m³ fume
TITANIUM DIOXIDE 13463-67-7	TWA: 10 mg/m³	TWA: 15 mg/m³ total dust (vacated) TWA: 10 mg/m³ total dust	IDLH: 5000 mg/m <sup>3</sup>

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration) NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

**Exposure controls** 

Engineering Measures Showers

Eyewash stations Ventilation systems.

# Individual protection measures, such as personal protective equipment

**Eye/Face Protection** Safety glasses with side-shields.

**Skin and body protection** Chemical resistant apron. Protective gloves.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

**Hygiene measures** Handle in accordance with good industrial hygiene and safety practice.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

# Physical and chemical properties

Physical state Aerosol Appearance opaque

Appearance opaque Odor Solvent

Color White Odor Threshold No information available

Based on propellant

Not applicable

Property Values Remarks • Methods

**pH** 11

Melting/freezing point

No information available

Boiling point/boiling range

No information available

Flash Point -97 °C / -143 °F

**Evaporation rate**Flammability (solid, gas)
No information available
No information available

Flammability Limits in Air

upper flammability limit<br/>lower flammability limitNo information available<br/>No information availableVapor pressureNo information availableVapor densityNo information available

Specific Gravity 0.845

Water solubility Practically insoluble
Partition coefficient: n-octanol/waterNo information available
Autoignition temperature No information available

Decomposition temperatureNo information availableViscosityNo information availableExplosive propertiesNo information available

**Other information** 

VOC Content(%) 23.1

# 10. STABILITY AND REACTIVITY

Reactivity

No data available

**Chemical stability** 

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

**Conditions to Avoid** 

Extremes of temperature and direct sunlight.

**Incompatible Materials** 

Strong acids, alkalis, or oxidizing agents.

**Hazardous Decomposition Products** 

None known based on information supplied.

# 11. TOXICOLOGICAL INFORMATION

# Information on likely routes of exposure

**Product Information** 

Inhalation Vapors may irritate throat and respiratory system. May cause drownsiness and dizziness

based on components. May cause irritation of respiratory tract. Avoid breathing vapors or

mists.

**Eye contact** Irritating to eyes. Avoid contact with eyes.

Skin contact Irritating to skin. Repeated exposure may cause skin dryness or cracking. Prolonged skin

contact may defat the skin and produce dermatitis. Avoid contact with skin.

Ingestion May be harmful if swallowed. Aspiration into the lungs during swallowing may cause serious lung damage which may be fatal.

**Component Information** 

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
HEXANE 64742-49-0	> 5000 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 73680 ppm (Rat)4 h
HYDROCARBON SOLVENT 64742-96-7	> 5000 mg/kg (Rat)	> 2000 mg/kg(Rabbit)	> 5.28 mg/L (Rat)4 h
ZINC OXIDE 1314-13-2	> 5000 mg/kg (Rat)	-	-
TITANIUM DIOXIDE 13463-67-7	> 10000 mg/kg (Rat)	-	-

# Information on toxicological effects

Symptoms Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Irritating to respiratory system. Irritating to skin and eyes. May be harmful or fatal if

ingested.

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Irritating to skin.

**Irritation** Irritating to respiratory system and skin.

Sensitization None known.
Germ Cell Mutagenicity None known.

**Carcinogenicity** The table below indicates whether each agency has evaluated a listed ingredient as a

carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
TITANIUM DIOXIDE	-	2B	-	-
13463-67-7				

ACGIH: (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive toxicity

Specific target organ systemic toxicity (single exposure)
Specific target organ systemic

toxicity (repeated exposure)

Chronic toxicity

**Aspiration hazard** 

Product is or contains a chemical which is a known or suspected reproductive hazard.

May cause respiratory irritation. May cause drowsiness and dizziness.

May cause damage to organs through prolonged or repeated exposure.

Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and

potential cardiac arrest. Prolonged skin contact may defat the skin and produce dermatitis. May be fatal if swallowed and enters airways.

#### Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

 ATEmix (oral)
 36362 mg/kg

 ATEmix (dermal)
 20071 mg/kg

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to	Toxicity to daphnia and
			microorganisms	other aquatic invertebrates

# F01460 - 57400 (109) WHITE LITHIUM GREA

Revision Date 07-May-2015

PROPANE/ISOBUTANE/N-	-	-	-	-
BUTANE				
68476-86-8				
NAPHTHENIC OIL,	-	5000 mg/L LC50	-	1000 mg/L EC50 Daphnia
SEVERLY HYDROT		Oncorhynchus mykiss 96h		magna 48h
64742-52-5				_

# Persistence and degradability

No information available.

#### **Bioaccumulation**

No information available.

Chemical Name	log Pow
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	2.8

Other adverse effects No information available

# 13. DISPOSAL CONSIDERATIONS

**Waste treatment** 

Waste Disposal Methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

Contaminated packaging Do not re-use empty containers.

# 14. TRANSPORT INFORMATION

**DOT Ground** CONSUMER COMMODITY ORM-D

or

LIMITED QUANTITY

IATA UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

IMDG UN1950, AEROSOLS, 2.1, LTD. QTY.

# 15. REGULATORY INFORMATION

# International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
PROPANE/ISOBUTA NE/N-BUTANE	Х	Х	X	Not listed	Х	Х	Х	Х
HEXANE	Χ	X	Х	Х	X	Χ	Х	Χ
NAPHTHENIC OIL, SEVERLY HYDROT	Х	Х	X	Х	Х	Х	Х	Х
HYDROCARBON SOLVENT	Х	Х	X	Not listed	Х	X	Х	X
ZINC OXIDE	Х	Х	Х	Х	Х	Χ	Х	Х
TITANIUM DIOXIDE	Х	X	Х	Х	Х	Х	Х	Х

#### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**CHINA** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

# U.S. Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
ZINC OXIDE - 1314-13-2	1314-13-2	0.1-1	1.0
SARA 311/312 Hazard Categories			

Yes
Yes
Yes
Yes
no

# **Clean Water Act**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
ZINC OXIDE		X		
1314-13-2				

#### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

# **U.S. State Regulations**

# **California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name California Prop. 65		
TITANIUM DIOXIDE - 13463-67-7	Carcinogen	

# U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ZINC OXIDE 1314-13-2	X	X	X
TITANIUM DIOXIDE 13463-67-7	X	X	X

EPA Pesticide Registration Number Not applicable

# Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

# **16. OTHER INFORMATION**

NFPA Health Hazard 2 Flammability 4 Instability 0 Physical and chemical

hazards -

HMIS Health Hazard 2\* Flammability 4 Physical Hazard 1 Personal protection B

Chronic Hazard Star Legend Chronic Health Hazard Repeated or prolonged exposure may cause central nervous system damage

Prepared By American Jetway

34136 Myrtle Street Wayne, MI 48184

Tel.734-721-5930

Issuing date 07-May-2015 Revision Date 07-May-2015

**Revision Note** 

No information available

**Disclaimer** 

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**