according to Hazard Communication Standard; 29 CFR 1910.1200



# KIWI® PROTECT- ALL WATERPROOFER

Version 2.0

Revision Date 02/22/2018

Print Date 05/23/2018

SDS Number 350000032736 GEN\_SOF Number 60022

# **1. PRODUCT AND COMPANY IDENTIFICATION**

Product information		
Product name	:	KIWI® PROTECT- ALL WATERPROOFER
Recommended use	:	Shoe Polish
Restrictions on use	:	Use only as directed on label
Manufacturer, importer, supplier	:	S.C. Johnson & Son, Inc. 1525 Howe Street Racine WI 53403-2236
Telephone	:	+1-800-558-5252
Emergency telephone number	:	24 Hour Medical Emergency Phone: (866)231-5406 24 Hour International Emergency Phone: (703)527-3887 24 Hour Transport Emergency Phone: (800)424-9300

### 2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

#### **Globally Harmonized System (GHS) Classification**

Hazard classification	Hazard category	Hazards identification
Aerosol	Category 1	Extremely flammable aerosol.
Specific target organ toxicity -	Category 3	May cause drowsiness or
single exposure		dizziness.
Gases under pressure	Liquefied gas	Contains gas under pressure;
		may explode if heated.

#### Labelling

#### Hazard symbols Flame Exclamation mark

**Signal word** Danger

according to Hazard Communication Standard; 29 CFR 1910.1200



# KIWI® PROTECT- ALL WATERPROOFER

Version 2.0

Revision Date 02/22/2018

Print Date 05/23/2018

SDS Number 350000032736 GEN\_SOF Number 60022

#### Hazard statements Extremely flammable aerosol. May cause drowsiness or dizziness. **Precautionary statements** If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Call a POISON CENTER/doctor if you feel unwell. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Dispose of contents/ container to an approved incineration plant. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing spray. Use only outdoors or in a well-ventilated area. Other hazards Intentional misuse by deliberately concentrating and inhaling : contents can be harmful or fatal. Excessive exposure to spray mist, fog or vapour may cause respiratory irritation.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS-No.	Weight percent
Naphtha (petroleum), hydrotreated light	64742-49-0	60.00 - 100.00
Butane	106-97-8	10.00 - 30.00
Propane	74-98-6	5.00 - 10.00
N-Butyl acetate	123-86-4	1.00 - 5.00
Isobutane	75-28-5	1.00 - 5.00

The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

For additional information on product ingredients, see www.whatsinsidescjohnson.com.

according to Hazard Communication Standard; 29 CFR 1910.1200



# KIWI® PROTECT- ALL WATERPROOFER

Version 2.0

Revision Date 02/22/2018

Print Date 05/23/2018

#### SDS Number 350000032736 GEN\_SOF Number 60022

# 4. FIRST AID MEASURES

Description of first a	aid measures
Eye contact	: No special requirements
Skin contact	: No special requirements
Inhalation	: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Ingestion	: No special requirements
Most important symp	otoms and effects, both acute and delayed
Eyes	: May irritate eyes.
Skin effect	: No adverse effects expected when used as directed.
Inhalation	<ul> <li>Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal.</li> <li>Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.</li> <li>Excessive exposure to spray mist, fog or vapour may cause respiratory irritation.</li> </ul>
Ingestion	: May cause irritation to mouth, throat and stomach. May cause abdominal discomfort. No adverse effects expected when used as directed.
Indication of any im	mediate medical attention and special treatment needed
See Description of fir	st aid measures unless otherwise stated.

## Safety Data Sheet hnson according to Hazard Communication Standard; 29 CFR 1910.1200 A FAMILY COMPANY **KIWI® PROTECT- ALL WATERPROOFER** Version 2.0 Print Date 05/23/2018 Revision Date 02/22/2018 SDS Number 350000032736 GEN SOF Number 60022 Specific hazards during Do not use a solid water stream as it may scatter and spread : firefighting fire. Aerosol Product - Containers may rocket or explode in heat of fire. Further information Fight fire from maximum distance or protected area. Cool and use caution when approaching or handling fire-exposed containers. Wear full protective clothing and positive pressure self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes. 6. ACCIDENTAL RELEASE MEASURES Personal precautions Remove all sources of ignition. Wash thoroughly after handling. Environmental : Outside of normal use, avoid release to the environment. precautions Methods and materials : If damage occurs to aerosol can: for containment and Contain spillage, soak up with non-combustible absorbent cleaning up material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Use only non-sparking equipment. Dike large spills. Clean residue from spill site. 7. HANDLING AND STORAGE Handling Precautions for safe : Avoid contact with skin, eyes and clothing. handling For personal protection see section 8. Use only as directed. KEEP OUT OF REACH OF CHILDREN AND PETS. Pressurized container. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Advice on protection : Keep away from sources of ignition - No smoking.

according to Hazard Communication Standard; 29 CFR 1910.1200



KIWI® PROTECT- ALL WATERPROOFER			
Version 2.0	Print Date 05/23/2018		
Revision Date 02/22/2018	SDS Number 350000032736 GEN_SOF Number 60022		
against fire and explosion	Do not spray on an open flame or other ignition source.		
Storage			
Requirements for storage areas and containers	<ul> <li>Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.</li> <li>Keep in a dry, cool and well-ventilated place.</li> <li>Store locked up.</li> <li>Store in a well-ventilated place.</li> <li>Keep container tightly closed.</li> </ul>		

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# **Occupational Exposure Limits**

Components	CAS-No.	mg/m3	ppm	Non- standard units	Basis
Butane	106-97-8	-	1,000 ppm	-	ACGIH STEL
Propane	74-98-6	1,800 mg/m3	1,000 ppm	-	OSHA TWA
Propane	74-98-6	-	-	-	ACGIH TWA
N-Butyl acetate	123-86-4	710 mg/m3	150 ppm	-	OSHA TWA
N-Butyl acetate	123-86-4	-	150 ppm	-	ACGIH STEL
N-Butyl acetate	123-86-4	-	50 ppm	-	ACGIH TWA
Isobutane	75-28-5	-	1,000 ppm	-	ACGIH STEL

# Personal protective equipment

**Respiratory protection** : No special requirements.

according to Hazard Communication Standard; 29 CFR 1910.1200



/ersion 2.0		Print Date 05/23/2018
Revision Date 02/22/2018		SDS Number 350000032736 GEN_SOF Number 60022
Hand protection	:	No special requirements.
Eye protection	:	No special requirements.
Skin and body protection	:	No special requirements.
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after handling.
). PHYSICAL AND CHEMICAL P	ROI	PERTIES
Form	:	aerosol
Color	:	transparent
Odour	:	solvent-like
Odour Threshold	:	Test not applicable for this product type
рН	:	Test not applicable for this product type
Melting point/freezing point	:	Test not applicable for this product type
Initial boiling point and boiling range	:	Test not applicable for this product type
Flash point	:	-5.2 °C 22.64 °F Method: Tag Closed Cup (TCC) liquid -104.4 °C -155.92 °F Propellant -60 °C -76 °F Propellant
Evaporation rate	:	Test not applicable for this product type

according to Hazard Communication Standard; 29 CFR 1910.1200



# KIWI® PROTECT- ALL WATERPROOFER

Version 2.0

Revision Date 02/22/2018

Print Date 05/23/2018

SDS Number 350000032736 GEN\_SOF Number 60022

Flammability (solid, gas)	: Sustains combustion
Upper/lower flammability or explosive limits	: Test not applicable for this product type
Vapour pressure	: Test not applicable for this product type
Vapour density	: Test not applicable for this product type
Relative density	: 0.699 g/cm3 at 25 °C
Solubility(ies)	: insoluble
Partition coefficient: n- octanol/water	: Test not applicable for this product type
Auto-ignition temperature	: not auto-flammable
Decomposition temperature	: Test not applicable for this product type
Viscosity, dynamic	: Test not applicable for this product type
Viscosity, kinematic	: Test not applicable for this product type
Oxidizing properties	: Test not applicable for this product type
Volatile Organic Compounds Total VOC (wt. %)*	<ul> <li>97.6 % - additional exemptions may apply</li> <li>*as defined by US Federal and State Consumer Product Regulations</li> </ul>

according to Hazard Commun	ication Standard; 29 CFR 19		
KIWI® PROTECT- A	LL WATERPROOFE	R	
Version 2.0		Print Date 05/23/2018	
Revision Date 02/22/2018		SDS Number 350000032736 GEN_SOF Number 60022	
Other information	: None identified		:
10. STABILITY AND REACTI	VITY		
Reactivity	: No dangerous react	tion known under conditions of normal u	ISE.
Chemical stability	: Stable under recom	mended storage conditions.	
Possibility of hazardous reactions	: Stable under recom	mended storage conditions.	
Conditions to avoid	: Heat, flames and sp	barks.	
Incompatible materials	: Strong oxidizing age	ents	
Hazardous decomposition products	on : Thermal decompos and vapours.	ition can lead to release of irritating gase	es
11. TOXICOLOGICAL INFOR	MATION		
Acute oral toxicity Acute inhalation toxicity	: LD50 > 5000 mg/ : LC50 > 10 mg/L	kg	
Acute dermal toxicity	: LD50 2158 mg/kg	3	
GHS Properties	Classification	Routes of entry	
Acute toxicity	No classification proposed	Oral	
Acute toxicity	No classification proposed	Dermal	
Acute toxicity	No classification proposed	Inhalation - Dust and Mist	
Acute toxicity	No classification proposed	Inhalation - Vapour	
Acute toxicity	No classification proposed	Inhalation - Gas	

Г

according to Hazard Communication Standard; 29 CFR 1910.1200



# **KIWI® PROTECT- ALL WATERPROOFER**

Version 2.0

Revision Date 02/22/2018

Print Date 05/23/2018

### SDS Number 350000032736 GEN\_SOF Number 60022

Skin irritation	No classification proposed	-
Serious eye damage/eye irritation	No classification proposed	-
Skin sensitisation	No classification proposed	-
Respiratory sensitisation	No classification proposed	-
Germ cell mutagenicity	No classification proposed	-
Carcinogenicity	No classification proposed	-
Reproductive toxicity	No classification proposed	-
Specific target organ toxicity - single exposure	Category 3	-
Specific target organ toxicity - repeated exposure	No classification proposed	-
Aspiration hazard	No classification proposed	-

Aggravated Medical : None known. Condition

# 12. ECOLOGICAL INFORMATION

**Product :** The product itself has not been tested.

#### Toxicity

The ingredients in this formula have been reviewed and no adverse impact to the environment is expected when used according to label directions.

## Toxicity to fish

Components	End point	Species	Value	Exposure time
Naphtha (petroleum), hydrotreated light	LC50	Oncorhynchus mykiss (rainbow trout)	> 13.4 mg/l	96 h

according to Hazard Communication Standard; 29 CFR 1910.1200



# KIWI® PROTECT- ALL WATERPROOFER

Version 2.0

Revision Date 02/22/2018

Print Date 05/23/2018

## SDS Number 350000032736 GEN\_SOF Number 60022

	NOELR	Pimephales promelas (fathead minnow)	2.6 mg/l	14 d
Butane	LC50 QSAR	Fish	27.98 mg/l	96 h
Propane	LC50	Fish	27.98 mg/l	96 h
N-Butyl acetate	flow- through test LC50	Pimephales promelas (fathead minnow)	18 mg/l	96 h
Isobutane	LC50 QSAR	Fish	27.98 mg/l	96 h

## Toxicity to aquatic invertebrates

Components	End point	Species	Value	Exposure time
Naphtha (petroleum), hydrotreated light	EC50	Daphnia magna (Water flea)	3 mg/l	48 h
	NOELR	Daphnia magna	2.6 mg/l	21 d
Butane	No data available			
Propane	LC50	Daphnid	14.22 mg/l	48 h
N-Butyl acetate	static test EC50	Daphnia (water flea)	44 mg/l	48 h

according to Hazard Communication Standard; 29 CFR 1910.1200



# KIWI® PROTECT- ALL WATERPROOFER

Version 2.0

Revision Date 02/22/2018

Print Date 05/23/2018

## SDS Number 350000032736 GEN\_SOF Number 60022

	NOEC Read- across (Analogy)	Daphnia magna	23 mg/l	21 d
Isobutane	LC50 QSAR	Daphnid	16.33 mg/l	48 h

# Toxicity to aquatic plants

Components	End point	Species	Value	Exposure time
Naphtha (petroleum), hydrotreated light	EC50	Pseudokirchneriella subcapitata (green algae)	10 - 30 mg/l	72 h
Butane	EC50 QSAR	Green algae	7.71 mg/l	96 h
Propane	No data available			
N-Butyl acetate	static test EC50	Desmodesmus subspicatus (green algae)	674.7 mg/l	72 h
Isobutane	EC50 QSAR	Green algae	8.57 mg/l	96 h

#### Persistence and degradability

Component	Biodegradation	Exposure time	Summary
Naphtha (petroleum), hydrotreated light	No data available		Not readily biodegradable.
Butane	100 %	385.5 h	Readily biodegradable.
Propane	70 %	< 10 d	Readily biodegradable.
N-Butyl acetate	83 %	28 d	Readily biodegradable.
Isobutane	70 %	< 10 d	Readily biodegradable.

according to Hazard Communication Standard; 29 CFR 1910.1200



# **KIWI® PROTECT- ALL WATERPROOFER**

Version 2.0

Revision Date 02/22/2018

Print Date 05/23/2018

SDS Number 350000032736 GEN\_SOF Number 60022

## **Bioaccumulative potential**

Component	Bioconcentration factor (BCF)	Partition Coefficient n- Octanol/water (log)
Naphtha (petroleum), hydrotreated light	No data available	No data available
Butane	No data available	2.89
Propane	No data available	2.36
N-Butyl acetate	No data available	2.3
Isobutane	1.57 - 1.97	2.8

#### Mobility

Component	End point	Value	
Naphtha (petroleum), hydrotreated light	log Koc	> 1.783 - < 2.36	
Butane	No data available		
Propane	No data available		
N-Butyl acetate	No data available		
Isobutane	No data available		

### PBT and vPvB assessment

Component	Results
Butane	Not fulfilling PBT and vPvB criteria
Propane	Not fulfilling PBT and vPvB criteria
N-Butyl acetate	Not fulfilling PBT and vPvB criteria
Isobutane	Not fulfilling PBT and vPvB criteria

#### Other adverse effects

: None known.

# **13. DISPOSAL CONSIDERATIONS**

Consumer may discard empty container in trash, or recycle where facilities exist.

according to Hazard Communication Standard; 29 CFR 1910.1200



# KIWI® PROTECT- ALL WATERPROOFER

Version 2.0

Revision Date 02/22/2018

Print Date 05/23/2018

SDS Number 350000032736 GEN\_SOF Number 60022

# 14. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up-to-date shipping information.

	Land transport	Sea transport	Air transport
UN number	1950	1950	1950
UN proper	AEROSOLS,	AEROSOLS,	AEROSOLS,
shipping name	Flammable	Flammable	Flammable
Transport hazard	2.1	2	2.1
class(es)			
Packing group	-	-	-
Environmental	-	-	-
hazards			
Special	Limited quantities	Limited quantities	Limited quantities
precautions for	derogation may be	derogation may be	derogation may be
user	applicable to this	applicable to this	applicable to this
	product, please check	product, please	product, please check
	transport documents.	check transport documents.	transport documents.
Transport in	Product not	Product not	Product not transported
bulk according	transported as bulk.	transported as bulk.	as bulk.
to Annex II of MARPOL 73/78 and the IBC Code			

#### 15. REGULATORY INFORMATION

Notification status	All ingredients of this product are listed or are exclud isting on the U.S. Toxic Substances Control Act (TS Chemical Substance Inventory.	
Notification status	All ingredients of this product comply with the New S Notification requirements under the Canadian Enviro Protection Act (CEPA).	

# Safety Data Sheet ohnson according to Hazard Communication Standard; 29 CFR 1910.1200 A FAMILY COMPANY **KIWI® PROTECT- ALL WATERPROOFER** Version 2.0 Print Date 05/23/2018 Revision Date 02/22/2018 SDS Number 350000032736 GEN SOF Number 60022 California Prop. 65 This product is not subject to the reporting requirements under : California's Proposition 65. **16. OTHER INFORMATION HMIS Ratings** Health 1 4 Flammability 0 Reactivity **NFPA Ratings** Health 1 Fire 4 Reactivity 0 Special This information is being provided in accordance with the Occupational Safety and Health Administration (OSHA) regulation (29 CFR 1910.1200). The information supplied is designed for workplaces where product use and frequency of exposure exceeds that established for the labeled consumer use. **Further information** This document has been prepared using data from sources considered to be technically reliable. It does not constitute a warranty, expressed or implied, as to the accuracy of the information contained herein. Actual conditions of use are beyond the seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State,

Prepared by	SC Johnson Global Safety Assessment &	
-	Regulatory Affairs (GSARA)	

Provincial and Local laws and regulations.

according to Hazard Communication Standard; 29 CFR 1910.1200



# **KIWI® PROTECT- ALL WATERPROOFER**

Version 2.0

Revision Date 02/22/2018

Print Date 05/23/2018

SDS Number 350000032736 GEN\_SOF Number 60022