



KWIK-STRIP™

SPRAYABLE

FAST PAINT & VARNISH STRIPPER

NON-METHYLENE CHLORIDE FORMULA



works in
15^{*}
minutes

STRIPS MULTIPLE LAYERS FAST

For use on Wood, Metal and Masonry

Liquid - Applies Quickly

Will Not Raise Wood Grain



DANGER! FLAMMABLE. VAPORS MAY CAUSE FLASH FIRE OR IGNITE EXPLOSIVELY. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. EYE AND SKIN IRRITANT.

Read entire label prior to use or storage.

¡PELIGRO! INFLAMABLE. LOS VAPORES PUEDEN CAUSAR UN INCENDIO O INCENDIO EXPLOSIVO. DANINO O LETAL SI LO INGIERE. VAPOR NOCIVO. IRRITANTE PARA LOS OJOS Y LA PIEL. Lea toda la etiqueta antes de usar o almacenar este producto.

ONE QUART (946 mL)

PATENT PENDING

18752

DIRECTIONS FOR USE: 1. Shake well. 2. Pour into sprayer bottle and tighten sprayer to bottle. With bottle in upright position, turn spray nozzle away from you and adjust nozzle to desired spray pattern (spray, stream or fan). Apply an even, liberal coat of stripper to a small area (up to 3 ft x 3 ft). Leave the area and let the stripper do the work. 3. After 15 minutes, test scrape a small area to see if finish is ready for removal. Remove loosened finish by gently scraping in direction of wood grain with a plastic stripping tool. A toothbrush, toothpick or stripping brush will help remove old finish buried in recesses. Multiple coats or stubborn finishes may require repeat application. 4. Use a clean abrasive pad dipped in After Wash or Odorless Mineral Spirits to loosen remaining finish and remove any residue. Surface should be completely clean and dry before applying new finish.

IMPORTANT: Do not apply to floors or any other large surface areas because fire and health safety risks will increase dramatically. Always wear chemical-splash goggles and chemical-resistant gloves when handling this product. A dust mask does not provide protection against vapors. Dispose of product within 3 months of opening.

DANGER! FLAMMABLE. VAPORS MAY CAUSE FLASH FIRE OR IGNITE EXPLOSIVELY. KEEP AWAY FROM HEAT, SPARKS, FLAME, AND ALL OTHER SOURCES OF IGNITION. Extinguish all flames and pilot lights, and turn off all stoves, heaters, electric motors and all other sources of ignition during use and until all vapors are gone. Do not smoke. Keep away from electrical outlets and switches. Beware of static electricity generated by synthetic clothing and other sources. **USE ONLY WITH ADEQUATE VENTILATION TO PREVENT BUILDUP OF VAPORS.** Do not use in areas where vapors can accumulate and concentrate such as basements, bathrooms and small, enclosed areas. If using indoors, open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience dizziness – STOP – ventilation is inadequate. Leave area immediately. **IF THE WORK AREA IS NOT WELL VENTILATED, DO NOT USE THIS PRODUCT.**

DANGER! HARMFUL OR FATAL IF SWALLOWED. EYE AND SKIN IRRITANT. VAPOR HARMFUL. Contains Dimethyl Carbonate and Xylene. Reports have associated repeated and prolonged over-exposure to solvents with neurological and other physiological damage. The risk to your health depends on the level and duration of exposure. Intentional misuse of this product by deliberately concentrating and inhaling vapors can be harmful or fatal. Avoid breathing vapors or mist and contact with skin, eyes, and clothing. Do not swallow.

⚠️WARNING: This product can expose you to Ethylbenzene, which is known to the State of California to cause cancer, and Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

FIRST AID: IF SWALLOWED, do not induce vomiting. Immediately call the Poison Control Center (1-800-222-1222), hospital emergency room or physician for instructions. **IN CASE OF EYE CONTACT,** immediately flush with water, remove any contact lens, continue flushing with water for at least 15 minutes, then get immediate medical attention. **IN CASE OF SKIN CONTACT,** immediately wash with soap and water. If irritation persists, get medical attention.

**KEEP OUT OF REACH OF CHILDREN.
DO NOT USE TO STRIP BATHTUBS.**

Product Category: Paint Remover • **Max VOC:** 50%

Latex	* Strips 5 layers in 15 minutes
Oil/Alkyd	Strips 5 layers in 45 minutes

Not for sale or use in California.

©2018 W.M. Barr & Co., Inc. • www.kleanstrip.com
All rights reserved.
Label design is a trademark of WM Barr & Co., Inc.

For assistance call:
The Barr Help Line 1-800-398-3892
Monday - Friday, 8:00am - 4:30pm Central Time

QKWL963 / J8753

IMPORTANTE: No aplica a pisos u otras superficies grandes porque se incrementarían dramáticamente los riesgos de incendio y a la salud. Siempre use gafas de protección contra salpicaduras de sustancias químicas y guantes resistentes a los productos químicos cuando maneje este producto. Una máscara antipolvo no proporciona protección contra vapores. Deseche el producto dentro de los 3 meses posteriores a la apertura.

¡PELIGRO! INFLAMABLE. LOS VAPORES PUEDEN CAUSAR UN INCENDIO O INCENDIO EXPLOSIVO. MANTÉNGASE FUERA DEL CALOR, CHISPAS, LLAMAS Y TODAS LAS DEMÁS FUENTES DE IGNICIÓN. Apague todas las llamas y luces piloto, y apague todas las estufas, calentadores, motores eléctricos y todas las otras fuentes de ignición durante el uso y hasta que todos los vapores se hayan ido. No fume. Mantener alejado de enchufes eléctricos e interruptores. Tenga cuidado con la electricidad estática



generada por la ropa sintética y otras fuentes. **ÚSELO ÚNICAMENTE CON VENTILACIÓN ADECUADA PARA EVITAR LA EXISTENCIA DE VAPORES.** No lo use en áreas donde los vapores se puedan acumular y concentrar, como sótanos, baños y áreas pequeñas y cerradas. Si lo usa en el interior, abra todas las ventanas y puertas y mantenga una ventilación cruzada de aire fresco en movimiento en el área de trabajo. Si se nota un fuerte olor o si experimenta mareos – DETÉNGASE – la ventilación es inadecuada. Salga del área inmediatamente. **SI EL ÁREA DE TRABAJO NO ESTÁ BIEN VENTILADA, NO USE ESTE PRODUCTO.**

¡PELIGRO! NOCIVO O LETAL SI SE INGIERE. IRRITANTE PARA LOS OJOS Y LA PIEL. VAPOR NOCIVO. Contiene dimetil carbonato y xileno. Los informes han asociado la sobreexposición repetida y prolongada a solventes con daños neurológicos y otros daños fisiológicos. El riesgo para su salud depende del nivel y la duración de la exposición. El uso indebido intencional de este producto al concentrar e inhalar vapores deliberadamente puede ser dañino o fatal. Evite respirar los vapores o la niebla y el contacto con la piel, los ojos y la ropa. No debe ingerirse.

⚠️ADVERTENCIA: Este producto puede exponerlo al etilbenceno, que en el estado de California es cancerígeno, y al metanol, que el estado de California considera que causa defectos de nacimiento u otros daños reproductivos. Para obtener más información, vaya a www.P65Warnings.ca.gov.

PRIMEROS AUXILIOS: EN CASO DE INGESTIÓN, no induzca el vómito. Llame inmediatamente al Centro de Control de Envenenamientos (1-800-222-1222), a la sala de emergencias del hospital o al médico para recibir instrucciones. **EN CASO DE CONTACTO CON LOS OJOS,** lave inmediatamente con agua, retire cualquier lente de contacto, continúe enjuagando con agua durante al menos 15 minutos, luego obtenga atención médica inmediata. **EN CASO DE CONTACTO CON LA PIEL,** lave inmediatamente con agua y jabón. Si la irritación persiste, obtenga atención médica.

**MANTÉNGASE FUERA DEL ALCANCE DE LOS NIÑOS.
NO LO UTILICE PARA DESMONTAR BAÑERAS.**

Categoría de producto: Removedor de Pintura • **Max VOC:** 50%
No está a la venta o uso en California.



IMPORTADOR SERVICIOS HOME DEPOT, S. de R.L. de C.V.
RICARDO MARGAIN 605
SANTA ENGRACIA,
SAN PEDRO GARZA GARCIA,
Nuevo León, C.P. 66267.
MEXICO R.F.C. SHD-940509-I58
TEL 81 55 70 00