

# **Material Safety Data Sheet**

Copyright, 2011, Meguiar's, Inc.. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Meguiar's products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

# **SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

**PRODUCT NAME:** G103, Scratch X 2.0 (20-191B): G10307

MANUFACTURER: Meguiar's, Inc.

> **DIVISION:** Automotive Aftermarket

ADDRESS: Meguiar's, Inc

17991 Mitchell South, Irvine, CA 92614

EMERGENCY PHONE: Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

Issue Date: 03/16/11 03/11/11 **Supercedes Date:** 

**Document Group:** 27-6195-5

**Product Use:** 

Intended Use: Automotive

Specific Use: Polishing agent/burnishing compound

## **SECTION 2: INGREDIENTS**

<u>Ingredient</u>	<u>C.A.S. No.</u>	% by Wt	
NON-HAZARDOUS INGREDIENTS	Mixture	60 - 90	
PETROLEUM DISTILLATE	64742-88-7	7 - 13	
PETROLEUM DISTILLATE	64742-46-7	7 - 13	
ALUMINUM OXIDE	1344-28-1	5 - 10 0.5 - 1.5	
GLYCERIN	56-81-5		
TRIETHANOLAMINE	102-71-6	0.5 - 1.5	

# SECTION 3: HAZARDS IDENTIFICATION

## 3.1 EMERGENCY OVERVIEW

**Odor, Color, Grade:** Sweet hydrocarbon odor; White, creamy, viscous lotion

General Physical Form: Liquid

**Immediate health, physical, and environmental hazards:** Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back.

May cause target organ effects.

#### 3.2 POTENTIAL HEALTH EFFECTS

### **Eye Contact:**

Mild Eye Irritation: Signs/symptoms may include redness, pain, and tearing.

#### **Skin Contact:**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, and itching.

#### Inhalation:

Intentional concentration and inhalation may be harmful or fatal.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May be absorbed following inhalation and cause target organ effects.

#### **Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May be absorbed following ingestion and cause target organ effects.

#### **Target Organ Effects:**

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

## **SECTION 4: FIRST AID MEASURES**

## 4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

**Eye Contact:** Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

**Skin Contact:** Wash affected area with soap and water. If signs/symptoms develop, get medical attention.

**Inhalation:** Remove person to fresh air. If signs/symptoms develop, get medical attention.

**If Swallowed:** Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

## **SECTION 5: FIRE FIGHTING MEASURES**

## 5.1 FLAMMABLE PROPERTIES

**Autoignition temperature** No Data Available

#### MATERIAL SAFETY DATA SHEET G103, Scratch X 2.0 (20-191B): G10307

03/16/11

Flash Point >= 200 °F [Test Method: Pensky-Martens Closed Cup]

Flammable Limits(LEL) No Data Available

Flammable Limits(LEL)

No Data Available
No Data Available
No Data Available

#### 5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

#### 5.3 PROTECTION OF FIRE FIGHTERS

**Special Fire Fighting Procedures:** Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

**Unusual Fire and Explosion Hazards:** Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

## 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode.

#### 6.2. Environmental precautions

For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Place in a closed container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

#### Clean-up methods

Observe precautions from other sections. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible using non-sparking tools. Clean up residue with detergent and water.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

## **SECTION 7: HANDLING AND STORAGE**

## 7.1 HANDLING

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Keep away from heat, sparks, open flame, pilot lights and other sources of ignition. Avoid breathing of vapors, mists or spray. Avoid eye contact with vapors, mists, or spray. Keep out of the reach of children. Avoid contact with oxidizing agents.

### 7.2 STORAGE

Store away from acids. Store away from heat. Store out of direct sunlight. Store away from oxidizing agents.

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### 8.1 ENGINEERING CONTROLS

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits and/or control mist, vapor, or spray. If ventilation is not adequate, use respiratory protection equipment.

## 8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

#### 8.2.1 Eye/Face Protection

Avoid eye contact with vapors, mists, or spray.

The following eye protection(s) are recommended: Safety Glasses with side shields

•

#### 8.2.2 Skin Protection

Avoid skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

Gloves made from the following material(s) are recommended: Nitrile Rubber

.

## 8.2.3 Respiratory Protection

Avoid breathing of vapors, mists or spray.

Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece or fullface air-purifying respirator with organic vapor cartridges and P95 particulate prefilters.

## 8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

### 8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<b>Authority</b>	<b>Type</b>	<u>Limit</u>	<b>Additional Information</b>
ALUMINUM OXIDE	CMRG	TWA	1 fiber/cc	
ALUMINUM OXIDE	OSHA	TWA, respirable	5 mg/m3	
		fraction		
ALUMINUM OXIDE	OSHA	TWA, as total dust	15 mg/m3	
GLYCERIN	ACGIH	TWA, as mist	10 mg/m3	
GLYCERIN	OSHA	TWA, respirable	5 mg/m3	
		fraction		
GLYCERIN	OSHA	TWA, as total dust	15 mg/m3	
PETROLEUM DISTILLATE	CMRG	TWA	100 ppm	
PETROLEUM DISTILLATES	OSHA	TWA	2000 mg/m3	
PETROLEUM DISTILLATE	CMRG	TWA	300 ppm	
TRIETHANOLAMINE	ACGIH	TWA	5 mg/m3	

## SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

Page 4 of 7

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**Odor, Color, Grade:** Sweet hydrocarbon odor; White, creamy, viscous lotion

General Physical Form: Liquid

**Autoignition temperature** No Data Available

Flash Point >= 200 °F [Test Method: Pensky-Martens Closed Cup]

Flammable Limits(LEL)

Flammable Limits(UEL)

No Data Available

No Data Available

No Data Available

No Data Available

1.18 g/cm3

**Density** 1.18 g/cm3 **Vapor Density** No Data Available

Vapor Pressure No Data Available

Specific Gravity 1.18 [Ref Std: WATER=1]

NH 8 - 8.8

Melting point Not Applicable

Solubility in Water Moderate

Evaporation rateNo Data AvailableVolatile Organic Compounds11.00 % weightKow - Oct/Water partition coefNo Data AvailableViscosity22000 - 28000 centipoise

# SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

**Materials and Conditions to Avoid:** 

10.1 Conditions to avoid

Heat

10.2 Materials to avoid

Strong acids Strong bases

Hazardous Polymerization: Hazardous polymerization will not occur.

# **Hazardous Decomposition or By-Products**

SubstanceConditionHydrocarbonsDuring CombustionCarbon monoxideDuring CombustionCarbon dioxideDuring CombustionIrritant Vapors or GasesDuring CombustionOxides of NitrogenDuring Combustion

# **SECTION 11: TOXICOLOGICAL INFORMATION**

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

## **SECTION 12: ECOLOGICAL INFORMATION**

# **ECOTOXICOLOGICAL INFORMATION**

Not determined.

## CHEMICAL FATE INFORMATION

Not determined

## **SECTION 13: DISPOSAL CONSIDERATIONS**

**Waste Disposal Method:** Incinerate in an industrial or commercial facility. As a disposal alternative, dispose of waste product in a facility permitted to accept chemical waste.

EPA Hazardous Waste Number (RCRA): Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

## **SECTION 14:TRANSPORT INFORMATION**

General Tansportation Statement

This product does not require classification by DOT, IATA, ICAO or IMDG.

## ID Number(s):

14-1000-0413-5, 14-1000-0414-3, 14-1000-0415-0, 14-1000-0416-8, 14-1000-0417-6

## **SECTION 15: REGULATORY INFORMATION**

## US FEDERAL REGULATIONS

Contact Meguiar's for more information.

## 311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

## STATE REGULATIONS

Contact Meguiar's for more information.

#### **CHEMICAL INVENTORIES**

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact Meguiar's for more information.

#### INTERNATIONAL REGULATIONS

Contact Meguiar's for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## **SECTION 16: OTHER INFORMATION**

NFPA Hazard Classification

Health: 1 Flammability: 1 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

**Revision Changes:** 

n/a

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. Meguiar's MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Meguiar's product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a Meguiar's product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Meguiar's product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Meguiar's provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, Meguiar's makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from Meguiar's.

Meguiar's MSDSs are available at www.Meguiars.com