

Majic Interior/Exterior Oil Base Floor Paint

8-0072 Series

DESCRIPTION

Majic Interior/Exterior Oil Base Floor Paint is a durable oil base finish that will give dependable, long lasting protection in all climates. Majic Oil Base Floor Paint is especially formulated for ease of application and trouble free performance.



FEATURES

- Applies easily
- For concrete, wood, and properly primed metal
- Scuff, mar and water resistant

VOC / MIR (sprays)

250 gm/l
(2.10 lbs/gal)

NET WEIGHT

11.81 lbs/gal

AVAILABLE SIZES

5-gallon, gallon,
quart

SHIPPING WT

5-gal pail/53 lbs
4-gal case/45 lbs
4-qt case/10 lbs

AVAILABLE COLORS

8-0072 Golden Brown, 8-0073 Black, 8-0074 White, 8-0075 Battleship Gray, 8-0076 Tile Red, 8-0077 Dark Brown, 8-0078 Colonial Green, 8-0079 Light Gray

SHIPPING RESTRICTION

CA - Gal & 5 Gal

PRODUCT STATISTICS

DRYTIME-TOUCH 8 hours	DRYTIME-RECOAT 24 hours	WET/ FILM THK 2.1 mils	FILM THK /DRY: 1.0 mils	FINISH Medium Gloss	GLOSS 35+ @ 60°
FLASHPOINT > 100° F	COVERAGE Up to 525 sq ft/gal	VISCOSITY 90 - 100 KU	VEHICLE Alkyd-Oil	SOLVENT Mineral Spirits	

SURFACE PREP

New Wood: Apply two coats, allowing a minimum of 24 hours dry time between coats. **Painted Wood:** Remove all loose paint. Wash off any wax with wax remover. Touch up any bare areas with Majic Oil Base Floor Paint. When dry, sand well and follow with one or two coats of Majic Oil Base Floor Paint. **New Concrete;** Majic Oil Base Floor Paint should not be applied to concrete which is positioned on ground without a moisture barrier. Allow new concrete to cure 90 days. Prior to painting, etch surface with a 10% solution of muriatic acid. Wear gloves and goggles to prevent contact with the muriatic acid. Rinse thoroughly and allow to dry completely. Follow with two coats of Majic Oil Base Floor Paint. Do not paint if floor is cold or room is cold and damp. **Painted Concrete:** Remove all loose paint. Wash off any wax with wax remover. Touch up any bare areas with Majic Oil Base Floor Paint. When dry, sand well and follow with one or two coats of Majic Oil Base Floor Paint. **Galvanized Metal Surface:** Check for stabilizing film, remove appropriately and prime with a galvanized metal primer. Follow with one or two coats of Majic Oil Base Floor Paint.

APPLICATION

Stir contents thoroughly until uniform. If using two or more gallons of the same color, mix together and stir paint thoroughly to make sure color is uniform throughout. Apply smoothly and evenly with a good quality nylon brush, short nap roller or pad applicator. Do not paint exterior surfaces when temperatures are below 50° F, in direct sunlight, or if rain is expected within 24 hours. Let dry overnight before opening to traffic.

WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Yenkin-Majestic Paint Corp. 1920 Leonard Ave. Columbus, OH 43219 Ph: (800) 848-1898 Fx: (614) 258-3062

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.