

The multipurpose CM Series is great for keeping patios, siding and equipment clean. Use its built-in detergent injector with a Mi-T-M cleaner to effectively remove mold, mildew and dirt.

ChoreMaster[®] Series Gasoline Direct Drive

Pump:

- · Thermal relief valve
- · In-line water strainer
- · Built-in low pressure detergent injector

Frame:

- Powder coated steel frame and base plate with 1¼-inch tube handles
- · 10-inch flat-free tires

Unit Includes:

- Quick connect nozzles 15°, 25° and detergent nozzle
- \cdot 25-foot x $\%\mathchar`-$ inch wire-braided high pressure hose (50-foot on CM-3600 and CM-4200 models)
- · Professional-grade trigger gun
- · Two-piece, 36-inch lance

Mi-T-M Pressure Relief Start:

Equipped with the Mi-T-M Pressure Relief Start which eliminates pressure build up in the system. No need to trigger the gun when starting the pressure washer.



Limited Warranties:

- 1 year AR and Mi-T-M pumps
- · 1 year Mi-T-M engine

| USAGE | Residential/Commercial | Commercial | Commercial | Commercial |
|---------------------|------------------------|---------------------|---------------------|---------------------|
| MODEL NO. | CM-3000-0MMB | CM-3200-0MMB | CM-3600-0MMB | CM-4200-0MMB |
| PSI | 3000 | 3200 | 3600 | 4200 |
| GPM | 2.4 | 2.4 | 2.8 | 3.4 |
| DISPLACEMENT/ENGINE | 212cc Mi-T-M OHV | 212cc Mi-T-M OHV | 300cc Mi-T-M OHV | 420cc Mi-T-M OHV |
| PUMP | Mi-T-M, axial | Mi-T-M, crankshaft | AR, crankshaft | AR, crankshaft |
| UNLOADER | Fixed pressure | Adjustable pressure | Adjustable pressure | Adjustable pressure |
| DIMENSIONS (LxWxH) | 37x21x24.5in. | 37x21x24.5in. | 40x22.5x24.5in. | 40x22.5x24.5in. |
| SHIP WT. | 100 lb. | 110 lb. | 180 lb. | 192 lb. |
| NET WT. | 75 lb. | 85 lb. | 130 lb. | 142 lb. |

Consult factory for more information on these available options:

· 25-foot high pressure hose with quick connects

· 50-foot high pressure hose, with and without quick connects