

SAFETY DATA SHEET

Revision Date 01-Dec-2016 Version 3

1. IDENTIFICATION

Product identifier

Product Name Wiping Stain Spanish Oak

Other means of identification

Product Code 12216

SKU(s) 12201, 12204, 12216

Recommended use of the chemical and restrictions on use
Recommended Use
Uses advised against
No information available.
No information available

Details of the supplier of the safety data sheet

Supplier Address

Old Masters 303 19th St. SE

Orange City, IA 51041 Phone: 712-737-4993 Fax: 712-737-4997

Emergency telephone number

Emergency Telephone Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| Skin sensitization | Category 1 |
|--|-------------|
| Germ cell mutagenicity | Category 1B |
| Carcinogenicity | Category 1A |
| Specific target organ toxicity (repeated exposure) | Category 1 |
| Aspiration toxicity | Category 1 |
| Flammable liquids | Category 3 |

Emergency Overview

Danger

Hazard statements

May cause an allergic skin reaction

May cause genetic defects

May cause cancer

Causes damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Flammable liquid and vapor



Appearance No information available

Physical state liquid

Odor No information available

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves

Do not breathe dust/fume/gas/mist/vapors/spray

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Use explosion-proof electrical/ ventilating/ lighting/ equipment

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

· May be harmful if swallowed

Unknown acute toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS No. | Weight-% | Trade Secret |
|-----------------------------------|------------|----------|--------------|
| Linseed Oil | 8001-26-1 | 30 - 60 | * |
| Mineral Spirits (Rule 66) | 64742-47-8 | 10 - 30 | * |
| Crystalline Silica | 14808-60-7 | 5 - 10 | * |
| Solvent Naphtha, Medium Aliphatic | 64742-88-7 | 1 - 5 | * |
| Carbon Black | 1333-86-4 | 1 - 5 | * |
| Stoddard Solvent | 8052-41-3 | 0.1 - 1 | * |
| Methyl Ethyl Ketoxime | 96-29-7 | 0.1 - 1 | * |
| Mineral Spirits | 64742-48-9 | 0.1 - 1 | * |

| Neo C9-13 Acid, Cobalt Salts | 68955-83-9 | 0.1 - 1 | * |
|------------------------------|------------|---------|---|
| Cobalt neodecanoate | 27253-31-2 | 0.1 - 1 | * |

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice Immediate medical attention is required. In case of accident or unwellness, seek medical

advice immediately (show directions for use or safety data sheet if possible).

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms

persist, call a physician.

Skin Contact Wash off immediately with plenty of water.

Inhalation Remove to fresh air. Call a physician. If breathing is irregular or stopped, administer

artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth

resuscitation.

Ingestion Do NOT induce vomiting. Rinse mouth. Drink plenty of water. If symptoms persist, call a

physician.

Self-protection of the first aider Remove all sources of ignition.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Flammable. WARNING: Spontaneous combustion (fire) may result from materials such as rags, steel wool, paper, clothing, and other waste soaked in linseed oil. Place in a sealed, water filled, metal container to prevent this.

Explosion data

Sensitivity to Mechanical Impact None. **Sensitivity to Static Discharge** None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate

ventilation, especially in confined areas. Use personal protective equipment as required.

Environmental precautions

Environmental precautions

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. See Section 12 for additional

ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers. Dam up. Soak up with inert absorbent

material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Soak up with inert

absorbent material.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks,

flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be

grounded.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep away

from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and

static electricity).

Incompatible materialsNone known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|----------------------------------|--|--|---|
| Crystalline Silica 14808-60-7 | TWA: 0.025 mg/m³ respirable particulate matter | TWA: 50 μg/m³ TWA: 50 μg/m³ excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 0.1 mg/m³ respirable dust: (250)/(%SiO2 + 5) mppcf TWA respirable fraction: (10)/(%SiO2 + 2) mg/m³ TWA respirable fraction | IDLH: 50 mg/m³ respirable dust TWA: 0.05 mg/m³ respirable dust |
| Carbon Black 1333-86-4 | TWA: 3 mg/m³ inhalable particulate matter | TWA: 3.5 mg/m³ (vacated) TWA: 3.5 mg/m³ | IDLH: 1750 mg/m³ TWA: 3.5 mg/m³ TWA: 0.1 mg/m³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH |
| Stoddard Solvent 8052-41-3 | TWA: 100 ppm | TWA: 500 ppm TWA: 2900 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m³ | IDLH: 20000 mg/m³ Ceiling: 1800 mg/m³ 15 min TWA: 350 mg/m³ |

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Skin and body protection No special technical protective measures are necessary.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

General Hygiene Considerations When using do not eat, drink or smoke. Regular cleaning of equipment, work area and

clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state liquid

AppearanceNo information availableOdorNo information availableColorNo information availableOdor thresholdNo information available

Property Values Remarks • Method

pH No information available
Melting point/freezing point No information available
Boiling point / boiling range
Flash point 39 °C / 102 °F
Evaporation rate No information available
Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor pressure
Vapor density

No information available
No information available
No information available
No information available

Specific Gravity 0.98

Water solubility No information available Solubility in other solvents No information available Partition coefficient No information available No information available **Autoignition temperature Decomposition temperature** No information available Kinematic viscosity No information available **Dynamic viscosity** No information available **Explosive properties** No information available Oxidizing properties No information available

Other Information

Softening point
Molecular weight
VOC Content (%)
No information available
No information available
No information available

Density 8.21 lbs/gal

Bulk density No information available

Percent solids by weight 76.0%
Percent volatile by weight 24.0%
Percent solids by volume 70.0%
Actual VOC (lbs/gal) 2
Actual VOC (grams/liter) 236.4
EPA VOC (lbs/gal) 2

EPA VOC (grams/liter) 236.4 EPA VOC (lb/gal solids) 2.8

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

None known based on information supplied.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information No data available

Inhalation No data available.

Eye contact No data available.

Skin Contact No data available.

Ingestion No data available.

| Chemical Name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|--|---------------------|----------------------------|-------------------------|
| Linseed Oil 8001-26-1 | > 15,000 mg/kg | - | - |
| Mineral Spirits (Rule 66) 64742-47-8 | > 5000 mg/kg (Rat) | > 2000 mg/kg (Rabbit) | > 5.2 mg/L (Rat)4 h |
| Crystalline Silica 14808-60-7 | = 500 mg/kg (Rat) | - | - |
| Solvent Naphtha, Medium Aliphatic 64742-88-7 | > 25 mL/kg (Rat) | > 3000 mg/kg (Rabbit) | > 13 mg/L (Rat)4 h |
| Carbon Black 1333-86-4 | > 15400 mg/kg (Rat) | > 3 g/kg(Rabbit) | - |
| Stoddard Solvent 8052-41-3 | - | > 3000 mg/kg (Rabbit) | - |
| Methyl Ethyl Ketoxime 96-29-7 | = 930 mg/kg (Rat) | 1000 - 1800 mg/kg (Rabbit) | > 4800 mg/m³ (Rat) 4 h |
| Mineral Spirits 64742-48-9 | > 5000 mg/kg (Rat) | > 3160 mg/kg (Rabbit) | 1.1 - 1.9 mg/L (Rat)4 h |

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

SensitizationNo information available.Germ cell mutagenicityNo information available.

Carcinogenicity No information available.

| Chemical Name | ACGIH | IARC | NTP | OSHA |
|---|-------|----------|-------|------|
| Crystalline Silica 14808-60-7 | A2 | Group 1 | Known | Х |
| Carbon Black 1333-86-4 | A3 | Group 2B | - | X |
| Neo C9-13 Acid, Cobalt Salts 68955-83-9 | - | Group 2B | - | X |
| Cobalt neodecanoate 27253-31-2 | - | Group 2B | - | Х |

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not classifiable as a human carcinogen

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
No information available.
No information available.

Target Organ Effects Eyes, lungs, Lymphatic System, Respiratory system.

Aspiration hazard No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

76.21% of the mixture consists of components(s) of unknown hazards to the aquatic environment

| Chemical Name | Algae/aquatic plants | Fish | Crustacea |
|--|---|--|--|
| Mineral Spirits (Rule 66) 64742-47-8 | - | 45: 96 h Pimephales promelas mg/L LC50 flow-through 2.2: 96 h Lepomis macrochirus mg/L LC50 static 2.4: 96 h Oncorhynchus mykiss mg/L LC50 static | 4720: 96 h Den-dronereides heteropoda mg/L LC50 |
| Solvent Naphtha, Medium Aliphatic 64742-88-7 | 450: 96 h Pseudokirchneriella subcapitata mg/L EC50 | 800: 96 h Pimephales promelas mg/L LC50 static | 100: 48 h Daphnia magna mg/L EC50 |
| Carbon Black 1333-86-4 | - | - | 5600: 24 h Daphnia magna mg/L EC50 |
| Methyl Ethyl Ketoxime 96-29-7 | 83: 72 h Desmodesmus subspicatus mg/L EC50 | 777 - 914: 96 h Pimephales promelas mg/L LC50 flow-through 320 - 1000: 96 h Leuciscus idus mg/L LC50 static 760: 96 h Poecilia reticulata mg/L LC50 static | 750: 48 h Daphnia magna mg/L EC50 |
| Mineral Spirits 64742-48-9 | - | 2200: 96 h Pimephales promelas mg/L LC50 | 2.6: 96 h Chaetogammarus marinus mg/L LC50 |

Persistence and degradability

No information available.

Bioaccumulation

No information available.

| Chemical Name | Partition coefficient |
|-----------------------|-----------------------|
| Methyl Ethyl Ketoxime | 0.65 |
| 96-29-7 | |

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number D001 U239

This product contains one or more substances that are listed with the State of California as a hazardous waste.

| Chemical Name | California Hazardous Waste Status |
|--|-----------------------------------|
| Neo C9-13 Acid, Cobalt Salts 68955-83-9 | Toxic |
| Cobalt neodecanoate 27253-31-2 | Toxic |

14. TRANSPORT INFORMATION

DOT Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies

DSL/NDSL Complies *

EINECS/ELINCS Complies *

ENCS Does not comply *

IECSC Complies *

KECL Complies *

PICCS Does not comply *

AICS Does not comply *

<u>Legend:</u>

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

^{*} This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard Yes
Fire hazard Yes
Sudden release of pressure hazard No
Reactive Hazard No

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

| Chemical Name | California Proposition 65 |
|---------------------------------|---------------------------|
| Crystalline Silica - 14808-60-7 | Carcinogen |
| Carbon Black - 1333-86-4 | Carcinogen |
| Ethyl Benzene - 100-41-4 | Carcinogen |

U.S. State Right-to-Know Regulations

| Chemical Name | New Jersey | Massachusetts |
|---|------------|---------------|
| Crystalline Silica 14808-60-7 | X | X |
| Solvent Naphtha, Medium Aliphatic 64742-88-7 | Х | - |
| Carbon Black 1333-86-4 | Х | Х |
| Xylene 1330-20-7 | X | X |
| Cobalt neodecanoate 27253-31-2 | Х | - |
| Neo C9-13 Acid, Cobalt Salts 68955-83-9 | Х | - |

| Chemical Name | Pennsylvania |
|----------------------------------|--------------|
| Linseed Oil 8001-26-1 | Х |
| Crystalline Silica 14808-60-7 | Х |
| Carbon Black 1333-86-4 | Х |

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

Hazardous air pollutants (HAPS) content

This product contains no Hazardous Air Pollutants individually at 1% by weight, or greater.

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 1 Flammability 2 Instability 0 Physical and Chemical Properties -

HMIS Health hazards 1 * Flammability 2 Physical hazards 0 Personal protection X

Chronic Hazard Star Legend *= Chronic Health Hazard

Revision Date 01-Dec-2016

Revision Note

No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

End of Safety Data Sheet