# SAFETY DATA SHEET



Date of issue/Date of revision 24 January 2019

Version 9.03

### Section 1. Identification

: ऑK500-190 PPG PROLUXE SRD SEMI-TRANSPARENT EXTERIOR MATTE TINT **Product name** 

**BASE 190** 

: 00366024 **Product code** Other means of : Not available.

identification

**Product type** : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

: Consumer applications, Professional applications. **Product use** 

Use of the substance/

mixture

Coating.

Uses advised against : Not applicable.

Manufacturer : PPG Industries, Inc.

One PPG Place Pittsburgh, PA 15272

**Emergency telephone** 

number

: (412) 434-4515 (U.S.) (514) 645-1320 (Canada)

01-800-00-21-400 or + 52 55 5559 1588 (Mexico)

**Technical Phone Number** : 1-800-441-9695 (8:00 am to 5:00 pm EST)

### Section 2. Hazards identification

**OSHA/HCS** status

: While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available

for employees and other users of this product.

Classification of the substance or mixture : Not classified.

Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 22.1% (Oral),

22.1% (Dermal), 22.1% (Inhalation)

**GHS** label elements

Signal word : No signal word.

**Hazard statements** : No known significant effects or critical hazards.

**Precautionary statements** 

: Read label before use. Keep out of reach of children. If medical advice is needed. General

have product container or label at hand.

**Prevention** : Not applicable.

**United States** Page: 1/11

Product name SIK500-190 PPG PROLUXE SRD SEMI-TRANSPARENT EXTERIOR MATTE TINT BASE 190

### Section 2. Hazards identification

Response : Not applicable.

Photosensitive agents: In case of accidental eye contact, avoid concurrent exposure to the sun or other sources of UV light which may increase the sensitivity of the eyes. In case of accidental skin contact, avoid concurrent exposure to the sun or other sources

of UV light which may increase the sensitivity of skin.

Storage : Not applicable.

Disposal : Not applicable.

Supplemental label

elements

: Contains isothiazolinones. May cause allergic reaction. Emits toxic fumes when heated.

Hazards not otherwise

classified

: None known.

# Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Product name : SIK500-190 PPG PROLUXE SRD SEMI-TRANSPARENT EXTERIOR MATTE TINT

**BASE 190** 

| Ingredient name  | %           | CAS number |
|------------------|-------------|------------|
| propane-1,2-diol | ≥1.0 - ≤5.0 | 57-55-6    |

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

#### **Description of necessary first aid measures**

| Eye contact  |   | Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. In case of accidental eye contact, avoid concurrent exposure to the sun or other sources of UV light which may increase the sensitivity of the eyes. |
|--------------|---|--|
| Inhalation   | : | Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.   |
| Skin contact | : | Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. In case of accidental skin contact, avoid concurrent exposure to the sun or other sources of UV light which may increase the sensitivity of skin.         |
| Ingestion    |   | If swallowed, seek medical advice immediately and show this container or label. Keep   |

Ingestion: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

United States Page: 2/11

Product name SIK500-190 PPG PROLUXE SRD SEMI-TRANSPARENT EXTERIOR MATTE TINT

**BASE 190** 

### Section 4. First aid measures

### Most important symptoms/effects, acute and delayed

### Potential acute health effects

**Eye contact** : No known significant effects or critical hazards. Inhalation : No known significant effects or critical hazards. Skin contact : No known significant effects or critical hazards. : No known significant effects or critical hazards. Ingestion

### Over-exposure signs/symptoms

Eye contact : No specific data. Inhalation : No specific data. Skin contact : No specific data. Ingestion : No specific data.

### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments** : No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

### See toxicological information (Section 11)

### Section 5. Fire-fighting measures

### **Extinguishing media**

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented

from being discharged to any waterway, sewer or drain.

**Hazardous thermal** decomposition products : Decomposition products may include the following materials: carbon oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective** equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

**United States** Page: 3/11

Product name SIK500-190 PPG PROLUXE SRD SEMI-TRANSPARENT EXTERIOR MATTE TINT **BASE 190** 

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible. absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

### Precautions for safe handling

**Protective measures Special precautions** 

- : Put on appropriate personal protective equipment (see Section 8).
- : If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

including any incompatibilities

Conditions for safe storage, : Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

> **United States** Page: 4/11

**Product code 00366024** 

Date of issue 24 January 2019 Version 9.03

Product name SIK500-190 PPG PROLUXE SRD SEMI-TRANSPARENT EXTERIOR MATTE TINT **BASE 190** 

# Section 8. Exposure controls/personal protection

#### **Control parameters**

### Occupational exposure limits

| Ingredient name  | Exposure limits              |  |
|------------------|------------------------------|--|
| propane-1,2-diol | IPEL (PPG).<br>TWA: 10 mg/m³ |  |

#### Key to abbreviations

| Α            | = Acceptable Maximum Peak  | S    | = Potential skin absorption                          |
|--------------|--|------|--|
| <b>ACGIH</b> | = American Conference of Governmental Industrial Hygienists.       | SR   | <ul> <li>Respiratory sensitization</li> </ul>        |
| С            | = Ceiling Limit  | SS   | = Skin sensitization                                 |
| F            | = Fume   | STEL | <ul> <li>Short term Exposure limit values</li> </ul> |
| IPEL         | = Internal Permissible Exposure Limit                              | TD   | = Total dust   |
| OSHA         | <ul> <li>Occupational Safety and Health Administration.</li> </ul> | TLV  | = Threshold Limit Value                              |
| R            | = Respirable   | TWA  | = Time Weighted Average                              |
| Z            | = OSHA 29 CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances |      |  |

#### Consult local authorities for acceptable exposure limits.

# procedures

**Recommended monitoring**: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### Appropriate engineering controls

**Environmental exposure** controls

- : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### **Eye/face protection** Skin protection **Hand protection**

**Body protection** 

Safety glasses with side shields.

worn at all times when handling chemical products if a risk assessment indicates this is necessary.

**Gloves** : polyethylene

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

: Chemical-resistant, impervious gloves complying with an approved standard should be

#### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**United States** Page: 5/11

Product name SIK500-190 PPG PROLUXE SRD SEMI-TRANSPARENT EXTERIOR MATTE TINT

**BASE 190** 

### Section 8. Exposure controls/personal protection

**Respiratory protection** 

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

# Section 9. Physical and chemical properties

**Appearance** 

Physical state : Liquid. Color Various Odor : Alcohol-like. Odor threshold : Not available.

рH

: Not available. **Melting point Boiling point** : 100°C (212°F)

Flash point : Closed cup: Not applicable. [Product does not sustain combustion.]

: Not available. **Auto-ignition temperature Decomposition temperature**: Not available. : Not available. Flammability (solid, gas) Lower and upper explosive : Not available.

(flammable) limits

: 0.0005 (butyl acetate = 1) **Evaporation rate** 

: 4.4 kPa (33.33 mm Hg) [room temperature] Vapor pressure

Vapor density : Not available.

: 1.05 Relative density 8.76 Density (lbs/gal)

: Partially soluble in the following materials: cold water. Solubility

Partition coefficient: n-

octanol/water

: Not available.

**Viscosity** : Kinematic (40°C (104°F)): >0.21 cm<sup>2</sup>/s (>21 cSt)

**Volatility** : 78% (v/v), 73.422% (w/w)

% Solid. (w/w) : 26.578

# Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

**Possibility of hazardous** 

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**United States** Page: 6/11

Product name SIK500-190 PPG PROLUXE SRD SEMI-TRANSPARENT EXTERIOR MATTE TINT BASE 190

# Section 10. Stability and reactivity

Conditions to avoid

: When exposed to high temperatures may produce hazardous decomposition products.

Refer to protective measures listed in sections 7 and 8.

Incompatible materials

: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

Hazardous decomposition products

: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

# **Section 11. Toxicological information**

### Information on toxicological effects

### **Acute toxicity**

| Product/ingredient name | Result                   | Species | Dose                   | Exposure |
|-------------------------|--------------------------|---------|------------------------|----------|
| propane-1,2-diol        | LD50 Dermal<br>LD50 Oral |         | 20800 mg/kg<br>20 g/kg | -        |

: There are no data available on the mixture itself.

Conclusion/Summary

Irritation/Corrosion

**Conclusion/Summary** 

Skin: There are no data available on the mixture itself.Eyes: There are no data available on the mixture itself.Respiratory: There are no data available on the mixture itself.

**Sensitization** 

**Conclusion/Summary** 

Skin: There are no data available on the mixture itself.Respiratory: There are no data available on the mixture itself.

**Mutagenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Carcinogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

Reproductive toxicity

**Conclusion/Summary**: There are no data available on the mixture itself.

**Teratogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

United States Page: 7/11

Product name SIK500-190 PPG PROLUXE SRD SEMI-TRANSPARENT EXTERIOR MATTE TINT

**BASE 190** 

# **Section 11. Toxicological information**

### Information on the likely routes of exposure

### Potential acute health effects

Eye contact: No known significant effects or critical hazards.Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

### Over-exposure signs/symptoms

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : No specific data.
Ingestion : No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

**Conclusion/Summary**: There are no data available on the mixture itself. Acrylate components of the mixture

have irritating properties. Prolonged or repeated contact with skin or mucous

membrane may result in irritation symptoms, such as redness, blistering, dermatitis etc. May cause allergic skin reactions with repeated exposure. The inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract. Ingestion may cause nausea, weakness and central nervous system effects. If splashed in the eyes, the liquid may cause irritation and reversible damage. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure

and eye contact.

**Short term exposure** 

Potential immediate : There are no data available on the mixture itself.

effects

**Potential delayed effects**: There are no data available on the mixture itself.

Long term exposure

Potential immediate : There are no data available on the mixture itself.

effects

Potential delayed effects : There are no data available on the mixture itself.

Potential chronic health effects

General : No known significant effects or critical hazards.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

No known significant effects or critical hazards.

United States Page: 8/11

Product code 00366024

Date of issue 24 January 2019 Version 9.03

Product name SIK500-190 PPG PROLUXE SRD SEMI-TRANSPARENT EXTERIOR MATTE TINT BASE 190

# Section 12. Ecological information

#### **Toxicity**

Not available.

### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

| Product/ingredient name | LogPow | BCF | Potential |
|-------------------------|--------|-----|-----------|
| propane-1,2-diol        | -0.92  | -   | low       |

### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

# Section 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

# 14. Transport information

|                             | DOT            | IMDG           | IATA           |
|-----------------------------|----------------|----------------|----------------|
| UN number                   | Not regulated. | Not regulated. | Not regulated. |
| UN proper shipping name     | -              | -              | -              |
| Transport hazard class (es) | -              | -              | -              |
| Packing group               | -              | -              | -              |
| Environmental hazards       | No.            | No.            | No.            |

United States Page: 9/11

Product name SIK500-190 PPG PROLUXE SRD SEMI-TRANSPARENT EXTERIOR MATTE TINT

**BASE 190** 

### 14. Transport information

Marine pollutantNot applicable.Not applicable.substancesNot applicable.

#### **Additional information**

DOT : None identified.IMDG : None identified.IATA : None identified.

Special precautions for user: Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

# Section 15. Regulatory information

#### **United States**

**United States inventory (TSCA 8b)**: All components are listed or exempted.

United States - TSCA 5(e) - Substances consent order:

partially fluorinated alcohol, reaction products

Listed

United States - TSCA 5(a)2 - Proposed significant new use rules:

partially fluorinated alcohol, reaction products

Listed

**SARA 302/304** 

SARA 304 RQ : Not applicable.

**Composition/information on ingredients** 

No products were found.

#### **SARA 311/312**

Classification : Not applicable.

**Composition/information on ingredients** 

No products were found.

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

### Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health: 1 Flammability: 0 Physical hazards: 0

( \* ) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

United States Page: 10/11

Product name SIK500-190 PPG PROLUXE SRD SEMI-TRANSPARENT EXTERIOR MATTE TINT BASE 190

### Section 16. Other information

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)

Health: 1 Flammability: 0 Instability: 0

Date of previous issue : 1/11/2019
Organization that prepared : EHS

the MSDS

**Key to abbreviations** : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

### Indicates information that has changed from previously issued version.

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

United States Page: 11/11