

Technical Data: PRO-880 Updated: 1/16/18



# PRO-880

## Ultra® Clear Adhesive

Clear, Strippable, Non-Staining Wallcovering Adhesive

**Product Number(s):** 12405, 12401

Base: Starch, Water-based

#### **Product Information**

**General Properties:** Premium clear, strippable wallcovering adhesive. PRO-880 is excellent for the retail customer as well as the most discriminating contractor. Undiluted PRO-880 will hang Type II and Type III wallcoverings, and may be diluted for use with lightweight and pre-pasted wallcoverings. PRO-880 applies easily with a roller or pasting machine.

- Maximum wet-tack
- Machinable
- Extended open time
- · Ease of clean up
- LEED compliant
- Strippable with most fabric-back wallcoverings
- Spreads and flows easily

**Recommended Uses:** For all weights of wallcoverings. Strippable when used with fabric-backed vinyl over bare drywall with a cure time of six weeks.

Compatible Coatings: All ROMAN® primers

**Substrates:** Apply over new, bare drywall or over a ROMAN<sup>®</sup> primer

Mildew-Resistant: All Roman products contain biocides for in-can

preservation

## **Specification Data**

Percent Solids: Approximately 32%

Coverage: Up to approx. 330 square feet per gallon

Viscosity: Approximately 40,000 - 45,000 cps

VOC (actual/regulatory): 0% / 0 g/L as calculated per EPA Method 24

Storage: Avoid freezing; keep in cool, dry place

**Drying Time:** Drying time will vary depending on the temperature, ventilation

and humidity of the room.



Technical Data: PRO-880 Updated: 1/16/18

#### Application Instructions

**Surface Preparation:** Surface must be free from grease and other residues, dry, smooth and structurally sound. Check surfaces for paint bonding, loose wallcoverings, damaged wall- board or plaster. Repair all unsound surfaces. Priming of bare drywall is not required with fabric-backed wallcoverings. Before proceeding with any unusual conditions, consult your adhesive or wallcovering supplier.

**Dilution:** May be diluted with up to one pint of clean water per gallon. DO NOT OVER DILUTE.

**Application Method:** Use only when the room temperature is above 50°F. Apply an even coat of adhesive with a pasting machine or roller. Avoid contact with the surface of embossed, textured or delicate wallcoverings. Book wallcovering according to the wallcovering manufacturer's instructions.

**Clean-Up:** Before the adhesive dries, remove any excess with clean water. Additional effort may be required if the adhesive is allowed to contact the surface of embossed or textured vinyls.

### Warning

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Roman Decorating Products, LLC does not endorse the use of any product in an installation that does not meet a Class A fire rating or any applicable code. Testing by a certified laboratory should be conducted to verify that the installation meets a Class A fire rating and to guarantee compliance with all applicable codes. Specifically, if a Roman product is used to hang wallpaper over existing wallpaper, it is unlikely to meet these standards.

## **Limited Warranty**

Roman Decorating Products, LLC warrants that it will replace this product free of charge, if, within 12 months of manufacture, it is found to be defective in material or workmanship. This warranty is in lieu of any other. The exclusive remedy is limited to the replacement of the product and Roman disclaims all liability for consequential, punitive, and special damages. Conditions of use are beyond our control.

#### **Caution**

Store in a cool, dry place. DO NOT FREEZE! Do not take internally. In case of ingestion, seek medical attention. Avoid contact with skin and eyes. Use of skin and eye protection is recommended at all times. If contact with eye occurs, flush with water for 15 minutes. If skin contact occurs, wash with soap and water. Seek medical attention if rash or other symptoms occur. Do not mix with other chemicals. Use in a well-ventilated work area. Close container after each use. Keep out of reach of children.