

• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®
INDUSTRIAL
— CHOICE —

AF1600 SYSTEM
ATHLETIC FIELD STRIPING PAINT AEROSOL

DESCRIPTION AND USES

A fast dry, water-based inverted aerosol striping paint, designed specifically for striping athletic fields. It dries fast in 30 minutes and creates sharp, well defined lines. It is safe for use on grass, smudge resistant, durable and long-lasting.

PRODUCTS

SKU	DESCRIPTION
206043	White
206045	Yellow
206044	Orange
257403	Fluorescent Green
257406	Fluorescent Orange
318191	Navy Blue
318192	Scarlet Red
318193	Royal Blue
318194	Turf Green
318195	Black
318196	Maroon
318197	Purple
318198	Old Gold
318192	Scarlett Red
318193	Royal Blue
318194	Turf Green
318195	Black
318196	Maroon
318197	Purple
318191	Navy

PACKAGING

20 fl. oz. aerosol container (17 oz. weight fill)
12 aerosols/carton

PRODUCT APPLICATION

The Athletic Field Striping sprays are designed for use with the Rust-Oleum Athletic Field Striping Machine item #206346. The Athletic Field Striping Machine has larger diameter wheels to accommodate high grass conditions. Follow machine directions for proper use.

The width of the stripe can be varied from 3 to 6 inches wide by adjusting the position of the can holder on the Striping Machine.

For best results be sure the Striping Machine is in motion before squeezing the trigger and release the trigger before stopping.

The athletic field striping aerosols can also be used with the #2388000 Striping Wand.

Clean valve by spraying upright for 2 to 3 seconds after each use. If valve clogs, carefully remove spray tip and clean in thinner. Do not insert any object into the can opening.

ALKYD	TECHNICAL DATA	IC-05
• TRUSTED QUALITY SINCE 1921 • RUST-OLEUM® INDUSTRIAL — CHOICE —	AF1600 SYSTEM ATHLETIC FIELD STRIPING PAINT AEROSOL	

PHYSICAL PROPERTIES

		ATHLETIC FIELD STRIPING PAINT
Resin Type	Modified Alkyd	
Pigment Type	Varies with color	
Solvents	Acetone, Toluene, VM&P Naphtha, Water, Xylene	
MIR	Maximum value of 0.85	
Fill Weight	17 oz.	
Practical Coverage	Approximately 100-200 linear feet at 3" wide (30-60 m. at 7.6 cm)	
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Tack Free	<30 minutes
	Full Use	30 minutes
Shelf Life	5 years	
Safety Information	For additional information, see SDS	

Calculated values are shown and may vary slightly from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.