

• TRUSTED QUALITY SINCE 1921 •

**RUST-OLEUM®**  
SPECIALTY

**SPECIALTY  
FROSTED GLASS SPRAY**

**DESCRIPTION AND USES**

Rust-Oleum® Frosted Glass Spray creates an etched glass appearance but permits light to transmit through the painted surface. It is designed for use on glass doors, windows, skylights, shower doors, and greenhouses. For a decorative effect, use a stencil to create an etched look on mirrors, shower door exteriors, glass accessories, and more.

**PRODUCTS**

SKU	Description
1903830	Frosted Glass

**PAINTING CONDITIONS**

Use outdoors or in a well ventilated area. Use when temperature is between 50-90°F (10-32°C) and humidity is below 85% to ensure proper drying. Do not apply to surfaces, when heated, exceed 200°F (93°C) or surfaces that are exposed to repeated or continuous water contact, such as the inside of shower doors. Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

**PRODUCT APPLICATION**

**SURFACE PREPARATION**

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry.

**PRODUCT APPLICATION (cont.)**

**APPLICATION**

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle **DO NOT STRIKE CAN**. Contact Rust-Oleum. Hold can upright 10-16" from surface and spray in a steady back and forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply two or more wet coats a few minutes apart for best appearance. A wet coat should appear shiny as it is applied to the surfaces. **WAIT 10 MINUTES FOR FROST EFFECT**. Not for outdoor use. **Do not use near open flame.**

**DRY & RECOAT**

Dry and recoat times are based on 70°F (21°C) and 50% relative humidity. Allow more time at cooler temperatures. Dries completely in 5-10 minutes. May recoat at any time.

**CLEAN-UP**

Clean valve immediately after use by turning can upside down and depressing spray button for 3-5 seconds (some paint will be sprayed out, so be careful to not inadvertently spray yourself or other objects). Clean up wet paint with xylene or mineral spirits. Properly discard empty container. Do not burn or place in home trash compactor.

**CLOGGING**

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve opening.

TECHNICAL DATA

**FROSTED GLASS SPRAY**

**PHYSICAL PROPERTIES**

Physical Properties		FROSTED GLASS SPRAY
Resin Type		Acrylic Lacquer
Pigment Type		Proprietary
Solvents		Acetone, N-Butyl Acetate, Xylene
MIR		1.35 Max
Fill Weight		11 ounces
Practical Coverage at Recommended DFT (assumes 15% material loss)		Approximately 7 sq.ft./can (0.63 m <sup>2</sup> /can)
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	5 minutes
	Fully Dry	10 minutes
	Recoat	Anytime
Dry Heat Resistance		200°F (93°C)
Shelf Life		5 years
Flash Point		-156°F (-104°C)
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.