



**GLASS CLEANER with
RAIN REPELLING PROPERTIES**

DESCRIPTION AND USES

Rust-Oleum® NeverWet Glass Cleaner with Rain Repelling Properties cleans glass completely streak-free while imparting repellent properties to keep glass cleaner, longer. This powerful 2 in 1 formula removes the toughest deposits on exterior glass. Great for automotive use as well as residential glass (interior and exterior).

FEATURES

- Cleans and removes the toughest deposits
- Streak-free formula
- Formulated with rain repelling properties for maximum repellency

PRODUCTS

SKU	Description
293122	NeverWet Glass Cleaner

SPRAYING CONDITIONS

Use when temperatures are between 50°F (10°C) and 90°F (32°C). Avoid spraying in very windy and dusty conditions.

PRODUCT APPLICATION

SURFACE PREPARATION

NeverWet Glass Cleaner is designed to clean glass surfaces. For any other surface, test in an inconspicuous area before continuing.

PRODUCT APPLICATION (cont.)

APPLICATION

Rotate nozzle to “ON” position. Spray NeverWet Glass Cleaner directly onto the glass surface. Using a clean cloth or paper towel, wipe the surface to remove all contaminants. For best results, apply two coats of NeverWet Glass Cleaner to remove the harshest of elements. Once the surface is completely dry, the water beading technology will be activated.

Do not use near open flame.

DRY & RECOAT

Dry and recoat times are based on 70°F and 50% relative humidity. Once wiped off, the surface will be dry. Recoat as needed.

CLEAN-UP

When finished spraying, wipe off nozzle before storing. Properly discard empty container.

**TECHNICAL DATA****GLASS CLEANER with RAIN REPELLING PROPERTIES****PHYSICAL PROPERTIES**

		GLASS CLEANER
Resin Type		NA
Pigment Type		NA
Solvents		Isopropyl Alcohol
Weight	Per Gallon	8.30 lbs.
	Per Liter	1.00 kg
Fill Weight		22 ounces
VOC		262 g/l (2.18 lbs./gal.)
Practical Coverage at Recommended DFT (assumes 15% material loss)		Coverage will vary on surface area and number of coats
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	Once wiped off it will be dry
	Handle	Once wiped off it will be dry
	Recoat	As needed
Shelf Life		2 years
Flash Point		53°F (12°C)
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.