



RAIN REPELLENT

DESCRIPTION AND USES

Rust-Oleum® NeverWet® Rain Repellent is a long lasting, hydrophobic glass treatment that improves visibility and safety while driving in poor weather conditions. A crystal clear, haze-free treatment is ideal for automotive and residential glass. NeverWet Rain Repellent's advanced technology repels rain, mud and dirt up to two times longer than other products.

FEATURES

- Excellent longevity (2X longer lasting)
- Repels rain, mud and dirt
- Easy-to-apply
- Haze-free formula

PRODUCTS

SKU	Description
287337	NeverWet Rain Repellent

SPRAYING CONDITIONS

Use when temperatures are between 50°F (10°C) and 90°F (32°C). Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

PRODUCT APPLICATION

SURFACE PREPARATION

NeverWet Rain Repellent is to be used on glass surfaces only. For best results, clean the glass with a glass cleaner such as NeverWet Glass Cleaner to remove any contaminants from the surface and let dry. Follow the cleaner instructions for best results.

PRODUCT APPLICATION (cont.)

APPLICATION

SHAKE bottle well before use. Rotate nozzle to "ON" position. Wearing gloves, spray NeverWet Rain Repellent onto a clean cloth or paper towel and buff into the windshield in a circular motion. Reapply the product to your cloth as needed until the entire window has been covered.

Once complete, let the treatment sit for 5 minutes. The treatment will appear lightly hazed. Buff off using a clean, dry cloth or paper towel in a circular motion. Apply a second coat of Rain Repellent using the same technique. **Do not use near open flame.**

ADDITIONAL INFORMATION

IMPORTANT! If a slight haze or shine remains after removing the second coat, use a damp clean cloth or paper towel to aide in the removal of any missed treatment.

To fully remove rain repellent, use a soft scrub with cold water and wipe the glass until the coating is gone.

DRY & RECOAT

Dry and recoat times are based on 70°F and 50% relative humidity. Allow the treatment to dry for 5 minutes and buff off using a clean cloth or paper towel. The treatment will be fully dry in 10 minutes.

CLEAN-UP

When finished spraying, wipe off nozzle before storing. Properly discard empty container.

**TECHNICAL DATA****RAIN REPELLENT****PHYSICAL PROPERTIES**

		RAIN REPELLENT
Resin Type		NA
Pigment Type		NA
Solvents		Methyl Ethyl Ketone, Isopropyl Alcohol
Weight	Per Gallon	7.0 lbs.
	Per Liter	0.84 kg
Fill Weight		11 ounces
VOC		569 g/l (5.48 lbs./gal.)
Practical Coverage at Recommended DFT (assumes 15% material loss)		Coverage will vary on surface area and number of coats
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Handle	Buff off after 5 minutes
	Recoat	Recoat after 5 minutes
	Full Cure	10 minutes
Shelf Life		2 years
Flash Point		23°F (-5°C)
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.