

Fireplace Mortar

1 PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: Fireplace Mortar

SDS Number: 3

Product Code: 63, 3063 **Revision Date:** 6/5/2019

Version: 1

Chemical Family: Silicate mortars

Product Description: High Temperature Mortar (Black)

Product Use: Repair chips or cracks, repointing mortar joints in fire brick; bonding fire bricks together.

Instructions: Not for exterior use. Masonry to masonry only, will not adhere to metal. Heat curing to 500 F required.

Supplier Details: Rutland Products

7 Crabtree Road Jacksonville, IL 62650

Contact: Faith Nergenah, Brian Miller

Phone: 217-245-7810 **Fax:** 217-245-1194

Email: faith@rutland.com bmiller@rutland.com

Web: www.rutland.com

Emergency: CHEMTREC (800) 424-9300 POISON CONTROL (800) 222-1222

HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Health, Skin corrosion/irritation, 2

Health, Serious Eye Damage/Eye Irritation, 2 B

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: WARNING

GHS Hazard Pictograms:

2



GHS Hazard Statements:

H315 - Causes skin irritation H320 - Causes eye irritation

GHS Precautionary Statements:

P264 - Wash hands thoroughly after handling.

P280 - Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical advice/attention. P362 + P364 - Take off contaminated clothing and wash it before reuse.

Hazards not Otherwise Classified (HNOC) or not Covered by GHS

Route of Entry: Eyes; Skin; Ingestion

Skin Contact: May cause irritation. **Eye Contact:** May cause irritation.

Ingestion: Ingestion is not an applicable route of entry for intended use. May be harmful if swallowed.

SDS Number: 3 Page: 1 / 4 Revision Date: 6/5/2019



Fireplace Mortar

3 COMPOSITION/INFORMATION OF INGREDIENTS

Chemical Ingredients:	
CAS#	% Chemical Name:
1332-58-7 1344-09-8 1333-86-4 1310-73-2 13983-17-0	Kaolin Silicic acid, sodium salt Carbon black Sodium hydroxide (NaOH) Calcium Metasilicate (Wollastonite)

Percentages withheld, Trade secret

4 FIRST AID MEASURES

Inhalation: Remove to fresh air. Seek medical attention if cough or other symptoms develop or persist.

Skin Contact: Wash with plenty of water. Get medical attention if irritation develops or persists.

Eye Contact: Immediately flush eyes with plenty of water. After initial flushing, remove contact lenses and continue flushing for at

least 15 minutes. If effects occur, consult a physician, preferably an ophthalmologist. May cause injury due to

mechanical action.

Ingestion: Do not induce vomiting. Seek immediate medical attention

FIRE FIGHTING MEASURES

Flash Point: None

5

Flash Point Method: Not Applicable
Burning Rate: Not Applicable
Autoignition Temp: Not Applicable
LEL: Not Applicable
UEL: Not Applicable

Use any standard agent - choose the one most appropriate for type of surrounding fire.

6 ACCIDENTAL RELEASE MEASURES

Absorb spilled material and place in appropriate container for disposal.

7 HANDLING AND STORAGE

Handling Precautions: Avoid contact with eyes, skin, or clothing. Use with adequate ventilation. Avoid prolonged and repeated

contact with skin. Wash thoroughly after handling. Keep away from food and drinking water.

Storage Requirements: Store in cool/dry area.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: A system of local and/or general exhaust is recommended to keep employee exposures as low as

possible.

Personal Protective

Equipment:

EYES AND FACE: Wear safety glasses with side shields. Chemical splash goggles and face shield

(ANSI Z87.1 or approved equivalent) are recommended.

SKIN: Wear protective clothing, including long sleeves and gloves, to prevent skin contact. Thoroughly

wash clothing before reuse.

RESPIRATORY: In case of insufficient ventilation, wear suitable respiratory equipment.

SDS Number: 3 Page: 2 / 4 Revision Date: 6/5/2019



Fireplace Mortar

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Black

Physical State: Paste Odor: Odorless **Odor Threshold:** Not Applicable Molecular Formula: Not Available Particle Size: Not Applicable Solubility: Soluble in water Spec Grav./Density: 1.76 **Softening Point:** Not Applicable

Spec Grav./Density:1.76Softening Point:Not ApplicableViscosity:Not ApplicablePercent Volatile:Not AvailableSaturated VaporNot AvailableHeat Value:Not Available

Concentration:

Boiling Point: Not Available Freezing/Melting Pt.: Not Available Flammability: Not Available **Flash Point:** Not Available **Partition Coefficient:** Not Available Octanol: Not Available **Vapor Pressure:** Not Available Vapor Density: Not Available pH: 11-12 VOC: Not Available Not Available Evap. Rate: Not Available **Bulk Density: Auto-Ignition Temp:** Molecular weight: Not Available Not Available **Decomp Temp:** Not Available UFL/LFL: Not Available

10 STABILITY AND REACTIVITY

Reactivity: This product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical Stability: Product is stable under normal conditions.

Conditions to Avoid: Contact with incompatible materials

Materials to Avoid: Alkali sensitive metals and alloys.

Hazardous Decomposition: No hazardous decomposition productions are known.

Hazardous Polymerization: Will not occur.

11 TOXICOLOGICAL INFORMATION

No data available.

12 ECOLOGICAL INFORMATION

No information available

13 DISPOSAL CONSIDERATIONS

Dispose of this product in accordance with all applicable local, state and federal regulations.

14 TRANSPORT INFORMATION

Not Regulated

SDS Number: 3 Page: 3 / 4 Revision Date: 6/5/2019



Fireplace Mortar

15

REGULATORY INFORMATION

RQ (CAS#) Substance - Reg Codes

Kaolin (1332-58-7) OSHAWAC, PA, TSCA, TXAIR

RQ(1000LBS), Sodium hydroxide (Na(OH)) (1310-73-2) CERCLA, CSWHS, MASS, OSHAWAC, PA, TSCA, TXAIR

Silicic acid, sodium salt (1344-09-8) TSCA

Calcium silicate (1344-95-2) MASS, OSHAWAC, PA, TSCA, TXAIR

Carbon black (1333-86-4) MASS, OSHAWAC, PA, PROP65, TSCA, TXAIR



This product can expose you to chemicals including Carbon black (airborne, unbound particles of respirable size), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Regulatory Code Legend

RQ = Reportable Quantity

OSHAWAC = OSHA Workplace Air Contaminants

PA = PA Right-To-Know List of Hazardous Substances

TSCA = Toxic Substances Control Act

TXAIR = TX Air Contaminants with Health Effects Screening Level

CERCLA = Superfund clean up substance

CSWHS = Clean Water Act Hazardous substances

MASS = MA Massachusetts Hazardous Substances List

PROP65 = CA Prop 65

16

OTHER INFORMATION

PREPARED BY: Brian Miller

MANUFACTURER DISCLAIMER: The information presented herein is believed to be accurate but is not warranted. Recipients are advised to confirm in advance that the information is current, applicable and suitable to their circumstances.

Revision Date: 6/5/2019

SDS Number: 3 Page: 4 / 4 Revision Date: 6/5/2019