

# SAFETY DATA SHEET

Revision Date 22-May-2018

Version 3

1. IDENTIFICATION			
<u>Product identifier</u> Product Name	Rain-X Original Glass Treatment		
<u>Other means of identification</u> Product Code Document	11890 SKU: 800002242, 800002243, 800002245, 800002250		
Recommended use of the chemical and restrictions on useRecommended UseGlass Treatment. Consumer Use.Uses advised againstNo information available			
Details of the supplier of the safety Supplier Address ITW Global Brands	data sheet_ Manufacturer Address Manufactured and Distributed by:		
16200 Park Row, Suite 120 Houston, TX 77084 <u>Distributor</u>	May Also Be Distributed by:		
Company Phone Number 24-hour emergency phone number	1-855-888-1988 (CHEMTREC) 1-800-424-9300 or 1-703-527-3887 (U.S.) (RMPDC) 1-877-504-9352 (U.S.)		
E-mail address	SDS@itwgb.com		
2. HAZARDS IDENTIFICATION			

## **Classification**

## **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3

## Label elements

**Emergency Overview** 

## <u>Signal word</u> Warning

Causes serious eye irritation May cause drowsiness or dizziness



## Appearance Clear Colorless

Physical state Liquid

**Precautionary Statements - Prevention** 

Wash face, hands and any exposed skin thoroughly after handling Wear eye/face protection Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor/physician if you feel unwell

## **Precautionary Statements - Storage**

Store in a well-ventilated place. Keep container tightly closed Store locked up

**Precautionary Statements - Disposal** Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Not applicable

# Other Information

- Not applicable

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Substance(s)

Chemical Name	CAS No	Weight-%
ETHANOL	64-17-5	30 - 60
ACETONE	67-64-1	10 - 30
Isopropanol	67-63-0	10 - 30

Any concentration shown as a range is due to batch variation.

## 4. FIRST AID MEASURES

#### Description of first aid measures

General advice	Get medical advice/attention if you feel unwell.		
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.		
Skin contact	IF ON SKIN:. Wash skin with soap and water. If skin irritation persists, call a physician. Take off contaminated clothing and wash before reuse.		
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.		
Ingestion	IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician.		
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.		

Most important symptoms and effects, both acute and delayed

#### Symptoms

See section 2 for more information.

## Indication of any immediate medical attention and special treatment needed

Note to physicians

Treat symptomatically.

## **5. FIRE-FIGHTING MEASURES**

## Suitable extinguishing media

Dry chemical, CO2, sand, earth, water spray or regular foam

## Unsuitable extinguishing media

CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient. Do not use a solid water stream as it may scatter and spread fire.

#### Specific hazards arising from the chemical

Flammable vapors may be present even at temperatures below the flash point.

Explosion data	
Sensitivity to Mechanical Impact	No
Sensitivity to Static Discharge	Ma

No information available. May be ignited by heat, sparks or flames.

## Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

## Personal precautions, protective equipment and emergency procedures

Personal precautions	Ensure adequate ventilation, especially in confined areas. Avoid contact with skin, eyes and inhalation of vapors. Use personal protective equipment as required. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).		
Environmental precautions			
Environmental precautions	See section 12 for additional ecological information.		
Methods and material for containment and cleaning up			
Methods for containment	Prevent further leakage or spillage if safe to do so.		
Methods for cleaning up	Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.		
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.		

# 7. HANDLING AND STORAGE

#### Precautions for safe handling

Advice on safe handling	Handle in accordance with good industrial hygiene and safety practice. Avoid breathing			
	vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling.			
	Wash contaminated clothing before reuse. Use personal protective equipment as required.			

## Conditions for safe storage, including any incompatibilities

 Storage Conditions
 Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep out of the reach of children.

 Incompatible materials
 None known

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Control parameters

## **Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ETHANOL	STEL: 1000 ppm	TWA: 1000 ppm	IDLH: 3300 ppm
64-17-5		TWA: 1900 mg/m <sup>3</sup>	TWA: 1000 ppm
		(vacated) TWA: 1000 ppm	TWA: 1900 mg/m <sup>3</sup>
		(vacated) TWA: 1900 mg/m <sup>3</sup>	_
ACETONE	STEL: 500 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 250 ppm	TWA: 2400 mg/m <sup>3</sup>	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m <sup>3</sup>
		(vacated) TWA: 1800 mg/m <sup>3</sup>	-
		(vacated) STEL: 2400 mg/m <sup>3</sup> The	
		acetone STEL does not apply to the	
		cellulose acetate fiber industry. It is	
		in effect for all other sectors	
		(vacated) STEL: 1000 ppm	
Isopropanol	STEL: 400 ppm	TWA: 400 ppm	IDLH: 2000 ppm
67-63-0	TWA: 200 ppm	TWA: 980 mg/m <sup>3</sup>	TWA: 400 ppm
		(vacated) TWA: 400 ppm	TWA: 980 mg/m <sup>3</sup>
		(vacated) TWA: 980 mg/m <sup>3</sup>	STEL: 500 ppm
		(vacated) STEL: 500 ppm	STEL: 1225 mg/m <sup>3</sup>
		(vacated) STEL: 1225 mg/m <sup>3</sup>	-

NIOSH IDLH Immediately Dangerous to Life or Health

#### **Other Information**

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

## Appropriate engineering controls

Engineering Controls	Showers Eyewash stations Ventilation systems
Individual protection measures, su	ch as personal protective equipment
Eye/face protection	Wear safety glasses or goggles if splashing is likely to occur.
Skin and body protection	Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.
Respiratory protection	Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

## Information on basic physical and chemical properties

Physical state Appearance Odor Odor threshold	Liquid Clear Colorless Alcohol No information available	
<u>Property</u> pH Melting point / freezing point	<u>Values</u> 1.5 - 2.5 No information available	Remarks • Method
Boiling point / boiling range Flash point Evaporation rate	No information available -3 °C / 27 °F No information available	Setaflash Closed Cup

Flammability (solid, gas) Flammability Limit in Air	No information available
Upper flammability limit:	No information available
Lower flammability limit:	No information available
Vapor pressure	No information available
Vapor density	No information available
Relative density	0.810 - 0.812
Water solubility	Soluble in water
Solubility in other solvents	No information available
Partition coefficient	No information available
Autoignition temperature	No information available
Decomposition temperature	No information available
Kinematic viscosity	No information available
Dynamic viscosity	No information available
Explosive properties	No information available
Oxidizing properties	No information available
Other Information	
Softening point	No information available
Molecular weight	No information available

Molecular weight VOC Content (%) Density Bulk density No information available No information available 89 0.806 - 0.808 g/cm3 No information available

# **10. STABILITY AND REACTIVITY**

#### **Reactivity**

Stable under normal use

# Chemical stability

Stable under normal conditions

## Possibility of Hazardous Reactions

None under normal processing.

#### Conditions to avoid

Heat, flames and sparks. Excessive heat.

# Incompatible materials

None known

# Hazardous Decomposition Products

Carbon oxides

# **11. TOXICOLOGICAL INFORMATION**

## Information on likely routes of exposure

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50	
Ingestion	Ingestion may cause irritation to mucous membranes. May be harmful if swallowed.			
Skin contact	May cause skin irritation a	May cause skin irritation and/or dermatitis.		
Eye contact	Contact with eyes may cau	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.		
Inhalation	May cause irritation of resp	May cause irritation of respiratory tract. May be harmful if inhaled.		

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
ETHANOL	= 7060 mg/kg (Rat)	-	= 124.7 mg/L (Rat)4 h
64-17-5			
ACETONE	= 5800 mg/kg (Rat)	-	= 50100 mg/m <sup>3</sup> (Rat) 8 h
67-64-1			
Isopropanol	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	= 72600 mg/m <sup>3</sup> (Rat) 4 h

67-63-0			
	67-63-0		

## Information on toxicological effects

Symptoms

No information available.

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization	No informatio	a availabla			
Germ cell mutagenicity	No information available. No information available.				
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.				
Chemical Name			NTP	OSHA	
ETHANOL	A3	-	Known	X	
64-17-5				~	
Isopropanol	-	Group 3	-	Х	
67-63-0		•			
A2 - Suspected Human C A3 - Animal Carcinogen IARC (International Age Group 1 - Carcinogenic to Not classifiable as a huma NTP (National Toxicolog Known - Known Carcinog	ncy for Research on Cancer Humans an carcinogen Iy Program)	)	of Labor)		
Chronic toxicity Target Organ Effects	adverse liver	effects. Contains a known	marrow and blood-forming or suspected reproductive iver, Reproductive System	toxin.	
The following values are ATEmix (oral) ATEmix (dermal) ATEmix (inhalation-de	9100 mg/kg 27060 mg/kg		ument .		

## **12. ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

0.75 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

#### Persistence and degradability

No information available.

## **Bioaccumulation**

No information available.

## Mobility

Disperses in water.

Chemical Name	Partition coefficient
ETHANOL 64-17-5	-0.32
ACETONE 67-64-1	-0.24
Isopropanol 67-63-0	0.05

## Other adverse effects

No information available

# 13. DISPOSAL CONSIDERATIONS

Waste treatment methods	
Disposal of wastes	Disposal should be in accordance with applicable regional, national and local laws and regulations. Recover or recycle if possible. This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).
Contaminated packaging	Do not reuse container.
US EPA Waste Number	D001, U002

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
ETHANOL	Toxic
64-17-5	Ignitable
ACETONE 67-64-1	Ignitable
Isopropanol 67-63-0	Toxic Ignitable

## 14. TRANSPORT INFORMATION

<u>DOT</u> UN/ID no Proper shipping name: Hazard Class Packing Group	UN 1987 Alcohols, n.o.s, (Ethyl alcohol), Limited Quantity (LQ) 3 II
IATA UN/ID no Proper shipping name: Hazard Class Packing Group	UN 1987 Alcohols, n.o.s, (Ethyl alcohol), Limited Quantity (LQ) 3 II
IMDG UN/ID no Proper shipping name: Hazard Class Packing Group	UN 1987 Alcohols, n.o.s, (Ethyl alcohol), Limited Quantity (LQ) 3 II

Internet the set because the state		
International Inventories		
TSCA	Complies	
DSL/NDSL	Complies	
EINECS/ELINCS	Complies	
ENCS	Not determined	
IECSC	Not determined	
KECL	Not determined	
PICCS	Not determined	
AICS	Not determined	

Legend:

\_ \_ \_

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

## US Federal Regulations

## SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Isopropanol - 67-63-0	1.0
SARA 311/312 Hazard Categories	
Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

#### CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

#### <u>CERCLA</u>

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
ACETONE	5000 lb	-	RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ

## US State Regulations

#### California Proposition 65

Ethanol is only considered a Proposition 65 developmental hazard when it is ingested as a alcoholic beverage, Intended use for this product does not include consumption

Chemical Name	California Proposition 65	
ETHANOL - 64-17-5	Carcinogen	
	Developmental	

## U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ETHANOL	Х	X	X
64-17-5			
ACETONE	Х	X	X
67-64-1			
Isopropanol	Х	X	X
67-63-0			
WATER	-	-	X X
7732-18-5			

#### U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

#### WHMIS Hazard Class

D2A - Very toxic materials, B2 - Flammable liquid, D2B - Toxic materials

## **16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION**

NFPA	
HMIS	

#### Health hazards 2 Health hazards 2

- Flammability 3 Flammability 3
- Instability 0 Physical hazards 1

Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date	22-May-2018	
Revision Note		4

**Disclaimer** 

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet