



DRIVEWAY SEALER UNSANDED

◆ The Pro's Choice Since 1936



Sakrete® Driveway Sealer Unsanded is an easy-stir sealer formula designed to beautify blacktop surfaces while resisting gasoline and oil drippings.

Features:

- One-coat easy application
- Renews asphalt surface with smooth rich black finish
- For light to moderate traffic areas
- Provides UV protection - slows aging and resists fading

Use For:

- Sealing and protecting driveways

Coverage:

Approximately 350 - 450 ft² (33 - 42 m²) per 4.75 gal (18 L) pail. Coverage will vary with surface texture and porosity.

Color:

Black

Preparation:

1. Clean surface to be sealed. To avoid peeling and flaking of seal coat, remove all dirt, loose and foreign materials.
2. Scrape off oil spots and scrub with strong detergent or cover with oil spot primer. Rinse thoroughly. Flush off entire area using hard stream of water if strong detergent is used for cleaning .
3. Stir product to uniform consistency before application. Liquid may have brown appearance but dries black.
4. Begin at highest area of pavement. Pour a 6 - 10" (153 - 254 mm) wide ribbon of sealer across the driveway.
5. For application using combo brush/squeegee applicator, use rubber blade of brush/ squeegee applicator to distribute product evenly. Then draw brush through applied area with long, even strokes to achieve uniform, thin coating without puddling in surface voids. Tap brush on uncoated area to remove excess before final brush stroke to blend "stops and starts".
6. Repeat steps 4 and 5 on uncoated areas, working toward lower areas.

NOTE: Best results come from a single, thin application.

APPLY ONE COAT ONLY. DO NOT APPLY THICK/HEAVY COATING. EXCESSIVE MATERIAL CAN CAUSE TRACKING.

Repairs prior to sealcoating:

- Fill cracks up to 1/2" (12 mm) wide with Sakrete Blacktop Filler.
- Fill cracks wider than 1/2" (12 mm) with Sakrete Trowelable Blacktop Patch.
- Repair pot holes with Sakrete All Weather Blacktop Patch or Sakrete US Cold Patch.

NOTE: When making repairs using Sakrete All Weather Blacktop Patch allow 90 days for curing before sealcoating the repair area. US Cold Patch can be sealed in 30 days.

Helpful Tips:

- In sunny, hot weather, pavements may reach temperatures high enough to "cook dry" sealer. Mist area with fine water spray to cool pavement about an hour before sealer application. Sweep out puddles or any standing water. Wait to apply sealer if pavement is still glistening wet. (This step can be skipped if sealer is applied early in the day, before pavement heats up.)
- In cooler weather, do not mist pavement. If practical, apply sealer early in the day to optimize drying during warmer daylight hours.
- Exposure to sunlight warms pavement surfaces to assist in proper curing.
- Curing time varies with weather conditions. Sealed areas can usually be opened to traffic after 24 hours. Test before use.
- Do not apply to concrete surfaces. Allow new blacktop paving to cure one year before sealcoating.

NOTE: Proper application and installation of all Sakrete products are the responsibility of the end user.

Curing:

Best results are achieved with temperatures of 70°F to 90°F (21°C to 32°C) during application. Cooler temperatures and/or high humidity may lengthen curing time. **DO NOT APPLY IF NIGHT TIME TEMPERATURES WILL FALL BELOW 50°F (10°C), OR RAIN IS PREDICTED WITHIN 24 HOURS OF APPLICATION.** Irreparable damage to the curing film may result. Allow coating to receive 2 or more hours exposure to sunlight during drying for best results.

Safety:

READ and UNDERSTAND the Safety Data Sheet (SDS) before using this product. **WARNING:** Wear protective clothing and equipment. For emergency information, call CHEMTREC at 800-424-9300 or 703-527-3887 (outside USA).

KEEP OUT OF REACH OF CHILDREN.

Limited Product Warranty:

The manufacturer warrants that this product shall be of merchantable quality when used or applied in accordance with the manufacturer's instructions. This product is not warranted as suitable for any purpose other than the general purpose for which it is intended. This warranty runs for one (1) year from the dates the product is purchased. **ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ON THIS PRODUCT IS LIMITED TO THE DURATION OF THIS WARRANTY.** Liability under this warranty is limited to replacement or defective products or, at the manufacturer's option, refund of the purchase price. **CONSEQUENTIAL AND INCIDENTAL DAMAGES ARE NOT RECOVERABLE UNDER THIS WARRANTY.**