

STANLEY® FATMAX® AUTO-LOCK TAPE RULES

- Auto-Lock Mode: For control and long blade life.
- Manual Mode: Disengage lock for speed marking.
- Detachable Hook: Allows user to work efficiently in different applications.
- 11' Blade Standout*: For reach and efficiency.
- BladeArmor®: 10X** blade life.
- Hook Storage: Securely stores hook on tape when not in use.
- Tether-ready: Through-hole for attaching a tool lanyard when working at heights. (Lanyard not included.)
- Made in the USA with global components.
- Mylar® film extends life of entire blade.



Product #	Blade Length (ft)	Blade Length (m)	Blade Width (in)	Graduation
FMHT333165	16	–	1-1/4	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.
FMHT33338	25	–	1-1/4	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.
FMHT33504	26	8	1-1/4	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Major scale numbered in consecutive meters. Minor scale numbered in consecutive 10 cm repeated every 100 cm.
FMHT33348	30	–	1-1/4	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.

*Standout claims based on maximum performance

**Compared to STANLEY 30-419

STANLEY® FATMAX® PREMIUM TAPE RULES W/ 13' BLADE STANDOUT

- 13' blade standout.
- 1-1/4" wide blade for easy readability.
- BladeArmor®: 10X** blade life.
- High-impact ABS case with durable rubber holds up to heavy use.
- AirLock® slide lock for durability and comfort.
- Rubber grip provides comfortable, slip-resistant hold.
- Three-rivet, corrosion-resistant Tru-Zero™ end hook for accurate measurements.



Product #	Blade Length (ft)	Blade Length (m)	Blade Width (in)	Stud Markings (in)	Graduation
FMHT33969	16	–	1-1/4	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.
FMHT33502	25	–	1-1/4	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.
XTHT36007	26	8	1-1/4	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Major scale numbered in consecutive meters. Minor scale numbered in consecutive 10 cm repeated every 100 cm.
FMHT33509	35	–	1-1/4	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.

*Standout claims based on maximum performance

Mylar® is a registered trademark of DuPont Teijin Films.

Country of origin accurate at time of printing, consult www.protoindustrial.com for updated information.



STANLEY® FATMAX® MAGNETIC TAPE RULES

- 11' blade standout.
- 1-1/4" wide blade for easy readability.
- AirLock® slide lock for durability and comfort.
- Mylar® film extends life of entire blade.
- Tru-Zero™ magnetic hook for accurate measurements in all positions.
- Powerful rare earth magnet securely holds to steel surfaces.
- High-impact ABS case with durable rubber holds up to heavy use.
- Plastic blade lock makes locking and unlocking easy.
- Rubber grip provides comfortable, slip-resistant hold.



Product #	Blade Length (ft)	Blade Length (m)	Blade Width (in)	Stud Markings (in)	Graduation
FMHT33865S	25	—	1-1/4	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.
FMHT33866	26	8	1-1/4	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Major scale numbered in consecutive meters. Minor scale numbered in consecutive 10 cm repeated every 100 cm.

*Standout claims based on maximum performance

STANLEY® FATMAX® TAPE RULES W/ 11' BLADE STANDOUT

- 11' blade standout.
- 1-1/4" wide blade for easy readability.
- BladeArmor® coating on the first 3" maximizes durability of the blade.
- Mylar® film extends life of entire blade.
- High-impact ABS case with durable rubber holds up to heavy use.
- Plastic blade lock makes locking and unlocking easy.
- Rubber grip provides comfortable, slip-resistant hold.
- Three-rivet, corrosion-resistant Tru-Zero™ end hook for accurate measurements.



Product #	Blade Length (ft)	Blade Length (m)	Blade Width (in)	Stud Markings (in)	Graduation
33-716	16	—	1-1/4	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.
33-725	25	—	1-1/4	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.
33-726	26	8	1-1/4	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Major scale numbered in consecutive meters. Minor scale numbered in consecutive 10 cm repeated every 100 cm.
33-730	30	—	1-1/4	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.
33-805	33	10	1-1/4	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Major scale numbered in consecutive meters. Minor scale numbered in consecutive 10 cm repeated every 100 cm.
33-735	35	—	1-1/4	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.
33-740	40	—	1-1/4	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.

*Standout claims based on maximum performance

Graduated in 16ths of an inch.

STANLEY® FATMAX® KEYCHAIN TAPE RULE

- 3' blade standout.
- Polymer-coated blade withstands abrasion.
- Convenient and lightweight. Handy for quick measurements.
- Compact size fits in the pocket.
- Durable key ring makes it easy to carry anywhere.



Product #	Blade Length (ft)	Blade Width (in)	Stud Markings (in)	Graduation
FMHT33706	6	1/2	16, 19.2	Scale numbered in consecutive inches and feet. First twelve inches graduated in 32nds of an inch. Remainder in 16ths of an inch.

STANLEY® POWERLOCK® TAPE RULES WITH BLADEARMOR® COATING

- 8' blade standout.
- BladeArmor® coating on the first 3" maximizes durability of the blade.
- Mylar® film extends life of entire blade.
- Compact case design.
- Chrome high-impact ABS case is job site tough.
- Secure blade lock won't creep during measurements.
- Three-rivet, corrosion-resistant Tru-Zero™ end hook for accurate measurements.



Product #	Blade Length (ft)	Blade Width (in)	Stud Markings (in)	Graduation
33-516	16	1	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.
33-525	25	1	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.
33-530	30	1	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.

STANLEY® POWERLOCK® STAINLESS STEEL TAPE RULES

- 7' blade standout.
- Stainless steel blade and spring for rust resistance.
- Stainless steel belt clip, hook and screws for rust resistance.
- Nylon blade coating to help protect the blade for long life.
- Compact case design.
- Back-side blade print for vertical measurements.
- Tru-Zero™ hook for accurate inside and outside measurements.



Product #	Blade Length (ft)	Blade Length (m)	Blade Width (in)	Stud Markings (in)	Graduation
STHT33456	16	5	3/4	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Major scale numbered in consecutive meters. Minor scale numbered in consecutive 10 cm repeated every 100 cm.
STHT33457	26	8	1	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Major scale numbered in consecutive meters. Minor scale numbered in consecutive 10 cm repeated every 100 cm.

Mylar® is a registered trademark of DuPont Teijin Films.



STANLEY® POWERLOCK® TAPE RULES

- 7' blade standout (excludes 33-116 and 33-158).
- Mylar® film extends life of entire blade.
- High-impact, chrome plated ABS case.
- Secure blade lock won't creep during measurements.
- Corrosion-resistant Tru-Zero™ end hook for accurate measurements.



Product #	Blade Length (ft)	Blade Length (m)	Blade Width (in)	Stud Markings (in)	Graduation
33-116	16	–	3/4	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. First twelve inches graduated in 32nds of an inch. Remainder in 16ths of an inch. Bottom edge: Numbered in consecutive inches. First twelve inches graduated in 32nds of an inch. Remainder in 16ths of an inch.
33-158	16	5	3/4	16, 19.2	Top edge: Major scale numbered in consecutive inches. First twelve inches graduated in 32nds of an inch. Remainder graduated in 16ths of an inch. Marked every 12 inches. Bottom edge: Major scale numbered in consecutive meters. Minor scale numbered in consecutive 10 cm repeated every 100 cm.
33-425	25	–	1	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.
33-428	26	8	1	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Major scale numbered in consecutive meters. Minor scale numbered in consecutive 10 cm repeated every 100 cm.
33-430	30	–	1	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.
33-835	35	–	1	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.

STANLEY® POWERLOCK® METAL CASE TAPE RULES

- Durable die-cast metal case.
- Mylar® film extends life of entire blade.
- Secure blade lock won't creep during measurements.
- Corrosion-resistant Tru-Zero™ end hook for accurate measurements.



Product #	Blade Length (ft)	Blade Length (m)	Blade Width (in)	Stud Markings (in)	Graduation
33-212	12	–	1/2	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. First twelve inches graduated in 32nds of an inch. Remainder in 16ths of an inch. Bottom edge: Numbered in consecutive inches. First twelve inches graduated in 32nds of an inch. Remainder in 16ths of an inch.
33-215	12	3.5	1/2	16, 19.2	Top edge: Numbered in consecutive inches. First twelve inches graduated in 32nds of an inch. Remainder graduated in 16ths of an inch. Marked every 12 inches. Bottom edge: Major scale numbered in consecutive meters. Intermediate scale numbered in consecutive 100 mm repeated every meter. Minor scale numbered in consecutive 10 mm repeated every 100 mm. Graduated in mm.
33-272	12	–	1/2	16, 19.2	Top edge: Numbered in consecutive inches. First six inches graduated in 0.03125". Remainder graduated in 0.0625". Bottom edge: Numbered in consecutive 0.10", repeated every inch. Graduated in 0.02" for the first six inches. Remainder graduated in 0.10".
33-312	12	–	3/4	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. First twelve inches graduated in 32nds of an inch. Remainder in 16ths of an inch. Bottom edge: Numbered in consecutive inches. First twelve inches graduated in 32nds of an inch. Remainder in 16ths of an inch.

STANLEY® POWERLOCK® POCKET TAPE RULE

- Polymer-coated blade withstands abrasion for long life.
- Chrome high-impact ABS case is job site tough.
- Slim case fits easily in pocket.
- Secure blade lock won't creep during measurements.
- Corrosion-resistant Tru-Zero™ end hook for accurate measurements.
- Back of blade provides scale that measures up to 3' diameter graduated in 1/64".



Product #	Blade Length (ft)	Blade Width (in)	Stud Markings (in)	Graduation
33-115	10	1/4	16, 19.2	Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches. First twelve inches graduated in 32nds of an inch. Remainder in 16ths of an inch.

STANLEY® POWERLOCK® KEYCHAIN TAPE RULE

- Polymer-coated blade withstands abrasion.
- Durable key ring makes it easy to take anywhere.
- Convenient and lightweight.



Product #	Blade Length (ft)	Blade Width (in)	Stud Markings (in)	Graduation
39-130	3	1/4	16	Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches. First twelve inches graduated in 32nds of an inch. Remainder in 16ths of an inch.

Mylar® is a registered trademark of DuPont Teijin Films.

Country of origin accurate at time of printing, consult www.protoindustrial.com for updated information.



STANLEY® VALUE PACK

Product #: 90-082

- 7' blade standout.
- Mylar® film extends life of entire blade.
- High-impact, chrome plated ABS case.
- Secure blade lock won't creep during measurements.
- Corrosion-resistant Tru-Zero™ end hook for accurate measurements.



Contents	Description
1	Tape Rule (33-425)
1	Knife (10-099)

SHORT TAPE RULES

STANLEY® PREMIUM TAPE RULES

- Rugged case design ABS structure core surrounded by rubber for superior impact resistance.
- Integrated lock protection lock button guarded by large rubber pad in case of drop.
- 10' standout best standout of MPP tapes for better efficiency.
- 1-1/8' wide blade premium feel with large easy to read numbers.



Product #	Blade Length (ft)	Blade Width (in)	Stud Markings (in)	Graduation
STHT33594S	16	1-1/8	16, 19.2	GraduationTop edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.
STHT33596LW	25	1-1/8	16, 19.2	GraduationTop edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.
STHT33597S	30	1-1/8	16, 19.2	GraduationTop edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.

STANLEY® LEVERLOCK® FRACTIONAL TAPE RULES WITH MAGNETIC TIP

- Push-release self-locking mechanism controls blade retraction.
- Polymer-coated blade withstands abrasion.
- Magnetic end hook holds securely to metal surfaces.
- High-impact ABS case with durable rubber holds up to heavy use.
- Corrosion-resistant Tru-Zero™ end hook for accurate measurements.
- fractional read blade graphics for quick and easy measurements.



Product #	Blade Length (ft)	Blade Width (in)	Stud Markings (in)	Color	Graduation
STHT33281	25	1	16, 19.2	Yellow	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.
STHT33270	25	1	16, 19.2	Orange	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.

STANLEY® LEVERLOCK® TAPE RULE

- Automatic blade lock holds blade securely in position.
- Write-on label for repeated use with carpenter pencil.
- Non-marring frictionless base to help protect work surface.
- Easy inside/outside measurements.
- 1.5X* stronger anti-glare blade.



Product #	Blade Length (ft)	Blade Length (m)	Blade Width (in)	Graduation
STHT30810	12	–	1/2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Numbered in consecutive inches. First twelve inches graduated in 32nds of an inch. Remainder in 16ths of an inch.
STHT30812	16	–	3/4	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. First twelve inches graduated in 32nds of an inch. Remainder in 16ths of an inch. Bottom edge: Numbered in consecutive inches. First twelve inches graduated in 32nds of an inch. Remainder in 16ths of an inch.
STHT30825	25	–	1	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.
STHT30824S	26	8	1	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Major scale numbered in consecutive meters. Minor scale numbered in consecutive 10 cm repeated every 100 cm.
STHT30830	30	–	1	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.
STHT30758L	25	–	1	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.
STHT30759L	25	–	1	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.

*1.5X improved wear resistance of blade markings in tests compared to STANLEY standard tape 30-419



STANLEY® TAPE RULES

- Versatile 1/2", 3/4", and 1" wide blades and 7' standout (1" wide blades only).
- Polymer-coated blade withstands abrasion.
- Corrosion-resistant Tru-Zero™ end hook for accurate measurements.
- fractional read blade graphics for quick and easy measurements (only on 30-454).
- Ergonomically designed high-impact, ABS case.



SHORT TAPE RULES

Product #	Blade Length (ft)	Blade Length (m)	Blade Width (in)	Stud Markings (in)	Graduation
30-506	6	—	1/2	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Numbered in consecutive inches. First twelve inches graduated in 32nds of an inch. Remainder in 16ths of an inch.
30-485	12	—	1/2	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Numbered in consecutive inches. First twelve inches graduated in 32nds of an inch. Remainder in 16ths of an inch.
30-495	16	—	3/4	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. First twelve inches graduated in 32nds of an inch. Remainder in 16ths of an inch. Bottom edge: Numbered in consecutive inches. First twelve inches graduated in 32nds of an inch. Remainder in 16ths of an inch.
30-496	16	5	3/4	16, 19.2	Top edge: Numbered in consecutive inches. First twelve inches graduated in 32nds of an inch. Remainder graduated in 16ths of an inch. Marked every 12 inches. Bottom edge: Numbered in consecutive cm. Graduated in mm. Marked every 10 cm.
30-456	26	8	1	16, 19.2	Top edge: Numbered in consecutive inches. First twelve inches graduated in 32nds of an inch. Remainder graduated in 16ths of an inch. Marked every 12 inches. Bottom edge: Numbered in consecutive cm. Graduated in mm. Marked every 10 cm.
30-454	25	—	1	16, 19.2	Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches. Graduated in 16ths of an inch. Numerical readouts every 8th of an inch.
30-455	25	—	1	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.
30-464	30	—	1	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.

STANLEY® HIGH-VISIBILITY TAPE RULE

- Polymer-coated blade withstands abrasion.
- High-impact, high-visibility green ABS case is over molded with soft-grip rubber.
- Corrosion-resistant Tru-Zero™ end hook for accurate measurements.



Product #	Blade Length (ft)	Blade Width (in)	Stud Markings (in)	Graduation
30-305	25	1	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.

STANLEY® FATMAX® CLOSED CASE LONG TAPE

- 3:1 gear drive for fast rewinds.
- Polymer-coated blade withstands abrasion.
- Steel roller cage protects case from being cut by blade during rewind.
- High-impact, yellow ABS case is over molded with soft-grip rubber for maximum comfort, slip-resistant grip, and durability.
- Corrosion-resistant Tru-Zero™ folding end hook for accurate measurements.



Product #	Blade Length (ft)	Blade Width (in)	Stud Markings (in)	Graduation
34-130	100	3/8	16	Major scale in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 8ths of an inch.

STANLEY® CLOSED CASE LONG TAPES

- High impact, high visibility yellow ABS case.
- Polymer-coated blade withstands abrasion for a long life.
- Easy wind drum for easy retraction.
- Easy to read markings.
- Hook nests neatly into contoured case.
- Belt clip for hands-free use and convenient transportation.
- Corrosion-resistant Tru-Zero™ folding end hook for accurate measurements.



Product #	Blade Length (ft)	Blade Width (in)	Stud Markings (in)	Graduation
34-103	50	3/8	16	Major scale in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 8ths of an inch.
34-106	100	3/8	16	Major scale in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 8ths of an inch.



STANLEY® POWERWINDER® OPEN REEL LONG TAPES

- Rewinds 3X faster* with 3:1 gear drive.
- 1/2" wide blade for easy readability.
- 2-sided blade graphics with fractional inch/decimal foot scales for versatility.
- Reinforced blade end for long life.
- End loop for easy pulling and anchoring.
- High-impact ABS case with durable rubber grip holds up to heavy use.
- Corrosion-resistant Tru-Zero™ folding end hook for accurate measurements.
- Blade bumper to help prevent blade damage.



LONG TAPE RULES

Product #	Blade Length (ft)	Blade Length (m)	Blade Width (in)	Graduation
34-760	100	–	1/2	Side One: Major scale in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 8ths of an inch. Side Two: Major scale in consecutive feet. Minor scale numbered in consecutive 10ths of a foot repeated every foot. Graduated in 100ths of a foot.
34-762	300	–	1/2	Side One: Major scale in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 8ths of an inch. Side Two: Major scale in consecutive feet. Minor scale numbered in consecutive 10ths of a foot repeated every foot. Graduated in 100ths of a foot.
34-771	100	30	1/2	Two sided blade graphics with fractional inch and metric graduations.
34-774	200	60	1/2	Two sided blade graphics with fractional inch and metric graduations.

*Than base STANLEY® model.

STANLEY® FIBERGLASS OPEN REEL LONG TAPES

- 1/2" wide blade with easy-to-read markings.
- 2-sided blade graphics with fractional inch/decimal foot scales.
- Polymer-coated blade withstands abrasion.
- High-impact ABS case with rubber grip holds up to heavy use
- Corrosion-resistant Tru-Zero™ folding end hook for accurate measurements.



Product #	Blade Length (ft)	Blade Width (in)	Graduation
34-790	100	1/2	Side One: Major scale in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 8ths of an inch. Side Two: Major scale in consecutive feet. Minor scale numbered in consecutive 10ths of a foot repeated every foot. Graduated in 100ths of a foot.
34-793	200	1/2	Side One: Major scale in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 8ths of an inch. Side Two: Major scale in consecutive feet. Minor scale numbered in consecutive 10ths of a foot repeated every foot. Graduated in 100ths of a foot.