


Exterior Nails

Wood Siding Nail

Features:

- Checker pattern on head blends with wood grain, reduces glare from sunlight and accepts surface finishes
- Annular ring shank increases pull-out resistance to provide a secure attachment that reduces cupping of siding boards
- Diamond point for easier driving
- Choose Type 316 stainless steel for seaside applications and superior corrosion resistance



Type 316 Stainless Steel

Penny Size	Length (in.)	Gauge	Shank Diameter (in.)	Head Diameter (in.)	Approx. Count per lb.	1 lb. Model No.	5 lb. Model No.	25 lb. Bucket Model No.	
3d	1 1/4	14	0.083	5/32	0.156	495	T3SND1	T3SND5	T3SNDB
4d	1 1/2	14	0.083	5/32	0.156	398	T4SND1	T4SND5	T4SNDB
5d	1 3/4	14	0.083	5/32	0.156	354	T5SND1	T5SND5	T5SNDB
6d	2	13	0.092	5/32	0.156	245	T6SND1	T6SND5	T6SNDB
7d	2 1/4	13	0.092	5/32	0.156	215	T7SND1	T7SND5	T7SNDB
8d	2 1/2	13	0.092	5/32	0.156	196	T8SND1	T8SND5	T8SNDB
10d	3	12	0.113	7/32	0.219	120	T10SND1	T10SND5	T10SNDB
12d	3 1/4	12	0.113	7/32	0.219	110	T12SND1	T12SND5	T12SNDB
16d	3 1/2	11	0.120	1/4	0.250	88	T16SND1	T16SND5	T16SNDB
20d	4	10	0.131	1/4	0.250	74	T20SND1	T20SND5	T20SNDB



Type 304 Stainless Steel

Penny Size	Length (in.)	Gauge	Shank Diameter (in.)	Head Diameter (in.)	Approx. Count per lb.	1 lb. Model No.	5 lb. Model No.	25 lb. Bucket Model No.	
3d	1 1/4	14	0.083	5/32	0.156	495	S3SND1	S3SND5	S3SNDB
4d	1 1/2	14	0.083	5/32	0.156	398	S4SND1	S4SND5	S4SNDB
5d	1 3/4	13	0.092	5/32	0.156	260	SP5SND1	SP5SND5	SP5SNDB
5d	1 3/4	14	0.083	5/32	0.156	354	S5SND1	S5SND5	S5SNDB
6d	2	13	0.092	5/32	0.156	245	S6SND1	S6SND5	S6SNDB
7d	2 1/4	13	0.092	5/32	0.156	215	S7SND1	S7SND5	S7SNDB
8d	2 1/2	13	0.092	5/32	0.156	196	S8SND1	S8SND5	S8SNDB
10d	3	12	0.113	7/32	0.219	120	S10SND1	S10SND5	S10SNDB
12d	3 1/4	12	0.113	7/32	0.219	110	S12SND1	S12SND5	S12SNDB
16d	3 1/2	11	0.120	1/4	0.250	88	S16SND1	S16SND5	S16SNDB
20d	4	10	0.131	1/4	0.250	74	S20SND1	S20SND5	S20SNDB

Cedar Trim Nail

Features:

- Designed to fashion woven corners
- Ultra-thin 0.072" wire diameter
- Unobtrusive 0.135" diameter head
- Blunt diamond point minimizes shingle splitting
- Annular ring-shank thread
- Choose Type 316 stainless steel for seaside applications and superior corrosion resistance



Type 316 Stainless Steel

Penny Size	Length (in.)	Wire Gauge	Shank Diameter (in.)	Head Diameter (in.)	Approx. Count per lb.	1 lb. Model No.	5 lb. Model No.	
3d	1 1/4	15	0.072	5/64	0.141	550	T3ACDRWVR1	T3ACDRWVR5



Type 304 Stainless Steel

Penny Size	Length (in.)	Wire Gauge	Shank Diameter (in.)	Head Diameter (in.)	Approx. Count per lb.	1 lb. Model No.	5 lb. Model No.	25 lb. Model No.	
3d	1 1/4	15	0.072	5/64	0.141	550	S3ACDRWVR1	S3ACDRWVR5	—
5d	1 3/4	15	0.072	5/64	0.141	550	—	—	S5ACDRWVRB

These products are subject to quantities on hand or may require special ordering and are subject to minimum order quantities and longer lead times. Call Simpson Strong-Tie for details (800) 999-5099.