

**Toll Free: 87 PERMATEX** (877-376-2839)

10 Columbus Blvd., Hartford, Connecticut 06106

6875 Parkland Boulevard, Solon Ohio 44139

# **PRODUCT DESCRIPTION**

Spray Nine® Corp. Grez-Off® Heavy Duty Degreaser is developed for heavy duty cleaning and degreasing jobs that ordinary degreasers cannot handle. Sprav Nine<sup>®</sup> Grez-Off<sup>®</sup> is a ready-to-use aqueous based composition of alkaline salts, powerful grease emulsifiers and a water soluble grease cutting solvent. Grez-Off<sup>®</sup> cuts heavy grease and soils guickly with no harsh fumes or unpleasant odors. Grez-Off® is readily biodegradable according to OECD 301-C modified MITI Test (I) and contains no petroleum solvents or acids and is nonflammable.

# PRODUCT BENEFITS

- VOC compliant in all 50 states
- Special blend of surfactants, detergents and emulsifiers
- Water soluble solution
- Contains no petroleum based solvents
- Biodegradable
- No acids
- Non-flammable .
- Non-combustible .
- Non-abrasive .
- Non-aerosol package eliminates product waste from propellant depletion

# **TYPICAL APPLICATIONS**

# Applications

| Machinery/equipment |                | Exterior siding     |
|---------------------|----------------|---------------------|
| Exhaust filters     | Fiberglass     | Lift trucks         |
| Cold engines        | Castings       | Janitorial cleaning |
| Wax remover         | Dies           | _                   |
| Grease traps        | Molds          | Countertops         |
| Tooling/tools       | Tanks          | Walls               |
| Shop floors         | Shop equipment | Farm equipment      |
| Concrete            | Carpets        | Mowers              |
|                     |                |                     |

### Substances (Soils) Removed

| Grease & grime | Lubricants  | Oil deposits   |
|----------------|-------------|----------------|
| Tar            | Food stains | Wax            |
| Ink            | Dirt/mud    | Smoke and soot |

# DIRECTIONS FOR USE

NOTE: Some surfaces such as aluminum alloys, plastic or painted surfaces are inherently sensitive to alkaline cleaners. Spot test on ALL surfaces before use. Do not use on motorcycles or glass. Use with adequate ventilation. Do not inhale mist. The use of safety glasses and rubber gloves is recommended. These directions must be followed or damage may result.

1. Before degreasing, be sure that all surfaces are cool to the touch. Do not apply in direct sunlight or if air temperature is above 100°F.

# **Technical Data Sheet**

Spray Nine<sup>®</sup> Grez-Off<sup>®</sup> Heavy **Duty Degreaser** 

Revised 04/08

Typical Value

- 2. Spray Grez-Off® full strength onto the cool, pre-tested surface to be degreased.
- Allow Grez-Off<sup>®</sup> to penetrate the soil. NEVER allow 3. Grez-Off<sup>®</sup> to dry on any surface. Stubborn soils may require brushing or a second application.
- 4 Immediately rinse with water until no sudsing is noticeable.

### **PROPERTIES OF MATERIAL**

|                  | i ypical value                      |
|------------------|-------------------------------------|
| Chemical Type    | Water-based alkaline degreaser      |
|                  | containing proprietary ingredients, |
|                  | surfactants and conditioners        |
| Appearance       | Clear orange liquid                 |
| Odor             | citrus                              |
| Flash Point      | >200°F                              |
| Specific Gravity | 1.01                                |
| pH               | 12.4                                |

### **GENERAL INFORMATION**

For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).

# **ORDERING INFORMATION**

| Part Number | Container Size         |
|-------------|------------------------|
| 22700       | 5 fl oz Pump Spray     |
| 22732       | 32 fl oz Trigger Spray |
| 22701       | 1 Gallon Capped Bottle |
| 22705       | 5 Gallon Pail          |

# STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8° and 49°C (46° and 120°F). Optimal storage is at the lower end of this range.

## NOTE

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. ITW Permatex, Inc specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Permatex, Inc. products and disclaims any liability for consequential or incidental damages of any kind, including lost profits. This product may be covered by one or more United States or foreign patents or patent applications.

NOT FOR PRODUCT SPECIFICATIONS. THE TECHNICAL DATA CONTAINED HEREIN ARE INTENDED AS REFERENCE ONLY. PLEASE CONTACT PERMATEX, INC., TECHNICAL SERVICE DEPARTIMENT FOR ASSISTANCE AND RECOMMENDATIONS FOR YOUR SPECIFIC APPLICATION. PERMATEX, INC., HARTFORD SQUARE NORTH, 10 COLUMBUS BOULEVARD, HARTFORD, CT 06106 PHONE – (1-87PERMATEX)