

Product availability : Stock - Normally stocked in distribution facility



Price\* : 1090.65 USD



### Main

Product or component type	Load Center
Range of product	Homeline
Load center type	Main breaker
Line Rated Current	200 A
Number of spaces	30
Number of circuits	60
NEMA degree of protection	NEMA 1 indoor
Cover type	Combination flush/surface cover
Electrical connection	Lugs
Provided equipment	Circuit breaker (1) 2P 200 A 120/240 V AC main supply ready assembled Circuit breaker (3) 1P 20 A 120/240 V AC Circuit breaker (2) 2P 30 A 120/240 V AC

### Complementary

Short-circuit current	22 kA
Number of tandem circuit breakers	30
Phase	1 phase
System Voltage	120/240 V AC
AWG gauge	AWG 4...250 kcmil (aluminium/copper)
Wiring configuration	3-wire
Cover finish	Gray baked enamel
Material	Tin plated aluminium busbar
Enclosure material	Welded sheet steel
Surface finish	Baked enamel grey
Box number	10

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environment

Product certifications	UL E-6294
------------------------	-----------

## Ordering and shipping details

Category	00185 - MISC. HOM LOAD CENTERS
Discount Schedule	DE3C
GTIN	00785901977827
Nbr. of units in pkg.	1
Package weight(Lbs)	34.800000000000004
Returnability	Y
Country of origin	US

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1414 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations