



Valspar® Weathercoat Latex Home & Ranch Paint



Product Description

A premium quality latex paint modified with linseed oil for good penetration and adhesion to new or weathered wood. It resists fading and dries to a non-toxic film that is safe for use around livestock. May be used as its own primer in a two coat application.

Features

- Linseed Oil Fortified
- Self Priming
- Water Clean-Up

Recommended Uses

- New or weathered wood
- Concrete block
- Metal trim
- Barns
- Fences
- Outbuildings

Colors and Base Information

	oz./gal.
Ranch Red	128
White	128
Brilliant Red	128

Shipping and Packaging

Freight Classification: Paint or Paint Related Material. Protect from freezing.

Packaging: Gallon – 4 per carton
5-gallon pail

Typical Properties (18-5221 White)

Vehicle Type: Vinyl Acrylic & Linseed Oil

Sheen: 5 Units Max @ 60° angle

Solids by Volume: 32%

Solids by Weight: 51%

Weight per Gallon: 11.7 lbs./gal.

VOC: Less than 50 g/L

Viscosity: 82–88 Krebs Units

Dry Time: 77°F @ 50% Relative Humidity

To the touch: 1 hour

Recoat: 24 hours

Washing: Allow at least 7 days before washing. Use mild detergent and sponge.

Surface Coverage:

400 sq. ft./gal.

At: 4.0 mil Wet, 1.2 mil Dry

Storage and Disposal

- Do not freeze.
- Keep container closed when not in use.
- Do not transfer contents to other containers for storage or disposal.
- In case of spillage, absorb with inert material such as sand or kitty litter.
- Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

Surface Preparation

Read the Lead Warning in Cautions section. Clean surface thoroughly. Remove dirt and grease by washing the surface with a non-residue all-purpose cleaner. Wash dirt from protected areas such as under eaves. Remove loose or peeling paint and rust with a wire brush and scraper. Dull glossy areas by sanding lightly. Caulk cracks and crevices around windows, doors and trim. Unpainted wood or weathered surfaces should be primed with a first coat of Valspar Latex Home & Ranch Paint thinned with one pint (16 fl. oz.) of water per gallon of paint. For metal trim, remove all loose paint, rust and scale before painting. Spot prime previously rusted areas with a rust inhibiting primer. **Clean Mildew from the Surface:** Mildew is a fungus that looks like dirt, but won't wash off. Mildew must be removed before finishing or it will grow through any new coating. To remove mildew, scrub with a commercial mildew remover or a solution of 1 part liquid chlorine bleach to 3 parts of water. Rinse thoroughly and allow to dry. Protect eyes and skin by wearing protective equipment including rubber gloves and eye goggles when working with bleach solution.

Application and Clean-up

Paint only when surface and air temperatures are above 50°F (10 °C). Stir paint thoroughly before and occasionally during painting. Do not paint in damn weather or when rain is threatening. Apply paint with premium quality brush, roller or by airless spray. Start painting at the highest point and work from left to right. Brush paint well into surface. Always finish at a door, window or outer edge. Do not stop painting in the middle of an open space. Thin sparingly, if necessary, with water. Clean brushes, rollers, equipment and hands with warm soapy water.

Cautions (18-5221 White)

WARNING: CONTAINS CRYSTALLINE SILICA. May cause eye and skin irritation. Avoid breathing spray mist or dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly-fitted respirator (NIOSH approved) during and after application. Avoid exposure to sanding dust by wearing an appropriate particulate respirator (NIOSH approved) during application, sanding and clean-up. Follow respirator manufacturer's directions for respirator use. **AVOID CONTACT WITH THE EYES AND SKIN.** Wash thoroughly after use. Close container after each use.

Warning: This product contains chemicals known to the State of California to cause cancer.

FIRST AID: EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.** **IF INHALED:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.** **IF SWALLOWED:** Drink 2 glasses of water. **Get medical attention immediately.**

Delayed effect from long term exposure: Cancer Hazard. Crystalline silica may cause lung damage and cancer. Risk depends upon duration and level of exposure to dust generated from sanding surfaces or spray mist.

**DO NOT TAKE INTERNALLY.
KEEP OUT OF REACH OF CHILDREN.
For additional safety and chronic health hazard
information, refer to the Material Safety Data
Sheet for this product.**

**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

This product contains less than 50 g/L VOC

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean-up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product, is the replacement of the defective product, or a refund of its purchase price, at our option.