



Armor Anti-Rust Enamel Spray



Product Description

Smooth, glossy finish provides the ultimate protection against rust. Creates a durable, scuff resistant finish on interior and exterior surfaces.

Features

- Advanced Corrosion Resistance
- Superior Coverage and Durability
- Fast Drying Smooth Finish
- Interior/Exterior Use

Colors and Part Numbers

	Part Number
Gloss White	21900
Satin White	21920
Semi-Gloss White	21941
Flat White	21921
Gloss Almond	21935
Gloss Safety Orange	21937
Gloss Safety Yellow	21945
Gloss Safety Red	21927
Gloss Safety Blue	21959
Gloss Dark Blue	21928
Gloss Hunter Green	21944
Gloss Brown	21933
Gloss Gray	21934
Gloss Black	21924
Wrought Iron Black	21925
Semi-Gloss Black	21942
Flat Black	21926
Heavy Duty Aluminum	21940
Metallic Gold	21930
Brushed Nickel	21956
Gloss Clear Sealer	21955

Typical Properties (21900 Series)

Dry Time:

To the touch: 30-50 minute(s)

Recoat: Within 4 hour(s) or after 36 hour(s)

Surface Coverage:

Coverage varies depending on surface color and porosity.

Recommended Uses

- Appliances
- Playground equipment
- Piping
- Wrought iron railings
- Mailboxes
- Tanks

Can Size and Fill Weight

Can Size: 16 oz.

Fill Weight: 12 oz.

USE WITH ADEQUATE VENTILATION

1. Surface should be clean and dry. Remove dirt, grease, loose particles, wax, etc. Bare metal should be primed.
2. Use outdoors or in well-ventilated area when temperature is between 60- 80 °F (16-27 °C) and humidity is below 60% to ensure proper drying.
3. Mask surrounding area on which spray may settle with newspapers or drop cloths.
4. Shake well, listening for rattle of mixing ball. Continue shaking for at least one minute. Shake for 10 seconds at 1-2 minute intervals during application.
5. Hold can 12-16 inches from surface. Press spray button firmly. Move can back and forth, releasing button after each stroke. Overlap each stroke. Two (2) thin coats are recommended rather than one (1) heavy coat. Recoat anytime.
6. If spray button should clog, remove button from can and run knife-edge through tiny slit at end of spray bottle stern. Do not insert pins or other sharp objects into valve opening of can.
7. To prevent valve from clogging after spraying, turn can upside down and press spray head for about 3 second.

Cautions (21900 Series)

CONTAINS NO CFC's – in accordance with Federal regulations which prohibit the use of CFC propellants in aerosols.

Contains: Dimethyl Ketone, Methyl Isobutyl Ketone, Butyl Acetate, Ethyl 3 Ethoxypropionate, Xylene, Ethyl Benzene. VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE, OR NAUSEA. CAUSES EYE, NOSE, THROAT AND SKIN IRRITATION. Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperatures above 120 °F (49 °C). Contains propane as pressurizing agent. **Vapors may ignite explosively.** Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent buildup of vapors by opening all windows and doors to achieve cross ventilation. **Use only with adequate ventilation.** Do not breathe dust, vapors, or spray mist. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA approved) or leave the area. Close container after each use. Avoid contact with eyes, skin and clothing.

WARNING: This product contains a chemical known to the State of California to cause cancer.

FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water.

Delayed effect from long-term exposure: Reports have associated repeated or prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

DO NOT TAKE INTERNALLY.

KEEP OUT OF REACH OF CHILDREN.

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean-up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product, is the replacement of the defective product, or a refund of its purchase price, at our option.

PDS 21900