



Valspar® Pristine Exterior Flat Paint

No. 18200 Series

GENERAL DESCRIPTION

Denies dirt on a molecular level. Tightly woven cross-linking molecules deliver steely smoothness that actually denies entry to dirt and stain molecules. Optimized for extreme adhesion and flexibility. Elastomeric polymerization delivers extreme-weather flexibility to ward off cracking, peeling and failing in all conditions. Mold, Mildew and Algae resistant.

PRODUCT FEATURES

- Ultra-smooth paint & primer
- Weather defense formula stands up to mother nature: resists cracking and peeling because formula is highly flexible
- Clean Science™ technology - engineered to repel dirt and resist stains
- Luxurious, fade-resistant color
- Easy application with maximum hide
- Mold, mildew and algae resistant finish
- Stay-clean smoothness
- Lifetime warranty
- Low odor, low VOC

RECOMMENDED USES

- Properly prepared, exterior wood and metal siding and trim
- Hardboard
- Fiber cement board
- Vinyl
- Primed metal
- Brick
- Cement
- Cinder block
- Stucco

SHIPPING AND PACKAGING

Freight Classification: Paint or paint related material. protect from freezing.

Packaging: Quart, Gallon, 5 Gallon – 4 per carton

Case Weight: 48.2 lbs.

COMPOSITION

Base and Fill Levels

	(oz./gal.)
Pastel (18208)	126 Fl oz.
Tint (18202)	124 Fl oz.
Clear (18205)	116 Fl oz.

APPLICATION AND CLEANUP

Stir paint thoroughly. Intermix containers to ensure uniform color. Apply with a premium-quality roller, polyester brush or airless sprayer. If applying by spray, back-roll or back-brush to work paint into the surface. Apply a liberal coat of paint uniformly, working well into the surface.

Airless Spray:

Pressure: 2000 PSI

Tip: 0.017–0.021"

Brush: Premium-quality polyester

Roller: Premium-quality roller 3/8" nap

SYSTEM RECOMMENDATIONS

New Wood:

Self-priming

2 Coats Pristine Exterior Latex Flat Paint

Previously Painted Surfaces:

Self-priming

1–2 Coats: Pristine Exterior Latex Flat Paint

Hardboard Siding:

Self-priming

1–2 Coats Pristine Exterior Latex Flat Paint

Masonry, Concrete, Stucco, and Block:

Self-priming

1–2 Coats Pristine Exterior Latex Flat Paint

Metal:

1 Coat: Valspar® Armor Anti-Rust Primer

or Valspar® Armor Galvanized Metal Primer

1–2 Coats: Pristine Exterior Latex Flat Paint

Aluminum and Vinyl Siding:

Self-priming

1–2 Coats: Pristine Exterior Latex Flat Paint

PRODUCT SPECIFICATIONS

Vehicle Type: 100% Acrylic Latex

Pigment Type: Titanium Dioxide

Viscosity: 101-109 Krebs Units

Gloss: 0–7 Units @ 85° angle

Flashpoint: 205

VOC (g/L): Less than 50 g/L

VOC (lbs./gal.): 0.38 lbs./gal.

Volume Solids: 38%

Weight Solids: 56%

Weight Per Gallon: 11.6 lbs./gal.

Practical Coverage: Covers up to 400 sq. ft. per gallon (37 m² per 3.78 L) depending on surface porosity.

Thinning: Thin only for spray application with up to 8 oz. (236 mL) of water per gallon (3.78 L) of paint.

Recommended Film Thickness:

4.0 mil Wet 1.3 mil Dry

Dry Time @ 77 °F and 50% Relative Humidity

To The Touch: 30–60 minutes

Recoat: 2–4 hours

Application Temperature: 35–90 °F (2–32 °C)

Storage Temperature: 40–90 °F (5–32 °C)

CERTIFICATIONS

Current as of: 2/10/2016

MPI #	N/A
MPI GPS 1	N/A
MPI GPS 2	N/A
LEED (US)	N/A
LEED (Canada)	N/A

REGULATORY COMPLIANCE

Current as of: 2/10/2016

SCAQMD	Yes
CARB 2000 SCM	Yes
CARB 2007 SCM	Yes
OTC/LADCO	Yes
US National	Yes



Valspar® Pristine Exterior Flat Paint

No. 18200 Series

SURFACE PREPARATION

General:

Read the Lead Warning paragraph. Thoroughly clean the surface and allow to dry. Remove all dirt, dust, chalk, rust, grease, wax and mildew. Patch all cracks with appropriate patching compound. Remove any powdery dust and efflorescence. This product may be used to prime most new or bare surfaces.

Clean mildew from the surface:

Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub house before painting with a commercial mildew remover or a solution of 1 part liquid chlorine bleach to 3 parts water. Rinse thoroughly. Avoid contact with skin and eyes. Protect skin and eyes by wearing rubber gloves and eye goggles when working with bleach solution.

Bare Wood:

Remove sap from knots and sappy areas. For maximum performance, two coats of Valspar® Pristine® are recommended.

Hardboard Siding:

Remove any wax from bleed-through areas by wiping with rags soaked with mineral spirits. Turn rags often to avoid merely spreading wax around.

Vinyl Siding/Aluminum Siding:

Power wash to remove chalk and mildew. Paint with a color lighter than original siding color.

WARNING! Painting vinyl siding with darker colors will cause warping or deformation from heat absorption.

Galvanized / Ferrous Metal (Steel, Iron):

Allow new galvanized metal to age six months or clean with mild muriatic solution. Hand- or power tool clean surfaces to remove oils and other contaminants, mill scale and rust. Metal should be free of oils and other contaminants. Prime with Valspar® Armor Anti-Rust Primer or Valspar® Galvanized Metal Primer.

Masonry, Concrete, Stucco, and Block:

New concrete, masonry, and mortar should be cured, usually 30 days. Remove all form release or curing agents, loose material, efflorescence, chalk, and mildew by power washing or scrubbing with appropriate cleaners. New stucco should be allowed to cure, and pH should be below 10.

LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

LIMITED WARRANTY

This product is warranted for your complete satisfaction for as long as you reside in your home. This warranty covers product that is applied to a properly prepared residential surface in accordance with label directions and excludes product failure due to deterioration of the underlying surface, structural defects or failure of previous product. If the product fails to perform to your satisfaction, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state.

CAUTIONS

WARNING! Contains Crystalline Silica. **KEEP OUT OF THE REACH OF CHILDREN.** May cause eye and skin irritation. **Use only with adequate ventilation.** Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. When sanding, wear a dust mask. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **DO NOT TAKE INTERNALLY.** Delayed effect from long-term exposure: Cancer hazard. Contains crystalline silica, which can cause cancer. Risk of cancer depends on duration and level of exposure to dust from sanding surfaces or spray mist. **WARNING:** This product contains a chemical known to the State of California to cause cancer. **First Aid: Eye Contact:** Immediately flush with plenty of water for at least 15 minutes. If irritation persists, get medical attention.* **If Inhaled:** If affected by inhalation of vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.* **If Swallowed:** Drink 2 glasses of water. Get medical attention immediately.*

*Call poison control center, hospital emergency room or physician immediately.

UCL 3.1

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

EMERGENCY MEDICAL TELEPHONE: 1-888-345-5732

This product contains less than 50 g/L VOC.

8725 W. Higgins Rd., Chicago, IL 60631

888.313.5569

valsparpaint.com

Revised: 2/10/16

Version: 18202A