

## SAFETY DATA SHEET

Revision date 17-Apr-2018

Version 11

Supersedes Date: 22-Jul-2017

# Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product identifier

**Product Code** 

044.0021959

**Product Name** 

VAL AR EN GLS SAF BLU

Other means of identification

No information available

Recommended use of the chemical and restrictions on use

Paint, Coatings

Details of the supplier of the safety data sheet

See section 16 for more information

The Valspar Corporation PO Box 1461 Minneapolis, MN 55440

E-mail address

msds@valspar.com

Emergency telephone number

United States of America 1-888-345-5732

## **Section 2: HAZARDS IDENTIFICATION**

## Classification

Skin corrosion/irritation	Category 2
Skin sensitization	Category 1A
Carcinogenicity	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable liquids	Category 3

## Label elements



Signal word

**DANGER** 

#### **HAZARD STATEMENTS**

Flammable liquid and vapor
Causes skin irritation
May cause an allergic skin reaction
Suspected of causing cancer
Suspected of damaging fertility or the unborn child
May cause drowsiness or dizziness
May be fatal if swallowed and enters airways

Causes damage to the following organs through prolonged or repeated exposure: Nervous System

#### **PREVENTION**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Wash face, hands and any exposed skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

#### **RESPONSE**

IF exposed or concerned: Get medical advice/attention.

#### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

#### Skin

If skin irritation or rash occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

## Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

## Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

#### Fire

In case of fire: Use CO2, dry chemical, or foam for extinction.

#### **STORAGE**

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool.

#### DISPOSAL

Dispose of contents/containers in accordance with local regulations.

#### HAZARDS NOT OTHERWISE CLASSIFIED (HNOC)

No information available.

#### **OTHER HAZARDS**

spontaneously combustible material. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal.

**UNKNOWN ACUTE TOXICITY** 

0% of the mixture consists of ingredient(s) of unknown toxicity.

#### Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	weight-%
Petroleum distillates, hydrotreated light	64742-47-8	25 - 50
Titanium dioxide	13463-67-7	5 - 10
Stoddard solvent	8052-41-3	1 - 3
Zirconium ethyl hexoate	22464-99-9	0.3 - 1
2-Butanone, oxime	96-29-7	0.1 - 0.3
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	0.1 - 0.3

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

## **Section 4: FIRST AID MEASURES**

#### **First Aid Measures**

#### General advice

IF exposed or concerned: Get medical advice/attention.

#### Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

#### Skin Contact

If skin irritation or rash occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

#### Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

#### Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

## Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

## Indication of any immediate medical attention and special treatment needed

## **Section 5: FIRE FIGHTING MEASURES**

#### Suitable extinguishing media

Dry chemical, CO2, water spray or alcohol-resistant foam.

Not to be used for safety reasons: Strong water jet

## Specific hazards arising from the chemical

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes. May cause sensitization by skin contact. spontaneously combustible material. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal. Keep product and empty container away from heat and sources of ignition.

#### Special protective equipment for fire-fighters

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

## **Section 6: ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures

#### Personal precautions

Avoid breathing vapors or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Take precautionary measures against static discharges.

## For emergency responders

Use personal protection recommended in Section 8.

#### **Environmental precautions**

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

#### Methods and material for containment and cleaning up

#### Methods for containment

Prevent further leakage or spillage if safe to do so.

#### Methods for cleaning up

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. Take up mechanically, placing in appropriate containers for disposal.

#### Section 7: HANDLING AND STORAGE

#### Precautions for safe handling

#### Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal.

#### **General Hygiene Considerations**

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Avoid contact with skin, eyes or clothing.

#### Conditions for safe storage, including any incompatibilities

#### **Storage Conditions**

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place. Keep tightly closed in a dry and cool place.

## Incompatible materials

Strong oxidizing agents. Acids.

#### Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

#### **Exposure Limits**

If S\* appears in the OEL table, it indicates this chemical contains a skin notation.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m³ total dust	IDLH: 5000 mg/m <sup>3</sup>
Stoddard solvent	TWA: 100 ppm	TWA: 500 ppm	IDLH: 20000 mg/m <sup>3</sup>

8052-41-3		TWA: 2900 mg/m <sup>3</sup>	Ceiling: 1800 mg/m <sup>3</sup> 15 min
			TWA: 350 mg/m <sup>3</sup>
Zirconium ethyl hexoate	STEL: 10 mg/m <sup>3</sup> Zr	TWA: 5 mg/m <sup>3</sup> Zr	IDLH: 25 mg/m <sup>3</sup> Zr
22464-99-9	TWA: 5 mg/m³ Zr	_	TWA: 5 mg/m³ except Zirconium
	_		tetrachloride Zr
			STEL: 10 mg/m³ Zr

#### Appropriate engineering controls

#### **Engineering Controls**

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

#### Individual protection measures, such as personal protective equipment

#### Eve/face protection

Tight sealing safety goggles.

## Skin and body protection

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Wear suitable protective clothing. Personnel should wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber.

#### **Hand Protection**

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

#### Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

## **Thermal Protection**

No information available

#### Section 9: PHYSICAL AND CHEMICAL PROPERTIES

## Information on basic physical and chemical properties

Physical state liquid

**Appearance** No information available

Odor Solvent Color blue

No information available **Odor Threshold** pH value No information available Melting point/freezing point No information available

No information available °C / °F Boiling point / boiling range

flash point 38 °C / 100 °F

No information available evaporation rate Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit: No information available Lower flammability limit: No information available **Vapor Pressure** No information available vapor density No information available

Density (lbs per US gallon) 8.97 specific gravity No information available No information available Solubility(ies) **Partition coefficient** No information available **Autoignition temperature** No information available **Decomposition temperature** No information available Kinematic viscosity No information available Dynamic viscosity No information available

#### Other information

**Section 10: STABILITY AND REACTIVITY** 

**Reactivity** No information available.

**Chemical stability** Stable under normal conditions.

Possibility of Hazardous Reactions None under normal processing.

**Hazardous polymerization**None under normal processing.

**Conditions to avoid** Heat, flames and sparks.

**Incompatible materials** Strong oxidizing agents. Acids.

Hazardous Decomposition Products Carbon monoxide. Carbon dioxide (CO2).

#### Section 11: TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Eye contact

Not applicable

**Skin Contact** 

Causes skin irritation

May cause an allergic skin reaction

Ingestion

May be fatal if swallowed and enters airways

Inhalation

May cause drowsiness or dizziness

## Numerical measures of toxicity - Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum distillates, hydrotreated light 64742-47-8	> 5000 mg/kg(Rat)	> 2000 mg/kg(Rabbit)	> 5.2 mg/L (Rat)4 h
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Stoddard solvent 8052-41-3	-	-	-
Zirconium ethyl hexoate 22464-99-9	-	-	-
2-Butanone, oxime 96-29-7	= 930 mg/kg (Rat)	1000 - 1800 mg/kg (Rabbit)	> 4800 mg/m³(Rat)4 h
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1) 136-52-7	-	> 5000 mg/kg(Rabbit)	> 10 mg/L (Rat)1 h

## Numerical measures of toxicity - Product Information

**UNKNOWN ACUTE TOXICITY** 0% of the mixture consists of ingredient(s) of unknown toxicity.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

## Carcinogenicity

According to IARC, Volume 93, no significant exposure to primary particles of titanium dioxide is thought to occur from use in paints since the pigment is bound to other materials. According to IARC, Volume 93, no significant exposure to primary particles of carbon black is thought to occur from use in paints since the pigment is bound to other materials.

Chemical Name	ACGIH	<u>IARC</u>	NTP	OSHA
---------------	-------	-------------	-----	------

Titanium dioxide 13463-67-7	Group 2B	X
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1) 136-52-7	Group 2B	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen.

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans.

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present.

Skin corrosion/irritation Causes skin irritation

Serious eye damage/eye irritation Not applicable

Skin sensitization May cause an allergic skin reaction

Respiratory sensitization Not applicable

Germ cell mutagenicity Not applicable

Carcinogenicity Suspected of causing cancer

Reproductive Toxicity Suspected of damaging fertility or the unborn child

Specific target organ toxicity (single exposure) May cause drowsiness or dizziness

Specific target organ toxicity (repeated exposure)

Causes damage to the following organs through prolonged or repeated exposure: Nervous System

Aspiration hazard May be fatal if swallowed and enters airways

## **Section 12: ECOLOGICAL INFORMATION**

**Ecotoxicity** 

Environmental precautions Prevent product from entering drains.

Marine pollutant This material meets the definition of a marine pollutant

Persistence and degradability

No information available

Bioaccumulation

No information available

**Mobility** 

No information available

Other adverse effects No information available

#### **Section 13: DISPOSAL CONSIDERATIONS**

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Improper disposal or reuse of this container may be dangerous and illegal. Empty

containers must be scrapped or reconditioned.

## **Section 14: TRANSPORT INFORMATION**

 DOT
 IMDG
 IATA

 14.1 UN/ID no
 UN1263
 UN1263
 UN1263

 14.2 Proper shipping name
 Paint
 Paint
 Paint

14.3 Hazard ClassCOMBUSTIBLE LIQUID3314.4 Packing GroupIIIIIIIII

14.5 Environmental hazard

Marine pollutant This material meets the definition of a marine pollutant

Marine pollutant Petroleum distillates, hydrotreated light, Stoddard solvent

**14.6 Special Provisions** B1, B52, IB3, T2, TP1, TP29, 367 163, 223, 367 955

**Emergency Response Guide EmS-No Number** F-E, S-E

128

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available

A3, A72, A192

The supplier may apply one of the following exceptions: Combustible Liquid (49 CFR 173.150(f)); Consumer Commodity (49 CFR 173.150(c), ICAO/IATA SP A112); Limited Quantity (49 CFR 173.150(b), ICAO Part 3 Chapter 4, IATA 2.7, IMDG Chapter 3.4); Viscous Liquid (49 CFR 173.121(b), IMDG 2.3.2.2, IATA 3.3.3.1.1, ICAO 3.2.2, ADR 2.2.3.1.5); Does Not Sustain Combustion (49 CFR 173.120(a), IATA 3.3.1.3, ICAO 3.1.3, IMDG 2.3.1.3, ADR 2.2.3.1.1 Note 1); or others as allowed under hazardous materials/dangerous goods regulations.

## **Section 15: REGULATORY INFORMATION**

#### **International Inventories**

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

from listing.

**DSL** - Canadian Domestic Substances List

Not all components are listed or

exempt from listing

All components are listed or exempt

## **US Federal Regulations**

Chemical Name	SARA 313 - Threshold Values %	Metals	Hazardous air pollutants (HAPs) content
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	1	Cobalt	Present
136-52-7			
0.1 - 0.3			

#### SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

## **US State Regulations**

#### Rule 66 status of product

Not photochemically reactive.

#### **California Proposition 65**

WARNING! This product contains a chemical known in the State of California to cause cancer.

#### U.S. EPA Label information

EPA Pesticide registration number Not applicable

#### **U.S. State Right-to-Know Regulations**

Chemical Name
Petroleum distillates, hydrotreated light
64742-47-8
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Limestone
1317-65-3
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Titanium dioxide

13463-67-7
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Stoddard solvent
8052-41-3
Zirconium ethyl hexoate
22464-99-9
2-Butanone, oxime
96-29-7
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)
136-52-7

## **Section 16: OTHER INFORMATION**

HMIS

Health hazards
\* = Chronic Health Hazard

Flammability
2
Physical hazards
0
Personal Protection
X

**Supplier Address** 

Valspar Consumer The Valspar Corporation Valspar Plasti-Kote Headquarters 4999 36th St. Valspar Plasti-Kote 1636 Shawson Dr.

8725 W. Higgins Rd. Suite Grand Rapids, MI 49512 Mississauga, Ontario L4W 1N7

1000 800-253-3957 905-671-8333

Chicago, IL 60631 773-628-5500

Prepared By Product Stewardship

Revision date 17-Apr-2018

Revision Note No information available

**Disclaimer** 

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

**End of Safety Data Sheet**