# valspar if it matters, we're on it.®

# SAFETY DATA SHEET

Revision date 17-Apr-2018

Version 14

Supersedes Date: 09-May-2017

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product identifier Product Code

044.0021982

Product Name

A/RUST EN SAT TNT BS

Other means of identification No information available

Recommended use of the chemical and restrictions on use Paint, Coatings

Details of the supplier of the safety data sheet See section 16 for more information

The Valspar Corporation PO Box 1461 Minneapolis, MN 55440

E-mail address

msds@valspar.com

Emergency telephone number United States of America 1-888-345-5732

Section 2: HAZARDS IDENTIFICATION

#### **Classification**

Skin corrosion/irritation	Category 2
Skin sensitization	Category 1
Carcinogenicity	Category 1A
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable liquids	Category 3

## Label elements



Signal word

DANGER

## HAZARD STATEMENTS

Flammable liquid and vapor Causes skin irritation May cause an allergic skin reaction May cause cancer Suspected of damaging fertility or the unborn child May cause drowsiness or dizziness May be fatal if swallowed and enters airways

#### PREVENTION

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Wash face, hands and any exposed skin thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace. Use only outdoors or in a well-ventilated area. P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

#### RESPONSE

IF exposed or concerned: Get medical advice/attention.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin

If skin irritation or rash occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction.

#### STORAGE

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool.

#### DISPOSAL

Dispose of contents/containers in accordance with local regulations.

### HAZARDS NOT OTHERWISE CLASSIFIED (HNOC)

No information available.

#### **OTHER HAZARDS**

spontaneously combustible material. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal.

UNKNOWN ACUTE TOXICITY

0% of the mixture consists of ingredient(s) of unknown toxicity.

# Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	weight-%
Petroleum distillates, hydrotreated light	64742-47-8	25 - 50
Titanium dioxide	13463-67-7	10 - 25
Zirconium ethyl hexoate	22464-99-9	0.1 - 0.3
Quartz	14808-60-7	0.1 - 0.3
2-Butanone, oxime	96-29-7	0.1 - 0.3

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

# Section 4: FIRST AID MEASURES

#### First Aid Measures

#### **General advice**

IF exposed or concerned: Get medical advice/attention.

#### Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

#### **Skin Contact**

If skin irritation or rash occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

#### Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

#### Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

#### Most important symptoms and effects, both acute and delayed

Symptoms No information available.

#### Indication of any immediate medical attention and special treatment needed

Note to physicians

Treat symptomatically.

# Section 5: FIRE FIGHTING MEASURES

#### Suitable extinguishing media

Dry chemical, CO2, water spray or alcohol-resistant foam.

Not to be used for safety reasons: Strong water jet

#### Specific hazards arising from the chemical

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes. May cause sensitization by skin contact. spontaneously combustible material. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal. Keep product and empty container away from heat and sources of ignition.

#### Special protective equipment for fire-fighters

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

# Section 6: ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

#### Personal precautions

Avoid breathing vapors or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Take precautionary

measures against static discharges.

#### For emergency responders

Use personal protection recommended in Section 8.

#### Environmental precautions

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

#### Methods and material for containment and cleaning up

#### Methods for containment

Prevent further leakage or spillage if safe to do so.

## Methods for cleaning up

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. Take up mechanically, placing in appropriate containers for disposal.

# Section 7: HANDLING AND STORAGE

#### Precautions for safe handling

#### Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal.

#### General Hygiene Considerations

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Avoid contact with skin, eyes or clothing.

#### Conditions for safe storage, including any incompatibilities

#### Storage Conditions

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place. Keep tightly closed in a dry and cool place.

#### Incompatible materials

Strong oxidizing agents. Acids. Alkali.

# Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

#### Exposure Limits

If S\* appears in the OEL table, it indicates this chemical contains a skin notation.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup>
Zirconium ethyl hexoate 22464-99-9	STEL: 10 mg/m³ Zr TWA: 5 mg/m³ Zr	TWA: 5 mg/m³ Zr	IDLH: 25 mg/m <sup>3</sup> Zr TWA: 5 mg/m <sup>3</sup> except Zirconium tetrachloride Zr STEL: 10 mg/m <sup>3</sup> Zr
Quartz	TWA: 0.025 mg/m <sup>3</sup> respirable	TWA: 50 µg/m³	IDLH: 50 mg/m <sup>3</sup> respirable dust

Γ	14808-60-7	particulate matter	TWA: (250)/(%SiO2 + 5) mppcf	TWA: 0.05 mg/m <sup>3</sup> respira	able dust
			TWA respirable fraction		
			TWA: (10)/(%SiO2 + 2) mg/m <sup>3</sup>		
			TWA respirable fraction		

#### Appropriate engineering controls

#### Engineering Controls

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

#### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Tight sealing safety goggles.

#### Skin and body protection

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Wear suitable protective clothing. Personnel should wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber.

#### **Hand Protection**

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

#### **Respiratory protection**

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

#### **Thermal Protection**

No information available

# Section 9: PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

Physical state Appearance Odor	liquid No information available Solvent
Color	white
Odor Threshold	No information available
pH value	No information available
Melting point/freezing point	No information available
Boiling point / boiling range	No information available °C / °F
flash point	39 °C / 102 °F
evaporation rate	No information available
Flammability (solid, gas)	No information available
Flammability Limit in Air	
Upper flammability limit:	No information available
Lower flammability limit:	No information available
Vapor Pressure	No information available
vapor density	No information available
Density (Ibs per US gallon)	10.84
specific gravity	No information available
Solubility(ies)	No information available
Partition coefficient	No information available
Autoignition temperature	No information available
Decomposition temperature	No information available
Kinematic viscosity	No information available
Dynamic viscosity	No information available

**Other information** 

# Section 10: STABILITY AND REACTIVITY

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of Hazardous Reactions	None under normal processing.
Hazardous polymerization	None under normal processing.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	Strong oxidizing agents. Acids. Alkali.

Hazardous Decomposition Products Carbon monoxide. Carbon dioxide (CO2).

# Section 11: TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Eye contact Not applicable Skin Contact Causes skin irritation May cause an allergic skin reaction Ingestion May be fatal if swallowed and enters airways Inhalation May cause drowsiness or dizziness

#### Numerical measures of toxicity - Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum distillates, hydrotreated	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat)4 h
light			
64742-47-8			
Titanium dioxide	> 10000 mg/kg (Rat)	-	-
13463-67-7	· ·		
Zirconium ethyl hexoate	-	-	-
22464-99-9			
Quartz	= 500 mg/kg (Rat)	-	-
14808-60-7			
2-Butanone, oxime	= 930 mg/kg (Rat)	1000 - 1800 mg/kg (Rabbit)	> 4800 mg/m³ (Rat)4 h
96-29-7			_ , ,

#### Numerical measures of toxicity - Product Information

**UNKNOWN ACUTE TOXICITY** 0% of the mixture consists of ingredient(s) of unknown toxicity.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Carcinogenicity

According to IARC, Volume 93, no significant exposure to primary particles of titanium dioxide is thought to occur from use in paints since the pigment is bound to other materials.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide 13463-67-7		Group 2B		X
Quartz 14808-60-7	A2	Group 1	Known	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen.

IARC (International Agency for Research on Cancer) Group 1 - Carcinogenic to Humans. Group 2B - Possibly Carcinogenic to Humans. NTP (National Toxicology Program) Known - Known Carcinogen. OSHA (Occupational Safety and Health Administration of the US Department of Labor) X - Present.

Skin corrosion/irritation Causes skin irritation Serious eye damage/eye irritation Not applicable Skin sensitization May cause an allergic skin reaction Respiratory sensitization Not applicable Germ cell mutagenicity Not applicable Carcinogenicity May cause cancer Reproductive Toxicity Suspected of damaging fertility or the unborn child Specific target organ toxicity (single exposure) May cause drowsiness or dizziness Specific target organ toxicity (repeated exposure) Not applicable Aspiration hazard May be fatal if swallowed and enters airways

# Section 12: ECOLOGICAL INFORMATION

Ecotoxicity Environmental precautions	Prevent product from e	entering drains.	
Marine pollutant	This material meets th	e definition of a marine po	ollutant
Persistence and degradabiling No information available	ity		
Bioaccumulation No information available			
<u>Mobility</u> No information available			
Other adverse effects	No information availab	ble	
	Section 13: DISPO	SAL CONSIDERAT	IONS
Waste treatment methods			
waste treatment methods			
Disposal of wastes	Disposal should be in regulations.	accordance with applicab	le regional, national and local laws and
Contaminated packaging		euse of this container may rapped or reconditioned.	y be dangerous and illegal. Empty
	Section 14: TRAN	SPORT INFORMAT	ION
	DOT	IMDG_	
14.1 UN/ID no 14.2 Proper shipping name	UN1263 Paint	UN1263 Paint	UN1263 Paint
14.3 Hazard Class 14.4 Packing Group	COMBUSTIBLE LIQUID	3 III	3 
	rial meets the definition of a marine p		
Marine pollutant Petroleum 14.6 Special Provisions	distillates, hydrotreated light , Trizi B1, B52, IB3, T2, TP1, TP29, 36 Emergency Response Guide Number 128		A3, A72, A192
14.7 Transport in bulk according	ng to Annex II of MARPOL 73/78 a	nd the IBC Code	No information available

The supplier may apply one of the following exceptions: Combustible Liquid (49 CFR 173.150(f)); Consumer Commodity (49 CFR 173.150(c), ICAO/IATA SP A112); Limited Quantity (49 CFR 173.150(b), ICAO Part 3 Chapter 4, IATA 2.7, IMDG Chapter 3.4); Viscous Liquid (49 CFR 173.121(b), IMDG 2.3.2.2, IATA 3.3.3.1.1, ICAO 3.2.2, ADR 2.2.3.1.5); Does Not Sustain Combustion (49 CFR 173.120(a), IATA 3.3.1.3, ICAO 3.1.3, IMDG 2.3.1.3, ADR 2.2.3.1.1 Note 1); or others as allowed under hazardous materials/dangerous goods regulations.

# Section 15: REGULATORY INFORMATION

#### International Inventories

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

All components are listed or exempt from listing. All components are listed or exempt from listing

# US Federal Regulations

# SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

## US State Regulations

#### Rule 66 status of product

Not photochemically reactive.

#### California Proposition 65

WARNING! This product contains a chemical known in the State of California to cause cancer.

# U.S. EPA Label information

EPA Pesticide registration number Not applicable

#### U.S. State Right-to-Know Regulations

Chemical Name
Petroleum distillates, hydrotreated light
64742-47-8
Limestone
1317-65-3
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Titanium dioxide
13463-67-7
Proprietary Inert
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Zirconium ethyl hexoate
22464-99-9
Quartz
14808-60-7
2-Butanone, oxime
96-29-7

# **Section 16: OTHER INFORMATION**

HMIS_	
Health hazards	3*
* = Chronic Health Hazard	
Flammability	2
Physical hazards	0
Personal Protection	Х

#### **Supplier Address**

Valspar Consumer Headquarters	The Valspar Corporation 4999 36th St.	Valspar Plasti-Kote 1636 Shawson Dr.
8725 W. Higgins Rd. Suite 1000	Grand Rapids, MI 49512 800-253-3957	Mississauga, Ontario L4W 1N7 905-671-8333
Chicago, IL 60631 773-628-5500		

#### **Prepared By**

Product Stewardship

Revision date Revision Note Disclaimer 17-Apr-2018 No information available

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

End of Safety Data Sheet