



**WATCO®
EXTERIOR WOOD FINISH (450 VOC)**

DESCRIPTION AND USES

Watco® Exterior Wood Finish is a unique, penetrating oil that hardens in the wood, not on the wood. New, old, or pressure treated wood becomes water repellent, provides UV and mildew protection and resists warping and swelling caused by changes in weather. Watco Exterior Wood Finish is durable and easy to use. It seals and protects in one easy step. Exterior Wood finish will not crack, chip, or peel. It is ideal for decks, siding, fences and more.

FEATURES

- Stains, seals & protects
- Penetrates deeply
- Excellent outdoor protection

PRODUCTS

SKU	Description
67741	1-Quart
67731	1-Gallon

PRODUCT APPLICATION

SURFACE PREPARATION

Ensure wood is dry and free from subsurface moisture. Remove any existing finishes with sandpaper or stripper. Before applying Watco Exterior Wood Finish, remove all sanding dust and dirt with a vacuum, tack cloth, or rag dampened with mineral spirits. To remove grease, oils or adhesive use a rag dampened with mineral spirits.

Protect landscaping by covering plants and shrubs. Protect eyes and skin, wear safety goggles and chemical resistant gloves.

WARNING! If you scrape, sand or remove old paint, you may

Release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead

PRODUCT APPLICATION (cont.)

APPLICATION

Use adequate ventilation at all times. Apply only when the air and surface temperatures are above 50°F (10°C) and below 95°F (35°C). Slower dry times may result from applications on redwood, cedar or woods with high tannin and /or oil content or with periods of high humidity and/or low temperatures. Use full strength. Test Watco Exterior Wood Finish in an inconspicuous area prior to use.

Thoroughly stir the contents before and during use. **NOTE:** To ensure uniform color and/or appearance, complete the entire project with the same stain color as shown on the label. Apply a heavy application (flood) with a lint-free cotton or polyester cloth or a high quality brush. Watco Exterior Wood Finish can also be applied with a roller or spray. Allow to penetrate for 30 minutes. Reapply the material and allow it to penetrate for an additional 15 minutes. Wipe surface thoroughly with a clean lint-free cloth to remove excess oil from the surface. Allow the finish to dry for 8 to 10 hours before light use.

Allow Watco Exterior Wood Finish to dry for 72 hours before applying a polyurethane topcoat finish.

MAINTENANCE

Penetrating oil finishes will require maintenance to ensure the beauty and effectiveness of the finish. Periodically reapply Watco Exterior Wood Finish to wood when the wood begins to appear dry.

CLEAN UP

Clean application tools and equipment with mineral spirits or paint thinner. Dispose of properly. For guidance on disposal of unused product, contact your local or state government environmental control agency.

**TECHNICAL DATA****WAT-10****WATCO® EXTERIOR WOOD FINISH****PHYSICAL PROPERTIES**

		EXTERIOR WOOD FINISH
Resin Type		Linseed Oil and Phenolic Rosin Ester
Pigment Type		NA
Solvents		Mineral Spirits
Weight	Per Gallon	7.2 lbs.
	Per Liter	0.87 kg
Solids	By Weight	48.1%
	By Volume	41.9%
Volatile Organic Compounds		450 g/l (3.75 lbs./gal.)
Practical Coverage at Recommended DFT (assumes 15% material loss)		560-680 sq.ft./gal. (13.8-16.7 m ² /l) Varies with type and porosity of wood
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity		8-10 hours
Shelf Life		3 years
Flash Point		105°F (40°C)
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.